

## SAR Test exclusion documentation according to FCC KDB 447498, RSS-102

Report identification number: 1-3709/21-01-26 Exclusion (FCC)

<b>contains the module with the following certification numbers</b>	
FCC ID	2AQYJ-FLUOREYEMD

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Document authorised:

Alexander Hnatovskiy  
Lab Manager  
Radio Communications & EMC

Marco Scigliano  
Testing Manager  
Radio Communications & EMC

**EUT technologies:**

Technologies:	Max. declared cond. AVG Power	Antenna gain	MAX EIRP for RF exposure
BT LE 2450 MHz	6.0 dBm (4.0 mW)	< 3.3 dBi	9.3 dBm (8.5 mW)

**NOTE:**

Test results for BT LE can be seen in CTC advanced GmbH report 1-3907/21-01-10

**SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)**

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances  $\leq 50$ mm

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{separation}} / f^{0.5}$$

where

Threshold<sub>1-g;10-g</sub> is 3 for 1-g; 7.5 for 10-g

$d_{\text{separation}}$  is the min. test separation distance; 5mm is used if the distance is less

$f$  is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	$d_{\text{separation}}$ [mm]	Threshold <sub>1-g</sub>	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
				[dBm]	[mW]	
2450.00	5	3	9.58	9.30	8.51	yes