



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.407

TEST REPORT

For

Shanghai Ratta Smart Technology Co.,Ltd.

Room 301, Building No.1, 168 Jixin Road, Minhang, Shanghai 201104 China

FCC ID: 2AQZ9-A6X

Report Type: Original Report	Product Type: SuperNote
Test Engineer: Jack Jiao	<i>Jack Jiao</i>
Report Number: RSHD200824001-00C	
Report Date: 2020-12-01	
Reviewed By: Oscar Ye EMC Manager	<i>Oscar Ye</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)4

 OBJECTIVE4

 RELATED SUBMITTAL(S)/GRANT(S).....4

 TEST METHODOLOGY5

 MEASUREMENT UNCERTAINTY.....6

 TEST FACILITY6

SYSTEM TEST CONFIGURATION.....7

 DESCRIPTION OF TEST CONFIGURATION7

 EUT EXERCISE SOFTWARE7

 EQUIPMENT MODIFICATIONS15

 SUPPORT EQUIPMENT LIST AND DETAILS16

 EXTERNAL I/O CABLE.....16

 BLOCK DIAGRAM OF TEST SETUP16

SUMMARY OF TEST RESULTS18

TEST EQUIPMENT LIST19

FCC §1.1310 & §2.1093 - RF EXPOSURE.....20

 MEASUREMENT RESULT20

FCC §15.203 – ANTENNA REQUIREMENT.....21

 APPLICABLE STANDARD21

 ANTENNA CONNECTOR CONSTRUCTION21

FCC §15.407 (b) (8) §15.207 (a) – AC POWER LINE CONDUCTED EMISSIONS.....22

 APPLICABLE STANDARD22

 EUT SETUP.....22

 EMI TEST RECEIVER SETUP.....22

 TEST PROCEDURE23

 FACTOR & OVER LIMIT CALCULATION.....23

 TEST RESULTS SUMMARY23

 TEST DATA23

§15.205 & §15.209 & §15.407(B)(1)(4) (8)(9) – UNDESIRABLE EMISSION & RESTRICTED BANDS.....28

 APPLICABLE STANDARD28

 EUT SETUP28

 EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP29

 TEST PROCEDURE29

 CORRECTED AMPLITUDE & MARGIN CALCULATION30

 TEST DATA30

FCC §15.407(a) & §15.407(e)–EMISSION BANDWIDTH.....68

 APPLICABLE STANDARD68

 TEST PROCEDURE68

 TEST DATA69

FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER92

 APPLICABLE STANDARD92

 TEST PROCEDURE92

 TEST DATA92

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY.....94

 APPLICABLE STANDARD94

TEST PROCEDURE	94
TEST DATA	94

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Shanghai Ratta Smart Technology Co.,Ltd.
Product Type:	SuperNote
Test Model	A6 X
Power Supply:	DC 3.8V from battery
RF Function:	5G Wi-Fi
Operating Band/Frequency:	5G Wi-Fi B1: 5150-5250 MHz, B4: 5725-5850 MHz
Channel Number:	5G Wi-Fi B1: 7, B4: 8
Channel Separation:	802.11a/802.11ac20/n20: 20MHz; 802.11n40/802.11ac40:40 MHz, 802.11ac80: 80 MHz
Modulation Type:	OFDM
Antenna Type:	FPC
*Maximum Antenna Gain:	Band 1 & Band 4: 0.1dBi

Note: The maximum antenna gain is provided by the applicant.

**All measurement and test data in this report was gathered from production sample serial number: 20200824001. (Assigned by the BACL). The EUT supplied by the applicant was received on 2020-08-24.*

Objective

This type approval report is prepared on behalf of *Shanghai Ratta Smart Technology Co.,Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submissions with FCC ID: 2AQZ9-A6X
FCC Part 15.247 DSS Submittal with FCC ID: 2AQZ9-A6X

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan).

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

In **5150~5250 MHz** band, test channel list is as below,

802.11a/802.11ac20/n20 mode Channel 36, 40, 48 were tested.
 802.11n40/802.11ac40 mode Channel 38, 46 were tested.
 802.11ac80 mode Channel 42 was tested

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For **5725~5850 MHz** band,

802.11a/802.11ac20/n20 mode Channel 149, 157, 165 were tested.
 802.11n40/802.11ac40 mode Channel 151, 159 were tested.
 802.11ac80 mode Channel 155 was tested.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	159	5795
151	5755	161	5805
153	5765	165	5825
155	5775	/	/
157	5785	/	/

EUT Exercise Software

RF test tool: QRCT

The worst case was performed under:

5150MHz-5250MHz Band:

Mode	Data rate	Frequency (MHz)	*Power Level Setting
802.11a	6 Mbps	5180	40
		5200	40
		5240	40
802.11ac20	MCS0	5180	40
		5200	40
		5240	40
802.11n-HT20	MCS0	5180	40
		5200	40
		5240	40
802.11ac40	MCS0	5190	40
		5230	40
802.11n-HT40	MCS0	5190	40
		5230	40
802.11ac80	MCS0	5210	40

5725MHz-5850MHz Band:


Mode	Data rate	Channel	*Power Level Setting
802.11a	6 Mbps	5745	40
		5785	40
		5825	40
802.11ac20	MCS0	5745	40
		5785	40
		5825	40
802.11n-HT20	MCS0	5745	40
		5785	40
		5825	40
802.11ac40	MCS0	5755	40
		5795	40
802.11n-HT40	MCS0	5755	40
		5795	40
802.11ac80	MCS0	5775	40

Note: The power level setting was declared by the applicant.


Duty Cycle

5150MHz-5250MHz Band:


802.11a mode




802.11ac20 mode




802.11n-HT20 mode




802.11 ac40 mode



802.11n-HT40 mode




802.11 ac80 mode




5725MHz-5850MHz Band:


802.11a mode




802.11ac20 mode




802.11n-HT20 mode




802.11 ac40 mode



802.11n-HT40 mode



802.11n-ac80 mode



Mode	Frequency Range (MHz)	Duty Cycle (%)	T (ms)	1/T (kHz)	10log(1/x)
802.11a	5150-5250	100	/	/	0
802.11ac20		100	/	/	0
802.11n-HT20		100	/	/	0
802.11ac40		100	/	/	0
802.11n-HT40		100	/	/	0
802.11ac80		100	/	/	0
802.11a	5725-5850	100	/	/	0
802.11ac20		100	/	/	0
802.11n-HT20		100	/	/	0
802.11ac40		100	/	/	0
802.11n-HT40		100	/	/	0
802.11ac80		100	/	/	0

Note: “x” means duty cycle.

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	Socket	/	/
SHENZHEN KEYU POWER SUPPLY TECHNOLOGY CO., LTD	Adapter	KA25-0501000EU	/

External I/O Cable

Cable Description	Shielding Type	Length (m)	From Port	To
Power Cable	1.0	EUT	Adapter	Power Cable
Power Cable	1.0	Socket	LISN/AC source	Power Cable


Block Diagram of Test Setup

For Conducted Emissions:




For Radiated Emissions (Below 1GHz):

Turntable
2m Diameter



For Radiated Emissions (Above 1GHz):

Turntable
2m Diameter



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 & §15.407(b) (8)	AC Power Line Conducted Emissions	Compliant
§15.205 & §15.209 & §15.407(B)(1)(4) (8)(9)	Undesirable Emission & Restricted Bands	Compliant
§15.407(a) (12) & §15.407 (e)	Emission Bandwidth	Compliant
§15.407(a) (1) (3)	Conducted Transmitter Output Power	Compliant
§15.407(a) (1) (3)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-12-12	2022-12-11
A.H.Systems, inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
SELECTOR	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRC50703	G094	2020-08-05	2021-08-04
MICRO-TRONICS	Band Reject Filter	BRC50705	G085	2020-08-05	2021-08-04
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2019-12-14	2020-12-13
Agilent	Power Meter	N1912A	MY5000492	2019-11-18	2020-11-17
Agilent	Power Sensor	N1921A	MY54210024	2019-11-18	2020-11-17
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Sunmi Co.,Ltd.	RF Cable	Sunmi C01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2020-08-05	2021-08-04
Rohde & Schwarz	LISN	ENV216	3560655016	2019-11-30	2020-11-29
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2019-11-30	2020-11-29
Audix	Test Software	e3	V9	--	--
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2020-04-03	2021-04-02
MICRO-COAX	Coaxial Cable	Cable-15	015	2020-08-15	2021-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1093 - RF EXPOSURE

Applicable Standard

According to FCC§1.1310,§2.1093.

Measurement Result

Compliance, please refer to SAR Report: RSH200825050-20B.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407, if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Connector Construction

The EUT has an FPC antenna for 5G Wi-Fi and antenna gain is 0.1 dBi which were permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.407 (b) (8) §15.207 (a) – AC POWER LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a), §15.407(b) (8)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 30 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of 7dB means the emission is 7 dB above the limit. The equation for over limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	24.5 °C
Relative Humidity:	51 %
ATM Pressure:	100.9 kPa

The testing was performed by Jack Jiao on 2020-09-07.


EUT operation mode: Transmitting in 802.11a mode low channel of 5150~5250MHz (worst case)

AC 120V/60 Hz, Line



	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.272	18.30	19.82	38.12	51.07	-12.95	Average
2	0.272	28.70	19.82	48.52	61.07	-12.55	QP
3	0.396	12.99	19.75	32.74	47.95	-15.21	Average
4	0.396	24.69	19.75	44.44	57.95	-13.51	QP
5	0.471	12.71	19.75	32.46	46.49	-14.03	Average
6	0.471	19.91	19.75	39.66	56.49	-16.83	QP
7	0.595	7.20	19.75	26.95	46.00	-19.05	Average
8	0.595	19.70	19.75	39.45	56.00	-16.55	QP
9	0.880	3.59	19.73	23.32	46.00	-22.68	Average
10	0.880	18.59	19.73	38.32	56.00	-17.68	QP
11	2.500	8.40	19.48	27.88	46.00	-18.12	Average
12	2.500	18.40	19.48	37.88	56.00	-18.12	QP


AC 120V/60 Hz, Neutral



	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.238	23.60	19.82	43.42	52.17	-8.75	Average
2	0.238	32.50	19.82	52.32	62.17	-9.85	QP
3	0.274	20.70	19.82	40.52	50.98	-10.46	Average
4	0.274	31.70	19.82	51.52	60.98	-9.46	QP
5	0.400	15.20	19.74	34.94	47.86	-12.92	Average
6	0.400	27.80	19.74	47.54	57.86	-10.32	QP
7	0.928	5.39	19.76	25.15	46.00	-20.85	Average
8	0.928	15.59	19.76	35.35	56.00	-20.65	QP
9	2.371	7.40	19.56	26.96	46.00	-19.04	Average
10	2.371	17.20	19.56	36.76	56.00	-19.24	QP
11	17.849	8.30	19.83	28.13	50.00	-21.87	Average
12	17.849	15.50	19.83	35.33	60.00	-24.67	QP

EUT operation mode: Transmitting in 802.11a mode low channel of 5725-5850MHz (worst case)


AC 120V/60 Hz, Line



	Read	Limit	Over	Remark			
Freq	Level	Factor	Level	Line			
MHz	dBuV	dB	dBuV	dBuV			
1	0.273	17.00	19.82	36.82	51.03	-14.21	Average
2	0.273	28.00	19.82	47.82	61.03	-13.21	QP
3	0.398	13.40	19.74	33.14	47.90	-14.76	Average
4	0.398	24.50	19.74	44.24	57.90	-13.66	QP
5	0.601	6.70	19.75	26.45	46.00	-19.55	Average
6	0.601	20.20	19.75	39.95	56.00	-16.05	QP
7	0.876	2.89	19.73	22.62	46.00	-23.38	Average
8	0.876	18.59	19.73	38.32	56.00	-17.68	QP
9	1.680	3.40	19.84	23.24	46.00	-22.76	Average
10	1.680	18.40	19.84	38.24	56.00	-17.76	QP
11	2.461	8.30	19.50	27.80	46.00	-18.20	Average
12	2.461	18.40	19.50	37.90	56.00	-18.10	QP

AC 120V/60 Hz, Neutral

Date: 2020-09-07



	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.206	10.40	19.82	30.22	53.36	-23.14	Average
2	0.206	24.80	19.82	44.62	63.36	-18.74	QP
3	0.273	20.40	19.82	40.22	51.03	-10.81	Average
4	0.273	31.90	19.82	51.72	61.03	-9.31	QP
5	0.398	15.00	19.74	34.74	47.90	-13.16	Average
6	0.398	27.80	19.74	47.54	57.90	-10.36	QP
7	0.963	3.50	19.79	23.29	46.00	-22.71	Average
8	0.963	13.50	19.79	33.29	56.00	-22.71	QP
9	2.487	8.40	19.48	27.88	46.00	-18.12	Average
10	2.487	17.40	19.48	36.88	56.00	-19.12	QP
11	3.310	9.90	19.46	29.36	46.00	-16.64	Average
12	3.310	17.20	19.46	36.66	56.00	-19.34	QP

§15.205 & §15.209 & §15.407(B)(1)(4) (8)(9) – UNDESIRABLE EMISSION & RESTRICTED BANDS

Applicable Standard

FCC §15.407 (b)(1)(4) (8) (9); §15.209; §15.205;

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27dBm/MHz

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of –27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

As per FCC §15.35(d):Unless otherwise specified, on any frequency or frequencies above 1000MHz,the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000MHz shall be performed using a minimum resolution bandwidth of 1MHz.


According to 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP [dBm] + 95.2$, for $d = 3$ meters.

EUT Setup

Below 1 GHz:



Above 1 GHz:



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions

Temperature:	22.6~23.0°C
Relative Humidity:	48~53%
ATM Pressure:	100.7~101.3 kPa


The testing was performed by Jack Jiao from 2020-10-01 to 2020-10-22.

Test Mode: Transmitting

Spurious Emission Test

30MHz-1GHz(5150-5250MHz Band):


Pre-scan with 802.11a, 802.11ac20, 802.11n-HT20, 802.11ac40, 802.11n-HT40 and 802.11 ac80 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11a mode in low channel in Z-axis of orientation was recorded.



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
30.18	27.74	100.0	V	73.0	-4.5	40.00	12.26
36.68	29.00	100.0	V	163.0	-8.9	40.00	11.00
69.08	23.87	100.0	V	42.0	-17.8	40.00	16.13
87.60	21.02	100.0	V	293.0	-18.0	40.00	18.98
151.14	25.84	200.0	H	208.0	-12.8	43.50	17.66
206.81	28.58	100.0	H	186.0	-12.7	43.50	14.92

30MHz-1GHz(5725-5850MHz Band):

Pre-scan with 802.11a, 802.11ac20, 802.11n-HT20, 802.11ac40, 802.11n-HT40 and 802.11 ac80 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11a mode in low channel in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
35.79	28.20	100.0	V	192.0	-8.3	40.00	11.80
70.83	24.04	200.0	V	257.0	-17.8	40.00	15.96
87.78	17.81	100.0	V	314.0	-18.0	40.00	22.19
152.64	26.41	200.0	H	171.0	-12.9	43.50	17.09
207.02	28.93	200.0	H	187.0	-12.7	43.50	14.57
239.48	27.48	100.0	H	0.0	-12.6	46.00	18.52

1GHz-18GHz(5150-5250MHz Band):


802.11a Mode:

(Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:


1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5180MHz




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1885.70	35.60	---	150	H	168.0	-14.9	68.20	32.60
4029.40	---	30.89	150	H	349.0	-7.0	54.00	23.11
4029.40	40.82	---	150	H	349.0	-7.0	74.00	33.18
6264.90	44.35	---	200	H	0.0	-2.0	68.20	23.85
7913.90	49.28	---	150	H	168.0	1.7	68.20	18.92
10365.30	46.10	---	200	V	300.0	2.2	68.20	22.10
17959.20	---	47.56	200	H	270.0	8.8	54.00	6.44
17959.20	56.37	---	200	H	270.0	8.8	74.00	17.63

Middle Channel: 5200MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
2292.00	---	27.62	200	V	0.0	-13.3	54.00	26.38
2292.00	37.25	---	200	V	0.0	-13.3	74.00	36.75
3912.10	---	32.94	200	V	115.0	-7.3	54.00	21.06
3912.10	41.63	---	200	V	115.0	-7.3	74.00	32.37
7434.50	---	39.00	200	H	153.0	0.9	54.00	15.00
7434.50	47.66	---	200	H	153.0	0.9	74.00	26.34
10402.70	45.64	---	200	H	153.0	2.2	68.20	22.56
13083.60	52.08	---	200	H	102.0	5.3	68.20	16.12
17588.60	56.80	---	200	H	231.0	8.9	68.20	11.40

High Channel: 5240MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1814.30	34.73	---	150	H	357.0	-15.2	68.20	33.47
3942.70	---	32.57	150	V	103.0	-7.2	54.00	21.43
3942.70	41.46	---	150	V	103.0	-7.2	74.00	32.54
7888.40	49.02	---	200	H	0.0	1.6	68.20	19.18
10480.90	47.55	---	150	V	141.0	2.3	68.20	20.65
13495.00	51.43	---	200	V	116.0	5.7	68.20	16.77
17955.80	---	47.70	150	V	0.0	8.8	54.00	6.30
17955.80	56.90	---	150	V	0.0	8.8	74.00	17.10


802.11ac20 Mode:

(Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:


1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5180MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2581.00	38.92	---	200	V	64.0	-12.0	68.20	29.28
3942.70	---	32.24	200	H	37.0	-7.2	54.00	21.76
3942.70	42.51	---	200	H	37.0	-7.2	74.00	31.49
7976.80	48.34	---	200	V	89.0	1.8	68.20	19.86
10360.20	45.09	---	150	H	99.0	2.2	68.20	23.11
13095.50	53.77	---	200	H	326.0	5.3	68.20	14.43
17524.00	57.44	---	150	H	345.0	8.9	74.00	16.56
17524.00	---	49.15	150	H	345.0	8.9	54.00	4.85


Middle Channel: 5200MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2181.50	36.43	---	150	H	49.0	-13.7	68.20	31.77
4007.30	41.59	---	200	H	115.0	-7.0	74.00	32.41
4007.30	---	32.35	200	H	115.0	-7.0	54.00	21.65
6258.10	44.41	---	200	H	62.0	-2.1	68.20	23.79
8320.20	---	39.64	150	V	129.0	1.5	54.00	14.36
8320.20	48.30	---	150	V	129.0	1.5	74.00	25.70
10401.00	47.13	---	150	H	1.0	2.2	68.20	21.07
17501.90	56.88	---	200	H	48.0	8.9	68.20	11.32

High Channel: 5240MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1884.00	35.88	---	200	H	146.0	-14.9	68.20	32.32
3159.00	39.95	---	150	V	0.0	-9.7	68.20	28.25
7453.20	---	38.52	200	H	311.0	0.9	54.00	15.48
7453.20	48.32	---	200	H	311.0	0.9	74.00	25.68
10479.20	47.04	---	200	V	4.0	2.3	68.20	21.16
13092.10	52.89	---	200	V	22.0	5.3	68.20	15.31
17947.30	---	48.15	200	H	107.0	8.8	54.00	5.85
17947.30	56.79	---	200	H	107.0	8.8	74.00	17.21


802.11n-HT20 Mode:

Pre-scan with X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude


Low Channel: 5180MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1516.80	---	25.42	150	H	87.0	-16.3	54.00	28.58
1516.80	34.15	---	150	H	87.0	-16.3	74.00	39.85
3597.60	40.12	---	150	V	158.0	-8.5	68.20	28.08
6220.70	44.25	---	150	V	286.0	-2.2	68.20	23.95
8304.90	---	39.94	150	V	67.0	1.5	54.00	14.06
8304.90	48.78	---	150	V	67.0	1.5	74.00	25.22
10360.20	45.17	---	150	V	324.0	2.2	68.20	23.03
17530.80	57.46	---	200	V	56.0	8.9	68.20	10.74

Middle Channel: 5200MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2329.40	---	28.84	150	H	325.0	-13.1	54.00	25.16
2329.40	33.40	---	150	H	325.0	-13.1	74.00	40.60
3908.70	42.25	---	150	V	293.0	-7.3	74.00	31.75
3908.70	---	32.89	150	V	293.0	-7.3	54.00	21.11
6232.60	44.84	---	150	V	230.0	-2.2	68.20	23.36
8374.60	---	39.90	150	H	154.0	1.5	54.00	14.10
8374.60	48.00	---	200	H	154.0	1.5	74.00	26.00
10401.00	45.59	---	200	H	256.0	2.2	68.20	22.61
17949.00	---	49.63	150	H	12.0	8.8	54.00	4.37
17949.00	57.10	---	150	H	12.0	8.8	74.00	16.90

High Channel: 5240MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2686.40	38.83	---	150	V	222.0	-11.6	68.20	29.37
4384.70	---	34.04	150	H	336.0	-6.4	54.00	19.96
4384.70	41.95	---	150	H	336.0	-6.4	74.00	32.05
7861.20	48.51	---	200	H	326.0	1.6	68.20	19.69
10480.90	48.17	---	200	H	130.0	2.3	68.20	20.03
13976.10	52.99	---	150	V	133.0	6.1	68.20	15.21
17558.00	57.34	---	200	H	15.0	8.9	68.20	10.86


802.11ac40 Mode:

(Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude


Low Channel: 5190MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
3091.00	39.37	---	200	H	169.0	-9.9	68.20	28.83
6281.90	44.66	---	200	V	128.0	-2.0	68.20	23.54
7898.60	48.98	---	200	H	64.0	1.7	68.20	19.22
10378.90	45.35	---	150	V	237.0	2.2	68.20	22.85
13974.40	53.88	---	150	H	4.0	6.1	68.20	14.32
17937.10	---	49.15	150	H	85.0	8.8	54.00	4.85
17937.10	57.62	---	150	H	85.0	8.8	74.00	16.38

High Channel: 5230MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
2198.50	35.63	---	150	V	219.0	-13.7	68.20	32.57
3893.40	---	32.85	200	H	198.0	-7.4	54.00	21.15
3893.40	41.49	---	200	H	198.0	-7.4	74.00	32.51
7475.30	---	38.10	200	V	97.0	1.0	54.00	15.90
7475.30	47.73	---	200	V	97.0	1.0	74.00	26.27
10462.20	49.00	---	200	V	46.0	2.3	68.20	19.20
13923.40	52.36	---	150	V	354.0	6.1	68.20	15.84
17498.50	56.61	---	200	H	300.0	8.9	68.20	11.59


802.11n-HT40 Mode:

Pre-scan with X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude


Low Channel: 5190MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1848.30	35.74	---	150	V	356.0	-15.0	68.20	32.46
3993.70	---	32.78	150	H	153.0	-7.0	54.00	21.22
3993.70	41.68	---	150	H	153.0	-7.0	74.00	32.32
7465.10	46.85	---	200	V	245.0	1.0	74.00	27.15
7465.10	---	41.13	200	V	245.0	1.0	54.00	12.87
10392.50	45.69	---	200	V	0.0	2.2	68.20	22.51
13053.00	51.82	---	200	V	47.0	5.3	68.20	16.38
17559.70	57.67	---	200	V	0.0	8.9	68.20	10.53

High Channel: 5230MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2295.40	---	29.27	200	V	335.0	-13.3	54.00	24.73
2295.40	35.06	---	200	V	335.0	-13.3	74.00	38.94
3951.20	---	30.98	150	V	2.0	-7.2	54.00	23.02
3951.20	41.09	---	150	V	2.0	-7.2	74.00	32.91
6251.30	44.04	---	150	V	82.0	-2.1	68.20	24.16
8327.00	---	39.05	150	V	149.0	1.5	54.00	14.95
8327.00	49.17	---	150	V	149.0	1.5	74.00	24.83
10460.50	48.49	---	200	H	324.0	2.3	68.20	19.71
17510.40	56.98	---	200	H	324.0	8.9	68.20	11.22


802.11ac80 Mode:

Pre-scan with X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5210MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2667.70	38.27	---	200	H	116.0	-11.6	68.20	29.93
4721.30	---	32.86	150	V	34.0	-5.8	54.00	21.14
4721.30	41.94	---	150	V	34.0	-5.8	74.00	32.06
7087.70	45.34	---	200	H	338.0	0.1	68.20	22.86
9114.10	---	38.35	200	H	349.0	1.9	54.00	15.65
9114.10	48.58	---	200	H	349.0	1.9	74.00	25.42
10421.40	46.83	---	200	V	116.0	2.2	68.20	21.37
17949.00	57.21	---	150	V	356.0	8.8	74.00	16.79
17949.00	---	49.56	150	V	356.0	8.8	54.00	4.44

5725-5850MHz Band:

1GHz-18GHz:


802.11a Mode:

(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded.)

Note:


1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5745MHz




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1304.30	34.64	---	150	V	0.0	-17.4	74.00	39.36
1304.30	---	25.00	150	V	0.0	-17.4	54.00	29.00
3242.30	40.40	---	200	V	68.0	-9.5	68.20	27.80
4626.10	---	31.76	150	H	307.0	-6.0	54.00	22.24
4626.10	41.30	---	150	H	307.0	-6.0	74.00	32.70
7664.00	47.90	---	200	H	64.0	1.3	74.00	26.10
7664.00	---	37.93	200	H	64.0	1.3	54.00	16.07
11489.40	44.82	---	150	V	0.0	2.3	74.00	29.18
11489.40	---	36.85	150	V	0.0	2.3	54.00	17.15
17575.00	56.90	---	200	V	356.0	8.9	68.20	11.30

Middle Channel: 5785MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2208.70	36.34	---	200	V	356.0	-13.6	74.00	37.66
2208.70	---	26.16	200	V	356.0	-13.6	54.00	27.84
3896.80	---	31.38	200	H	52.0	-7.4	54.00	22.62
3896.80	40.91	---	200	H	52.0	-7.4	74.00	33.09
8106.00	---	39.10	200	V	224.0	1.7	54.00	14.90
8106.00	47.89	---	200	V	224.0	1.7	74.00	26.11
11571.00	---	38.64	150	H	261.0	2.4	54.00	15.36
11571.00	45.15	---	150	V	22.0	2.4	74.00	28.85
13071.70	52.87	---	200	H	14.0	5.3	68.20	15.33
17471.30	57.51	---	150	V	4.0	8.8	68.20	10.69

High Channel: 5825MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2456.90	36.62	---	150	H	220.0	-12.6	68.20	31.58
3658.80	---	29.86	150	V	301.0	-8.2	54.00	24.14
3658.80	39.23	---	150	V	301.0	-8.2	74.00	34.77
5161.60	43.26	---	150	H	130.0	-4.8	68.20	24.94
8055.00	---	38.65	200	V	263.0	1.8	54.00	15.35
8055.00	47.90	---	200	V	263.0	1.8	74.00	26.10
11652.20	46.24	---	150	V	217.0	3.1	74.00	27.76
11652.20	---	39.19	150	V	217.0	3.1	54.00	14.81
17473.00	57.68	---	150	H	357.0	8.8	68.20	10.52


802.11ac20 Mode:

(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude


Low Channel: 5745MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1936.70	35.22	---	150	V	256.0	-14.7	68.20	32.98
3261.00	---	30.12	200	V	23.0	-9.4	54.00	23.88
3261.00	39.15	---	200	V	23.0	-9.4	74.00	34.85
6963.60	46.00	---	200	H	155.0	-0.1	68.20	22.20
9868.90	48.49	---	200	V	150.0	2.0	68.20	19.71
11489.00	45.95	---	150	V	205.0	2.8	74.00	28.05
11489.00	---	39.91	150	V	205.0	2.8	54.00	14.09
17972.80	---	47.94	150	V	0.0	8.8	54.00	6.06
17972.80	57.05	---	150	V	0.0	8.8	74.00	16.95


Middle Channel: 5785MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2397.40	37.27	---	150	V	311.0	-12.8	68.20	30.93
4661.80	---	32.12	200	V	4.0	-5.9	54.00	21.88
4661.80	42.44	---	200	V	4.0	-5.9	74.00	31.56
7402.20	---	36.59	150	V	112.0	0.8	54.00	17.41
7402.20	47.00	---	150	V	112.0	0.8	74.00	27.00
9819.60	48.11	---	150	H	98.0	2.0	68.20	20.09
11575.70	---	39.75	150	H	86.0	3.0	54.00	14.25
11575.70	48.10	---	150	H	86.0	3.0	74.00	25.90
17966.00	56.64	---	200	H	359.0	8.8	74.00	17.36
17966.00	---	48.11	200	H	359.0	8.8	54.00	5.89

High Channel: 5825MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2655.80	38.26	---	150	V	159.0	-11.7	68.20	29.94
4830.10	41.63	---	200	H	349.0	-5.5	74.00	32.37
4830.10	---	32.25	200	H	349.0	-5.5	54.00	21.75
6501.20	44.84	---	150	V	261.0	-1.2	68.20	23.36
9015.50	---	37.60	150	V	274.0	1.9	54.00	16.40
9015.50	47.74	---	150	V	274.0	1.9	74.00	26.26
11647.10	46.60	---	150	V	287.0	3.1	74.00	27.40
11647.10	---	39.16	150	V	287.0	3.1	54.00	14.84
17563.10	56.89	---	150	V	223.0	8.9	68.20	11.31


802.11n-HT20 Mode:

(Pre-scan with X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude


Low Channel: 5745MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2637.10	37.64	---	150	V	0.0	-11.8	68.20	30.56
4304.80	---	31.60	200	H	356.0	-6.5	54.00	22.40
4304.80	40.58	---	200	H	356.0	-6.5	74.00	33.42
6856.50	45.13	---	200	V	35.0	-0.4	68.20	23.07
9343.60	---	38.62	150	H	15.0	2.1	54.00	15.38
9343.60	48.12	---	150	H	15.0	2.1	74.00	25.88
11485.60	---	39.07	200	H	338.0	2.8	54.00	14.93
11485.60	48.01	---	200	H	338.0	2.8	74.00	25.99
17561.40	57.77	---	200	H	249.0	8.9	68.20	10.43


Middle Channel: 5785MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2667.70	38.90	---	150	H	192.0	-11.6	68.20	29.30
4462.90	40.90	---	150	V	155.0	-6.3	68.20	27.30
6695.00	45.21	---	200	V	40.0	-0.7	68.20	22.99
9858.70	48.17	---	150	V	103.0	2.0	68.20	20.03
11570.60	---	40.76	150	V	231.0	2.9	54.00	13.24
11570.60	47.33	---	150	V	231.0	2.9	74.00	26.67
17481.50	56.98	---	200	H	348.0	8.8	68.20	11.22

High Channel: 5825MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2295.40	37.62	---	200	H	308.0	-13.3	74.00	36.38
2295.40	---	29.62	200	H	308.0	-13.3	54.00	24.38
4092.30	---	31.90	150	V	349.0	-6.9	54.00	22.10
4092.30	41.34	---	150	V	349.0	-6.9	74.00	32.66
7698.00	---	38.99	150	V	198.0	1.3	54.00	15.01
7698.00	47.61	---	150	V	198.0	1.3	74.00	26.39
11650.50	---	38.53	200	H	283.0	3.1	54.00	15.47
11650.50	45.88	---	200	H	283.0	3.1	74.00	28.12
13053.00	52.52	---	150	V	0.0	5.3	68.20	15.68
17476.40	57.60	---	200	V	91.0	8.8	68.20	10.60


802.11ac40 Mode:

(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:


1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5755MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
2632.00	37.74	---	200	V	0.0	-11.8	68.20	30.46
4078.70	42.10	---	150	V	194.0	-6.9	74.00	31.90
4078.70	---	31.77	150	V	194.0	-6.9	54.00	22.23
6752.80	45.17	---	200	V	265.0	-0.6	68.20	23.03
9816.20	48.46	---	200	V	72.0	2.0	68.20	19.74
11511.10	46.94	---	200	V	358.0	2.8	74.00	27.06
11511.10	---	40.69	200	V	358.0	2.8	54.00	13.31
17603.90	57.41	---	200	V	0.0	8.9	68.20	10.79

High Channel: 5795MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
2064.20	36.02	---	150	V	325.0	-14.2	68.20	32.18
4078.70	---	31.93	150	H	321.0	-6.9	54.00	22.07
4078.70	40.84	---	150	H	321.0	-6.9	74.00	33.16
6501.20	45.28	---	200	V	187.0	-1.2	68.20	22.92
8531.00	48.07	---	200	V	35.0	1.4	68.20	20.13
11589.30	---	39.03	150	H	90.0	3.0	54.00	14.97
11589.30	46.00	---	150	H	90.0	3.0	74.00	28.00
17974.50	56.73	---	150	V	2.0	8.8	74.00	17.27
17974.50	---	47.36	150	V	2.0	8.8	54.00	6.64


802.11n-HT40 Mode:

(Pre-scan with X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude


Low Channel: 5755MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
2009.80	35.86	---	150	H	352.0	-14.4	68.20	32.34
3437.80	39.96	---	150	V	346.0	-9.0	68.20	28.24
4932.10	---	33.33	200	H	300.0	-5.3	54.00	20.67
4932.10	42.33	---	200	H	300.0	-5.3	74.00	31.67
7721.80	47.60	---	150	H	270.0	1.4	74.00	26.40
7721.80	---	37.81	150	H	270.0	1.4	54.00	16.19
11511.10	---	39.95	150	V	245.0	2.8	54.00	14.05
11511.10	46.78	---	150	V	245.0	2.8	74.00	27.22
17955.80	---	48.93	150	V	143.0	8.8	54.00	5.07
17955.80	57.10	---	150	V	143.0	8.8	74.00	16.90

High Channel: 5795MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2295.40	35.85	---	200	V	8.0	-13.3	74.00	38.15
2295.40	---	29.50	200	V	8.0	-13.3	54.00	24.50
4971.20	---	32.35	150	V	10.0	-5.2	54.00	21.65
4971.20	42.30	---	150	V	10.0	-5.2	74.00	31.70
8022.70	47.79	---	200	V	212.0	1.8	68.20	20.41
11589.30	---	39.87	200	H	1.0	3.0	54.00	14.13
11589.30	44.98	---	200	H	1.0	3.0	74.00	29.02
13059.80	52.33	---	150	H	199.0	5.3	68.20	15.87
17561.40	56.76	---	150	V	179.0	8.9	68.20	11.44


802.11ac80 Mode:

(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5775MHz




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
2295.40	---	30.60	200	H	49.0	-13.3	54.00	23.40
2295.40	38.08	---	200	H	49.0	-13.3	74.00	35.92
4964.40	---	32.59	200	V	148.0	-5.3	54.00	21.41
4964.40	42.03	---	200	V	148.0	-5.3	74.00	31.97
7575.60	---	37.60	150	V	253.0	1.1	54.00	16.40
7575.60	47.03	---	150	V	253.0	1.1	74.00	26.97
9846.80	48.41	---	150	V	358.0	2.0	68.20	19.79
11550.20	47.61	---	200	H	359.0	2.9	74.00	26.39
11550.20	---	40.06	200	H	359.0	2.9	54.00	13.94
17974.50	---	47.60	150	H	4.0	8.8	54.00	6.40
17974.50	57.12	---	150	H	4.0	8.8	74.00	16.88

18GHz-40GHz(5150-5250MHz Band):


Pre-scan with 802.11a, 802.11ac20, 802.11n-HT20, 802.11ac40, 802.11n-HT40 and 802.11 ac80 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11a mode in low channel 5240 in Z-axis of orientation was recorded.

Horizontal



Date: 22.OCT.2020 22:58:44

Vertical




Date: 22.OCT.2020 22:10:25

18GHz-40GHz(5725-5850MHz Band):


Pre-scan with 802.11a, 802.11ac20, 802.11n-HT20, 802.11ac40, 802.11n-HT40 and 802.11 ac80 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11a mode in low channel 5825 in Z-axis of orientation was recorded.

Horizontal



Date: 22.OCT.2020 22:25:18

Vertical



Date: 22.OCT.2020 22:28:10

Restricted Bands Emissions Test (5150-5250MHz Band):

Note:

1. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
2. Corrected Amplitude = Corrected Factor + Reading
3. Margin = Limit - Corrected. Amplitude

802.11a Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5180MHz								
5150.00	---	52.89	200.0	V	11.0	5.2	54.00	1.11
5150.00	59.17	---	200.0	V	11.0	5.2	74.00	14.83
High Channel: 5240MHz								
5350.00	56.16	---	200.0	V	332.0	5.7	74.00	17.84
5350.00	---	50.92	200.0	V	323.0	5.7	54.00	3.08

802.11ac20 Mode : (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5180MHz								
5150.00	56.36	---	150.0	V	58.0	5.2	74.00	17.64
5150.00	---	51.32	150.0	V	58.0	5.2	54.00	2.68
High Channel: 5240MHz								
5350.00	---	49.51	150.0	V	5.0	5.7	54.00	4.49
5350.00	56.01	---	150.0	V	5.0	5.7	74.00	17.99

802.11n-HT20 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5180MHz								
5150.00	56.30	---	150.0	V	31.0	5.2	74.00	17.70
5150.00	---	51.07	150.0	V	31.0	5.2	54.00	2.93
High Channel: 5240MHz								
5350.00	---	51.24	200.0	V	302.0	5.7	54.00	2.76
5350.00	56.43	---	200.0	V	302.0	5.7	74.00	17.57

802.11ac40 Mode : (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5190MHz								
5150.00	---	52.44	150.0	V	124.0	5.2	54.00	1.56
5150.00	59.97	---	150.0	V	124.0	5.2	74.00	14.03
High Channel: 5230MHz								
5350.00	57.35	---	150.0	V	114.0	5.7	74.00	16.65
5350.00	---	50.97	150.0	V	114.0	5.7	54.00	3.03

802.11n-HT40 Mode : (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5190MHz								
5150.00	55.95	---	150.0	V	81.0	5.2	74.00	18.05
5150.00	---	52.57	150.0	V	81.0	5.2	54.00	1.43
High Channel: 5230MHz								
5350.00	---	51.08	150.0	V	109.0	5.7	54.00	2.92
5350.00	54.81	---	150.0	V	109.0	5.7	74.00	19.19

802.11ac80 Mode : (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5210MHz								
5150.00	56.30	---	200.0	V	344.0	5.2	74.00	17.70
5150.00	---	52.44	200.0	V	344.0	5.2	54.00	1.56
5350.00	54.67	---	150.0	V	30.0	5.7	74.00	19.33
5350.00	---	51.18	150.0	V	30.0	5.7	54.00	2.82

Restricted Bands Emissions Test (5725-5850MHz Band):

Note:

1. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
2. Corrected Amplitude = Corrected Factor + Reading
3. Margin = Limit - Corrected. Amplitude

802.11a Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5745MHz								
5650.00	55.21	---	150.0	H	259.0	6.4	68.20	12.99
5700.00	53.54	---	200.0	V	276.0	6.5	105.20	51.66
5720.00	60.29	---	150.0	V	185.0	6.5	110.80	50.51
5725.00	61.87	---	200.0	V	58.0	6.5	122.20	60.33
High Channel: 5825MHz								
5850.00	57.53	---	150.0	H	306.0	6.7	122.20	64.67
5855.00	54.01	---	150.0	V	3.0	6.7	110.80	56.79
5875.00	55.17	---	150.0	V	12.0	6.8	105.20	50.03
5925.00	54.28	---	150.0	H	242.0	6.9	68.20	13.92

802.11ac20 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5745MHz								
5650.00	53.24	---	150.0	V	302.0	6.4	68.20	14.96
5700.00	53.86	---	150.0	V	197.0	6.5	105.20	51.34
5720.00	57.26	---	150.0	V	180.0	6.5	110.80	53.54
5725.00	58.25	---	150.0	V	147.0	6.5	122.20	63.95
High Channel: 5825MHz								
5850.00	53.22	---	150.0	H	157.0	6.7	122.20	68.98
5855.00	54.53	---	150.0	V	88.0	6.7	110.80	56.27
5875.00	53.75	---	150.0	H	307.0	6.8	105.20	51.45
5925.00	55.28	---	150.0	V	41.0	6.9	68.20	12.92

802.11n-HT20 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5745MHz								
5650.00	54.52	---	150.0	V	200.0	6.4	68.20	13.68
5700.00	54.08	---	150.0	V	0.0	6.5	105.20	51.12
5720.00	57.51	---	150.0	H	287.0	6.5	110.80	53.29
5725.00	59.34	---	150.0	V	0.0	6.5	122.20	62.86
High Channel: 5825MHz								
5850.00	54.39	---	150.0	V	11.0	6.7	122.20	67.81
5855.00	54.74	---	150.0	V	72.0	6.7	110.80	56.06
5875.00	55.85	---	150.0	H	128.0	6.8	105.20	49.35
5925.00	53.57	---	150.0	H	242.0	6.9	68.20	14.63

802.11ac40 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5755MHz								
5650.00	54.10	---	150.0	H	0.0	6.4	68.20	14.10
5700.00	55.35	---	150.0	V	9.0	6.5	105.20	49.85
5720.00	57.74	---	150.0	V	9.0	6.5	110.80	53.06
5725.00	58.45	---	150.0	H	280.0	6.5	122.20	63.75
High Channel: 5795MHz								
5850.00	55.55	---	150.0	H	0.0	6.7	122.20	66.65
5855.00	53.97	---	150.0	H	274.0	6.7	110.80	56.83
5875.00	54.00	---	150.0	H	358.0	6.8	105.20	51.20
5925.00	54.34	---	150.0	H	157.0	6.9	68.20	13.86

802.11n-HT40 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5755MHz								
5650.00	55.34	---	150.0	H	0.0	6.4	68.20	12.86
5700.00	55.03	---	150.0	V	206.0	6.5	105.20	50.17
5720.00	58.90	---	150.0	V	15.0	6.5	110.80	51.90
5725.00	62.52	---	150.0	V	15.0	6.5	122.20	59.68
High Channel: 5795MHz								
5850.00	53.93	---	150.0	H	0.0	6.7	122.20	68.27
5855.00	55.23	---	150.0	H	308.0	6.7	110.80	55.57
5875.00	53.45	---	150.0	H	292.0	6.8	105.20	51.75
5925.00	55.65	---	150.0	V	187.0	6.9	68.20	12.55

802.11ac80 Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 5775MHz								
5650.00	53.06	---	150.0	V	174.0	6.4	68.20	15.14
5700.00	56.64	---	150.0	V	73.0	6.5	105.20	48.56
5720.00	57.84	---	150.0	V	41.0	6.5	110.80	52.96
5725.00	57.86	---	150.0	V	73.0	6.5	122.20	64.34
5850.00	55.20	---	150.0	V	207.0	6.7	122.20	67.00
5855.00	55.11	---	150.0	H	341.0	6.7	110.80	55.69
5875.00	53.51	---	150.0	H	353.0	6.8	105.20	51.69
5925.00	54.29	---	150.0	V	11.0	6.9	68.20	13.91

FCC §15.407(a) & §15.407(e) – EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure


1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	21.2°C~22.8°C
Relative Humidity:	45%~49%
ATM Pressure:	101.1kPa~101.2 kPa

The testing was performed by Jack Jiao from 2020-10-01 to 2020-12-01.

Test Result: Compliant

5150-5250 MHz:

Test mode	Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
802.11a	Low	5180	21.82	17.07
	Middle	5200	21.76	17.07
	High	5240	21.88	17.07
802.11ac20	Low	5180	22.00	18.16
	Middle	5200	21.82	18.22
	High	5240	22.00	18.22
802.11n-HT20	Low	5180	22.06	18.22
	Middle	5200	22.00	18.16
	High	5240	21.94	18.22
802.11ac40	Low	5190	40.64	36.43
	High	5230	40.64	36.43
802.11n-HT40	Low	5190	40.40	36.43
	High	5230	40.28	36.43
802.11ac80	Low	5210	82.48	75.75


5725-5850MHz:

Test mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
802.11a	Low	5745	16.35	17.07	≥0.5
	Middle	5785	16.41	17.01	≥0.5
	High	5825	16.47	17.13	≥0.5
802.11ac20	Low	5745	17.62	18.22	≥0.5
	Middle	5785	17.62	18.16	≥0.5
	High	5825	17.62	18.16	≥0.5
802.11n-HT20	Low	5745	17.68	18.10	≥0.5
	Middle	5785	17.43	18.16	≥0.5
	High	5825	17.49	18.16	≥0.5
802.11ac40	Low	5755	36.19	36.43	≥0.5
	High	5795	36.19	36.55	≥0.5
802.11n-HT40	Low	5755	36.19	36.43	≥0.5
	High	5795	36.19	36.43	≥0.5
802.11ac80	Low	5775	75.99	75.75	≥0.5


5150-5250 MHz Band:

26 Bandwidth & 99% Occupied Bandwidth


802.11a mode, 5180MHz




802.11a mode, 5200MHz




802.11a mode, 5240MHz




802.11ac20 mode, 5180MHz




802.11 ac20 mode, 5200MHz




802.11 ac20 mode, 5240MHz




802.11n-HT20 mode, 5180MHz




802.11n-HT20 mode, 5200MHz




802.11 ac40 mode, 5230MHz




802.11n-HT40 mode, 5190MHz



802.11n-HT40 mode, 5230MHz




802.11ac80 mode, 5210MHz




5725-5850 MHz Band

6 Bandwidth:


802.11a mode, 5745MHz




802.11a mode, 5785MHz




802.11a mode, 5825MHz




802.11ac20 mode, 5745MHz




802.11 ac20 mode, 5785MHz




802.11 ac20 mode, 5825MHz




802.11n-HT20 mode, 5745MHz




802.11n-HT20 mode, 5785MHz




802.11n-HT20 mode, 5825MHz




802.11ac40 mode, 5755MHz




802.11 ac40 mode, 5795MHz




802.11n-HT40 mode, 5755MHz



802.11n-HT40 mode, 5795MHz




802.11ac80 mode, 5775MHz




99% Occupied Bandwidth:


802.11a mode, 5745MHz




802.11a mode, 5785MHz




802.11a mode, 5825MHz




802.11ac20 mode, 5745MHz




802.11 ac20 mode, 5785MHz




802.11 ac20 mode, 5825MHz




802.11n-HT20 mode, 5745MHz




802.11n-HT20 mode, 5785MHz




802.11n-HT20 mode, 5825MHz




802.11ac40 mode, 5755MHz




802.11 ac40 mode, 5795MHz




802.11n-HT40 mode, 5755MHz



802.11n-HT40 mode, 5795MHz



802.11n-ac80 mode, 5775MHz



FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER

Applicable Standard

According to §15.407(a)(1)


(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to §15.407(a) (3)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	22.8°C
Relative Humidity:	49%
ATM Pressure:	101.2 kPa

The testing was performed by Jack Jiao on 2020-10-01.

Test Mode: Transmitting

Test Mode: Transmitting

Test mode	Band	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)	Limit (dBm)	Result
802.11a	5150-5250 MHz	Low	5180	19.54	24	PASS
		Middle	5200	19.27	24	PASS
		High	5240	18.94	24	PASS
	5725-5850 MHz	Low	5745	18.30	30	PASS
		Middle	5785	17.67	30	PASS
		High	5825	16.99	30	PASS
802.11n-HT20	5150-5250 MHz	Low	5180	18.91	24	PASS
		Middle	5200	18.97	24	PASS
		High	5240	18.79	24	PASS
	5725-5850 MHz	Low	5745	17.96	30	PASS
		Middle	5785	17.28	30	PASS
		High	5825	16.46	30	PASS
802.11n-HT40	5150-5250 MHz	Low	5190	19.07	24	PASS
		High	5230	19.00	24	PASS
	5725-5850 MHz	Low	5755	17.91	30	PASS
		High	5795	17.96	30	PASS
802.11ac20	5150-5250 MHz	Low	5180	19.01	24	PASS
		Middle	5200	18.96	24	PASS
		High	5240	18.64	24	PASS
	5725-5850 MHz	Low	5745	17.88	30	PASS
		Middle	5785	17.26	30	PASS
		High	5825	16.81	30	PASS
802.11ac40	5150-5250 MHz	Low	5190	19.12	24	PASS
		High	5230	19.15	24	PASS
	5725-5850 MHz	Low	5755	18.20	30	PASS
		High	5795	17.51	30	PASS
802.11ac80	5150-5250 MHz	/	5210	19.14	24	PASS
	5725-5850 MHz	/	5775	17.65	30	PASS

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY

Applicable Standard

According to §15.407(a)(1)

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to §15.407(a) (3)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

The measurements are base on FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices section F: Maximum power spectral density (PPSD)

Test Data

Environmental Conditions

Temperature:	22.8°C
Relative Humidity:	49%
ATM Pressure:	101.2 kPa

The testing was performed by Jack Jiao on 2020-10-01.

*Test Mode: Transmitting***5150MHz-5250MHz:**


Mode	Channel	Frequency (MHz)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
802.11a	Low	5180	2.21	11	PASS
	Middle	5200	2.22	11	PASS
	High	5240	1.79	11	PASS
802.11ac20	Low	5180	1.72	11	PASS
	Middle	5200	1.73	11	PASS
	High	5240	1.46	11	PASS
802.11n20	Low	5180	1.75	11	PASS
	Middle	5200	1.58	11	PASS
	High	5240	1.24	11	PASS
802.11ac40	Low	5190	-1.24	11	PASS
	High	5230	-1.40	11	PASS
802.11n40	Low	5190	-0.85	11	PASS
	High	5230	-1.18	11	PASS
802.11ac80	/	5210	-4.29	11	PASS

5725MHz-5850MHz:


Mode	Channel	Frequency MHz	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
802.11a	Low	5745	-0.98	30	PASS
	Middle	5785	-1.30	30	PASS
	High	5825	-2.33	30	PASS
802.11ac20	Low	5745	-1.09	30	PASS
	Middle	5785	-1.94	30	PASS
	High	5825	-2.37	30	PASS
802.11n20	Low	5745	-1.13	30	PASS
	Middle	5785	-1.79	30	PASS
	High	5825	-2.66	30	PASS
802.11ac40	Low	5755	-3.99	30	PASS
	High	5795	-4.37	30	PASS
802.11n40	Low	5755	-3.99	30	PASS
	High	5795	-4.88	30	PASS
802.11ac80	/	5775	-7.13	30	PASS

5150MHz-5250MHz Band:


802.11a mode, Power spectral density-5180MHz




802.11a mode, Power spectral density-5200MHz




802.11a mode, Power spectral density-5240MHz




802.11ac20 mode, Power spectral density-5180MHz




802.11 ac20 mode, Power spectral density-5200MHz




802.11ac20 mode, Power spectral density-5240MHz




802.11n-HT20 mode, Power spectral density-5180MHz




802.11n-HT20 mode, Power spectral density-5200MHz




802.11n-HT20 mode, Power spectral density-5240MHz




802.11ac40 mode, Power spectral density-5190MHz




802.11 ac40 mode, Power spectral density-5230MHz




802.11n-HT40 mode, Power spectral density-5190MHz



802.11n-HT40 mode, Power spectral density-5230MHz




802.11n- ac80 mode, Power spectral density-5210MHz




5725MHz-5850 MHz Band:


802.11a mode, Power spectral density-5745MHz




802.11a mode, Power spectral density-5785MHz




802.11a mode, Power spectral density-5825MHz




802.11ac20 mode, Power spectral density-5745MHz




802.11 ac20 mode, Power spectral density-5785MHz




802.11 ac20 mode, Power spectral density-5825MHz




802.11n-HT20 mode, Power spectral density-5745MHz




802.11n-HT20 mode, Power spectral density-5785MHz




802.11n-HT20 mode, Power spectral density-5825MHz




802.11ac40 mode, Power spectral density-5755MHz




802.11 ac40 mode, Power spectral density-5795MHz




802.11n-HT40 mode, Power spectral density-5755MHz



802.11n-HT40 mode, Power spectral density-5795MHz



802.11 ac80 mode, Power spectral density-5775MHz



Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******