




99% Bandwidth:






GFSK DH5 Channel 0




GFSK DH5 Channel 39




GFSK DH5 Channel 78


 $\pi/4$ DQPSK_2-DH5_Channel 0 $\pi/4$ DQPSK_2-DH5_Channel 39 $\pi/4$ DQPSK_2-DH5_Channel 78



8DPSK 3-DH5 Channel 0




8DPSK 3-DH5 Channel 39



8DPSK 3-DH5 Channel 78



20dB Bandwidth:



CTC Laboratories, Inc.




Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China


Tel.: (86)755-27521059

Fax: (86)755-27521011


Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>


 $\pi/4$ DQPSK_2-DH5_Channel 0 $\pi/4$ DQPSK_2-DH5_Channel 39 $\pi/4$ DQPSK_2-DH5_Channel 78



8DPSK 3-DH5 Channel 0



8DPSK 3-DH5 Channel 39



8DPSK 3-DH5 Channel 78




3.6. Channel Separation

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)

Test Item	Limit	Frequency Range (MHz)
Channel Separation	>25kHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Set RBW = 100 kHz.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

Test Mode


Please refer to the clause 2.4.

Test Result

Test Mode	Frequency (MHz)	Carrier Frequencies Separation (MHz)	Limit (MHz)	Verdict
GFSK	Hop_2441	1.0483	0.677	Pass
$\pi/4$ -DQPSK	Hop_2441	1.1617	0.898	Pass
8-DPSK	Hop_2441	1.0021	0.873	Pass



Test plot as follows:



CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>




3.7. Number of Hopping Channel

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(iii)

Section	Test Item	Limit
15.247 (a)(iii) RSS-247 5.1 d	Number of Hopping Channel	≥ 15

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Peak Detector: RBW=100 kHz, VBW $\geq$ RBW, Sweep time= Auto.

Test Mode




Please refer to the clause 2.4.

Test Result

Test Mode	Channel Number	Limit	Verdict
GFSK	79	≥ 15	Pass
$\pi/4$ -DQPSK	79	≥ 15	Pass
8-DPSK	79	≥ 15	Pass



Test plot as follows:

Hopping Plot
GFSKHopping Plot
 $\pi/4$ DQPSKHopping Plot
8DPSK




3.8. Dwell Time

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(iii)

Section	Test Item	Limit
15.247 (a)(iii) RSS-247 5.1 d	Average Time of Occupancy	0.4 sec

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Spectrum Setting: RBW=1MHz, VBW $\geq$ RBW.
 - (2) Use video trigger with the trigger level set to enable triggering only on full pulses.
 - (3) Sweep Time is more than once pulse time.
 - (4) Set the center frequency on any frequency would be measure and set the frequency span to zero.
 - (5) Measure the maximum time duration of one single pulse.
 - (6) Set the EUT for packet transmitting.

Test Mode

Please refer to the clause 2.4.

**Test Result**

Test Mode	Channel	Frequency (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (ms)	Limit (second)	Verdict
GFSK	DH1	2441	0.382	122.1	31.60	≤0.40	Pass
	DH3	2441	1.620	259.2	31.60		
	DH5	2441	2.864	305.5	31.60		
π/4-DQPSK	2DH1	2441	0.386	123.6	31.60	≤0.40	Pass
	2DH3	2441	1.656	265.0	31.60		
	2DH5	2441	2.896	308.9	31.60		
8-DPSK	3DH1	2441	0.389	124.4	31.60	≤0.40	Pass
	3DH3	2441	1.632	261.1	31.60		
	3DH5	2441	2.896	308.9	31.60		


Note: 1DH1/2DH1/3DH1 Total of Dwell = Pulse Time*(1600/2)*31.6/79

1DH3/2DH3/3DH3 Total of Dwell = Pulse Time*(1600/4)*31.6/79


1DH5/2DH5/3DH5 Total of Dwell = Pulse Time*(1600/6)*31.6/79




Test plot as follows:






Pulse Width
GFSK_DH1






Pulse Width
GFSK_DH3



Pulse Width
GFSK_DH5

Pulse Width
 $\pi/4$ DQPSK 2-DH1Pulse Width
 $\pi/4$ DQPSK 2-DH3Pulse Width
 $\pi/4$ DQPSK 2-DH5

Pulse Width
8DPSK_3-DH1Pulse Width
8DPSK_3-DH3Pulse Width
8DPSK_3-DH5




3.9. Peak Output Power

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1)

Section	Test Item	Limit	Frequency Range (MHz)
FCC CFR 47 Part15.247 (b)(1)	Maximum Conducted Output Power	Hopping Channels $\geq$ 75, Power <1W(30dBm); Others <125mW(21dBm)	2400~2483.5

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Set RBW > 20dB Bandwidth.
 - (2) Set VBW $\geq$ RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.
 - (6) Span = Approximately five times the 20dB bandwidth, centered on a hopping channel.

Test Mode




Please refer to the clause 2.4.


Test Result

Test Mode	Frequency (MHz)	Conducted Output Power (dBm)	Limit (dBm)	Verdict
GFSK	2402	7.097	≤ 30	Pass
	2441	6.561	≤ 30	Pass
	2480	5.977	≤ 30	Pass
$\pi/4$ -DQPSK	2402	6.833	≤ 30	Pass
	2441	5.980	≤ 30	Pass
	2480	6.962	≤ 30	Pass
8-DPSK	2402	7.360	≤ 30	Pass
	2441	6.461	≤ 30	Pass
	2480	7.474	≤ 30	Pass




Test plot as follows:


Peak Output Power
GFSK Channel 0Peak Output Power
GFSK Channel 39Peak Output Power
GFSK Channel 78




Peak Output Power
 $\pi/4$ DQPSK Channel 0




Peak Output Power
 $\pi/4$ DQPSK Channel 39




Peak Output Power
 $\pi/4$ DQPSK Channel 78



Peak Output Power
8DPSK Channel 0



Peak Output Power
8DPSK Channel 39



Peak Output Power
8DPSK Channel 78




3.10. Duty Cycle

Limit

None, for report purposes only.

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
3. Spectrum Setting:
Set analyzer center frequency to test channel center frequency.
Set the span to 0Hz.
Set the RBW to 10MHz.
Set the VBW to 10MHz.
Detector: Peak.
Sweep time: Auto.
Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

Test Mode


Please refer to the clause 2.4.

Test Result


Test Mode	Frequency (MHz)	Transmission Duration (ms)	Transmission Period (ms)	Duty Cycle (%)	1/T Minimum VBW (kHz)	Final Setting for VBW (kHz)
GFSK	2402	2.887	3.749	77.01	0.35	1
	2441	2.885	3.749	76.96	0.35	1
	2480	2.885	3.747	77.00	0.35	1
$\pi/4$ -DQPSK	2402	2.887	3.749	77.01	0.35	1
	2441	2.887	3.749	77.01	0.35	1
	2480	2.887	3.747	77.05	0.35	1
8-DPSK	2402	2.889	3.747	77.11	0.35	1
	2441	2.889	3.747	77.11	0.35	1
	2480	2.889	3.749	77.07	0.35	1




Test plot as follows:






GFSK(DH5)_Channel 0




GFSK(DH5)_Channel 39




GFSK(DH5)_Channel 78


 $\pi/4$ DQPSK(2-DH5) Channel 0 $\pi/4$ DQPSK(2-DH5) Channel 39 $\pi/4$ DQPSK(2-DH5) Channel 78



8DPSK(3-DH5) Channel 0



8DPSK(3-DH5) Channel 39



8DPSK(3-DH5) Channel 78



3.11. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i)

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result

The directional gain of the antenna is less than 6dBi, please refer to the EUT internal photographs antenna photo.

*****THE END*****