



# FCC 47 CFR MPE REPORT

MMD Hong Kong Holding Limited

CAR AUDIO SYSTEM

Model Number: CE235BT

Additional Model: TAC8338, TAC8338/10, TAC8338/12, TAC8338/XX,  
CE235DAB, CE235BT/05, CE235BT/13, CE235BT/XX, CE235DAB/XX

("X" is variable, and it can be letter A to Z, 0 to 9; "-", "/" or blank)

FCC ID: 2AR2S-CE235BTN

|                          |  |
|--------------------------|--|
| Applicant:               | MMD Hong Kong Holding Limited  |
| Address:                 | Units 1208-11, 12th Floor, C-Bons International Center,<br>108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong |
|                          |  |
| Prepared By:             | EST Technology Co., Ltd.<br>Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong,<br>China           |
| Tel: 86-769-83081888-808 |  |

|                 |                               |
|-----------------|-------------------------------|
| Report Number:  | ESTE-R2405055                 |
| Date of Test:   | Apr. 19, 2024 ~ May. 07, 2024 |
| Date of Report: | May. 10, 2024                 |

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6  |
| 3.0-30                | 1842/f                            | 4.89/f                            | (900/f)*                                | 6  |
| 30-300                | 61.4                              | 0.163                             | 1.0                                     | 6  |
| 300-1500              |                                   |                                   | F/300                                   | 6  |
| 1500-10000            |                                   |                                   | 5                                       | 6  |

##### (b) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30   |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                | 30   |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30   |
| 300-1500              |                                   |                                   | F/1500                                  | 30   |
| 1500-10000            |                                   |                                   | 1.0                                     | 30   |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2\text{m}$ , as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

| Mode           | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) |
|----------------|-----------------|-------------------------|------------------------|
| GFSK           | 2402            | 9.39                    | 8.690                  |
|                | 2441            | 7.3                     | 5.370                  |
|                | 2480            | 4.83                    | 3.041                  |
| $\pi/4$ -DQPSK | 2402            | 9.37                    | 8.650                  |
|                | 2441            | 7.23                    | 5.284                  |
|                | 2480            | 4.78                    | 3.006                  |
| 8-DPSK         | 2402            | 9.35                    | 8.610                  |
|                | 2441            | 7.21                    | 5.260                  |
|                | 2480            | 4.75                    | 2.985                  |

## 3. Calculated Result and Limit

| Mode             | Peak output power (dBm) | Target power (dBm) | MAX Target power (dBm) | Antenna gain |          | Power Density (S) (mW/cm <sup>2</sup> ) | Limited of Power Density (S) (mW/cm <sup>2</sup> ) | Test Result |
|------------------|-------------------------|--------------------|------------------------|--------------|----------|---|--|-------------|
|                  |                         |                    |                        | (dBi)        | (Linear) |   |  |             |
| <b>2.4G Band</b> |                         |                    |                        |              |          |   |  |             |
| GFSK             | 9.39                    | 9±1                | 10                     | -1.81        | 0.659    | 0.00131                                 | 1  | Complies    |
| $\pi/4$ -DQPSK   | 9.37                    | 9±1                | 10                     | -1.81        | 0.659    | 0.00131                                 | 1  | Complies    |
| 8-DPSK           | 9.35                    | 9±1                | 10                     | -1.81        | 0.659    | 0.00131                                 | 1  | Complies    |

**End of Test Report**