

# RF EXPOSURE EVALUATION REPORT

**Product Name:** Soundbar Speaker

**Trade Mark:**  or PHILIPS

**HVIN:** HTL3320/37

**Model No.:** HTL3320/37

**Add. Model No.:** HTL3320/98, HTL3320/10, HTL3320/05, HTL3320/12, HTL3320/00, HTL3320/xx, HTL3325/98, HTL3325/37, HTL3325/10, HTL3325/05, HTL3325/12, HTL3325/00, HTL3325/xx (/xx= blank or /00 to /99, denoted for different country destination)

**Report Number:** 200722005RFC-3

**Test Standards:** FCC 47 CFR Part 1 Subpart I  
RSS-102 Issue 5

**FCC ID:** 2AR2SHTL3320

**IC:** 24589-HTL3320

**Test Result:** PASS

**Date of Issue:** August 25, 2020

Prepared for:

**MMD Hong Kong Holding Limited**  
**Units 1006-1007, 10th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong, China**

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China**

**TEL: +86-755-2823 0888**

**FAX: +86-755-2823 0886**

Prepared by:

*Ryan Zhou*

Ryan Zhou  
Senior Project Engineer

Reviewed by:

*Kevin Liang*

Kevin Liang  
Assistant Manager

Approved by:

*Billy Li*

Billy Li  
Technical Director

Date:

August 25, 2020

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.0

**Version**

Version No.	Date	Description
V1.0	August 25, 2020	Original



## CONTENTS


<b>1. GENERAL INFORMATION</b>	<b>4</b>
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	5
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	5
1.6 DEVIATION FROM STANDARDS	5
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	5
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
<b>2. EQUIPMENT LIST</b>	<b>5</b>
<b>3. MPE EVALUATION</b>	<b>6</b>
3.1 REFERENCE DOCUMENTS FOR EVALUATION	6
3.2 MPE COMPLIANCE REQUIREMENT	6
3.2.1 LIMITS	6
3.2.2 TEST PROCEDURE	7
3.3 MPE CALCULATION METHOD	7
3.4 MPE CALCULATION RESULTS	7
3.4.1 FOR BT & 2.4GHZ WIRELESS DIGITAL AUDIO	7
3.4.2 SIMULTANEOUS MULTI-BAND TRANSMISSION MPE ANALYSIS	8
<b>APPENDIX 1 PHOTOS OF TEST SETUP</b>	<b>9</b>
<b>APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS</b>	<b>9</b>

# 1. GENERAL INFORMATION

## 1.1 CLIENT INFORMATION

<b>Applicant:</b>	MMD Hong Kong Holding Limited
<b>Address of Applicant:</b>	Units 1006-1007,10th Floor, C-Bons International Center,108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong, China
<b>Manufacturer:</b>	MMD Hong Kong Holding Limited
<b>Address of Manufacturer:</b>	Units 1006-1007,10th Floor, C-Bons International Center,108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong, China
<b>Factories:</b>	Zhong shan City Richsound Electronic Industrial Ltd
<b>Address of Factories:</b>	No.16, East Shagang Road, Gangkou, Zhongshan, Guangdong, China

## 1.2 EUT INFORMATION

<b>Product Name:</b>	Soundbar Speaker	
<b>HVIN:</b>	HTL3320/37	
<b>Model No. :</b>	HTL3320/37	
<b>Add. Model No. :</b>	HTL3320/98, HTL3320/10, HTL3320/05, HTL3320/12, HTL3320/00, HTL3320/xx , HTL3325/98, HTL3325/37, HTL3325/10, HTL3325/05, HTL3325/12, HTL3325/00, HTL3325/xx (/xx= blank or /00 to /99, denoted for different country destination)	
<b>Trade Mark:</b>	 or PHILIPS	
<b>DUT Stage:</b>	Identical Prototype	
<b>EUT Supports Function:</b>	2.4 GHz ISM Band:	Bluetooth V4.2
		2.4GHz Wireless Digital Audio
<b>Sample Received Date:</b>	July 22, 2020	
<b>Sample Tested Date:</b>	July 31, 2020 to August 17, 2020	
<b>Note:</b> The additional model HTL3320/98, HTL3320/10, HTL3320/05, HTL3320/12, HTL3320/00, HTL3320/xx , HTL3325/98, HTL3325/37, HTL3325/10, HTL3325/05, HTL3325/12, HTL3325/00, HTL3325/xx (/xx= blank or /00 to /99, denoted for different country destination) is identical with the test model HTL3320/37 except the model number and trade mark for marketing purpose.		

## 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

<b>For BT</b>	
<b>Frequency Band:</b>	2400 MHz to 2483.5 MHz
<b>Frequency Range:</b>	2402 MHz to 2480 MHz
<b>Bluetooth Version:</b>	Bluetooth BR + EDR
<b>Modulation Technique:</b>	Frequency Hopping Spread Spectrum(FHSS)
<b>Type of Modulation:</b>	GFSK, π/4DQPSK
<b>Number of Channels:</b>	79
<b>Channel Separation:</b>	1 MHz
<b>Hopping Channel Type:</b>	Adaptive Frequency Hopping Systems
<b>Antenna Type:</b>	PCB Antenna
<b>Antenna Gain:</b>	-2.0 dBi
<b>Maximum Peak Power:</b>	1.240 dBm

For 2.4GHz Wireless Digital Audio	
Frequency Range:	2404.5 MHz to 2479.5 MHz
Type of Modulation:	GFSK
Number of Channels:	16
Channel Separation:	5 MHz
Antenna Type:	Internal Integral Antenna
Antenna Gain:	0 dBi
Maximum Peak Power:	-13.547dBm
Frequency Range:	2404.5 MHz to 2479.5 MHz

### 1.4 OTHER INFORMATION

Test channels for 2.4GHz Wireless Digital Audio				
Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2404.5 MHz to 2479.5 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 8	Channel 15
		2404.5 MHz	2444.5 MHz	2479.5 MHz

Test channels for BT				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
GFSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 39	Channel 78
$\pi$ /4DQPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	2402 MHz	2441 MHz	2480 MHz
		Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz

### 1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

**FCC 47 CFR Part 1 Subpart I**  
**RSS-102 Issue 5**

All test items have been performed and recorded as per the above standards

### 1.6 DEVIATION FROM STANDARDS

None.

### 1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

### 1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 2. EQUIPMENT LIST

Please refer to the RF test report.

### **Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.0

### 3. MPE EVALUATION

#### 3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	RSS-102 Issue 5	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
3	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

#### 3.2 MPE COMPLIANCE REQUIREMENT

##### 3.2.1 Limits

##### 3.2.1.1 FCC 47 CFR Part 1 Subpart I

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

##### Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

##### Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

**Note:** f = frequency in MHz: \* = Plane-wave equivalent power density.

### 3.2.1.2 RSS-102 Issue 5

According to RSS-102 Issue 5, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

According to RSS-102 Issue 5, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz<sup>6</sup> and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

### 3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 3.3 MPE CALCULATION METHOD

### FCC 47 CFR Part 1 Subpart I

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

## 3.4 MPE CALCULATION RESULTS

**Note:** For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

### 3.4.1 For BT & 2.4GHz Wireless Digital Audio

For BT function, operating at 2402MHz to 2480 MHz for GFSK,  $\pi/4$  DQPSK and

For 2.4GHz Wireless Digital Audio function, operating at 2404.5MHz to 2479.5 MHz for GFSK.

#### 3.4.2.1 Antenna Type:

**BT:** PCB Antenna

**2.4GHz Wireless Digital Audio:** Internal Integral Antenna

#### 3.4.2.2 Antenna Gain:

**BT:** -2.0dBi

**2.4GHz Wireless Digital Audio:** 0dBi

## Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.0

**3.4.2.3 Results for FCC 47 CFR Part 1 Subpart I**

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)	(dB)	(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	
BT	2402-2480	0	2	-2.0	0	1.0	1	0.000199
2.4GHz Wireless Digital Audio	2404.5-2479.5	-17	2	0	-15	0.03	1	0.000006

**3.4.2.4 Results for RSS-102 Issue 5**

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	Limit
	(MHz)	(dBm)	(dB)	(dBi)	(dBm)	(W)	(W)
BT	2402-2480	0	2	-2.0	0.0	0.001	2.6764
2.4GHz Wireless Digital Audio	2404.5-2479.5	-17	2	0	-15	0.00003	2.6783

**3.4.2 Simultaneous Multi-band Transmission MPE Analysis**

**3.4.4.1 List of Mode for Simultaneous Multi-band Transmission**

No.	Configurations	Support/Not Support
1	2.4GHz Wireless Digital Audio+ BT	Support

**3.4.4.2 Results for transmit simultaneously**

**FCC 47 CFR Part 1 Subpart I**

No.	Configurations	Maximum MPE Value			Limits
		2.4GHz Wireless Digital Audio	BT	Transmit simultaneously	
1	2.4GHz Wireless Digital Audio + BT	0.000006	0.000199	<b>0.000205</b>	1

**Note:**

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

$$\text{Transmit simultaneously MPE} = \Sigma \text{ of MPE ratios}$$

$$\text{MPE ratios} = \text{Field strengths or power density} / \text{MPE limit at the test frequency}$$

**RSS-102 Issue 5**

No.	Configurations	Maximum MPE Value			Limits
		2.4GHz Wireless Digital Audio	BT	Transmit simultaneously	
1	2.4GHz Wireless Digital Audio+ BT	0.0000112	0.000374	<b>0.0003852</b>	1

**Note:**

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

$$\text{Transmit simultaneously MPE} = \Sigma \text{ of MPE ratios}$$

$$\text{MPE ratios} = \text{Field strengths or power density} / \text{MPE limit at the test frequency}$$



## APPENDIX 1 PHOTOS OF TEST SETUP

N/A

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

\*\*\* End of Report \*\*\*

---

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---

---