

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	Micro Music System
<b>Model Number</b>	TAM4205/37, M4205/37, TAM4205x/yy, M4205x/yy (x = A -Z or blank, for different color or package; yy = 00 - 99, for country code)
<b>FCC ID</b>	2AR2STAM4205
<b>Antenna gain (Max)</b>	0dBi
<b>Operation Frequency</b>	2402-2480MHz
<b>Input Rating</b>	AC 120V 60Hz
<b>Classification Per Stipulated Test Standard</b>	§15.247(i), §2.1093
<b>Kind of Device: Bluetooth Ver.5.0</b>	
<b>Modulation</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK
<b>Max. output power</b>	2.69dBm(0.001858W)

### Test Requirement:

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

## 1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = Numeric gain of the antenna relative to isotropic antenna

$\pi$ =3.1416

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## 2 Measurement Result

Antenna gain:0 dBi

BT DSS:

Transmit Frequency(MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
2.402	GFSK	0.51	0±1	1	1.259	0	1.000	0.0002505	1
2.441	GFSK	0.04	0±1	1	1.259	0	1.000	0.0002505	1
2.480	GFSK	0.19	0±1	1	1.259	0	1.000	0.0002505	1
2.402	Π/4-DQ PSK	2.12	2±1	3	1.995	0	1.000	0.0003969	1
2.441	Π/4-DQ PSK	1.88	2±1	3	1.995	0	1.000	0.0003969	1
2.480	Π/4-DQ PSK	1.60	2±1	3	1.995	0	1.000	0.0003969	1
2.402	8DPSK	2.69	2±1	3	1.995	0	1.000	0.0003969	1
2.441	8DPSK	2.11	2±1	3	1.995	0	1.000	0.0003969	1
2.480	8DPSK	2.00	2±1	3	1.995	0	1.000	0.0003969	1

Signature:

A handwritten signature in black ink is written over a purple circular stamp. The stamp contains the text "EMTEK (HONGGUAN) CO., LTD." around the top inner edge and "TESTING" at the bottom. In the center of the stamp is a stylized logo consisting of a circle with a checkmark and a downward-pointing arrow.

Sam Lv

Date: 2020-08-07