



Test Report No.:
FCC2023-0049-H

RF Test Report

EUT : **Micro Music System**

MODEL : **TAM8905/37**

ADDITIONAL MODEL : **See section 2.1**

BRAND NAME : **PHILIPS**

APPLICANT : **MMD Hong Kong Holding Limited**

Classification Of Test : **N/A**

CVC Testing Technology Co., Ltd.



CVC Testing Technology Co., Ltd.

Test Report No.: FCC2023-0049-H

Page 2 of 10

| | | | |
|---|---|--|-------------------------|
| Applicant | | Name : MMD Hong Kong Holding Limited | |
| | | Address : Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong | |
| Manufacturer | | Name : MMD Hong Kong Holding Limited | |
| | | Address : Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong | |
| Equipment Under Test | | Name : Micro Music System | |
| | | Model/Type: TAM8905/37 | |
| | | Additional Model: See section 2.1 | |
| | | Brand : PHILIPS | |
| | | Serial NO.: N/A | |
| | | Sample NO.: HS2306280027 | |
| Date of Receipt. | 2023-06-28 | Date of Testing | 2023-07-01 ~ 2023-07-20 |
| Test Specification | | Test Result | |
| FCC Part 2 (Section 2.1091) KDB 447498 D04 IEEE C95.1 | | PASS | |
| Evaluation of Test Result | The equipment under test was found to comply with the requirements of the standards applied. | | |
| | Seal of CVC Issue Date: 2023-07-21 | | |
| Tested by:  Lu Wei Ji Name Signature | Reviewed by:  Xu Zhen Fei Name Signature | Approved by:  Chen Hua Wen Name Signature | |
| Other Aspects: NONE. | | | |
| Abbreviations:OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested | | | |

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



TABLE OF CONTENTS

| | |
|--|----------|
| RELEASE CONTROL RECORD | 4 |
| 1. GENERAL INFORMATION | 5 |
| 2. RF EXPOSURE LIMIT | 6 |
| 3. CLASSIFICATION | 8 |
| 4. ANTENNA GAIN | 8 |
| 5. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER | 9 |



RELEASE CONTROL RECORD

| ISSUE NO. | REASON FOR CHANGE | DATE ISSUED |
|----------------|-------------------|-------------|
| FCC2023-0049-H | Original release | 2023-07-21 |



1. GENERAL INFORMATION

| | |
|---|--|
| PRODUCT | Micro Music System |
| MODEL | TAM8905/37 |
| ADDITIONAL MODEL | TAM8905,M8905,TAM8905/10,TAM8905/12,TAM8905/98,TAM8905/67,M8905/37,TAM8905x/yy, M8905x/yy (x = A-Z or blank, for different color or package; yy = 00 - 99, for country code) |
| FCC ID | 2AR2STAM8905 |
| STATUS OF EUT | Engineering Prototype |
| POWER SUPPLY | AC 120V,60Hz |
| OPERATING FREQUENCY | 2402MHz~2480MHz for BT 2412MHz ~ 2462MHz for 2.4G WiFi 5180MHz ~ 5825MHz for 5G WiFi |
| MAX AVERAGE POWER | 3.15 dBm for BT 12.66 dBm for 2.4G WIFI 10.99 dBm for 5G WIFI |
| ANTENNA TYPE AND GAIN (Remark 4) | BT: PIFA Antenna, with 2.50dBi gain 2.4G WiFi: PIFA Antenna, with 2.50dBi gain 5G WIFI: PIFA Antenna, with 3.50dBi gain |
| HW | VER 0.0 |
| SW | FS2340-0000-0501 |
| I/O PORTS | Refer to user's manual |
| ACCESSORY DEVICE | Remote Control*1 · subwoofer*2 |

Remark:

1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. EUT photo refer to the report (Report NO.: FCC2023-0049-EUT).
4. Please refer to the antenna report.
5. Model difference: All models are identical except model name and country destination for marketing purpose.



2. RF EXPOSURE LIMIT

(Option B) According to FCC Part2.1091 and FCC Part1.1307b, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where:

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz;

and

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

(Option C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to §1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source Frequency (MHz) | Threshold ERP (W) |
|---------------------------|---------------------------------------|
| 0.3 - 1.34 | 1920R ² |
| 1.34 - 30 | 3450R ² / f ² |
| 30 - 300 | 3.38R ² |
| 300 - 1500 | 0.0128R ² / f ² |
| 1500 - 100000 | 19.2R ² |



For multiple RF sources: Multiple RF sources are exempt if:

- a) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
- b) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluatedk = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limitk = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.



3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

4. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

| Transmitter Circuit | Peak Gain (dBi) | Antenna Type |
|---------------------|-----------------|--------------|
| BT | 2.5 | PIFA Antenna |
| 2.4G WiFi | 3.5 | PIFA Antenna |
| 5G WiFi | 3.5 | PIFA Antenna |

This is provided by the manufacturer. The laboratory is not responsible for technical data provided by the customer.



5. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The measured Conducted Average Power

| Mode | Frequency (MHz) | Target Power (dBm) | Tolerance (dBm) | Lower Tolerance (dBm) | Upper Tolerance (dBm) |
|-----------|-----------------|--------------------|-----------------|-----------------------|-----------------------|
| BT | 2402 ~ 2480 | 3 | +/-1 | 2 | 4 |
| 2.4G WiFi | 2412 ~ 2462 | 12 | +/-1 | 11 | 13 |
| 5G WiFi | 5180 ~ 5825 | 10 | +/-1 | 9 | 11 |

The tuned Conducted Average Power (declared by client)

| Technology | Maximum conducted power (dBm) | Maximum Antenna Gain (dBi) | EIRP (dBm) | ERP (dBm) | ERP (mW) | Part1.1307b Threshold (mW) | Verify |
|------------|-------------------------------|----------------------------|------------|-----------|----------|----------------------------|--------|
| BT | 3.15 | 2.5 | 5.65 | 3.5 | 2.24 | 3060 | PASS |
| 2.4G WiFi | 12.66 | 2.5 | 15.16 | 13.01 | 19.99 | 3060 | PASS |
| 5G WiFi | 10.99 | 3.5 | 14.49 | 12.28 | 16.90 | 3060 | PASS |

Note: This device can operate simultaneously in BT, 2.4G WIFI or 5G WIFI.

CALCULATION FOR SIMULTANEOUS TRANSMISSION:

BT and WIFI can transmit simultaneously, the formula of calculated the MPE is

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Max: (2.24/3060) + (19.90/3060) = 0.005 < 1,

which is less than the "1" limit.

----- End of the Report -----



Important

- (1) The test report is valid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

The test data and test results given in this test report should only be used for purposes of scientific research, teaching and internal quality control when the CMA symbol is not presented.

Laboratory: CVC Testing Technology Co., Ltd.

Address: No.3, TiantaiyiRoad, KaitaiAvenue, ScienceCity, Guangzhou, China

Post Code: 510663

Tel: 020-32293888

FAX: 020-32293889

E-mail: office@cvc.org.cn