

TEST REPORT

of

FCC Part 15 Subpart C

New Application; Class I PC; Class II PC

Product : ProDVX APPC-10SLBe
Brand: ProDVX
Model: APPC-10SLBe 10 inch Android Panel PC
Impact
Model Difference: N/A
FCC ID: 2AR42APPC10SLBE
FCC Rule Part: §15.247, Cat: DSS
Applicant: ProDVX Europe B.V.
Address: Europalaan 10, 5232 BC Den Bosch, The
Netherlands

Test Performed by:



International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325,
Taiwan

Report No.: ISL-22LR0167FCDSS
Issue Date :2022/10/03



Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

The uncertainty of the measurement does not include in consideration of the test result unless the customer required the determination of uncertainty via the agreement, regulation or standard document specification.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.




VERIFICATION OF COMPLIANCE

Applicant: ProDVX Europe B.V.
Product Description: ProDVX APPC-10SLBe
Brand Name: ProDVX
Model No.: APPC-10SLBe 10 inch Android Panel PC Impact
Model Difference: N/A
FCC ID: 2AR42APPC10SLBE
Date of test: 2022/09/12 ~ 2022/09/30
Date of EUT Received: 2022/09/12

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:		Date:	2022/10/03
	<hr/> <i>Barry Lee / Senior Engineer</i>		<hr/>
Prepared By:		Date:	2022/10/03
	<hr/> <i>Gigi Yeh / Senior Engineer</i>		<hr/>
Approved By:		Date:	2022/10/03
	<hr/> <i>Jerry Liu / Assistant Manager</i>		<hr/>

Version

Version No.	Date	Description
00	2022/10/03	Initial creation of document

Uncertainty of Measurement

ISO/IEC 17025 requires that an estimate of measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Parameter	Uncertainty (k=2)
Conducted Emission (AC power line)	±0.852 dB
Spurious emissions, radiated	±3.46 dB
RF power, conducted	±1.386 dB
Power Density	±1.432 dB
RF Frequency	±0.00298%
Time	±0.01%
DC Voltage	±0.808%

Table of Contents

1. General Information	6
1.1. Product Description	6
1.2. Related Submittal(s) / Grant (s)	7
1.3. Test Methodology	7
1.4. Test Facility.....	7
1.5. Special Accessories	7
1.6. Equipment Modifications.....	7
2. System Test Configuration.....	8
2.1 EUT Configuration	8
2.2 EUT Exercise	8
2.3 Test Procedure.....	8
2.4 Configuration of Tested System.....	9
3. Summary of Test Results.....	11
4. Description of Test Modes.....	11
5. Conduced Emission Test	12
5.1 Standard Applicable:	12
5.2 Measurement Equipment Used:	12
5.3 EUT Setup:.....	12
5.4 Measurement Procedure:	13
5.5 Measurement Result:	13
6. Peak Output Power Measurement	16
6.1 Standard Applicable:	16
6.2 Measurement Equipment Used:	16
6.3 Test Set-up:	17
6.4 Measurement Procedure:	17
6.5 Measurement Result:	18
7. Spurious Emission Test	19
7.1 Standard Applicable:	19
7.2 Measurement Equipment Used:	19
7.3 Test SET-UP:.....	20
7.4 Measurement Procedure:	21
7.5 Field Strength Calculation	22
7.6 Measurement Result:	22
8. 100kHz Bandwidth of Band Edges Measurement	29
8.1 Standard Applicable:	29
8.2 Measurement Equipment Used:	29
8.3 Test SET-UP:.....	29
8.4 Measurement Procedure:	29
8.5 Field Strength Calculation	30
8.6 Measurement Result:	30
9. FREQUENCY SEPARATION	55
9.1 Standard Applicable:	55
9.2 Measurement Equipment Used:	55

9.3	Test Set-up:	55
9.4	Measurement Procedure:	55
9.5	Measurement Result:	55
10.	Number of Hopping Frequency	58
10.1	Standard Applicable:	58
10.2	Measurement Equipment Used:	58
10.3	Test Set-up:	58
10.4	Measurement Procedure:	58
10.5	Measurement Result:	58
11.	Time of Occupancy (Dwell Time).....	60
11.1	Standard Applicable:	60
11.2	Measurement Equipment Used:	60
11.3	Test Set-up:	60
11.4	Measurement Procedure:	60
11.5	Measurement Result:	61
12.	20dB Bandwidth.....	67
12.1	Standard Applicable:	67
12.2	Measurement Equipment Used:	67
12.3	Test Set-up:	67
12.4	Measurement Procedure:	67
12.5	Measurement Result:	68
13.	Antenna Requirement	74
13.1	Standard Applicable:	74
13.2	Antenna Connected Construction:	74

1. General Information

1.1. Product Description

General:

General Information		
Product Name:	ProDVX APPC-10SLBe	
Brand Name:	ProDVX	
Model Name:	APPC-10SLBe 10 inch Android Panel PC Impact	
Model Difference:	N/A	
Temperature Range	0°C to 40°C	
Power Supply:	12V DC from adaptor	
	Adaptor:	Model:2AAJ024FC

Bluetooth Information		
BT Modular:	AP6256	
Bluetooth Version:	V2.1 + EDR	V5.0
Frequency Range:	2402 – 2480MHz	2402 – 2480MHz
Max Output Power:	6.53dBm	7.13dBm
Channel number:	79 channels	40 channels
Modulation type:	FHSS	GFSK
Product HW Version:	22080147	
Product SW Version:	11	
Product FW Version:	11	
Test SW Version:	Ampak RFTTestTool 7.3	
RFpower setting:	default	

	Antenna Type	Brand	Model	Peak Gain	Frequency Range	Connector Type
1	PCB	TSKY CO., LTD.	A8-A006-00509	2.7 dBi	2400-2485 MHz	i-pex

This report applies for BT V2.1 + EDR

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2AR42APPC10SLBE filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.3. Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at an antenna to EUT distance 3 meters.

KDB Document: 558074 D01 15.247 Meas Guidance v05r02

1.4. Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of International Standards Laboratory Corp. <LT Lab.> No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan which are constructed and calibrated to meet the FCC requirements in documents . FCC Registration Number is: 487532; Designation Number is: TW0997, Canada Registration Number: 4067B-4.

1.5. Special Accessories

Not available for this EUT intended for grant.

1.6. Equipment Modifications

Not available for this EUT intended for grant.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT (Transmitter) was tested with a test program to fix the TX/RX frequency that was for the purpose of the measurements. For more information please see test data and APPENDIX 1 for set-up photographs.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 6 of ANSI C63.10: 2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR 16-1-1 Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m/1.5m (frequency above 1GHz) above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 6 and 11 of ANSI C63.10: 2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System (Fixed channel)




Table 1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1	adaptor	CWT	2AAJ024FC	NA	NA	300cm

Fig. 2-2 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1	USB HDD	AKiTIO	SK2-U31AS-A KT	N/A	Shielded /1m	N/A
2	Portable Computer	Lenovo	TP00067B	N/A	N/A	Non-shielded /1.8m
3	Speaker/ microphone	KOKA	ST-304	N/A	Non-shielded /1.5m	N/A
4	Bluetooth Speaker/ microphone	N/A	SA-868	N/A	N/A	N/A
5	Wireless AP router	ASUS	RT-AC66U	N/A	Non-shield / 10m	Non-shield / 1.8m
6	SD card	SanDisk	11287080S2CA RD	N/A	N/A	N/A

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.

3. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207(a)	AC Power line Conducted Emission	Compliant
§15.247(b)(1)	Peak Output Power	Compliant
§15.247(d)	100 kHz Bandwidth Of Frequency Band Edges	Compliant
§15.247(c)	Spurious Emission	Compliant
§15.247(a)(1)	Frequency Separation	Compliant
§15.247(a)(1)(iii)	Number of hopping frequency	Compliant
§15.247(a)(1)(ii)	Time of Occupancy	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.203, §15.247(c)	Antenna Requirement	Compliant

4. Description of Test Modes

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low (2402MHz), mid (2441MHz) and high (2480MHz) with each modulation were chosen for full testing.

The worst case BDR mode was reported for Radiated Emission.

5. Conduced Emission Test

5.1 Standard Applicable:

According to §15.207 frequency range within 150kHz to 30MHz shall not exceed the Limit table as below.

Frequency range MHz	Limits dB(uV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Note

- 1.The lower limit shall apply at the transition frequencies
- 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.2 Measurement Equipment Used:

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 02	EMI Receiver 14	ROHDE& SCHWARZ	ESCI	101034	05/25/2022	05/25/2023
Conduction 02	Conduction 02-1 Cable	WOKEN	CFD 300-NL	Conduction 02 -1	10/13/2021	10/13/2022
Conduction 02	LISN 26	R&S	ENV216	102378	12/03/2021	12/03/2022
Conduction 02	LISN 21	R&S	ENV216	101476	07/20/2022	07/20/2023
Conduction 02	ISN T4 07	Teseq GmbH	ISN T400A	30449	07/28/2022	07/28/2023
Conduction 02	ISN T8 10	TESEQ	ISN T800	42773	08/05/2022	08/05/2023
Conduction 02	ISN T8 CAT6A 01	SCHWARZ-BECK	NTFM 8158	8158 0123	01/25/2022	01/25/2023
Conduction 02	CDN ISN ST08A 1	Teseq GmbH	CDN ISN ST08A	43352	10/07/2021	10/07/2022
Conduction 02	Capacitive Voltage Probe 01	SCHAFFNER	CVP 2200A	18711	02/23/2022	02/23/2023
Conduction 02	Current Probe	SCHAFFNER	SMZ 11	18030	02/23/2022	02/23/2023

5.3 EUT Setup:

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.10-2013.
2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.

5.4 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.
4. Both 120V & 240V have been verified, and 120V/60Hz was defined as the worst-case and record in the report.

5.5 Measurement Result:

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Note: Refer to next page for measurement data and plots.

AC POWER LINE CONDUCTED EMISSION TEST DATA




Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Conducted Emission Measurement

Date: 2022/10/6

operator: Martin
Temperature: 25 ℃
Humidity: 53 %



Site: Conduction 02

Phase: L1

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.178	30.87	6.71	9.67	40.54	64.58	-24.04	16.38	54.58	-38.20
2	0.238	24.93	4.41	9.67	34.60	62.17	-27.57	14.08	52.17	-38.09
3	0.274	21.73	5.36	9.67	31.40	61.00	-29.60	15.03	51.00	-35.97
4	0.382	19.13	11.76	9.68	28.81	58.24	-29.43	21.44	48.24	-26.80
5	5.074	13.23	6.43	9.81	23.04	60.00	-36.96	16.24	50.00	-33.76
6	6.834	9.91	3.19	9.84	19.75	60.00	-40.25	13.03	50.00	-36.97




Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Conducted Emission Measurement

operator: Martin
Temperature: 25 ℃
Humidity: 53 %

Date: 2022/10/6



Site: Conduction 02

Phase: *N*

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.166	31.79	8.20	9.67	41.46	65.16	-23.70	17.87	55.16	-37.29
2	0.190	28.85	8.02	9.67	38.52	64.04	-25.52	17.69	54.04	-36.35
3	0.218	25.76	8.08	9.67	35.43	62.89	-27.46	17.75	52.89	-35.14
4	0.250	20.43	4.46	9.67	30.10	61.76	-31.66	14.13	51.76	-37.63
5	12.362	5.63	0.47	9.95	15.58	60.00	-44.42	10.42	50.00	-39.58
6	23.922	14.20	3.26	10.07	24.27	60.00	-35.73	13.33	50.00	-36.67

6. Peak Output Power Measurement


6.1 Standard Applicable:

According to §15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850MHz band: 1Watt. For all other frequency hopping systems in the 2400 – 2483.5MHz band: 0.125 Watts.

6.2 Measurement Equipment Used:

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Chamber 19	Signal analyzer	R&S	FSV40	101919	08/17/2022	08/17/2023
Chamber 19	EMI Receiver	R&S	ESR3	102461	05/10/2022	05/10/2023
Chamber 19	Loop Antenna	EM	EM-6879	271	10/05/2022	10/05/2023
Chamber 19	Bilog Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168 w 6dB Att.	9168-736	03/09/2022	03/09/2023
Chamber 19	Horn antenna (1GHz-18GHz)	ETS	3117	00218718	10/12/2022	10/12/2023
Chamber 19	Horn antenna (18GHz-26GHz)	Com-power	AH-826	081001	11/30/2021	11/30/2022
Chamber 19	Horn antenna (26GHz-40GHz)	Com-power	AH-640	100A	03/18/2022	03/18/2023
Chamber 19	Preamplifier (9kHz-1GHz)	HP	8447F	3113A04621	06/24/2022	06/24/2023
Chamber 19	Preamplifier (1GHz - 26GHz)	EM	EM01M26G	060681	05/12/2022	05/12/2023
Chamber 19	Preamplifier (26GHz-40GHz)	MITEQ	JS4-26004000- 27-5A	818471	05/12/2022	05/12/2023
Chamber 19	RF Cable (100kHz-26.5GHz)	Huber Suhner & Woken	Sucoflex 104A & 18GHz SMA(M)-SM A(M)-10M	MY817/4A & 20200525	12/23/2021	12/23/2022
Chamber 19	RF Cable (18GHz-40GHz)	HUBER SU- HNER	Sucoflex 102	27963/2&374 21/2	11/17/2021	11/17/2022
Chamber 19	Signal Generator	Anritsu	MG3692A	20311	12/28/2021	12/28/2022
Chamber 19	Test Software	Audix	E3 Ver:6.120203b	N/A	N/A	N/A

6.3 Test Set-up:



6.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter
3. Record the max. reading.
4. Repeat above procedures until all frequency measured were complete.

6.5 Measurement Result:

BDR Mode

Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (dBm)
Low	6.44	0.00440	30
Mid	6.53	0.00450	30
High	6.01	0.00399	30

EDR 2M Mode

Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (dBm)
Low	2.69	0.00186	21
Mid	3.32	0.00215	21
High	2.89	0.00194	21

EDR 3M Mode

Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (dBm)
Low	3.08	0.00203	21
Mid	3.67	0.00233	21
High	3.28	0.00213	21

7. Spurious Emission Test

7.1 Standard Applicable:

According to §15.247(d), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

7.2 Measurement Equipment Used:

7.2.1. Conducted Emission at antenna port:

Refer to section 6.2 for details.


7.2.2. Radiated emission:

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Chamber 19	Signal analyzer	R&S	FSV40	101919	08/17/2022	08/17/2023
Chamber 19	EMI Receiver	R&S	ESR3	102461	05/10/2022	05/10/2023
Chamber 19	Loop Antenna	EM	EM-6879	271	10/05/2022	10/05/2023
Chamber 19	Bilog Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168 w 6dB Att.	9168-736	03/09/2022	03/09/2023
Chamber 19	Horn antenna (1GHz-18GHz)	ETS	3117	00218718	10/12/2022	10/12/2023
Chamber 19	Horn antenna (18GHz-26GHz)	Com-power	AH-826	081001	11/30/2021	11/30/2022
Chamber 19	Horn antenna (26GHz-40GHz)	Com-power	AH-640	100A	03/18/2022	03/18/2023
Chamber 19	Preamplifier (9kHz-1GHz)	HP	8447F	3113A04621	06/24/2022	06/24/2023
Chamber 19	Preamplifier (1GHz - 26GHz)	EM	EM01M26G	060681	05/12/2022	05/12/2023
Chamber 19	Preamplifier (26GHz-40GHz)	MITEQ	JS4-26004000-27-5A	818471	05/12/2022	05/12/2023
Chamber 19	RF Cable (100kHz-26.5GHz)	Huber Suhner & Woken	Sucoflex 104A & 18GHz SMA(M)-SMA(M)-10M	MY817/4A & 20200525	12/23/2021	12/23/2022
Chamber 19	RF Cable (18GHz-40GHz)	HUBER SUHNER	Sucoflex 102	27963/2&374 21/2	11/17/2021	11/17/2022
Chamber 19	Signal Generator	Anritsu	MG3692A	20311	12/28/2021	12/28/2022
Chamber 19	Test Software	Audix	E3 Ver:6.120203b	N/A	N/A	N/A


7.3 Test SET-UP:

The test item only performed radiated mode

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-Up Frequency Over 1 GHz



7.4 Measurement Procedure:

1. According 414788 section 2, Either OATS or chamber for radiated emission below 30MHz, the test was done at 966 chamber, the test site was evaluated with OATS and the Chamber has test signals level greater than OATS's .
2. The EUT was placed on a turn table which is 0.8m/1.5m above ground plane in 966 chamber.
3. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
4. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
5. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. Repeat above procedures until all frequency measured were complete.

Test receiver setting : Blew 1GHz
 Detector : Average(9kHz – 90kHz, 110kHz – 90kHz), Quasi-Peak
 Bandwidth : 9kHz, 120kHz
 Test spectrum setting : Above 1GHz
 Peak : RBW=1MHz, VBW=3MHz, Sweep=auto
 Average (for BT) : RBW=1MHz, VBW=0.5kHz, Sweep=auto

Average Measurement Setting (VBW)

Mode	ON time (ms)	Total time (ms)	Duty Cycle	Duty Factor	1/Ton	VBW (kHz)
BDR	2.835	3.750	75.600%	1.21	0.353	0.5
EDR-1	2.880	3.750	76.800%	1.15	0.347	0.5
EDR-2	2.880	3.750	76.800%	1.15	0.347	0.5

7.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

7.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Radiated Spurious Emission Measurement Result: (below 1GHz) (Worst case: BDR)

Operation Mode	TX CH Low	Test Date	2022/09/27
Fundamental Frequency	2402MHz	Test By	Barry
Temperature	25 °C	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	369.50	47.08	-3.12	43.96	46.00	-2.04	Peak	VERTICAL
2	444.19	44.27	-1.11	43.16	46.00	-2.84	Peak	VERTICAL
3	591.63	39.22	1.55	40.77	46.00	-5.23	Peak	VERTICAL
4	625.58	40.44	2.00	42.44	46.00	-3.56	Peak	VERTICAL
5	740.04	34.57	4.03	38.60	46.00	-7.40	Peak	VERTICAL
6	888.45	38.89	5.96	44.85	46.00	-1.15	Peak	VERTICAL
1	216.24	45.24	-7.77	37.47	46.00	-8.53	Peak	HORIZONTAL
2	369.50	45.44	-3.12	42.32	46.00	-3.68	Peak	HORIZONTAL
3	444.19	40.73	-1.11	39.62	46.00	-6.38	Peak	HORIZONTAL
4	591.63	37.59	1.55	39.14	46.00	-6.86	Peak	HORIZONTAL
5	625.58	39.43	2.00	41.43	46.00	-4.57	Peak	HORIZONTAL
6	888.45	38.23	5.96	44.19	46.00	-1.81	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100kHz, VBW=300kHz.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	TX CH Mid	Test Date	2022/09/27
Fundamental Frequency	2441MHz	Test By	Barry
Temperature	25 °C	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	369.50	39.53	-3.12	36.41	46.00	-9.59	Peak	VERTICAL
2	399.57	39.86	-2.54	37.32	46.00	-8.68	Peak	VERTICAL
3	444.19	44.41	-1.11	43.30	46.00	-2.70	Peak	VERTICAL
4	625.58	38.17	2.00	40.17	46.00	-5.83	Peak	VERTICAL
5	837.04	26.87	5.50	32.37	46.00	-13.63	Peak	VERTICAL
6	888.45	32.42	5.96	38.38	46.00	-7.62	Peak	VERTICAL
1	216.24	41.53	-7.77	33.76	46.00	-12.24	Peak	HORIZONTAL
2	369.50	43.23	-3.12	40.11	46.00	-5.89	Peak	HORIZONTAL
3	399.57	36.02	-2.54	33.48	46.00	-12.52	Peak	HORIZONTAL
4	591.63	37.20	1.55	38.75	46.00	-7.25	Peak	HORIZONTAL
5	625.58	32.05	2.00	34.05	46.00	-11.95	Peak	HORIZONTAL
6	888.45	31.14	5.96	37.10	46.00	-8.90	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100kHz, VBW=300kHz.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	TX CH High	Test Date	2022/09/27
Fundamental Frequency	2480MHz	Test By	Barry
Temperature	25 °C	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	222.06	41.30	-7.93	33.37	46.00	-12.63	Peak	VERTICAL
2	295.78	37.92	-4.21	33.71	46.00	-12.29	Peak	VERTICAL
3	369.50	42.91	-3.12	39.79	46.00	-6.21	Peak	VERTICAL
4	592.60	36.51	1.58	38.09	46.00	-7.91	Peak	VERTICAL
5	625.58	31.59	2.00	33.59	46.00	-12.41	Peak	VERTICAL
6	888.45	31.41	5.96	37.37	46.00	-8.63	Peak	VERTICAL
1	222.06	41.30	-7.93	33.37	46.00	-12.63	Peak	HORIZONTAL
2	295.78	37.92	-4.21	33.71	46.00	-12.29	Peak	HORIZONTAL
3	369.50	42.91	-3.12	39.79	46.00	-6.21	Peak	HORIZONTAL
4	592.60	36.51	1.58	38.09	46.00	-7.91	Peak	HORIZONTAL
5	625.58	31.59	2.00	33.59	46.00	-12.41	Peak	HORIZONTAL
6	888.45	31.41	5.96	37.37	46.00	-8.63	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100kHz, VBW=300kHz.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	TX CH Low	Test Date	2022/09/27
Fundamental Frequency	2402 MHz	Test By	Barry
Temperature	25 °C	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	4804.00	55.35	-5.85	49.50	74.00	-24.50	Peak	VERTICAL
2	7206.00	52.35	-2.17	50.18	74.00	-23.82	Peak	VERTICAL
1	4804.00	57.16	-5.85	51.31	74.00	-22.69	Peak	HORIZONTAL
2	7206.00	53.47	-2.17	51.30	74.00	-22.70	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	TX CH Mid	Test Date	2022/09/27
Fundamental Frequency	2441 MHz	Test By	Barry
Temperature	25 °C	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	4882.00	44.90	-5.77	39.13	74.00	-34.87	Peak	VERTICAL
2	7323.00	44.85	-2.24	42.61	74.00	-31.39	Peak	VERTICAL
1	4882.00	45.11	-5.77	39.34	74.00	-34.66	Peak	HORIZONTAL
2	7323.00	45.09	-2.24	42.85	74.00	-31.15	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	TX CH High	Test Date	2022/09/27
Fundamental Frequency	2480 MHz	Test By	Barry
Temperature	25 °C	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	4960.00	45.43	-5.57	39.86	74.00	-34.14	Peak	VERTICAL
2	7440.00	43.60	-2.09	41.51	74.00	-32.49	Peak	VERTICAL
1	4960.00	45.45	-5.57	39.88	74.00	-34.12	Peak	HORIZONTAL
2	7440.00	46.00	-2.09	43.91	74.00	-30.09	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. 100kHz Bandwidth of Band Edges Measurement

8.1 Standard Applicable:

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Measurement Equipment Used:

8.2.1. Conducted Emission at antenna port:

Refer to section 6.2 for details.

8.2.2. Radiated emission:

Refer to section 7.2 for details.

8.3 Test SET-UP:

Refer to section 7.3 for details.

8.4 Measurement Procedure:

- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
- 2 The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3 EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4 When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
- 5 Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 6 And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 7 Repeat above procedures until all frequency measured were complete.

8.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

8.6 Measurement Result:


Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Non-hopping mode:

Radiated Emission: (BDR mode)

Operation Mode TX CH Low
 Fundamental Frequency 2402 MHz
 Temperature 25 °C

Test Date 2022/09/27
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	58.19	-10.79	47.40	74.00	-26.60	Peak	VERTICAL
2	2400.00	68.32	-10.70	57.62	77.75	-20.13	Peak	VERTICAL
3	2402.26	108.45	-10.70	97.75	F	--	Peak	VERTICAL

Remark:

- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	2390.00	58.37	-10.79	47.58	74.00	-26.42	Peak	HORIZONTAL
2	2399.95	72.96	-10.70	62.26	74.00	-11.74	Peak	HORIZONTAL
3	2400.00	72.96	-10.70	62.26	80.11	-17.85	Peak	HORIZONTAL
4	2402.26	110.81	-10.70	100.11	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW $\geq 1/Ton$, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2480 MHz
 Temperature 25 °C

Test Date 2022/09/27
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2479.80	107.52	-10.57	96.95	F	--	Peak	VERTICAL
2	2483.50	57.86	-10.55	47.31	74.00	-26.69	Peak	VERTICAL

Remark:

- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2480.16	109.10	-10.57	98.53	F	--	Peak	HORIZONTAL
2	2483.50	58.30	-10.55	47.75	74.00	-26.25	Peak	HORIZONTAL

Remark:


- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW \geq 1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Radiated Emission (EDR 2M mode):

Operation Mode TX CH Low
 Fundamental Frequency 2402 MHz
 Temperature 25 °C

Test Date 2022/09/27
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	58.11	-10.79	47.32	74.00	-26.68	Peak	VERTICAL
2	2400.00	65.53	-10.70	54.83	74.06	-19.23	Peak	VERTICAL
3	2401.88	104.76	-10.70	94.06	F	--	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	58.13	-10.79	47.34	74.00	-26.66	Peak	HORIZONTAL
2	2400.00	69.89	-10.70	59.19	77.38	-18.19	Peak	HORIZONTAL
3	2401.88	108.08	-10.70	97.38	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW \geq 1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2480 MHz
 Temperature 25 °C

Test Date 2022/09/27
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2479.89	105.30	-10.57	94.73	F	--	Peak	VERTICAL
2	2483.50	58.61	-10.55	48.06	74.00	-25.94	Peak	VERTICAL

Remark:

- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2479.85	107.06	-10.57	96.49	F	--	Peak	HORIZONTAL
2	2483.50	58.02	-10.55	47.47	74.00	-26.53	Peak	HORIZONTAL

Remark:


- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW $\geq 1/Ton$, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Radiated Emission (EDR 3M mode):

Operation Mode TX CH Low
 Fundamental Frequency 2402 MHz
 Temperature 25 °C

Test Date 2022/09/27
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	58.33	-10.79	47.54	74.00	-26.46	Peak	VERTICAL
2	2400.00	67.60	-10.70	56.90	75.58	-18.68	Peak	VERTICAL
3	2401.98	106.28	-10.70	95.58	F	--	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	57.60	-10.79	46.81	74.00	-27.19	Peak	HORIZONTAL
2	2400.00	69.30	-10.70	58.60	76.76	-18.16	Peak	HORIZONTAL
3	2401.98	107.46	-10.70	96.76	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW \geq 1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2480 MHz
 Temperature 25 °C

Test Date 2022/09/27
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	2479.94	105.21	-10.57	94.64	F	--	Peak	VERTICAL
2	2483.50	59.06	-10.55	48.51	74.00	-25.49	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2479.91	107.32	-10.57	96.75	F	--	Peak	HORIZONTAL
2	2483.50	59.11	-10.55	48.56	74.00	-25.44	Peak	HORIZONTAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW $\geq 1/Ton$, Sweep time= 200 ms.


Note: “F” denotes fundamental frequency

Hopping mode:

Radiated Emission: (BDR mode)

Operation Mode TX CH Low
 Fundamental Frequency 2402 MHz
 Temperature 25 °C

Test Date 2020/11/12
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	58.59	-10.79	47.80	74.00	-26.20	Peak	VERTICAL
2	2400.00	58.02	-10.70	47.32	77.62	-30.3	Peak	VERTICAL
3	2401.93	108.32	-10.70	97.62	F	--	Peak	VERTICAL

Remark:

- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	59.17	-10.79	48.38	74.00	-25.62	Peak	HORIZONTAL
2	2400.00	59.53	-10.70	48.83	78.47	-29.64	Peak	HORIZONTAL
3	2403.25	109.17	-10.70	98.47	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW \geq 1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2480 MHz
 Temperature 25 °C

Test Date 2020/11/12
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2479.83	106.97	-10.57	96.40	F	--	Peak	VERTICAL
2	2483.50	58.35	-10.55	47.80	74.00	-26.20	Peak	VERTICAL

Remark:

- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2478.82	108.77	-10.57	98.20	F	--	Peak	HORIZONTAL
2	2483.50	58.77	-10.55	48.22	74.00	-25.78	Peak	HORIZONTAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW \geq 1/Ton, Sweep time= 200 ms.


Note: “F” denotes fundamental frequency

Hopping mode:

Radiated Emission (EDR 2M mode):

Operation Mode TX CH Low
 Fundamental Frequency 2402 MHz
 Temperature 25 °C

Test Date 2020/11/12
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	58.62	-10.79	47.83	74.00	-26.17	Peak	VERTICAL
2	2400.00	66.78	-10.70	56.08	76.91	-20.83	Peak	VERTICAL
3	2402.31	107.61	-10.70	96.91	F	--	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	58.05	-10.79	47.26	74.00	-26.74	Peak	HORIZONTAL
2	2400.00	65.87	-10.70	55.17	76.9	-21.73	Peak	HORIZONTAL
3	2401.84	107.60	-10.70	96.90	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW \geq 1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2480 MHz
 Temperature 25 °C

Test Date 2020/11/12
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2477.14	105.45	-10.58	94.87	F	--	Peak	VERTICAL
2	2483.50	58.29	-10.55	47.74	74.00	-26.26	Peak	VERTICAL

Remark:

- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2480.20	106.84	-10.57	96.27	F	--	Peak	HORIZONTAL
2	2483.50	58.24	-10.55	47.69	74.00	-26.31	Peak	HORIZONTAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW $\geq 1/Ton$, Sweep time= 200 ms.


Note: “F” denotes fundamental frequency

Hopping mode:

Radiated Emission (EDR 3M mode):

Operation Mode TX CH Low
 Fundamental Frequency 2402 MHz
 Temperature 25 °C

Test Date 2020/11/12
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	58.11	-10.79	47.32	74.00	-26.68	Peak	VERTICAL
2	2400.00	65.99	-10.70	55.29	75.77	-20.48	Peak	VERTICAL
3	2401.98	106.47	-10.70	95.77	F	--	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	57.90	-10.79	47.11	74.00	-26.89	Peak	HORIZONTAL
2	2400.00	66.87	-10.70	56.17	77.01	-20.84	Peak	HORIZONTAL
3	2402.81	107.71	-10.70	97.01	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW \geq 1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2480 MHz
 Temperature 25 °C

Test Date 2020/11/12
 Test By Barry
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2479.94	105.00	-10.57	94.43	F	--	Peak	VERTICAL
2	2483.50	57.60	-10.55	47.05	74.00	-26.95	Peak	VERTICAL

Remark:

- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW ≥1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	2478.86	106.41	-10.57	95.84	F	--	Peak	HORIZONTAL
2	2483.50	57.20	-10.55	46.65	74.00	-27.35	Peak	HORIZONTAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW \geq 1/Ton, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

9. FREQUENCY SEPARATION


9.1 Standard Applicable:

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

9.2 Measurement Equipment Used:

Refer to section 6.2 for details.

9.3 Test Set-up:



9.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel .
4. Set the spectrum analyzer as RBW,VBW=100kHz, Adjust Span to 3.0 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.


9.5 Measurement Result:

Channel separation (MHz)	Limit	Result
1	$\geq 25\text{kHz}$ or 2/3 times 20dB bandwidth	PASS

Note: Refer to next page for plots.

Frequency Separation Test Data

Low



Mid



High



10. Number of Hopping Frequency

10.1 Standard Applicable:

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

10.2 Measurement Equipment Used:

Refer to section 6.2 for details.

10.3 Test Set-up:

Refer to section 9.3 for details.

10.4 Measurement Procedure:


1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW=100kHz, VBW=300kHz
5. Max hold, view and count how many channel in the band. Measurement value

10.5 Measurement Result:


Channels Number	Limit (CH)	Measurement value (CH)	Result
	15	79	Pass

Note: Refer to next page for plots.

Channel Number
2.4 GHz – 2.441.5GHz



2.441.5 GHz – 2.4835GHz



11. Time of Occupancy (Dwell Time)

11.1 Standard Applicable:

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

11.2 Measurement Equipment Used:

Refer to section 6.2 for details.

11.3 Test Set-up:

Refer to section 9.3 for details.

11.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW / VBW = 1MHz, Span = 0Hz ,
5. Repeat above procedures until all frequency measured were complete.

11.5 Measurement Result:

A period time = 0.4 (ms) * 79 = 31.6 (s)

CH Low	DH1 time slot	=	0.380 (ms)	*	(1600/2/79)	*	31.6 =	121.60	(ms)
	DH3 time slot	=	1.640 (ms)	*	(1600/4/79)	*	31.6 =	262.40	(ms)
	DH5 time slot	=	2.860 (ms)	*	(1600/6/79)	*	31.6 =	305.07	(ms)
CH Mid	DH1 time slot	=	0.384 (ms)	*	(1600/2/79)	*	31.6 =	122.88	(ms)
	DH3 time slot	=	1.630 (ms)	*	(1600/4/79)	*	31.6 =	260.80	(ms)
	DH5 time slot	=	2.860 (ms)	*	(1600/6/79)	*	31.6 =	305.07	(ms)
CH High	DH1 time slot	=	0.380 (ms)	*	(1600/2/79)	*	31.6 =	121.60	(ms)
	DH3 time slot	=	1.620 (ms)	*	(1600/4/79)	*	31.6 =	259.20	(ms)
	DH5 time slot	=	2.880 (ms)	*	(1600/6/79)	*	31.6 =	307.20	(ms)

AFH Mode


A period time = 0.4 (ms) * 20 = 8 (s)

CH Low	DH1 time slot	=	0.380 (ms)	*	(800/2/20)	*	8 =	60.80	(ms)
	DH3 time slot	=	1.640 (ms)	*	(800/4/20)	*	8 =	131.20	(ms)
	DH5 time slot	=	2.860 (ms)	*	(800/6/20)	*	8 =	152.53	(ms)
CH Mid	DH1 time slot	=	0.384 (ms)	*	(800/2/20)	*	8 =	61.44	(ms)
	DH3 time slot	=	1.630 (ms)	*	(800/4/20)	*	8 =	130.40	(ms)
	DH5 time slot	=	2.860 (ms)	*	(800/6/20)	*	8 =	152.53	(ms)
CH High	DH1 time slot	=	0.380 (ms)	*	(800/2/20)	*	8 =	60.80	(ms)
	DH3 time slot	=	1.620 (ms)	*	(800/4/20)	*	8 =	129.60	(ms)
	DH5 time slot	=	2.880 (ms)	*	(800/6/20)	*	8 =	153.60	(ms)


Note: Refer to next page for plots.

Low Channel


DH1



DH3




DH5




Mid Channel


DH1



DH3




DH5




High Channel


DH1



DH3



DH5



12. 20dB Bandwidth

12.1 Standard Applicable:

According to §15.247(a)(1),and RSS210 A8.1(b) for frequency hopping systems operating in the 2400MHz-2483.5 MHz no limit for 20dB bandwidth.

12.2 Measurement Equipment Used:

Refer to section 6.2 for details.

12.3 Test Set-up:

Refer to section 9.3 for details.

12.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW= 1 % - 5% of Bandwidth., Span= 3MHz, Sweep=auto
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat above procedures until all frequency measured were complete.

12.5 Measurement Result:

BDR Mode

CH	20dB Bandwidth (MHz)
Low	0.926
Mid	0.936
High	0.940

EDR 2M Mode

CH	20dB Bandwidth (MHz)	2/3* 20dB Bandwidth (MHz)
Lower	1.359	0.906
Mid	1.361	0.907
Higher	1.361	0.907


EDR 3M Mode

CH	20dB Bandwidth (MHz)	2/3* 20dB Bandwidth (MHz)
Lower	1.318	0.879
Mid	1.320	0.880
Higher	1.318	0.879


Note: Refer to next page for plots.

BDR Mode


20dB Bandwidth Test Data CH-Low



20dB Bandwidth Test Data CH-Mid




20dB Bandwidth Test Data CH-High




EDR 2M Mode


20dB Bandwidth Test Data CH-Low




20dB Bandwidth Test Data CH-Mid




20dB Bandwidth Test Data CH-High




EDR 3M Mode
20dB Bandwidth Test Data CH-Low



20dB Bandwidth Test Data CH-Mid



20dB Bandwidth Test Data CH-High



13. Antenna Requirement

13.1 Standard Applicable:

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than furnished by the responsible party shall be used with the device.

And according to §15.247(c), if transmitting antennas of directional gain greater than 6dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

13.2 Antenna Connected Construction:

The directional gains of antenna used for transmitting is below table, and the antenna connector is designed with unique type RF connector and no consideration of replacement. Please see EUT photo and antenna spec. for details.

Antenna Designation:

	Antenna Type	Brand	Model	Peak Gain	Frequency Range	Connector Type
1	PCB	TSKY CO., LTD.	A8-A006-00509	2.7dBi	2400-2485 MHz	i-peX