



SOFTWARE SECURITY INFORMATION

FCC ID: 2AR42APPC1213XP IC : _____

Pursuant to:
FCC Part 15E 15.407(l) and KDB 594280 D02 UNII Device Security v01r03 / IC RSS-247 issue 2 article 6.4(4).

The information within this section is to show compliance against the SW Security Requirements laid out within KDB 594280 D02 U-NII Device Security v01r03. The information below describes how to maintain the overall security measures and systems so that only:

1. **Authenticated software is loaded and operating on the device.**
2. **The device is not easily modified to operate with RF parameters outside of the authorization.**

SOFTWARE SECURITY DESCRIPTION		
	Requirement	Answer
General Description	1. Describe how any software/firmware updates for elements that can affect the device's RF parameters will be obtained, downloaded, validated and installed. For software that is accessed through manufacturer's website or device's management system, describe the different levels of security as appropriate.	ProDVX introduces new SW through an ZC process after a complete SW validation process. ProDVX uses proprietary radio that can only runs ProDVX SW. This is available through secure ProDVX technical support.
	2. Describe the RF parameters that are modified by any software/firmware without any hardware changes. Are these parameters in some way limited such that any other software/firmware changes will not allow the device to exceed the authorized RF characteristics?	All the radio frequency parameters are Transmit power, operating channel, modulation type. Only authorized parameters are available and can be set in software.
	3. Describe in detail the authentication protocols that are in place to ensure that the source of the RF-related software/firmware is valid. Describe in detail how the RF-related software is protected against modification.	The ProDVX SW runs a load validation during the SW upgrade process to ensure that the SW is legitimate, unaltered, and downloaded correctly. The SW, radios, and load validation are proprietary. Software image contains security key signature and contains platform type imbedded in header.
	4. Describe in detail any encryption methods used to support the use of legitimate RF-related software/firmware.	Software images are not encrypted but are compressed.
	5. For a device that can be configured as a master and client (with active or passive scanning), explain how the device ensures compliance for each mode? In particular if the device acts as master in some band of operation and client in another; how is compliance ensured in each band of operation?	This is a client device.



	Requirement	Answer
Third Party Access Control	1. Explain if any third parties have the capability to operate a U.S./Canada - sold device on any other regulatory domain, frequencies, or in any manner that may allow the device to operate in violation of the device's authorization if activated in the U.S./Canada.	The devices sold to the US cannot be operated on any other country or domains. This is locked into the manufacturing data and cannot be changed.
	2. Describe, if the device permits third-party software or firmware installation, what mechanisms are provided by the manufacturer to permit integration of such functions while ensuring that the RF parameters of the device cannot be operated outside its authorization for operation in the U.S./Canada. In the description include what controls and/or agreements are in place with providers of third-party functionality to ensure the devices' underlying RF parameters are unchanged and how the manufacturer verifies the functionality.	Not available
	3. For Certified Transmitter modular devices, describe how the module grantee ensures that host manufacturers fully comply with these software security requirements for U-NII devices. If the module is controlled through driver software loaded in the host, describe how the drivers are controlled and managed such that the modular transmitter RF parameters are not modified outside the grant of authorization.	The SW and radios are ProDVX proprietary. The SW is updated through a ProDVX controller (a closed system).

This section is required for devices which have a "User Interface" (UI) to configure the device in a manner that may impact the operational parameter. The operation description must address if the device supports any of the country code configurations or peer-peer mode communications discussed in KDB 594280 D01 v02r01

SOFTWARE CONFIGURATION DESCRIPTION		
	Requirement	Answer
USER CONFIGURATION GUIDE	1. Describe the user configurations permitted through the UI. If different levels of access are permitted for professional installers, system integrators or end-users, describe the differences.	User can not set any configurations.
	a) What parameters are viewable and configurable by different parties?	Not available
	b) What parameters are accessible or modifiable by the professional installer or system integrators?	Not available



(1) Are the parameters in some way limited, so that the installers will not enter parameters that exceed those authorized?	Not available
(2) What controls exist that the user cannot operate the device outside its authorization in the U.S./Canada?	Not available
c) What parameters are accessible or modifiable by the end-user?	Not available
(1) Are the parameters in some way limited, so that the user or installers will not enter parameters that exceed those authorized?	Not available
(2) What controls exist so that the user cannot operate the device outside its authorization in the U.S./Canada?	Not available
d) Is the country code factory set? Can it be changed in the UI?	Yes the country code is factory set. It cannot be changed in the UI.
(1) If it can be changed, what controls exist to ensure that the device can only operate within its authorization in the U.S./Canada?	The devices are configured at manufacturing to be US only and only ProDVX US SW loads can be installed.
e) What are the default parameters when the device is restarted?	Not available
2. Can the radio be configured in bridge or mesh mode? If yes, an attestation may be required. Further information is available in KDB Publication 905462 D02.	Not available
3. For a device that can be configured as a master and client (with active or passive scanning), if this is user configurable, describe what controls exist, within the UI, to ensure compliance for each mode. If the device acts as a master in some bands and client in others, how is this configured to ensure compliance?	This is a client device.
4. For a device that can be configured as different types of access points, such as point-to-point or point-to-multipoint, and use different types of antennas, describe what controls exist to ensure compliance with applicable limits and the proper antenna is used for each mode of operation. (See Section 15.407(a)).	Not available

Name and surname of applicant (or authorized representative): Patrick van Schaik / Director _____

Date: 2023/0707 _____

Signature: _____



Revision Record Sheet:

Revision	Section number	Page number	Date	Remark(s)	issued by
6		1	28-12-2022	History sheet added	WJJ

Issued/modified by : Willem Jan Jong
Function : Team Lead
Revision : 6
Date : 28-12-2022

Verified by : Axel Gase
Function : Quality Manager
Date : 28-12-2022

Released by : Axel Gase
Function : Manager Quality Assurance
Date of release: : 28-12-2022