

FCC ID: 2AR45-CPE

# **RF Exposure Evaluation**

#### **FCC Limits**

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)					
(A) Limits for Occupational/Controlled Exposures									
0.3–3.0	614	1.63	*(100)	6					
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6					
30–300	61.4	0.163	1.0	6					
300–1500			f/300	6					
1500-100,000			5	6					
(B) Limits for General Population/Uncontrolled Exposure									
0.3–1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30					
30–300	27.5	0.073	0.2	30					
300–1500			f/1500	30					
1500–100,000			1.0	30					

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

### Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



## **Test Result of RF Exposure Evaluation**

## WIFI

Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Result
Lowest	38.548	0.01083	1.0	PASS
Middle	36.475	0.01025	1.0	PASS
Highest	39.719	0.01116	1.0	PASS

Remark: antenna gain=1.5 dBi

## LTE mode

Band	Frequency (MHz)	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Result
LTE Band 4	1732.5	22.99	199.067	0.06277	1.0	PASS
LTE Band 7	2560	23.95	248.313	0.09857	1.0	PASS

Remark: antenna gain: 2dBi for Band 4, 3dBi for Band 7

The max power density is less than SAR exempt limit, so SAR evaluation is not required.