

FCC ID: 2AR5ALP-2018

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:

Antenna Type: FPC Antenna

Antenna Gain: -0.68 dBi

| Modulation | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculatio n | 1g SAR Exclusion threshold | SAR test exclusion |
|------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|---------------------|----------------------------|--------------------|
| GFSK | 2.402 | -6.50 | 0.224 | -7±1 | -6.0 | 0.251 | <5 | 0.07786 | 3.00 | YES |
| | 2.441 | -6.80 | 0.209 | -7±1 | -6.0 | 0.251 | <5 | 0.07849 | 3.00 | YES |
| | 2.480 | -7.84 | 0.164 | -7±1 | -6.0 | 0.251 | <5 | 0.07911 | 3.00 | YES |
| π/4-DQPSK | 2.402 | -5.36 | 0.291 | -6±1 | -5.0 | 0.316 | <5 | 0.09802 | 3.00 | YES |
| | 2.441 | -5.66 | 0.272 | -6±1 | -5.0 | 0.316 | <5 | 0.09881 | 3.00 | YES |
| | 2.480 | -6.72 | 0.213 | -6±1 | -5.0 | 0.316 | <5 | 0.09960 | 3.00 | YES |

Conclusion:

For the max result : 0.09881 ≤ 3.0 for 1-g SAR, No SAR is required.

Signature:

Date: 2019/1/24

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China