

TEST REPORT

Applicant Name : LEADER ELECTRONICS CORP.
Address : No.8 Yuanshan Rd., Kunshan,Jiangsu, China
Report Number : KS2211222-66483E-RF-00A
FCC ID: 2AR5U-DOCK163129W

Test Standard (s)

FCC Part 15C

Sample Description

Product Type: DOCK163129W
Model No.: DOCK163129W
Trade Mark: N/A
Date Received: 2021-12-22
Report Date: 2022-10-31

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Approved By:




 Ting Lü
 EMC Engineer

 Candy Li
 EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "*". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
 Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	3
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
LOCAL SUPPORT EQUIPMENT.....	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §1.1310, §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	10
APPLICABLE STANDARD	10
BLOCK DIAGRAM OF TEST SETUP	11
TEST DATA	11
FCC§15.203 – ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTED CONSTRUCTION	13
FCC §15.207 – AC LINE CONDUCTED EMISSION	14
APPLICABLE STANDARD	14
EUT SETUP.....	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
CORRECTED FACTOR & MARGIN CALCULATION	15
TEST DATA	15
FCC §15.205 & §15.209 - RADIATED EMISSIONS TEST	18
APPLICABLE STANDARD	18
EUT SETUP.....	18
EMI TEST RECEIVER SETUP.....	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	19
TEST DATA	19

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	110.5-205kHz
Antenna Type	Coil
Input Voltage	AC 120V/60Hz
Output Power	10W*3
Sample serial number	KS2211222-66483E-RF-S1 (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2, Subpart J, and Part 15, Subparts A and C of the Federal Communications Commission's rules.

The objective is to determine the compliance of EUT with FCC rules, section 15.203, 15.205, 15.207 and 15.209.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz – 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a test mode.

EUT Exercise Software

No software used in test.

Local Support Equipment


Manufacturer	Description	Model	Serial Number
HUAWEI	Mobile phone1	Mate30	FEC0220617000901
HUAWEI	Mobile phone2	Mate30	88Y5T19A03011842
Apple	Mobile phone3	MNDN3CH/A	YWJJ4J6Q9W
Unknown	Load 5	50W100RJ*7	Unknown
Unknown	Load 6	50W100RJ*16	Unknown
Unknown	Load *1&2	/	Unknown
Unknown	Light*1&2	/	Unknown
Unknown	Light*3	/	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielded Un-Detachable EUT AC Power Cable	2.6	LISN	EUT
Un-shielded Detachable USB Cable (Load 1)	0.6	Load	EUT
Un-shielded Detachable USB Cable (Load 2)	0.94	Load	EUT
Un-shielded Detachable Type C Cable (Load 5)	0.56	Load	EUT
Un-shielded Detachable Type C Cable (Load 6)	1.2	Load	EUT
Un-shielded Un-Detachable lampholder AC Power Cable (Light 1)	2.2	lampholder	EUT
Un-shielded Un-Detachable lampholder AC Power Cable (Light 2)	2.2	lampholder	EUT
Un-shielded Un-Detachable lampholder AC Power Cable (Light 3)	1.8	lampholder	EUT

Block Diagram of Test Setup

For Conducted Emissions



For Radiate emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§1.1310 & §2.1091	Maximum Permissible Exposure(MPE)	Compliant
FCC§15.203	Antenna Requirement	Compliant
FCC§15.207	AC Line Conducted Emission	Compliant
§15.209 §15.205	Radiated Emission Test	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
MPE					
Narda	Electric and Magnetic Field Analyzer	EHP-200AC	180ZX10204	2021/06/07	2024/06/06
Narda	USB-RS232 Converter	Unknown	20042558	/	/
Narda	Software	EHP200-TS	Unknown	/	/
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
R & S	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50ΩCoaxial Switch	MP59B	6200506474	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
RF Radiated test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
SCHWARZBECK	LOOP ANTENNA	FMZB1516	1516131	2021/12/22	2024/12/21
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Radiated Emission Test Software: e3 19821b (V9)					

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310, §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;


According with KDB 680106 D01 RF Exposure Wireless Charging Apps v03r01 clause 3 c)

- c) For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

According to KDB 680106 D01 RF Exposure Wireless Charging App v03r01 clause 5 b)

- b) Inductive wireless power transfer applications with supporting field strength results and meeting all of the following requirements are not required to submit a KDB inquiry for devices approved using SDoC² or a PAG³ for equipment approved using certification to address RF exposure compliance. However, the responsible party is required to keep a copy of the test report in accordance with KDB 865664 D02. A copy of the test report is to be submitted with the application if the device is approved using certification.
- (1) Power transfer frequency is less than 1 MHz
 - (2) Output power from each primary coil is less than or equal to 15 watts.
 - (3) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.
 - (4) Client device is placed directly in contact with the transmitter.
 - (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
 - (6) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.

Block Diagram of Test Setup



Note:
 For mobile condition distance: A/B/C/D is 15cm; E is 20cm;

Test Data

Environmental Conditions

Temperature:	26°C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Nick Fang on 2022-10-30.

Test Mode: Wireless Charging (Worst case for maximum power full load)

H-Field Strength

Frequency Range (kHz)	Position A (A/m)	Position B (A/m)	Position C (A/m)	Position D (A/m)	Position E (A/m)	50% Limit (A/m)	Limit (A/m)
110 .5kHz-205kHz	0.222	0.104	0.111	0.114	0.106	0.815	1.63

E-Field Strength

Frequency Range (kHz)	Position A (V/m)	Position B (V/m)	Position C (V/m)	Position D (V/m)	Position E (V/m)	50% Limit (V/m)	Limit (V/m)
110 .5kHz-205kHz	2.174	0.542	0.625	0.586	0.319	307	614

Note: Test with 15cm distance from the center of the probe(s) to the edge of the device, 20cm from the center of the probe(s) to the top of the device.

Result: Pass**Considerations of compliance 680106 D01 RF Exposure Wireless Charging App v03r01 clause 5 b:**

(1) Power transfer frequency is less than 1 MHz.

Yes, the operation frequency is 110.5-205kHz.

(2) Output power from each primary coil is less than or equal to 15 watts.

Yes, the maximum output power of primary coil is 10 Watts.

(3) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.

The transfer system includes nine primary coils to detect. They divided into three sets, each set has three coils. Three sets can work at the same time, but each set of coils only one was worked at a time which has the same power and other performance declared by manufacturer*.

(4) Client device is placed directly in contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter

(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Yes, mobile exposure conditions only.

(6) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.

Yes, the test result for H and E-Field strength less than 50% of the MPE limit.

FCC§15.203 – ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Antenna Connected Construction

The EUT has nine internal coil antennas arrangement which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 – AC LINE CONDUCTED EMISSION

Applicable Standard

FCC§15.207

EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	64 %
ATM Pressure:	101.0 kPa

The testing was performed by Bin Deng on 2021-12-30.

Test Mode: Wireless charging (Worst case for maximum power full load)


AC 120 V/60 Hz, Line:



Site : Shielding Room
 Condition: Line
 Mode : Full Load
 Model : DOCK163129W
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.153	9.89	22.32	32.21	55.82	-23.61	Average
2	0.153	9.89	34.45	44.34	65.82	-21.48	QP
3	0.229	9.80	22.57	32.37	52.49	-20.12	Average
4	0.229	9.80	35.64	45.44	62.49	-17.05	QP
5	0.499	9.80	24.11	33.91	46.01	-12.10	Average
6	0.499	9.80	29.23	39.03	56.01	-16.98	QP
7	0.725	9.81	32.76	42.57	46.00	-3.43	Average
8	0.725	9.81	33.51	43.32	56.00	-12.68	QP
9	4.152	9.95	20.26	30.21	46.00	-15.79	Average
10	4.152	9.95	31.39	41.34	56.00	-14.66	QP
11	11.941	10.08	36.95	47.03	50.00	-2.97	Average
12	11.941	10.08	48.35	58.43	60.00	-1.57	QP

AC 120V/ 60 Hz, Neutral:



Site : Shielding Room
 Condition: Neutral
 Mode : Full Load
 Model : DOCK163129W
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.155	9.91	10.37	20.28	55.70	-35.42	Average
2	0.155	9.91	17.48	27.39	65.70	-38.31	QP
3	0.233	9.98	12.42	22.40	52.36	-29.96	Average
4	0.233	9.98	18.60	28.58	62.36	-33.78	QP
5	0.498	9.90	18.37	28.27	46.03	-17.76	Average
6	0.498	9.90	23.35	33.25	56.03	-22.78	QP
7	1.864	9.92	17.94	27.86	46.00	-18.14	Average
8	1.864	9.92	28.69	38.61	56.00	-17.39	QP
9	4.672	10.05	21.85	31.90	46.00	-14.10	Average
10	4.672	10.05	33.17	43.22	56.00	-12.78	QP
11	11.776	10.08	37.21	47.29	50.00	-2.71	Average
12	11.776	10.08	45.40	55.48	60.00	-4.52	QP

FCC §15.205 & §15.209 - RADIATED EMISSIONS TEST

Applicable Standard


As per FCC Part 15.209

(a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

EUT Setup



The radiated emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	Measurement
9 kHz – 150 kHz	300 Hz	1 kHz	PK
150 kHz – 30 MHz	10 kHz	30 kHz	PK
30 MHz – 1000 MHz	120 kHz	300 kHz	QP

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP/Average measurement

Corrected Amplitude & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data


Environmental Conditions

Temperature:	22 °C
Relative Humidity:	62 %
ATM Pressure:	101 kPa

The testing was performed by Chao Mo on 2021-12-30.


Test Mode: Wireless charging (Worst case for maximum power full load)

9 kHz~30MHz:




Site : chamber
 Condition: 3m
 Job No. : KS2211222-66483E-RF
 Test Mode: Full Load
 Note : Ground-parallel

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.016	-11.54	30.77	19.23	123.75-104.52		Peak
2	0.021	-11.69	28.18	16.49	121.09-104.60		Peak
3	0.032	-11.63	27.12	15.49	117.47-101.98		Peak
4	0.127	-11.86	69.03	57.17	105.50	-48.33	Peak




Site : chamber
 Condition: 3m
 Job No. : KS2211222-66483E-RF
 Test Mode: Full Load
 Note : Perpendicular

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.016	-11.54	31.68	20.14	123.68	-103.54	Peak
2	0.021	-11.69	29.52	17.83	121.14	-103.31	Peak
3	0.031	-11.63	29.67	18.04	117.69	-99.65	Peak
4	0.127	-11.86	68.61	56.75	105.50	-48.75	Peak




Site : chamber
 Condition: 3m
 Job No. : KS2211222-66483E-RF
 Test Mode: Full Load
 Note : Parallel

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.015	-11.53	32.20	20.67	123.83-103.16		Peak
2	0.022	-11.69	31.79	20.10	120.72-100.62		Peak
3	0.034	-11.62	30.40	18.78	117.01 -98.23		Peak
4	0.128	-11.87	68.59	56.72	105.48 -48.76		Peak




Site : chamber
 Condition: 3m
 Job No. : KS2211222-66483E-RF
 Test Mode: Full Load
 Note : Ground-parallel

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.474	-11.61	26.32	14.71	94.10	-79.39	Peak
2	1.680	-11.41	26.97	15.56	62.87	-47.31	Peak
3	4.900	-11.69	28.82	17.13	69.54	-52.41	Peak



Site : chamber
 Condition: 3m
 Job No. : KS2211222-66483E-RF
 Test Mode: Full Load
 Note : Perpendicular

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.486	-11.60	24.99	13.39	93.87	-80.48	Peak
2	1.790	-11.38	25.04	13.66	69.54	-55.88	Peak
3	18.721	-10.12	28.41	18.29	69.54	-51.25	Peak




Site : chamber
 Condition: 3m
 Job No. : KS2211222-66483E-RF
 Test Mode: Full Load
 Note : Parallel

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.391	-11.71	25.44	13.73	95.75	-82.02	Peak
2	0.948	-11.65	25.63	13.98	67.95	-53.97	Peak
3	24.790	-10.10	28.74	18.64	69.54	-50.90	Peak

30MHz~1GHz:


Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No. : KS2211222-66483E-RF
 Test Mode: Full Load

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	43.850	-9.91	41.16	31.25	40.00	-8.75	Peak
2	72.369	-15.69	43.49	27.80	40.00	-12.20	Peak
3	142.324	-15.54	49.66	34.12	43.50	-9.38	Peak
4	168.119	-13.77	49.48	35.71	43.50	-7.79	Peak
5	223.635	-11.29	46.49	35.20	46.00	-10.80	Peak
6	367.145	-7.44	36.80	29.36	46.00	-16.64	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : KS2211222-66483E-RF
 Test Mode: Full Load

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	43.793	-9.91	45.67	35.76	40.00	-4.24	QP
2	71.049	-15.22	47.76	32.54	40.00	-7.46	Peak
3	99.965	-11.81	43.99	32.18	43.50	-11.32	Peak
4	141.392	-15.51	47.63	32.12	43.50	-11.38	Peak
5	217.258	-11.56	42.54	30.98	46.00	-15.02	Peak
6	411.824	-6.29	36.23	29.94	46.00	-16.06	Peak

***** END OF REPORT *****