



# CMA Testing and Certification Laboratories

廠商會檢定中心

## RF EXPOSURE EVALUATION

Report No. : AY0012770(6) Date: 12 Mar 2019

Application No. : LW039613(0)

Applicant : Yacht Sentinel Ltd

Sample Description : One(1) item of submitted sample stated to be

Product Description : Siren  
Model : SIR001  
Sample registration No. : RY047476-001(7)  
Radio Frequency : 916MHz  
Supply voltage : 6 x 1.5V AA size batteries  
No. of submitted sample : 1

FCC ID : 2AR6YSIR001

Date Received : 19 Feb 2019

Evaluation Period : 20 Feb 2019 – 12 Mar 2019

Evaluation Method : 447498 D01 General RF Exposure Guidance v06 - RF Exposure Procedure and Equipment Authorization Policies for Mobile and Portable Devices

Conclusion : The source-based time-averaged maximum conducted power of Bluetooth operation were satisfied RF exposure requirements.

For and on behalf of  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_

  
Mr. WONG Lap-ping, Andrew  
Manager  
Electrical Division

Page 1 of 2

Document name: FCC RF exposure - Document Ref No: RT-EL-EMC-008 - Issue Date: 01 Dec 2017 - Edition: 1

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmatesting.org](http://www.cmatesting.org).  
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : [info@cmatesting.org](mailto:info@cmatesting.org) Web Site : <http://www.cmatesting.org>



# CMA Testing and Certification Laboratories

廠商會檢定中心

## RF EXPOSURE EVALUATION

Report No. : AY0012770(6)

Date: 12 Mar 2019

### Simultaneous power

No Simultaneous transmission

### RF Exposure Evaluation

According to KDB 447498 D01 clause 4.3.1 a), transmission from 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f(\text{GHz})} \right]$$

### Calculation

- Frequency : 916MHz
- Max. peak conducted output power , including tune-up tolerance : 1.318mW
- Minimum test separation distances : <5mm

where

-f(GHz) is the RF channel transmit frequency in GHz.

-Power and distance are rounded to the nearest mW and mm before calculation.

-The result is rounded to two decimal place for comparison.

Substitute above reading for calculation.

$$[(\text{mW}) / (\text{mm})] \times \sqrt{\text{GHz}}$$

Result = 0.2523

Requirements:  $\leq 3.00$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

### Conclusion

The corresponding SAR test exclusion threshold was satisfied 4.3.1a) requirements. Measurement or numerical simulation is not required.

\*\*\*\*\* End of Evaluation \*\*\*\*\*