



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20181200041E-02

Applicant: Shenzhen Jimei Creative Industrial Design Co., Ltd.

Address of Applicant: 606 Gaofeng Building, Longguan West Road, Dalang Street, Longhua District, Shenzhen, China

Manufacturer: Shenzhen Jimei Creative Industrial Design Co., Ltd.

Address of Manufacturer: 606 Gaofeng Building, Longguan West Road, Dalang Street, Longhua District, Shenzhen, China

Factory Shenzhen Jimei Creative Industrial Design Co., Ltd.

Address of Factory 606 Gaofeng Building, Longguan West Road, Dalang Street, Longhua District, Shenzhen, China

Equipment Under Test (EUT):

Product: Smart band

Model No.: M01, M02, M05, M06, M07, M08plus, M08, M09, M10, M20, M30, M50, M18 M68, M88, S2, S3, S4, S6, S8, S9, S10, S18

Test Model No.: M01

Brand Name: N/A

FCC ID: 2AR7Y-JMCY-MS-168

Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-12-20 to 2018-12-24

Date of Issue: 2018-12-24

Test Result : PASS*

Tested By:

(Daisy Qin)

Reviewed By:

(Aaron Ma)

Approved By:

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20181200041E-02	Rev.01	Initial report	2018-12-24

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BLE.....	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	Shenzhen Jimei Creative Industrial Design Co., Ltd.
Address of Applicant:	606 Gaofeng Building, Longguan West Road, Dalang Street, Longhua District, Shenzhen, China
Manufacturer:	Shenzhen Jimei Creative Industrial Design Co., Ltd.
Address of Manufacturer:	606 Gaofeng Building, Longguan West Road, Dalang Street, Longhua District, Shenzhen, China
Factory	Shenzhen Jimei Creative Industrial Design Co., Ltd.
Address of Factory	606 Gaofeng Building, Longguan West Road, Dalang Street, Longhua District, Shenzhen, China

3.2 General Description of EUT

Product Name:	Smart band
All Model No.:	M01, M02, M05, M06, M07, M08plus, M08, M09, M10, M20, M30, M50, M18 M68, M88, S2, S3, S4, S6, S8, S9, S10, S18
Test Model No.:	M01
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Power Supply:	lithium battery:DC3.7V, Charge by USB

3.3 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.2
Modulation Type:	GFSK
Number of Channel:	40
Test Software of EUT:	BLE_Tool (manufacturer declare)
Antenna Type:	Integral antenna
Antenna Gain:	0dBi

Note:

All model: M01, M02, M05, M06, M07, M08plus, M08, M09, M10, M20, M30, M50, M18 M68, M88, S2, S3, S4, S6, S8, S9, S10, S18

Only the model M01 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

1) For BLE

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.98	3±1	4	2.512
Middle(2441MHz)	3.09	3±1	4	2.512
Highest(2480MHz)	3.35	3±1	4	2.512

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	2.98	3±1	4	2.512	0.78	3.0
Middle (2440MHz)	3.09	3±1	4	2.512	0.78	
Highest (2480MHz)	3.35	3±1	4	2.512	0.79	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20181200041E-01