



FCC TEST REPORT

**Test report
On Behalf of
Shenzhen Topwell Technology Co., Ltd.
For
Home Assistant for Seniors and Disabled
Model No.: 18US1-1.7**

FCC ID: 2AR7Z-18US1

Prepared for : Shenzhen Topwell Technology Co., Ltd.
Room B518-520, Yousong Keji Building, Donghuan 1st Road, Longhua New
District, Shenzhen City, Guangdong Province, China

Prepared By : Shenzhen HUAKE Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: Dec. 10, 2018 ~ Dec. 24, 2018

Date of Report: Dec. 24, 2018

Report Number: HK1812131950-9E



TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Topwell Technology Co., Ltd.
 Address : Room B518-520, Yousong Keji Building, Donghuan 1st Road,
 Longhua New District, Shenzhen City, Guangdong Province, China

Manufacture's Name..... : Shenzhen Topwell Technology Co., Ltd.
 Address : Room B518-520, Yousong Keji Building, Donghuan 1st Road,
 Longhua New District, Shenzhen City, Guangdong Province, China

Product description

Trade Mark: Sofihub
 Product name : Home Assistant for Seniors and Disabled
 Model and/or type reference : 18US1-1.7

Standards : FCC Rules and Regulations Part 15 Subpart C Section 15.249
 ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test :
 Date (s) of performance of tests : Dec. 10, 2018 ~ Dec. 24, 2018
 Date of Issue..... : Dec. 24, 2018
 Test Result..... : **Pass**

Testing Engineer : Gary Qian
 (Gary Qian)

Technical Manager : Eden Hu
 (Eden Hu)

Authorized Signatory : Jason Zhou
 (Jason Zhou)



| Table of Contents | Page |
|---|-------------|
| 1 . TEST SUMMARY | 4 |
| 2 . GENERAL INFORMATION | 5 |
| 2.1 GENERAL DESCRIPTION OF EUT | 5 |
| 2.2 Carrier Frequency of Channels | 6 |
| 2.3 Operation of EUT during testing | 6 |
| 2.4 DESCRIPTION OF TEST SETUP | 6 |
| 2.5 MEASUREMENT INSTRUMENTS LIST | 7 |
| 3 . CONDUCTED EMISSIONS TEST | 8 |
| 3.1 Conducted Power Line Emission Limit | 8 |
| 3.2 Test Setup | 8 |
| 3.3 Test Procedure | 8 |
| 3.4 Test Result | 8 |
| 4 RADIATED EMISSION TEST | 11 |
| 4.1 Radiation Limit | 11 |
| 4.2 Test Setup | 11 |
| 4.3 Test Procedure | 12 |
| 4.4 Test Result | 12 |
| 5 BAND EDGE | 14 |
| 5.1 Limits | 14 |
| 5.2 Test Procedure | 14 |
| 5.3 Test Result | 14 |
| 6 OCCUPIED BANDWIDTH MEASUREMENT | 15 |
| 6.1 Test Setup | 15 |
| 6.2 Test Procedure | 15 |
| 6.3 Measurement Equipment Used | 15 |
| 6.4 Test Result | 15 |
| 7 ANTENNA REQUIREMENT | 16 |
| 8 PHOTOGRAPH OF TEST | 17 |



1. TEST SUMMARY

1.1 TEST PROCEDURES AND RESULTS

| DESCRIPTION OF TEST | RESULT |
|---|---------------------------|
| CONDUCTED EMISSIONS TEST | Pass |
| RADIATED EMISSION TEST BAND EDGE | COMPLIANT compliance * |
| OCCUPIED BANDWIDTH MEASUREMENT ANTENNA REQUIREMENT | compliance * Pass |

Note:

1. *PASS: Test item meets the requirement.*
2. *Fail: Test item does not meet the requirement.*
3. *compliance *: Test data refers to FCC ID: XBAZW090, and report number is: WTS15S0122741E*
4. *The test result judgment is decided by the limit of test standard.*
5. *Test data refers to FCC ID: XBAZW090, and report number is: WTS15S0122741E*

1.2 TEST FACILITY

Test Firm : Shenzhen HUAKE Testing Technology Co., Ltd.

Address : 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

1.3 MEASUREMENT UNCERTAINTY

| | |
|---|---------------|
| Measurement Uncertainty | |
| Conducted Emission Expanded Uncertainty | = 2.23dB, k=2 |
| Radiated emission expanded uncertainty(9kHz-30MHz) | = 3.08dB, k=2 |
| Radiated emission expanded uncertainty(30MHz-1000MHz) | = 4.42dB, k=2 |
| Radiated emission expanded uncertainty(Above 1GHz) | = 4.06dB, k=2 |



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | |
|------------------------|--|
| Equipment | Home Assistant for Seniors and Disabled |
| Model Name | 18US1-1.7 |
| Serial No. | N/A |
| Trade Mark | Sofihub |
| Model Difference | N/A |
| FCC ID | 2AR7Z-18US1 |
| Antenna Type | PCB antenna |
| Antenna Gain | 0 dBi |
| BT Operation frequency | 908.40MHz, 908.42MHz |
| Number of Channels | 2CH |
| Modulation Type | FSK |
| Power Source | DC 3.7V From Battery; DC6V/2.8A From Adapter |
| Power Rating | DC 3.7V From Battery; DC6V/2.8A From Adapter |



2.2 Carrier Frequency of Channels

| Channel List | | |
|--------------|-----------------|---------|
| Channel | Frequency (MHz) | Channel |
| 01 | 908.40 | 1 |
| 02 | 908.42 | 2 |

2.3 Operation of EUT during testing

Operating Mode

The mode is used: **Transmitting mode**


Low Channel: 908.40MHz

Middle Channel: N/A

High Channel: 908.42MHz

2.4 DESCRIPTION OF TEST SETUP

Operation of EUT during conducted testing and Radiation testing:



Operation of EUT during Above1GHz Radiation testing:



● Adapter information

Model: KT241060280H

Input: 100-240V~, 50/60Hz, 0.35A

Output: 6VDC, 2.8A



2.5 MEASUREMENT INSTRUMENTS LIST

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|---|-----------------|--------------------------------|------------|---------------|---------------|
| 1. | L.I.S.N. Artificial Mains Network | R&S | ENV216 | HKE-002 | Dec. 28, 2017 | 1 Year |
| 2. | Receiver | R&S | ESCI 7 | HKE-010 | Dec. 28, 2017 | 1 Year |
| 3. | RF automatic control unit | Tonscend | JS0806-2 | HKE-060 | Dec. 28, 2017 | 1 Year |
| 4. | Spectrum analyzer | R&S | FSP40 | HKE-025 | Dec. 28, 2017 | 1 Year |
| 5. | Spectrum analyzer | Agilent | N9020A | HKE-048 | Dec. 28, 2017 | 1 Year |
| 6. | Preamplifier | Schwarzbeck | BBV 9743 | HKE-006 | Dec. 28, 2017 | 1 Year |
| 7. | EMI Test Receiver | Rohde & Schwarz | ESCI 7 | HKE-010 | Dec. 28, 2017 | 1 Year |
| 8. | Bilog Broadband Antenna | Schwarzbeck | VULB9163 | HKE-012 | Dec. 28, 2017 | 1 Year |
| 9. | Loop Antenna | Schwarzbeck | FMZB 1519 B | HKE-014 | Dec. 28, 2017 | 1 Year |
| 10. | Horn Antenna | Schwarzbeck | 9120D | HKE-013 | Dec. 28, 2017 | 1 Year |
| 11. | Pre-amplifier | EMCI | EMC051845 SE | HKE-015 | Dec. 28, 2017 | 1 Year |
| 12. | Pre-amplifier | Agilent | 83051A | HKE-016 | Dec. 28, 2017 | 1 Year |
| 13. | EMI Test Software EZ-EMC | Tonscend | JZOZtheBO T120-B Version | HKE-083 | Dec. 28, 2017 | N/A |
| 14. | Power Sensor | Agilent | E9300A | HKE-086 | Dec. 28, 2017 | 1 Year |
| 15. | Spectrum analyzer | Agilent | N9020A | HKE-048 | Dec. 28, 2017 | 1 Year |
| 16. | Signal generator | Agilent | N5182A | HKE-029 | Dec. 28, 2017 | 1 Year |
| 17. | Signal Generator | Agilent | 83630A | HKE-028 | Dec. 28, 2017 | 1 Year |
| 18. | Shielded room | Shiel Hong | 4*3*3 | HKE-039 | Dec. 28, 2017 | 3 Year |



3. CONDUCTED EMISSIONS TEST

3.1 Conducted Power Line Emission Limit


For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following

| Frequency (MHz) | Maximum RF Line Voltage (dB μ V) | | | |
|-----------------|--------------------------------------|------|---------|--------|
| | CLASS A | | CLASS B | |
| | Q.P. | Ave. | Q.P. | Ave. |
| 0.15 - 0.50 | 79 | 66 | 66-56* | 56-46* |
| 0.50 - 5.00 | 73 | 60 | 56 | 46 |
| 5.00 - 30.0 | 73 | 60 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

3.2 Test Setup



3.3 Test Procedure

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.


3.4 Test Result

PASS

All the test modes completed for test. only the worst result of High Channel was reported as below:



Test Specification: Line




| Suspected List | | | | | | |
|----------------|-------------|--------------|-------------|--------------|-------------|----------|
| NO. | Freq. [MHz] | Level [dBμV] | Factor [dB] | Limit [dBμV] | Margin [dB] | Detector |
| 1 | 0.1545 | 59.21 | 10.03 | 65.75 | 6.54 | PK |
| 2 | 0.4650 | 43.12 | 10.04 | 56.60 | 13.48 | PK |
| 3 | 1.3630 | 33.53 | 10.11 | 56.00 | 22.47 | PK |
| 4 | 2.3640 | 31.64 | 10.18 | 56.00 | 24.36 | PK |
| 5 | 6.6480 | 38.31 | 10.21 | 60.00 | 21.69 | PK |
| 6 | 12.8130 | 34.58 | 9.97 | 60.00 | 25.42 | PK |

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level



Test Specification: Neutral



| Suspected List | | | | | | |
|----------------|-------------|--------------|-------------|--------------|-------------|----------|
| NO. | Freq. [MHz] | Level [dBµV] | Factor [dB] | Limit [dBµV] | Margin [dB] | Detector |
| 1 | 0.1770 | 57.90 | 10.05 | 64.63 | 6.73 | PK |
| 2 | 0.2670 | 47.32 | 10.03 | 61.21 | 13.89 | PK |
| 3 | 0.4020 | 44.50 | 10.04 | 57.81 | 13.31 | PK |
| 4 | 0.6945 | 35.17 | 10.05 | 56.00 | 20.83 | PK |
| 5 | 4.8075 | 36.33 | 10.26 | 56.00 | 19.67 | PK |
| 6 | 12.8715 | 34.86 | 9.97 | 60.00 | 25.14 | PK |

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

4 RADIATED EMISSION TEST

4.1 Radiation Limit


For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency (MHz) | Distance (Meters) | Radiated (dB μ V/m) | Radiated (μ V/m) |
|-----------------|-------------------|-------------------------|-----------------------|
| 30-88 | 3 | 40 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46 | 200 |
| Above 960 | 3 | 54 | 500 |


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

4.2 Test Setup


(1) Radiated Emission Test-Up Frequency Below 30MHz



(2) Radiated Emission Test-Up Frequency 30MHz~1GHz



(3) Radiated Emission Test-Up Frequency Above 1GHz



4.3 Test Procedure

1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

Note:

For battery operated equipment, the equipment tests shall be performed using a new battery.

4.4 Test Result

PASS

All the test modes completed for test. The worst case of Radiated Emission is High Channel; the test data of this mode was reported.



| Freque ncy | Receiver Reading | Dete ctor | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.249/209/20 | |
|---------------|---------------------|--------------|------------------------|------------|-------|---------------------|------------------------|---------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dBμV) | (PK/ QP) | Degree | (m) | (H/V) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) |
| 92.54 | 19.47 | QP | 188 | 1.7 | V | 13.39 | 32.86 | 43.50 | -10.64 |
| 520.46 | 13.54 | QP | 231 | 2.0 | V | 23.23 | 36.77 | 46.00 | -9.23 |
| 908.42 | 61.57 | PK | 226 | 1.8 | H | 27.26 | 88.83 | 114.00 | -25.17 |
| 908.42 | 72.16 | PK | 325 | 1.3 | V | 27.26 | 99.42 | 114.00 | -14.58 |
| 1816.84 | 50.64 | PK | 104 | 1.8 | H | -13.21 | 37.43 | 74.00 | -36.57 |
| 1816.84 | 59.33 | PK | 88 | 1.3 | V | -13.21 | 46.12 | 74.00 | -27.88 |
| 2725.26 | 54.73 | PK | 127 | 1.3 | H | -13.08 | 41.65 | 74.00 | -32.35 |
| 2725.26 | 54.64 | PK | 355 | 1.7 | V | -13.08 | 41.56 | 74.00 | -32.44 |
| 3633.68 | 56.07 | PK | 32 | 1.2 | H | -9.08 | 46.99 | 74.00 | -27.01 |
| 3633.68 | 52.40 | PK | 145 | 1.5 | V | -9.08 | 43.32 | 74.00 | -30.68 |

| Freque ncy | PK | Turn table Angle | RX Antenna | | Duty cycle Factor | AV | FCC Part 15.249/209/2 | |
|---------------|------------|------------------------|------------|-------|-------------------------|----------|--------------------------|--------|
| | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V/m) | Degree | (m) | (H/V) | (dB/m) | (dBμV/m) | (dBμV/m) | (dB) |
| 908.42 | 88.83 | 226 | 1.8 | H | -10.59 | 78.24 | 94.00 | -15.76 |
| 908.42 | 99.42 | 325 | 1.3 | V | -10.59 | 88.83 | 94.00 | -5.17 |
| 1816.84 | 37.43 | 104 | 1.8 | H | -10.59 | 26.84 | 54.00 | -27.16 |
| 1816.84 | 46.12 | 88 | 1.3 | V | -10.59 | 35.53 | 54.00 | -18.47 |
| 2725.26 | 41.65 | 127 | 1.3 | H | -10.59 | 31.06 | 54.00 | -22.94 |
| 2725.26 | 41.56 | 355 | 1.7 | V | -10.59 | 30.97 | 54.00 | -23.03 |
| 3633.68 | 46.99 | 32 | 1.2 | H | -10.59 | 36.40 | 54.00 | -17.60 |
| 3633.68 | 43.32 | 145 | 1.5 | V | -10.59 | 32.73 | 54.00 | -21.27 |

Remark: only the worst case was recorded.

AV = Peak +20Log10(duty cycle) =PK+(-10.59) [refer to section 8 for more detail]

Test Frequency: 30MHz ~ 10GHz

Test Mode: Transmitting



5 BAND EDGE

5.1 Limits

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 100KHz and VBM to 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength. The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 KHz and VBW to 300 KHz, to measure the conducted peak band edge.

5.3 Test Result

N/A*

Note: Test data refers to FCC ID: XBAZW090, and report number is: WTS15S0122741E



6 OCCUPIED BANDWIDTH MEASUREMENT

6.1 Test Setup

Same as Radiated Emission Measurement

6.2 Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation.
3. Based on ANSI C63.10 section 6.9.2: RBW= 30KHz. VBW= 100 KHz, Span=4MHz.
4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

6.3 Measurement Equipment Used

Same as Radiated Emission Measurement

6.4 Test Result

N/A*

Note: Test data refers to FCC ID: XBAZW090, and report number is: WTS15S0122741E

7 ANTENNA REQUIREMENT


Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Connected Construction

The antenna used in this product is a PCB antenna, The directional gains of antenna used for transmitting is 0dBi.

BT ANTENNA





8 PHOTOGRAPH OF TEST

