

FCC RF EXPOSURE REPORT

FCC ID: 2AR82-SKOW603601

Project No. : 2208C116
Equipment : IEEE 802.11b/g/n 2T2R USB Wi-Fi Module
Brand Name : N/A
Test Model : SKO.W603.6
Series Model : N/A
Applicant : Guangzhou Shikun Electronics Co., Ltd
Address : NO.6 Liankun Road, Huangpu District, Guangzhou, China
Manufacturer : Guangzhou Shikun Electronics Co., Ltd
Address : NO.6 Liankun Road, Huangpu District, Guangzhou, China
Date of Receipt : Aug. 15, 2022
Date of Test : Aug. 16, 2022 ~ Aug. 29, 2022
Issued Date : Sep. 09, 2022
Report Version : R00
Test Sample : Engineering Sample No.: DG202208169
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Nick Chen

Prepared by : Nick Chen

Chay Cai

Approved by : Chay Cai



TESTING CERT #5123.02

BTL Inc.

No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-2-2208C116	R00	Original Report	Sep. 09, 2022	Valid

1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

BTL's Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

Ant.	P/N	Type	Antenna Mfr.	Connector	Antenna Gain(dBi)
1	D40F-J09	PIFA	ZHONGTIAN XUN	N/A	4.93
2	D40F-J09	PIFA	ZHONGTIAN XUN	N/A	4.93

- Both Ant.1 and Ant.2 had been pre-tested and found the Ant.1 the worst case and recorded.
- This EUT supports CDD, and all antennas have the same gain, Directional gain = $G_{ANT} + \text{Array Gain}$.
- For power measurements, Array Gain=0dB ($N_{ANT} \leq 4$), so the Directional gain=4.93 dBi.
- The antenna gain is provided by the manufacturer.

3. TEST RESULTS

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
4.93	3.1117	16.27	42.3643	0.02624	1	Complies

Note: The calculated distance is 20 cm.

End of Test Report