

#### FCC RF EXPOSURE REPORT

For

IEEE 802.11b/g/n 1T1R USB WiFi Module

MODEL NUMBER: SKO.W7601.3

FCC ID: 2AR82-SKOW7601301 IC: 24728-SKOW7601301

REPORT NUMBER: 4788992194 -2

ISSUE DATE: April 29, 2019

Prepared for

Guangzhou Shikun Electronics Co., Ltd NO.192 KEZHU ROAD,SCIENCE PARK GUANGZHOU,GUANGDONG,CHINA

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone, Dongguan, People's Republic of China Tel: +86 769-22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.



### TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	. 3
2.	TEST METHODOLOGY	. 4
3.	FACILITIES AND ACCREDITATION	. 4
4.	REQUIREMENT	. 5



## **1. ATTESTATION OF TEST RESULTS**

#### Applicant Information

Company Name: Address:	Guangzhou Shikun Electronics Co., Ltd NO.192 KEZHU ROAD,SCIENCE PARK GUANGZHOU,GUANGDONG,CHINA
<b>Manufacturer Information</b> Company Name: Address:	Guangzhou Shikun Electronics Co., Ltd NO.192 KEZHU ROAD,SCIENCE PARK GUANGZHOU,GUANGDONG,CHINA
<b>EUT Description</b> EUT Name: Model: Sample Status: Sample Received Date:	IEEE 802.11b/g/n 1T1R USB WiFi Module SKO.W7601.3 Normal April 26, 2019

April 26 ~ 29, 2019

#### APPLICABLE STANDARDS

STANDARD

**TEST RESULTS** 

FCC 47CFR§2.1091 KDB-447498 D01 V06 Complies

Prepared By:

Date of Tested:

Kebo. zhung.

Shenny les

Checked By:

Kebo Zhang Engineer Project Associate Approved By: Shawn Wen Laboratory Leader

Aephenbuo

Stephen Guo Laboratory Manager



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

## 3. FACILITIES AND ACCREDITATION

<ul> <li>A2LA (Certificate No.: 4102.01)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</li> <li>FCC (FCC Designation No.: CN1187)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules</li> <li>IC(Company No.: 21320)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320.</li> <li>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.</li> <li>Facility Name:</li> </ul>
1

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



# 4. REQUIREMENT

#### <u>LIMIT</u>

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure								
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)				
0.3-1.34	614	1.63	(100)*	30				
1.34-30	824/f	2.19/f	(180/f2)*	30				
30-300	27.5	0.073	0.2	30				
300-1500			f/150	30				
1500-100,000			1.0	30				

Note 1: f = frequency in MHz, \* means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm<sup>2</sup> is available for this EUT.

#### MPE CALCULATION METHOD

 $S = PG/(4\pi R^2)$ 

where: S = power density (in appropriate units, e.g. mW/ cm2)

- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Radio Frequency Radiation Exposure Evaluation

WIFI2.4G (Worst case)									
Operating	Max. Tune up Power	Antenna Gain		Power density	Limit				
Mode	(dBm)	(dBi)	(num)	(mW/ cm <sup>2</sup> )					
802.11b	16	1.876	1.54	0.0122	1				

Note: the calculated distance is 20cm.

### **END OF REPORT**