

Content

1. Introduction (简介)	1
2. FEATURES (特性)	1
3. Block Diagram (结构框图)	2
4. Package Outline and Mounting (外形及安装尺寸)	2
5. Pin Definition (引脚定义)	3
6. Product Pictures (实物图片)	3
7. Key Materials (关键物料)	4
8. General Requirements (一般要求)	4
9. Electrical Characteristics (电气特性)	4
9.1 IEEE 802.11b Section	4
9.2 IEEE 802.11g Section	5
9.3 IEEE 802.11n HT20 Section(2.4GHz)	6
9.4 IEEE 802.11n HT40 Section(2.4GHz)	7
9.5 IEEE 802.11a Section	8
9.6 IEEE 802.11n HT20 Section(5GHz)	8
9.7 IEEE 802.11n HT40 Section(5GHz)	10
9.8 IEEE 802.11ac Section	11
10. Mechanical,Environmental and Reliability Tests (机械、环境和可靠性测试)	12
11. Software Requirements (软件要求)	15

1. Introduction (简介)

SKO.W7612U.2 module is based on MEDIATEK MT7612U solution. MT7612U is a highly integrated single chip which features a low power 2x2 11a/b/g/n/ac dual-band Wi-Fi subsystem. The Wi-Fi subsystem contains the 802.11a/b/g/n/ac radio, baseband, and MAC that are designed to meet both the low power and high throughput application. This documentation describes the engineering requirements specification.

SKO.W7612U.2 模块基于 MEDIATEK MT7612U 解决方案。MT7612U 是一款高度集成的芯片，具有低功耗 2x2 11a/b/g/n/ac 双频 Wi-Fi 子系统。Wi-Fi 子系统包含 802.11a/b/g/n/ac 射频、基带和 MAC，旨在满足低功耗和高吞吐量应用。本文件描述了工程需求规范。


2. FEATURES (特性)

Reserving System 接收制式	IEEE Std. 802.11a
	IEEE Std. 802.11b
	IEEE Std. 802.11g
	IEEE Std. 802.11n
	IEEE Std. 802.11ac
Chip Solution 芯片方案	MT7612U
Band 波段	2.4/5GHz
Dimensions 尺寸	90.0mm*25.0mm*3.85mm

model型号	Installation mode 安装方式	Radio Technology 支持标准	Operation frequency	Antenna port 天线接口	Remark备注
SKO.W7612U.2	SMD	IEEE 802.11a/b/g/n/ac	2.4/5GHz	板载	90.0mm*25.0mm*3.85mm


Figure 2.1 SKO.W7612U.2 Block Diagram

3. Package Outline and Mounting (外形及安装尺寸)



注意：1单位为mm
2模组外形尺寸公差为0.2mm，板厚以及未标注公差为0.1mm

4. Pin Definition (引脚定义)



正视图

PIN	SYMBOL	DESCRIPTION
1	RST	System reset\复位
2	VCC	+5V input\+5V 输入
3	USB_DM	USB2.0 DM Signal\ USB2.0 差分负电压信号
4	USB_DP	USB2.0 DP Signal\ USB2.0 差分正电压信号
5	GND	Ground\地
6	WOW	WIFI WAKE HOST \WIFI 唤醒主机

5. Product Pictures (实物图片)



正视图 (top view)



背视图 (bottom view)

丝印说明:

产品铭牌尺寸及内容如下 (镭雕):



6. Key Materials (关键物料)

序号	关键件名称	型号	规格/材料	生产者	备注
1	集成电路	MT7612U	76-QFN	MEDIATEK	
2	PCB	SKO.W7612U.2	FR-4,4LAY	福昌发	
3	晶体振荡器	2.3.3.400001535	40MHz	明德亨 (MDH)	
4	双工器	SLFD18-2R450G-13T		Sunlord	

7. General Requirements (一般要求)

No.	Feature	Description
7-1	Operation Voltage 工作电压范围	5V+/-0.5V
7-2	Current Consumption 最大电流	370mA
7-3	Ripple 纹波	≤100mV
7-4	Operation Temperature 工作温度范围	0°C to +40°C
7-5	Antenna Type 天线类型	Internal antenna
7-6	USB	High Speed USB 2.0 Interface
7-7	Storage Temperature 存储温度	-40°C to +125°C

8. Electrical Characteristics (电气特性)

(0°C,+25°C,+40°C)、(3.0V,3.3V,3.6V)。

8.1 IEEE 802.11b Section

Items	Contents
Specification	IEEE802.11b
Mode	CCK
Channel	CH1 to CH13

Data rate	1, 2, 5.5, 11Mbps				
TX Characteristics	Min.	Typ.	Max.	Unit	Remark
1. Power Levels(Calibrated)					
1) For Each antenna port	13	15	17	dBm	
2. Spectrum Mask @ target power					
1) fc +/-11MHz to +/-22MHz	-	-	-30	dBr	
2) fc > +/-22MHz	-	-	-50	dBr	
3 Constellation Error(EVM)@ target power					
1) 1Mbps	-	-	-10	dB	
2) 2Mbps	-	-	-10	dB	
3) 5.5Mbps	-	-	-10	dB	
4) 11Mbps	-	-	-10	dB	
4. Frequency Error	-25	-	25	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
5 Minimum Input Level Sensitivity (each chain)					
1) 1Mbps (FER ≤ 8%)	-	-	-83	dBm	
2) 2Mbps (FER ≤ 8%)	-	-	-80	dBm	
3) 5.5Mbps (FER ≤ 8%)	-	-	-79	dBm	
4) 11Mbps (FER ≤ 8%)	-	-	-76	dBm	
6 Maximum Input Level (FER ≤ 8%)	-10	-	-	dBm	

8.2 IEEE 802.11g Section

Items	Contents				
Specification	IEEE802.11g				
Mode	OFDM				
Channel	CH1 to CH13				
Data rate	6, 9, 12, 18, 24, 36, 48, 54Mbps				
TX Characteristics	Min.	Typ.	Max.	Unit	Remark
1. Power Levels					
1) For Each antenna port	13	15	17	dBm	
2. Spectrum Mask @ target power					
1) at fc +/-11MHz	-	-	-20	dBr	
2) at fc +/-20MHz	-	-	-28	dBr	
3) at fc > +/-30MHz	-	-	-40	dBr	
3 Constellation Error(EVM)@ target power					
1) 6Mbps	-	-	-5	dB	
2) 9Mbps	-	-	-8	dB	
3) 12Mbps	-	-	-10	dB	
4) 18Mbps	-	-	-13	dB	
5) 24Mbps	-	-	-16	dB	
6) 36Mbps	-	-	-19	dB	

7) 48Mbps	-	-	-22	dB	
8) 54Mbps	-	-	-25	dB	
4 Frequency Error	-25	-	25	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
5 Minimum Input Level Sensitivity (each chain)					
1) 6Mbps (PER ≤ 10%)	-	-	-85	dBm	
2) 9Mbps (PER ≤ 10%)	-	-	-84	dBm	
3) 12Mbps (PER ≤ 10%)	-	-	-82	dBm	
4) 18Mbps (PER ≤ 10%)	-	-	-80	dBm	
5) 24Mbps (PER ≤ 10%)	-	-	-77	dBm	
6) 36Mbps (PER ≤ 10%)	-	-	-73	dBm	
7) 48Mbps (PER ≤ 10%)	-	-	-69	dBm	
8) 54Mbps (PER ≤ 10%)	-	-	-65	dBm	
6 Maximum Input Level (PER ≤ 10%)	-20	-	-	dBm	

8.3 IEEE 802.11n HT20 Section(2.4GHz)

Items	Contents				
Specification	EEE802.11n HT20 @ 2.4GHz				
Mode	OFDM				
Channel	CH1 to CH13				
Data rate (MCS index)	MCS0/1/2/3/4/5/6/7				
TX Characteristics	Min.	Typ.	Max.	Unit	
2. Power Levels					
1) For Each antenna port	12	14	16	dBm	
3. Spectrum Mask @ target power					
1) at fc +/-11MHz	-	-	-20	dBr	
2) at fc +/-20MHz	-	-	-28	dBr	
3) at fc > +/-30MHz	-	-	-45	dBr	
4. Constellation Error(EVM)@ target power					
1) MCS0	-	-	-5	dB	
2) MCS1	-	-	-10	dB	
3) MCS2	-	-	-13	dB	
4) MCS3	-	-	-16	dB	
5) MCS4	-	-	-19	dB	
6) MCS5	-	-	-22	dB	
7) MCS6	-	-	-25	dB	
8) MCS7	-	-	-28	dB	
5. Frequency Error	-25	-	25	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
6. Minimum Input Level Sensitivity (each chain)					

1) MCS0 (PER ≤ 10%)	-	-	-82	dBm	
2) MCS1 (PER ≤ 10%)	-	-	-79	dBm	
3) MCS2 (PER ≤ 10%)	-	-	-77	dBm	
4) MCS3 (PER ≤ 10%)	-	-	-74	dBm	
5) MCS4 (PER ≤ 10%)	-	-	-70	dBm	
6) MCS5 (PER ≤ 10%)	-	-	-66	dBm	
7) MCS6 (PER ≤ 10%)	-	-	-65	dBm	
8) MCS7 (PER ≤ 10%)	-	-	-64	dBm	
7. Maximum Input Level (PER ≤ 10%)	-20	-	-	dBm	

8.4 IEEE 802.11n HT40 Section(2.4GHz)

Items	Contents				
Specification	IEEE802.11n HT40 @ 2.4GHz				
Mode	OFDM				
Channel	CH3 to CH11				
Data rate (MCS index)	MCS0/1/2/3/4/5/6/7				
	Min.	Typ.	Max.	Unit	Remark
TX Characteristics	Min.	Typ.	Max.	Unit	
1. Power Levels (Calibrated)					
1) For Each antenna port	12	14	16	dBm	
2. Spectrum Mask @target power					
1) at fc +/-22MHz	-	-	-20	dBr	
2) at fc +/-40MHz	-	-	-28	dBr	
3) at fc > +/-60MHz	-	-	-45	dBr	
3. Constellation Error(EVM)@ target power					
1) MCS0	-	-	-5	dB	
2) MCS1	-	-	-10	dB	
3) MCS2	-	-	-13	dB	
4) MCS3	-	-	-16	dB	
5) MCS4	-	-	-19	dB	
6) MCS5	-	-	-22	dB	
7) MCS6	-	-	-25	dB	
8) MCS7	-	-	-28	dB	
4. Frequency Error	-25	-	25	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
5. Minimum Input Level Sensitivity (each chain)					
1) MCS0 (PER ≤ 10%)	-	-	-79	dBm	
2) MCS1 (PER ≤ 10%)	-	-	-76	dBm	
3) MCS2 (PER ≤ 10%)	-	-	-74	dBm	
4) MCS3 (PER ≤ 10%)	-	-	-71	dBm	
5) MCS4 (PER ≤ 10%)	-	-	-67	dBm	

6) MCS5 (PER \leq 10%)	-	-	-63	dBm	
7) MCS6 (PER \leq 10%)	-	-	-62	dBm	
8) MCS7 (PER \leq 10%)	-	-	-61	dBm	
6. Maximum Input Level (PER \leq 10%)	-20	-	-	dBm	

8.5 IEEE 802.11a Section

Items	Contents				
Specification	IEEE802.11a				
Mode	OFDM				
Channel	CH1 to CH13				
Data rate	6, 9, 12, 18, 24, 36, 48, 54Mbps				
TX Characteristics	Min.	Typ.	Max.	Unit	Remark
1. Power Levels					
1) For Each antenna port	12	14	16	dBm	
2. Spectrum Mask @ target power					
1) at fc +/-11MHz	-	-	-20	dBr	
2) at fc +/-20MHz	-	-	-28	dBr	
3) at fc > +/-30MHz	-	-	-40	dBr	
3 Constellation Error(EVM)@ target power					
1) 6Mbps	-	-	-5	dB	
2) 9Mbps	-	-	-8	dB	
3) 12Mbps	-	-	-10	dB	
4) 18Mbps	-	-	-13	dB	
5) 24Mbps	-	-	-16	dB	
6) 36Mbps	-	-	-19	dB	
7) 48Mbps	-	-	-22	dB	
8) 54Mbps	-	-	-25	dB	
4 Frequency Error	-20	-	20	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
5 Minimum Input Level Sensitivity (each chain)					
1) 6Mbps (PER \leq 10%)	-	-	-82	dBm	
2) 9Mbps (PER \leq 10%)	-	-	-81	dBm	
3) 12Mbps (PER \leq 10%)	-	-	-79	dBm	
4) 18Mbps (PER \leq 10%)	-	-	-77	dBm	
5) 24Mbps (PER \leq 10%)	-	-	-74	dBm	
6) 36Mbps (PER \leq 10%)	-	-	-70	dBm	
7) 48Mbps (PER \leq 10%)	-	-	-66	dBm	
8) 54Mbps (PER \leq 10%)	-	-	-65	dBm	
6 Maximum Input Level (PER \leq 10%)	-30	-	-	dBm	

8.6 IEEE 802.11n HT20 Section(5GHz)

Items	Contents				
Specification	EEE802.11n HT20 @ 5GHz				
Mode	BPSK, QPSK, 16QAM, 64QAM and OFDM				
Channel	CH1 to CH13				
Data rate (MCS index)	MCS0/1/2/3/4/5/6/7				
TX Characteristics	Min.	Typ.	Max.	Unit	
2. Power Levels					
1) For Each antenna port	11	13	15	dBm	
3. Spectrum Mask @ target power					
1) at fc +/-11MHz	-	-	-20	dB	
2) at fc +/-20MHz	-	-	-28	dB	
3) at fc > +/-30MHz	-	-	-45	dB	
4. Constellation Error(EVM)@ target power					
1) MCS0	-	-	-5	dB	
2) MCS1	-	-	-10	dB	
3) MCS2	-	-	-13	dB	
4) MCS3	-	-	-16	dB	
5) MCS4	-	-	-19	dB	
6) MCS5	-	-	-22	dB	
7) MCS6	-	-	-25	dB	
8) MCS7	-	-	-28	dB	
5. Frequency Error	-20	-	20	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
7. Minimum Input Level Sensitivity (each chain)					
1) MCS0 (PER ≤ 10%)	-	-	-82	dBm	
2) MCS1 (PER ≤ 10%)	-	-	-79	dBm	
3) MCS2 (PER ≤ 10%)	-	-	-77	dBm	
4) MCS3 (PER ≤ 10%)	-	-	-74	dBm	
5) MCS4 (PER ≤ 10%)	-	-	-70	dBm	
6) MCS5 (PER ≤ 10%)	-	-	-66	dBm	
7) MCS6 (PER ≤ 10%)	-	-	-65	dBm	
8) MCS7 (PER ≤ 10%)	-	-	-64	dBm	
7. Maximum Input Level (PER ≤ 10%)	-30	-	-	dBm	

8.7 IEEE 802.11n HT40 Section(5GHz)

Items	Contents				
Specification	IEEE802.11n HT40 @ 5GHz				
Mode	BPSK, QPSK, 16QAM, 64QAM and OFDM				
Channel	CH3 to CH11				
Data rate (MCS index)	MCS0/1/2/3/4/5/6/7				
	Min.	Typ.	Max.	Unit	Remark
TX Characteristics	Min.	Typ.	Max.	Unit	
1. Power Levels (Calibrated)					
1) For Each antenna port	11	13	15	dBm	
2. Spectrum Mask @target power					
1) at fc +/-21MHz	-	-	-20	dBr	
2) at fc +/-40MHz	-	-	-28	dBr	
3) at fc > +/-60MHz	-	-	-45	dBr	
3. Constellation Error(EVM)@ target power					
1) MCS0	-	-	-5	dB	
2) MCS1	-	-	-10	dB	
3) MCS2	-	-	-13	dB	
4) MCS3	-	-	-16	dB	
5) MCS4	-	-	-19	dB	
6) MCS5	-	-	-22	dB	
7) MCS6	-	-	-25	dB	
8) MCS7	-	-	-28	dB	
4. Frequency Error	-20	-	20	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
6. Minimum Input Level Sensitivity (each chain)					
1) MCS0 (PER ≤ 10%)	-	-	-79	dBm	
2) MCS1 (PER ≤ 10%)	-	-	-76	dBm	
3) MCS2 (PER ≤ 10%)	-	-	-74	dBm	
4) MCS3 (PER ≤ 10%)	-	-	-71	dBm	
5) MCS4 (PER ≤ 10%)	-	-	-67	dBm	
6) MCS5 (PER ≤ 10%)	-	-	-63	dBm	
7) MCS6 (PER ≤ 10%)	-	-	-62	dBm	
8) MCS7 (PER ≤ 10%)	-	-	-61	dBm	
6. Maximum Input Level (PER ≤ 10%)	-30	-	-	dBm	

8.8 IEEE 802.11ac Section

Items	Contents						
Specification	IEEE802.11ac						
Mode	BPSK, QPSK, 16QAM, 64QAM ,256QAM and OFDM						
Channel	CH36 to CH165 VHT20 CH38 to CH163 VHT40 CH42 to CH157 VHT80						
Data rate (MCS index)	MCS0/1/2/3/4/5/6/7/8/9						
TX Characteristics	Min.	Typ.	Max.			Unit	Remark
1. Power Levels (Calibrated)							
1) For Each antenna port @VHT20&VHT40 MCS0~7	11	13	15			dBm	
2) For Each antenna port @VHT80 MCS0~7	10	12	14			dBm	
3) For Each antenna port @MCS 8~9	9	11	13			dBm	
2. Spectrum Mask @VHT20/VHT40/VHT80 target power							
1) at fc +/-11MHz/21MHz/41MHz	-	-	-20			dBr	
2) at fc +/-20MHz/40MHz/80MHz	-	-	-28			dBr	
3) at fc +/-30MHz/60MHz/120MHz	-	-	-40			dBr	
3. Constellation Error(EVM)@ target power							
1) MCS0	-	-	-5			dB	
2) MCS1	-	-	-10			dB	
3) MCS2	-	-	-13			dB	
4) MCS3	-	-	-16			dB	
5) MCS4	-	-	-19			dB	
6) MCS5	-	-	-22			dB	
7) MCS6	-	-	-25			dB	
8) MCS7	-	-	-27			dB	
9) MCS8			-30			dB	
10) MCS9			-32			dB	
4. Frequency Error	-20	-	20			ppm	
RX Characteristics	Min.	Typ.	Max.			Unit	
7. Minimum Input Level Sensitivity (each chain)			VHT 20	VHT 40	VHT 80		
1) MCS0 (PER ≤ 10%)	-	-	-82	-79	-76	dBm	
2) MCS1 (PER ≤ 10%)	-	-	-79	-76	-73	dBm	
3) MCS2 (PER ≤ 10%)	-	-	-77	-74	-71	dBm	
4) MCS3 (PER ≤ 10%)	-	-	-74	-71	-68	dBm	
5) MCS4 (PER ≤ 10%)	-	-	-70	-67	-64	dBm	

6) MCS5 (PER ≤ 10%)	-	-	-66	-63	-60	dBm	
7) MCS6 (PER ≤ 10%)	-	-	-65	-62	-59	dBm	
8) MCS7 (PER ≤ 10%)	-	-	-64	-61	-58	dBm	
9) MCS8 (PER ≤ 10%)			-59	-56	-53	dBm	
10) MCS9 (PER ≤ 10%)			-57	-54	-51	dBm	
6. Maximum Input Level (PER ≤ 10%)	-30	-	-			dBm	

9. Mechanical, Environmental and Reliability Tests

(机械、环境和可靠性测试)

Test Items		Test Conditions	Qty	Criteria Condition
4-1	Drop test	The packed samples within 100Kg can be tested Drop height: Face Side: 800/600/450mm Edge line: 600/450/350mm Drop time: 1 each Face and edge.	1xBox	After drop test, the outer box and inner box will not be broken by appearance visual inspection.
4-2	Vibration test	X-Y-Z direction, first Frequency changing from 10Hz to 30Hz to 10Hz, amplitude 0.75mm, 5 times vibrations, then frequency Changing from 30Hz to 55 Hz to 30 Hz, amplitude 0.15mm, 5 time vibration.	3	After test, the Appearance, Power EVM and Frequency error shall be satisfied with the specification.
4-3	Impact test	Impact acceleration: 50m/sec ² ; Impact duration: 16ms; Impact times: 1000.	3	After test, the Appearance, Power EVM and Frequency error shall be satisfied with the specification.
4-4	Soldering ability test	Soldering temperature: 235±5℃ Soldering duration: 2±0.5S	3	1.After soldering, the soldered area must be covered by a smooth bright solder layer, some deficiencies such as a small amount of the pinhole, not wetting are allowed, but the deficiencies can not be in the same place; 2.At least 90% of soldered area shall be covered continuously by the soldering material.
4-5	Humidity test	Leave samples in 40±3℃, 93% RH @ 96 hours	3	Leave samples in standard test condition for 2 hours then test, the Appearance, Power, EVM and Frequency error

				functional parameter shall be satisfied with the test specification.
--	--	--	--	--

4-6	High temperature load life test	Thermostat cabinet temperature: 55±5℃ Applied voltage: 110% rated voltage Working duration: 200 hour (Supply Voltage Cycle 23h power on, 1h power off)	60	After test, leave samples in standard condition for 1 hour and test, Power, EVM and Frequency error shall be satisfied with the test specification.
4-7	High temperature load test	Temperature: 55±5℃ Samples work for 16 hours	3	After test, the Appearance, Power, EVM and Frequency error shall be Satisfied with the test specification.
4-8	Low temperature storage test	Leave the samples in -25±3℃@24 hours	3	Leave samples in standard test condition for 2 hours then test, the Appearance, Power, EVM and Frequency error shall be satisfied with the test specification.
4-9	Low temperature load test	Leave samples in -15±3℃@ 2 hours, samples' function shall be normal, the let samples work for 1 hour	3	After test, leave the samples in standard condition and tested the Appearance, Power, EVM and Frequency error shall be satisfied with the test specification.
4-10	Temperature circle test	One cycle duration -10±3℃@3H 40±3℃ @3H Total cycle: 10x	3	After test, leave the samples in standard condition and tested Power EVM and Frequency error shall be qualified and all the characters shall be satisfied with the test specification.
4-11	Continuous TP test	Twice cycle duration -10±3℃@4H +60±3℃@4H, +25@2H@2H	3	During test, There will not been appeared signal disconnection or interruption between DUT and AP.
4-12	ESD	Discharge voltage: 1kV C: 150pF Discharge resistance: 330Ω Positive10 times 1 time for each second	3	The products can recoverable smoothly after ESD test.

FCC Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Caution: The user is cautioned that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC RF Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator and any part of your body.

The device must be professionally installed

The intended use is generally not for the general public. It is generally for industry/commercial use.

The connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter that is not normally required. The user has no access to the connector.

Installation must be controlled. Installation requires special training

CFR 47 FCC PART 15 SUBPART C has been investigated. It is applicable to the modular transmitter

This radio transmitter 2AR82-SKOW7612U21 has been approved by Federal Communications Commission to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Antenna No.	Frequency (MHz)	Antenna Type	Max Antenna Gain (dBi)
1	5150-5850	PCB Antenna	1.49
2	5150-5850		1.66

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	PCB Antenna	2.00
2	2412-2462	PCB Antenna	1.45

Canada Statement

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

(1) This device may not cause interference.

(2) This device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

1) L'appareil ne doit pas produire de brouillage;

2) L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

No operation is permitted for the frequency "5600-5650MHz

For indoor use only

Please notice that if the ISED certification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: " Contains IC: 24728-SKOW7612U21 " any similar wording that expresses the same meaning may be used.

l'appareil hôte doit porter une étiquette donnant le numéro de certification du module d'Industrie Canada, précédé des mots « Contient un module d'émission », du mot « IC: 24728-SKOW7612U21 » ou d'une formulation similaire exprimant le même sens, comme suit

The device meets the exemption from the routine evaluation limits in section 2.5 of RSS 102 and compliance with RSS-102 RF exposure, users can obtain Canadian information on RF exposure and compliance.

Le dispositif rencontre l'exemption des limites courantes d'évaluation dans la section 2.5 de RSS 102 et la conformité à l'exposition de RSS-102 rf, utilisateurs peut obtenir l'information canadienne sur l'exposition et la conformité de rf.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body.

Cet émetteur ne doit pas être Co-placé ou ne fonctionnant en même temps qu'aucune autre antenne ou émetteur. Cet équipement devrait être installé et actionné avec une distance minimum de 20 centimètres entre le radiateur et votre corps.

Notice to OEM integrator

Must use the device only in host devices that meet the FCC/ISED RF exposure category of mobile, which means the device is installed and used at distances of at least 20cm from persons.

The end user manual shall include FCC Part 15 /ISED RSS GEN compliance statements related to the transmitter as show in this manual.

Host manufacturer is responsible for compliance of the host system with module installed with all other applicable requirements for the system such as Part 15 B, ICES 003.

Host manufacturer is strongly recommended to confirm compliance with FCC/ISED requirements for the transmitter when the module is installed in the host.

Must have on the host device a label showing Contains FCC ID: 2AR82-SKOW7612U21, Contains IC:
24728-SKOW7612U21

The use condition limitations extend to professional users, then instructions must state that this information also extends to the host manufacturer's instruction manual.

This module is stand-alone modular. If the end product will involve the Multiple simultaneously transmitting condition or different operational conditions for a stand-alone modular transmitter in a host, host manufacturer have to consult with module manufacturer for the installation method in end system.

l'hôte doit utiliser l'instrument uniquement dans des dispositifs qui répondent à la fcc / (catégorie d'exposition rf mobile, ce qui signifie le dispositif est installé et utilisé à une distance d'au moins 20 cm de personnes.

le manuel de l'utilisateur final doit inclure la partie 15 / (fac rss gen déclarations de conformité relatives à l'émetteur que de montrer dans ce manuel).

le fabricant est responsable de la conformité de l'hôte, le système d'accueil avec le module installé avec toutes les autres exigences applicables du système comme la partie 15 b, ices - 003.

accueillir le fabricant est fortement recommandé de confirmer la conformité avec les exigences de la fcc / (émetteur lorsque le module est installé dans l'hôte).

le dispositif d'accueil doivent avoir une étiquette indiquant contient FCC ID: 2AR82-SKOW7612U21, IC:
24728-SKOW7612U21
