



**FCC RF EXPOSURE REPORT**

*For*

**IEEE 802.11a/b/g/n/ac 2T2R USB WiFi Module**

**MODEL NUMBER: SKO.W7612U.2**

**FCC ID: 2AR82-SKOW7612U21**

**REPORT NUMBER: 4788955528-3**

**ISSUE DATE: April 29, 2019**

*Prepared for*

**Guangzhou Shikun Electronics Co., Ltd  
NO.192 KEZHU ROAD,SCIENCE PARK GUANGZHOU,GUANGDONG,CHINA**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road,  
Song Shan Lake Hi-Tech Development Zone, Dongguan, People's Republic of China  
Tel: +86 769-22038881  
Fax: +86 769 33244054  
Website: www.ul.com**



## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	3
2. TEST METHODOLOGY .....	3
3. FACILITIES AND ACCREDITATION .....	4
4. REQUIREMENT .....	5



# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: Guangzhou Shikun Electronics Co., Ltd  
Address: NO.192 KEZHU ROAD,SCIENCE PARK  
GUANGZHOU,GUANGDONG,CHINA

## Manufacturer Information

Company Name: Guangzhou Shikun Electronics Co., Ltd  
Address: NO.192 KEZHU ROAD,SCIENCE PARK  
GUANGZHOU,GUANGDONG,CHINA

## EUT Description

EUT Name: IEEE 802.11a/b/g/n/ac 2T2R USB WiFi Module  
Model: SKO.W7612U.2  
Sample Status: Normal  
Sample Received Date: April 21, 2019  
Date of Tested: April 22~ 28, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR§2.1091	Complies
KDB-447498 D01 V06	

Prepared By:

Kebo Zhang  
Engineer Project Associate  
Approved By:

Stephen Guo  
Laboratory Manager

Checked By:

Shawn Wen  
Laboratory Leader



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>IC(Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



## 4. REQUIREMENT

### LIMIT

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/150	30
1500-100,000	--	--	1.0	30

Note 1: f = frequency in MHz, \* means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm<sup>2</sup> is available for this EUT.

### MPE CALCULATION METHOD

$$S = PG / (4\pi R^2)$$

where: S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)  
P = power input to the antenna (in appropriate units, e.g., mW)  
G = power gain of the antenna in the direction of interest relative to an isotropic radiator  
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



**CALCULATED RESULTS**

Radio Frequency Radiation Exposure Evaluation

WIFI2.4G (Worst case)					
Operating Mode	Max. Tune up Power	Directional gain		Power density	Limit
	(dBm)	(dBi)	(num)	(mW/ cm <sup>2</sup> )	
802.11 n40 MIMO	18	3.74	2.37	0.0297	1

Note: Directional gain=  $10\log[(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}] = 3.74\text{dBi}$   
 $N_{ANT}$ : the number of Antenna  
 $G1=1.49\text{dBi}$ ;  $G2=1.66\text{dBi}$

WIFI5G (Worst case)					
Operating Mode	Max. Tune up Power	Antenna Gain		Power density	Limit
	(dBm)	(dBi)	(num)	(mW/ cm <sup>2</sup> )	
802.11 n40 MIMO	17	4.59	2.88	0.0287	1

Note: Directional gain=  $10\log[(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}] = 4.59\text{ dBi}$   
 $N_{ANT}$ : the number of Antenna  
 $G1=2\text{dBi}$ ;  $G2=1.45\text{dBi}$

Note: the calculated distance is 20cm.

**END OF REPORT**