

保密等级：机密

# SPECIFICATION

## 产品规格书

### SKI.W7603.1

#### IEEE 802.11b/g/n 2T2R USB Wi-Fi Module

Approved by Shikun		
Checked by 审核	Rechecked by 复审	Approved by 批准

Please send the original back to us after you have approved and signed.

客户承认签章后敬请寄回正本一份。

Approved by customer		
Comments 确认意见	Approved by 批准签字	Company's seal 盖章
Customer's Name:		

## REVISION HISTORY

VERSION	DATE	BOARD ID	PAGE	DESCRIPTION	AUTHOR
V0	2018.12.15	SKI.W7603.1 A18432	All	First Issued.	Candy
V1	2019.02.14	SKI.W7603.1 A18432	1	Modified the features.	Danny

# Content

1. Introduction (简介)	1
2. FEATURES (特性)	1
3. Block Diagram (结构框图)	1
4. Package Outline and Mounting (外形及安装尺寸)	2
5. Pin Definition (引脚定义)	2
6. Product Pictures (实物图片)	3
7. Key Materials (关键物料)	3
8. General Requirements (一般要求)	4
9. Electrical Characteristics (电气特性)	4
9.1 IEEE 802.11b Section	4
9.2 IEEE 802.11g Section	5
9.3 IEEE 802.11n HT20 Section	6
9.4 IEEE 802.11n HT40 Section	7
10. Mechanical, Environmental and Reliability Tests (机械、环境和可靠性测试)	8
11. Package (包装)	10
12. Software Requirements (软件要求)	11

## 1. Introduction (简介)

SKI.W7603.1 module is based on MEDIATEK MT7603U solution. The MT7603U is a highly integrated Wi-Fi single chip which supports 300 Mbps PHY rate. It fully complies with IEEE 802.11n and IEEE 802.11 b/g standards, offering feature-rich wireless connectivity at high standards, and delivering reliable, cost-effective throughput from an extended distance. This documentation describes the engineering requirements specification.


## 2. FEATURES (特性)

<b>Reserving System</b> 接收制式	IEEE Std. 802.11b
	IEEE Std. 802.11g
	IEEE Std. 802.11n
<b>Chip Solution</b> 芯片方案	MT7603U
<b>Band</b> 波段	2.4GHz
<b>Dimensions</b> 尺寸	20.0mm*16.0mm*2.45mm

型号	安装方式	支持标准	频段	天线接口	备注
SKI.W7603.1	SMD	IEEE 802.11b/g/n	2.4GHz	邮票孔	20.0mm*16.0mm*2.45mm

## 3. Block Diagram (结构框图)

## 4. Package Outline and Mounting (外形及安装尺寸)



模组主视图


模组侧视图

模组后视图

注意：1单位为mm

2模组外形尺寸公差为0.2mm，板厚以及未标注公差为0.1mm


## 5. Pin Definition (引脚定义)



正视图

PIN	SYMBOL	DESCRIPTION
1	GND	Connected to Ground
2	ANT0	Antenna 0
3	GND	Connected to Ground
4	GND	Connected to Ground
5	ANT1	Antenna 1
6	GND	Connected to Ground
7	GND	Connected to Ground
8	USB_DP	USB2.0 DP Signal
9	USB_DM	USB2.0 DM Signal
10	VCC	+3.3V DC Power supply input
11	SLEEP	WiFi sleep
12	Wake	WiFi wake host

## 6. Product Pictures (实物图片)



正视图 (top view)



背视图 (bottom view)

## 7. Key Materials (关键物料)

Número	Componentes clave	Model	specificaciones	Observación	Remark
1	Circuito integrado	MT7603U	48-QFN	MEDIATEK	
2	PCB	SKI.W7603.1	FR-4,4LAY	--	
3	Oscilador de cristal	2.3.3.400001208	40MHz		

## 8. General Requirements (一般要求)

No.	Feature	Description
7-1	Operation Voltage	3.3V±0.3V
7-2	Current Consumption	430mA
7-3	Ripple	≤100mV
7-4	Operation Temperature	0°C to +40°C
7-5	Antenna Type	External antenna
7-6	USB	High Speed USB 2.0 Interface
7-7	Storage Temperature	-40°C to +85°C

## 9. Electrical Characteristics (电气特性)

Electrical characteristics are based on test results of prototype conduction. Under the following extreme test conditions, the electrical characteristics can be met: temperature (0°C, +25°C, +40°C), voltage (3.0V, 3.3V, 3.6V).

电气特性指标基于样机传导测试结果。如下极端测试条件下，均可满足电气特性指标：温度（0°C,+25°C,+40°C）、电压（3.0V,3.3V,3.6V）。

### 9.1 IEEE 802.11b Section

Items	Contents				
Specification	IEEE802.11b				
Mode	CCK				
Channel	CH1 to CH13				
Data rate	1, 2, 5.5, 11Mbps				
TX Characteristics	Min.	Typ.	Max.	Unit	Remark
1. Power Levels(Calibrated)					
1) For Each antenna port	14.5	16.5	18.5	dBm	
2. Spectrum Mask @ target power					
1) fc +/-11MHz to +/-22MHz	-	-	-30	dBr	
2) fc > +/-22MHz	-	-	-50	dBr	
3 Constellation Error(EVM)@ target power					
1) 1Mbps	-	-	-10	dB	
2) 2Mbps	-	-	-10	dB	
3) 5.5Mbps	-	-	-10	dB	
4) 11Mbps	-	-	-10	dB	
4. Frequency Error	-25	-	25	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
5 Minimum Input Level Sensitivity (each chain)					
1) 1Mbps (FER ≤8%)	-	-	-83	dBm	
2) 2Mbps (FER ≤8%)	-	-	-80	dBm	
3) 5.5Mbps (FER ≤8%)	-	-	-79	dBm	
4) 11Mbps (FER ≤8%)	-	-	-76	dBm	

6 Maximum Input Level (FER $\leq$ 8%)	-10	-	-	dBm	
---------------------------------------	-----	---	---	-----	--

## 9.2 IEEE 802.11g Section

Items	Contents				
Specification	IEEE802.11g				
Mode	OFDM				
Channel	CH1 to CH13				
Data rate	6, 9, 12, 18, 24, 36, 48, 54Mbps				
TX Characteristics	Min.	Typ.	Max.	Unit	Remark
1. Power Levels					
1) For Each antenna port	12	14	16	dBm	
2. Spectrum Mask @ target power					
1) at fc +/-11MHz	-	-	-20	dBr	
2) at fc +/-20MHz	-	-	-28	dBr	
3) at fc > +/-30MHz	-	-	-40	dBr	
3 Constellation Error(EVM)@ target power					
1) 6Mbps	-	-	-5	dB	
2) 9Mbps	-	-	-8	dB	
3) 12Mbps	-	-	-10	dB	
4) 18Mbps	-	-	-13	dB	
5) 24Mbps	-	-	-16	dB	
6) 36Mbps	-	-	-19	dB	
7) 48Mbps	-	-	-22	dB	
8) 54Mbps	-	-	-25	dB	
4 Frequency Error	-25	-	25	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
5 Minimum Input Level Sensitivity (each chain)					
1) 6Mbps (PER $\leq$ 10%)	-	-	-85	dBm	
2) 9Mbps (PER $\leq$ 10%)	-	-	-84	dBm	
3) 12Mbps (PER $\leq$ 10%)	-	-	-82	dBm	
4) 18Mbps (PER $\leq$ 10%)	-	-	-80	dBm	
5) 24Mbps (PER $\leq$ 10%)	-	-	-77	dBm	
6) 36Mbps (PER $\leq$ 10%)	-	-	-73	dBm	
7) 48Mbps (PER $\leq$ 10%)	-	-	-69	dBm	
8) 54Mbps (PER $\leq$ 10%)	-	-	-65	dBm	
6 Maximum Input Level (PER $\leq$ 10%)	-20	-	-	dBm	



### 9.3 IEEE 802.11n HT20 Section

Items	Contents				
Specification	IEEE802.11n HT20 @ 2.4GHz				
Mode	OFDM				
Channel	CH1 to CH13				
Data rate (MCS index)	MCS0/1/2/3/4/5/6/7				
TX Characteristics	Min.	Typ.	Max.	Unit	
2. Power Levels					
1) For Each antenna port	11	13	15	dBm	
3. Spectrum Mask @ target power					
1) at fc +/-11MHz	-	-	-20	dBr	
2) at fc +/-20MHz	-	-	-28	dBr	
3) at fc > +/-30MHz	-	-	-45	dBr	
4. Constellation Error(EVM)@ target power					
1) MCS0	-	-	-5	dB	
2) MCS1	-	-	-10	dB	
3) MCS2	-	-	-13	dB	
4) MCS3	-	-	-16	dB	
5) MCS4	-	-	-19	dB	
6) MCS5	-	-	-22	dB	
7) MCS6	-	-	-25	dB	
8) MCS7	-	-	-28	dB	
5. Frequency Error	-25	-	25	ppm	
RX Characteristics	Min.	Typ.	Max.	Unit	
6. Minimum Input Level Sensitivity (each chain)					
1) MCS0 (PER ≤10%)	-	-	-82	dBm	
2) MCS1 (PER ≤10%)	-	-	-79	dBm	
3) MCS2 (PER ≤10%)	-	-	-77	dBm	
4) MCS3 (PER ≤10%)	-	-	-74	dBm	
5) MCS4 (PER ≤10%)	-	-	-70	dBm	
6) MCS5 (PER ≤10%)	-	-	-66	dBm	
7) MCS6 (PER ≤10%)	-	-	-65	dBm	
8) MCS7 (PER ≤10%)	-	-	-64	dBm	
7. Maximum Input Level (PER ≤10%)	-20	-	-	dBm	

## 9.4 IEEE 802.11n HT40 Section

Items	Contents				
Specification	IEEE802.11n HT40 @ 2.4GHz				
Mode	OFDM				
Channel	CH3 to CH11				
Data rate (MCS index)	MCS0/1/2/3/4/5/6/7				
	Min.	Typ.	Max.	Unit	Remark
TX Characteristics					
	Min.	Typ.	Max.	Unit	
1. Power Levels (Calibrated)					
1) For Each antenna port	11	13	15	dBm	
2. Spectrum Mask @target power					
1) at fc +/-22MHz	-	-	-20	dBr	
2) at fc +/-40MHz	-	-	-28	dBr	
3) at fc > +/-60MHz	-	-	-45	dBr	
3. Constellation Error(EVM)@ target power					
1) MCS0	-	-	-5	dB	
2) MCS1	-	-	-10	dB	
3) MCS2	-	-	-13	dB	
4) MCS3	-	-	-16	dB	
5) MCS4	-	-	-19	dB	
6) MCS5	-	-	-22	dB	
7) MCS6	-	-	-25	dB	
8) MCS7	-	-	-28	dB	
4. Frequency Error	-25	-	25	ppm	
RX Characteristics					
	Min.	Typ.	Max.	Unit	
5. Minimum Input Level Sensitivity (each chain)					
1) MCS0 (PER ≤10%)	-	-	-79	dBm	
2) MCS1 (PER ≤10%)	-	-	-76	dBm	
3) MCS2 (PER ≤10%)	-	-	-74	dBm	
4) MCS3 (PER ≤10%)	-	-	-71	dBm	
5) MCS4 (PER ≤10%)	-	-	-67	dBm	
6) MCS5 (PER ≤10%)	-	-	-63	dBm	
7) MCS6 (PER ≤10%)	-	-	-62	dBm	
8) MCS7 (PER ≤10%)	-	-	-61	dBm	
6. Maximum Input Level (PER ≤10%)	-20	-	-	dBm	

## 10. Mechanical, Environmental and Reliability Tests


(机械、环境和可靠性测试)

Test Items		Test Conditions	Qty	Criteria Condition
10-1	<b>Drop test</b>	The packed samples within 100Kg can be tested Drop height: Face Side: 800/600/450mm Edge line: 600/450/350mm Drop time: 1 each Face and edge.	1xBox	After drop test, the outer box and inner box will not be broken by appearance visual inspection.
10-2	<b>Vibration test</b>	X-Y-Z direction, first Frequency changing from 10Hz to 30Hz to 10Hz, amplitude 0.75mm, 5 times vibrations, then frequency Changing from 30Hz to 55 Hz to 30 Hz, amplitude 0.15mm, 5 time vibration.	3	After test, the Appearance, Power EVM and Frequency error shall be satisfied with the specification.
10-3	<b>Impact test</b>	Impact acceleration: 50m/sec <sup>2</sup> ; Impact duration: 16ms; Impact times: 1000.	3	After test, the Appearance, Power EVM and Frequency error shall be satisfied with the specification.
10-4	<b>Soldering ability test</b>	Soldering temperature: 235±5℃ Soldering duration: 2±0.5S	3	1.After soldering, the soldered area must be covered by a smooth bright solder layer, some deficiencies such as a small amount of the pinhole, not wetting are allowed, but the deficiencies can not be in the same place; 2.At least 90% of soldered area shall be covered continuously by the soldering material.
10-5	<b>Humidity test</b>	Leave samples in 40±3℃, 93% RH @ 96 hours	3	Leave samples in standard test condition for 2 hours then test, the Appearance, Power, EVM and Frequency error functional parameter shall be satisfied with the test specification.



<b>10-6</b>	<b>High temperature load life test</b>	Thermostat cabinet temperature: 55±5℃  Applied voltage: 110% rated voltage Working duration: 200 hour (Supply Voltage Cycle 23h power on, 1h power off)	60	After test, leave samples in standard condition for 1 hour and test, Power, EVM and Frequency error shall be satisfied with the test specification.
<b>10-7</b>	<b>High temperature load test</b>	Temperature: 55±5℃ Samples work for 16 hours	3	After test, the Appearance, Power, EVM and Frequency error shall be Satisfied with the test specification.
<b>10-8</b>	<b>Low temperature storage test</b>	Leave the samples in -25±3℃@24 hours	3	Leave samples in standard test condition for 2 hours then test, the Appearance, Power, EVM and Frequency error shall be satisfied with the test specification.
<b>10-9</b>	<b>Low temperature load test</b>	Leave samples in -15±3℃@ 2 hours, samples' function shall be normal, the let samples work for 1 hour	3	After test, leave the samples in standard condition and tested the Appearance, Power, EVM and Frequency error shall be satisfied with the test specification.
<b>10-10</b>	<b>Temperature circle test</b>	One cycle duration -10±3℃@3H 40±3℃ @3H  Total cycle: 10x	3	After test, leave the samples in standard condition and tested Power EVM and Frequency error shall be qualified and all the characters shall be satisfied with the test specification.
<b>10-11</b>	<b>Continuous TP test</b>	Twice cycle duration -10±3℃@4H +60±3℃@4H, +25@2H@2H	3	During test, There will not been appeared signal disconnection or interruption between DUT and AP.
<b>10-12</b>	<b>ESD</b>	Discharge voltage: 1kV C: 150pF Discharge resistance: 330Ω Positive10 times 1 time for each second	3	The products can recoverable smoothly after ESD test.

## 11. Package (包装)

(1) Size/编带尺寸:



(2) Direction /编带方向: (箭头代表编带走)



(3) Package/包装示意图:



注：上图 3 个框示处为内盒标签粘贴位置。



注：红色箭头处为外箱标签粘贴位置。

(4) Label/标签样式：



内盒标签示例【具体内容根据系统打印为准】

## 12. Software Requirements (软件要求)

The driver supports the following operating systems: Microsoft Windows XP, Vista and Win7.

驱动程序支持以下操作系统：微软 Windows XP, Vista 和 win7。

## FCC Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Caution: The user is cautioned that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

### FCC RF Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator and any part of your body.

The device must be professionally installed

The intended use is generally not for the general public. It is generally for industry/commercial use.

The connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter that is not normally required. the user has no access to the connector.

Installation must be controlled. Installation requires special training

This module has been assessed against the following FCC rule parts: CFR 47 FCC Part 15 C (15.247, DTS). It is applicable to the modular transmitter

This radio transmitter 2AR82-SKIW7603101 has been approved by Federal Communications Commission to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	PIFA antenna	2.62
2	2412-2462	PIFA antenna	2.62

## Canada Statement

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

- (1) This device may not cause interference.
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

- 1) L'appareil ne doit pas produire de brouillage;
- 2) L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Please notice that if the ISED certification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains IC: **24728-SKIW7603101**" any similar wording that expresses the same meaning may be used.

l'appareil hôte doit porter une étiquette donnant le numéro de certification du module d'Industrie Canada, précédé des mots « Contient un module d'émission », du mot « IC: **24728-SKIW7603101** » ou d'une formulation similaire exprimant le même sens, comme suit

The device meets the exemption from the routine evaluation limits in section 2.5 of RSS 102 and compliance with RSS-102 RF exposure, users can obtain Canadian information



on RF exposure and compliance.

Le dispositif rencontre l'exemption des limites courantes d'évaluation dans la section 2.5 de RSS 102 et la conformité à l'exposition de RSS-102 rf, utilisateurs peut obtenir l'information canadienne sur l'exposition et la conformité de rf.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body.

Cet émetteur ne doit pas être Co-placé ou ne fonctionnant en même temps qu'aucune autre antenne ou émetteur. Cet équipement devrait être installé et actionné avec une distance minimum de 20 centimètres entre le radiateur et votre corps.

This radio transmitter **24728-SKIW7603101** has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain

Le présent émetteur radio **24728-SKIW7603101** a été approuvé par Innovation, Sciences et Développement économique Canada pour fonctionner avec les types d'antenne énumérés ci-dessous et ayant un gain admissible maximal. Les types d'antenne non inclus dans cette liste, et dont le gain est supérieur au gain maximal indiqué pour tout type figurant sur la liste, sont strictement interdits pour l'exploitation de l'émetteur.

The concrete contents to check are the following three points.

- 1) Must use following one of the three antenna
  - 2) Should be installed so that the end user cannot modify the antenna;
  - 3) Feed line should be designed in 50ohm
- Fine tuning of return loss etc. can be performed using a matching network.

Le contenu concret à vérifier sont les trois points suivants.

- 1) il doit utiliser suivant de l'antenne.
- 2) doivent être installés de façon que l'utilisateur final ne peut pas modifier l'antenne
- 3) La ligne d'alimentation doit être conçue en 50ohm

Le réglage précis de la perte de rendement, etc. peut être effectué en utilisant un réseau correspondant.

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	PIFA antenna	2.62
2	2412-2462	PIFA antenna	2.62

## Notice to OEM integrator

Must use the device only in host devices that meet the FCC/ISED RF exposure category of mobile, which means the device is installed and used at distances of at least 20cm from persons.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

The end user manual shall include FCC Part 15/ISED RSS GEN compliance statements related to the transmitter as show in this manual. (FCC/ISED Statement).

Host manufacturer is responsible for compliance of the host system with module installed with all other applicable requirements for the system such as Part 15 B, ICES 003.

The devices must be installed and used in strict accordance with the manufacturer's instruction as described in the user documentation that comes with the product.

Host manufacturer is strongly recommended to confirm compliance with FCC/ISED requirements for the transmitter when the module is installed in the host.

Must have on the host device a label showing Contains FCC ID: 2AR82-SKIW7603101

IC: 24728-SKIW7603101

The use condition limitations extend to professional users, then instructions must state that this information also extends to the host manufacturer's instruction manual.

This module is stand-alone modular. If the end product will involve the Multiple simultaneously transmitting condition or different operational conditions for a stand-alone modular transmitter in a host, host manufacturer have to consult with module manufacturer for the installation method in end system.

l'hôte doit utiliser l'instrument uniquement dans des dispositifs qui répondent à la fcc / (catégorie d'exposition rf mobile, ce qui signifie le dispositif est installé et utilisé à une distance d'au moins 20 cm de personnes.

le manuel de l'utilisateur final doit inclure la partie 15 / (fac rss gen déclarations de conformité relatives à l'émetteur que de montrer dans ce manuel.

le fabricant est responsable de la conformité de l'hôte, le système d'accueil avec le module installé avec toutes les autres exigences applicables du système comme la partie 15 b, ices - 003.

accueillir le fabricant est fortement recommandé de confirmer la conformité avec les exigences de la fcc / (émetteur lorsque le module est installé dans l'hôte.

le dispositif d'accueil doivent avoir une étiquette indiquant contient FCC ID: 2AR82-SKIW7603101 ic: 24728-SKIW7603101