
FCC §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

When an antenna qualifies for the standalone SAR test exclusion of 4.3.1 and also transmits simultaneously with other antennas, the standalone SAR value must be estimated according to the following to determine the simultaneous transmission SAR test exclusion criteria: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})/x}]$ W/kg, for test separation distances ≤ 50 mm; where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

Measurement Result

Operation modes	Frequency (MHz)	Maximum Power (dBm)	Duty Cycle (%)	Time based average Power (mW)	Separated distance from user (mm)	Calculated value	Exempt from Test? (Yes/No)
Band 2	1850-1910	25	0.07	0.22	0	0.06	Yes
BLE	2402-2480	-1	100	0.79	0	0.25	Yes

The maximum transmission rate when active is once every 10 second and the data consist of 140bytes. For Cat-NB1, the lowest data rate 20 kbit/s every transmission will last for less than 0,007s with a resulting dutycycle of <0.07%. Please refer to the attention letter for more detail.

WWAN and Bluetooth can transmit Simultaneously:

Operation modes	Frequency (MHz)	Maximum Power (dBm)	Duty Cycle (%)	Time based average Power (mW)	Separated distance from user (mm)	SAR estimation (W/kg)
Band 2	1850-1910	25	0.07	0.22	0	0.01
BLE	2402-2480	-1	100	0.79	0	0.03

SAR estimation=

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}/x]$
W/kg, for test separation distances ≤ 50 mm; where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

$$\Sigma\text{SAR} = 0.01 + 0.03 = 0.04 \text{ W/kg} < 1.6 \text{ W/kg}$$

So the SAR test is not necessary.