



FCC PART 15.407 TEST REPORT

For

Beijing Beebox Technology Co., Ltd.

#2207, 22nd Floor, No.1-2 Building, ShangDi 10th street, Haidian District, Beijing, China

FCC ID: 2AR80-BSD01DS

Report Type: Original Report	Product Name: Biometric Recognition Device (Microcomputer)
Report Number:	RBJ181108057-00D
Report Date:	2019-04-15
Reviewed By:	Jerry Zhang <i>Jerry Zhang</i> EMC Manager
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	10
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	10
SUPPORT CABLE LIST AND DETAILS	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	12
FCC §15.407 (f) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	13
APPLICABLE STANDARD	13
FCC §15.203– ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST PROCEDURE	16
TEST DATA	17
FCC §15.209, §15.205 & §15.407(b) –UNWANTED EMISSION.....	19
APPLICABLE STANDARD	19
EUT SETUP.....	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
CORRECTED AMPLITUDE & MARGIN CALCULATION	22
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST DATA	23
FCC §15.407(a)(e) – EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH.....	35
APPLICABLE STANDARD	35
TEST EQUIPMENT LIST AND DETAILS.....	35
TEST PROCEDURE	35
TEST DATA	35
FCC §15.407(a) –MAXIMUM CONDUCTED OUTPUT POWER.....	57
APPLICABLE STANDARD	57
TEST EQUIPMENT LIST AND DETAILS.....	58
TEST PROCEDURE	58

TEST DATA58

FCC §15.407(a) - POWER SPECTRAL DENSITY60

APPLICABLE STANDARD60

TEST PROCEDURE61

TEST EQUIPMENT LIST AND DETAILS.....61

TEST DATA61

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	Biometric Recognition Device (Microcomputer)
EUT Model:	BRD-DS-SD1
Multiple Models:	BRD-DS-SD2, BRD-DS-SD3, BRD-DS-SD* (* = 1-9, only for different)
Operation Frequency:	5180-5240(802.11a/n ht20/ac20), 5190-5230 MHz(802.11n ht40/ac 40) 5210 MHz(802.11ac80) 5745-5825(802.11a/n ht20/ac20), 5755-5795 MHz(802.11n ht40/ac 40) 5775 MHz(802.11ac80)
Maximum Output Power (Conducted):	5150-5250 MHz:14.09 dBm 5725-5850 MHz:13.39 dBm
Modulation Type:	OFDM
Rated Input Voltage:	DC12V from adapter
Adapter Information	Model: FSP050-DIBAN2
	Input: 100-240V,1.5A,50-60Hz
	Output: 12.0V===4.16A MAX(50W MAX)
External Dimension:	287mm(L)*134mm(W)*227mm(H)
Serial Number:	181108057
EUT Received Date:	2018.11.12

Objective

This type approval report is prepared on behalf of *Beijing Beebox Technology Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A, and E of the Federal Communications Commission's rules.

The tests were performed in order to determine compliance with FCC Rules Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: 2AR80-BSD01DS.
FCC Part 15C DSS submissions with FCC ID: 2AR80-BSD01DS.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical 1G~6GHz: 4.45 dB, 6G~40GHz: 5.23 dB
Unwanted Emissions,conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218,the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

The system supports 802.11a/n ht20/n ht40/ac vht 20/40/80 modes. The vh20/vht40 were reduced since the identical parameters with 802.11n ht20 and ht40.

For 5150~5250 MHz band, 7 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 802.11a, 802.11n ht20 Channel 36, 40 and 48 were tested, for 802.11n ht40 Channel 38, 46 were tested, for 802.11ac vht 80, channel 42 was tested.

For 5725~5850MHz band, 8 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	159	5795
151	5755	161	5805
153	5765	165	5825
155	5775	/	/
157	5785	/	/

For 802.11a, 802.11n ht20 Channel 149, 157 and 165 was tested, for 802.11n ht40 Channel 151, 159 was tested, for 802.11ac vht80, channel 155 was tested.

EUT Exercise Software


The software “Engineering mode” was used for testing, which was provided by manufacturer. The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations. The maximum power was configured as below table, that provided by the manufacturer:

Band	Mode	Test Frequency (MHz)	Data rate (Mbps)	Power level Setting
5150-5250 MHz	802.11a	5180	6 Mbps	18
		5200	6 Mbps	18
		5240	6 Mbps	18
	802.11n ht20	5180	MCS0	18
		5200	MCS0	18
		5240	MCS0	18
	802.11n ht40	5190	MCS0	16
		5230	MCS0	25
	802.11 ac80	5210	MCS0	18.5
5725-5850 MHz	802.11a	5745	6 Mbps	17
		5785	6 Mbps	17
		5825	6 Mbps	17
	802.11n ht20	5745	MCS0	17
		5785	MCS0	17
		5825	MCS0	16
	802.11n ht40	5755	MCS0	16
		5795	MCS0	16
	802.11 ac80	5775	MCS0	14.5

The duty cycle as below:


Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle(x) (%)	Duty cycle Factor (10*log(1/x))
802.11a	1.420	1.442	98	0
802.11n ht20	1.326	1.348	98	0
802.11n ht40	0.669	0.691	97	0.14
802.11ac80	1.058	1.080	98	0

802.11a mode




Date: 15.MAR.2019 06:22:07

802.11n ht20 mode




Date: 15.MAR.2019 06:23:45

802.11n ht40 mode



Date: 15.MAR.2019 06:26:11

802.11ac80 mode



Date: 15.MAR.2019 06:28:08

Equipment Modifications

No modification was made to the EUT.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Huawei	Earphone	/	/
TOSHIBA	USB HDD	256	/
TOSHIBA	USB HDD	256	/
TP-LINK	Router	TL-SF1008P	114A297001782
Schneider	Relay	RXM2LB2BD	/

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45 Cable	No	No	5.00	RJ45 Port of EUT	Router
Adapter Cable	No	No	1.20	Adapter	EUT
Signal Cable	No	No	5.00	EUT	Relay
USB Cable	Yes	No	5.00	EUT	HDD
USB Cable	Yes	No	5.00	EUT	HDD

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

Rules	Description of Test	Result
§15.407 (f) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
FCC §15.203,	Antenna Requirement	Compliance
FCC §15.407(b)(6)& §15.207(a),	Conducted Emissions	Compliance
FCC §15.205& §15.209 &§15.407(b),	Undesirable Emission& Restricted Bands	Compliance
§15.407(a) ,	Emission Bandwidth	Compliance
FCC §15.407(a),	Conducted Transmitter Output Power	Compliance
FCC §15.407 (a),	Power Spectral Density	Compliance

FCC §15.407 (f) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.407(f) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency Range	Antenna Gain		Max. Target Power including Tolerance		Evaluation Distance (cm)	Power Density (W/m ²)	MPE Limit (W/m ²)
	(dBi)	(numeric)	(dBm)	(mW)			
5150-5250	3	2.00	15	31.62	20.00	0.01	1.0
5725-5850	3	2.00	14	25.12	20.00	0.01	1.0

Note 1: the Max. Target Power including Tolerance was declared by manufacturer.

Note 2: Wifi 5GHz can’t transmit simultaneously with Bluetooth or 2.4G wifi.

Result: Compliance, The device meets MPE requirement for Devices Used by the General Public (Uncontrolled Environment) at distance ≥20 cm.

FCC §15.203– ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal antenna arrangement for BT and 2.4GHz wifi, the antenna gain is 3 dBi, one internal antenna for 5G wifi, the antenna gain is 3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a), §15.407(b) (6)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisen with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2018-12-10	2019-12-10
N/A	Coaxial Cable	C-NJNJ-50	C-0200-01	2018-09-05	2019-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Data


Environmental Conditions

Temperature:	25.3 °C
Relative Humidity:	52 %
ATM Pressure:	100.5 kPa

The testing was performed by Ade Xiao on 2019-01-16.

Test Mode: Transmitting (802.11a 5785MHz was the worst)


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.186708	45.3	9.000	L1	10.7	18.9	64.2	Compliance
0.267135	34.9	9.000	L1	10.3	26.3	61.2	Compliance
0.500009	40.0	9.000	L1	9.9	16.0	56.0	Compliance
0.838859	27.9	9.000	L1	9.8	28.1	56.0	Compliance
1.435633	27.9	9.000	L1	9.8	28.1	56.0	Compliance
13.604227	33.3	9.000	L1	9.9	26.7	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.181216	32.1	9.000	L1	10.8	22.3	54.4	Compliance
0.225563	28.6	9.000	L1	10.5	24.0	52.6	Compliance
0.409780	25.4	9.000	L1	10.0	22.3	47.7	Compliance
0.457178	31.7	9.000	L1	9.9	15.0	46.7	Compliance
0.500009	33.8	9.000	L1	9.9	12.2	46.0	Compliance
0.830554	22.0	9.000	L1	9.8	24.0	46.0	Compliance

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.150000	47.1	9.000	N	11.2	18.9	66.0	Compliance
0.264490	33.7	9.000	N	10.3	27.6	61.3	Compliance
0.500009	40.1	9.000	N	9.9	15.9	56.0	Compliance
0.838859	28.6	9.000	N	9.8	27.4	56.0	Compliance
1.108377	29.7	9.000	N	9.8	26.3	56.0	Compliance
13.604227	33.4	9.000	N	9.9	26.6	60.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.183029	30.6	9.000	N	10.8	23.7	54.3	Compliance
0.230097	28.1	9.000	N	10.4	24.3	52.4	Compliance
0.409780	26.5	9.000	N	10.0	21.2	47.7	Compliance
0.500009	34.6	9.000	N	9.9	11.4	46.0	Compliance
0.822331	22.4	9.000	N	9.8	23.6	46.0	Compliance
1.044142	22.3	9.000	N	9.8	23.7	46.0	Compliance

FCC §15.209, §15.205 & §15.407(b) –UNWANTED EMISSION

Applicable Standard

FCC §15.407; §15.209; §15.205;

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.


(5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.


(7) The provisions of §15.205 apply to intentional radiators operating under this section.

EUT Setup


Below 1 GHz:



1-26.5 GHz:



26.5-40 GHz:



The radiated emission Below 1GHz tests were performed in the 3 meters chamber test site A , above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

According to C63.10, the above 1G test result shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade from 3m to 1.5m or 1m

Distance extrapolation factor = $20 \log (\text{specific distance } [3m]/\text{test distance } [1.5m])$ dB= 6.02 dB

or

Distance extrapolation factor = $20 \log (\text{specific distance } [3m]/\text{test distance } [1m])$ dB= 9.54 dB

All emissions under the average limit and under the noise floor have not recorded in the report.

Corrected Amplitude & Margin Calculation

For the range 30MHz-1GHz, the Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

For the range 1GHz-40GHz, Test performed at 1.5m or 1m, the Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading and the Distance extrapolation factor. The basic equation is as follows:

$$\begin{aligned} &\text{Corrected Amplitude} \\ &= \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain} - \text{Distance extrapolation factor} \end{aligned}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2018-12-10	2019-12-10
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2018-05-06	2019-05-06
HP	Amplifier	8447D	2727A05902	2018-09-05	2019-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2018-01-04	2019-01-04
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-04
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2016-11-18	2019-11-18
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2018-06-27	2019-06-27
MITEQ	Amplifier	AFS42-00101800- 25-S-42	2001271	2018-09-05	2019-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2018-06-27	2019-06-27
Sinoscite	Bandstop Filters	BSF5150-5850MN- 0899-003	0899003	2018-05-06	2019-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	27.3 °C
Relative Humidity:	41 %
ATM Pressure:	100.6 kPa

* The testing was performed by Tyler Pan & Blake Yang on 2019-01-26 and 2019-02-28.

Test Mode: Transmitting


1) Below 1GHz(802.11a 5785 MHz was the worst):

Horizontal



Frequency (MHz)	Receiver Reading (dBμV)	Remark	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.0000	25.64	peak	1.72	27.36	40.00	12.64
227.8800	40.64	peak	-6.57	34.07	46.00	11.93
298.6900	40.30	peak	-3.88	36.42	46.00	9.58
370.4700	39.31	peak	-2.76	36.55	46.00	9.45
642.0700	29.62	peak	2.22	31.84	46.00	14.16
889.4200	36.54	peak	-4.07	32.47	46.00	13.53

Vertical



Frequency (MHz)	Receiver Reading (dBμV)	Remark	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
37.7600	37.97	peak	-4.22	33.75	40.00	6.25
95.9600	42.18	peak	-9.99	32.19	43.50	11.31
315.1800	37.87	peak	-3.45	34.42	46.00	11.58
347.1900	36.62	peak	-3.15	33.47	46.00	12.53
588.7200	32.41	peak	0.86	33.27	46.00	12.73
929.1900	36.85	peak	-3.53	33.32	46.00	12.68

**1GHz-40GHz:
5150-5250MHz
802.11a**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Extrapolation result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Remark	Polar (H/V)	Factor (dB/m)						
Low Channel: 5180 MHz										
5180.00	71.22	PK	H	33.59	3.58	0.00	108.39	102.37	N/A	N/A
5180.00	62.43	AV	H	33.59	3.58	0.00	99.60	93.58	N/A	N/A
5180.00	74.63	PK	V	33.59	3.58	0.00	111.80	105.78	N/A	N/A
5180.00	65.74	AV	V	33.59	3.58	0.00	102.91	96.89	N/A	N/A
5150.00	29.82	PK	V	33.54	3.56	0.00	66.92	60.9	74.00	13.10
5150.00	17.25	AV	V	33.54	3.56	0.00	54.35	48.33	54.00	5.67
10360.00	56.80	PK	V	38.17	6.29	36.85	64.41	58.39	68.20	9.81
15540.00	61.19	PK	V	38.06	8.85	39.04	69.06	63.04	74.00	10.96
15540.00	47.99	AV	V	38.06	8.85	39.04	55.86	49.84	54.00	4.16
Middle Channel: 5200 MHz										
5200.00	72.25	PK	H	33.62	3.60	0.00	109.47	103.45	N/A	N/A
5200.00	63.47	AV	H	33.62	3.60	0.00	100.69	94.67	N/A	N/A
5200.00	75.22	PK	V	33.62	3.60	0.00	112.44	106.42	N/A	N/A
5200.00	66.35	AV	V	33.62	3.60	0.00	103.57	97.55	N/A	N/A
10400.00	56.56	PK	V	38.18	6.32	36.86	64.20	58.18	68.20	10.02
15600.00	61.72	PK	V	38.00	8.83	39.09	69.46	63.44	74.00	10.56
15600.00	48.44	AV	V	38.00	8.83	39.09	56.18	50.16	54.00	3.84
igh Channel: 5240 MHz										
5240.00	72.69	PK	H	33.68	3.52	0.00	109.89	103.87	N/A	N/A
5240.00	63.81	AV	H	33.68	3.52	0.00	101.01	94.99	N/A	N/A
5240.00	75.45	PK	V	33.68	3.52	0.00	112.65	106.63	N/A	N/A
5240.00	66.78	AV	V	33.68	3.52	0.00	103.98	97.96	N/A	N/A
5350.00	26.33	PK	V	33.86	3.52	0.00	63.71	57.69	74.00	16.31
5350.00	14.68	AV	V	33.86	3.52	0.00	52.06	46.04	54.00	7.96
10480.00	56.03	PK	V	38.20	6.37	36.88	63.72	57.7	68.20	10.5
15720.00	61.00	PK	V	37.88	8.79	39.18	68.49	62.47	74.00	11.53
15720.00	47.76	AV	V	37.88	8.79	39.18	55.25	49.23	54.00	4.77

802.11n ht20

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Extrapolation result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Remark	Polar (H/V)	Factor (dB/m)						
Low Channel: 5180 MHz										
5180.00	71.48	PK	H	33.59	3.58	0.00	108.65	102.63	N/A	N/A
5180.00	62.62	AV	H	33.59	3.58	0.00	99.79	93.77	N/A	N/A
5180.00	75.28	PK	V	33.59	3.58	0.00	112.45	106.43	N/A	N/A
5180.00	66.43	AV	V	33.59	3.58	0.00	103.60	97.58	N/A	N/A
5150.00	32.60	PK	V	33.54	3.56	0.00	69.70	63.68	74.00	10.32
5150.00	17.90	AV	V	33.54	3.56	0.00	55.00	48.98	54.00	5.02
10360.00	58.70	PK	V	38.17	6.29	36.85	66.31	60.29	68.20	7.91
15540.00	62.25	PK	V	38.06	8.85	39.04	70.12	64.1	74.00	9.90
15540.00	46.70	AV	V	38.06	8.85	39.04	54.57	48.55	54.00	5.45
Middle Channel: 5200 MHz										
5200.00	72.65	PK	H	33.62	3.60	0.00	109.87	103.85	N/A	N/A
5200.00	63.42	AV	H	33.62	3.60	0.00	100.64	94.62	N/A	N/A
5200.00	76.01	PK	V	33.62	3.60	0.00	113.23	107.21	N/A	N/A
5200.00	67.15	AV	V	33.62	3.60	0.00	104.37	98.35	N/A	N/A
10400.00	58.63	PK	V	38.18	6.32	36.86	66.27	60.25	68.20	7.95
15600.00	62.36	PK	V	38.00	8.83	39.09	70.10	64.08	74.00	9.92
15600.00	49.27	AV	V	38.00	8.83	39.09	57.01	50.99	54.00	3.01
High Channel: 5240 MHz										
5240.00	72.14	PK	H	33.68	3.52	0.00	109.34	103.32	N/A	N/A
5240.00	63.47	AV	H	33.68	3.52	0.00	100.67	94.65	N/A	N/A
5240.00	75.53	PK	V	33.68	3.52	0.00	112.73	106.71	N/A	N/A
5240.00	66.63	AV	V	33.68	3.52	0.00	103.83	97.81	N/A	N/A
5350.00	26.31	PK	V	33.86	3.52	0.00	63.69	57.67	74.00	16.33
5350.00	14.65	AV	V	33.86	3.52	0.00	52.03	46.01	54.00	7.99
10480.00	59.87	PK	V	38.20	6.37	36.88	67.56	61.54	68.20	6.66
15720.00	61.70	PK	V	37.88	8.79	39.18	69.19	63.17	74.00	10.83
15720.00	46.76	AV	V	37.88	8.79	39.18	54.25	48.23	54.00	5.77

802.11n ht40

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Extrapolation result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Remark	Polar (H/V)	Factor (dB/m)						
Low Channel:5190 MHz										
5190.00	67.51	PK	H	33.60	3.59	0.00	104.70	98.68	N/A	N/A
5190.00	58.70	AV	H	33.60	3.59	0.00	95.89	89.87	N/A	N/A
5190.00	70.87	PK	V	33.60	3.59	0.00	108.06	102.04	N/A	N/A
5190.00	61.81	AV	V	33.60	3.59	0.00	99.00	92.98	N/A	N/A
5150.00	35.27	PK	V	33.54	3.56	0.00	72.37	66.35	74.00	7.65
5150.00	18.91	AV	V	33.54	3.56	0.00	56.01	49.99	54.00	4.01
10380.00	53.91	PK	V	38.18	6.31	36.85	61.55	55.53	68.20	12.67
15570.00	55.87	PK	V	38.03	8.84	39.06	63.68	57.66	74.00	16.34
15570.00	42.51	AV	V	38.03	8.84	39.06	50.32	44.3	54.00	9.70
High Channel:5230 MHz										
5230.00	69.20	PK	H	33.67	3.54	0.00	106.41	100.39	N/A	N/A
5230.00	60.15	AV	H	33.67	3.54	0.00	97.36	91.34	N/A	N/A
5230.00	72.52	PK	V	33.67	3.54	0.00	109.73	103.71	N/A	N/A
5230.00	63.30	AV	V	33.67	3.54	0.00	100.51	94.49	N/A	N/A
5350.00	27.92	PK	V	33.86	3.52	0.00	65.30	59.28	74.00	14.72
5350.00	14.67	AV	V	33.86	3.52	0.00	52.05	46.03	54.00	7.97
10460.00	58.04	PK	V	38.19	6.36	36.87	65.72	59.7	68.20	8.50
15690.00	57.09	PK	V	37.91	8.80	39.15	64.65	58.63	74.00	15.37
15690.00	44.99	AV	V	37.91	8.80	39.15	52.55	46.53	54.00	7.47

802.11 ac80

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Extrapolation result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Remark	Polar (H/V)	Factor (dB/m)						
Middle Channel: 5210 MHz										
5210.00	64.59	PK	H	33.64	3.58	0.00	101.81	95.79	N/A	N/A
5210.00	54.92	AV	H	33.64	3.58	0.00	92.14	86.12	N/A	N/A
5210.00	67.51	PK	V	33.64	3.58	0.00	104.73	98.71	N/A	N/A
5210.00	57.93	AV	V	33.64	3.58	0.00	95.15	89.13	N/A	N/A
5150.00	32.33	PK	V	33.54	3.56	0.00	69.43	63.41	74.00	10.59
5150.00	18.94	AV	V	33.54	3.56	0.00	56.04	50.02	54.00	3.98
5350.00	25.98	PK	V	33.86	3.52	0.00	63.36	57.34	74.00	16.66
5350.00	14.69	AV	V	33.86	3.52	0.00	52.07	46.05	54.00	7.95
10420.00	52.99	PK	V	38.18	6.33	36.86	60.64	54.62	68.20	13.58
15630.00	51.27	PK	V	37.97	8.82	39.11	58.95	52.93	74.00	21.07
15630.00	37.77	AV	V	37.97	8.82	39.11	45.45	39.43	54.00	14.57

**5725-5850MHz:
802.11a**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Extrapolation result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Remark	Polar (H/V)	Factor (dB/m)						
Low Channel: 5745MHz										
5745.00	66.14	PK	H	34.20	3.69	0.00	104.03	98.01	N/A	N/A
5745.00	58.01	AV	H	34.20	3.69	0.00	95.90	89.88	N/A	N/A
5745.00	69.35	PK	V	34.20	3.69	0.00	107.24	101.22	N/A	N/A
5745.00	60.75	AV	V	34.20	3.69	0.00	98.64	92.62	N/A	N/A
5725.00	42.18	PK	V	34.19	3.69	0.00	80.06	74.04	122.20	48.16
5720.00	31.02	PK	V	34.19	3.69	0.00	68.90	62.88	110.80	47.92
5700.00	26.28	PK	V	34.18	3.68	0.00	64.14	58.12	105.20	47.08
5650.00	27.74	PK	V	34.16	3.63	0.00	65.53	59.51	68.20	8.69
11490.00	52.33	PK	V	38.99	6.59	37.35	60.56	54.54	74.00	19.46
11490.00	39.00	AV	V	38.99	6.59	37.35	47.23	41.21	54.00	12.79
17235.00	48.68	PK	V	41.56	8.78	38.61	60.41	54.39	68.20	13.81
Middle Channel: 5785 MHz										
5785.00	66.81	PK	H	34.21	3.71	0.00	104.73	98.71	N/A	N/A
5785.00	58.92	AV	H	34.21	3.71	0.00	96.84	90.82	N/A	N/A
5785.00	69.49	PK	V	34.21	3.71	0.00	107.41	101.39	N/A	N/A
5785.00	60.93	AV	V	34.21	3.71	0.00	98.85	92.83	N/A	N/A
11570.00	51.86	PK	V	39.00	6.61	37.44	60.03	54.01	74.00	19.99
11570.00	38.96	AV	V	39.00	6.61	37.44	47.13	41.11	54.00	12.89
17355.00	47.67	PK	V	42.26	8.81	38.52	60.22	54.2	68.20	14.00
High Channel: 5825 MHz										
5825.00	64.52	PK	H	34.23	3.73	0.00	102.48	96.46	N/A	N/A
5825.00	55.62	AV	H	34.23	3.73	0.00	93.58	87.56	N/A	N/A
5825.00	67.98	PK	V	34.23	3.73	0.00	105.94	99.92	N/A	N/A
5825.00	59.01	AV	V	34.23	3.73	0.00	96.97	90.95	N/A	N/A
5850.00	28.69	PK	V	34.24	3.75	0.00	66.68	60.66	122.20	61.54
5855.00	28.04	PK	V	34.24	3.75	0.00	66.03	60.01	110.80	50.79
5875.00	27.05	PK	V	34.25	3.77	0.00	65.07	59.05	105.20	46.15
5925.00	27.56	PK	V	34.27	3.80	0.00	65.63	59.61	68.20	8.59
11650.00	54.75	PK	V	39.00	6.64	37.53	62.86	56.84	74.00	17.16
11650.00	41.08	AV	V	39.00	6.64	37.53	49.19	43.17	54.00	10.83
17475.00	48.95	PK	V	42.96	8.84	38.44	62.31	56.29	68.20	11.91

802.11n ht20

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Extrapolation result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Remark	Polar (H/V)	Factor (dB/m)						
Low Channel: 5745MHz										
5745.00	65.01	PK	H	34.20	3.69	0.00	102.90	96.88	N/A	N/A
5745.00	56.22	AV	H	34.20	3.69	0.00	94.11	88.09	N/A	N/A
5745.00	69.24	PK	V	34.20	3.69	0.00	107.13	101.11	N/A	N/A
5745.00	60.12	AV	V	34.20	3.69	0.00	98.01	91.99	N/A	N/A
5725.00	43.10	PK	V	34.19	3.69	0.00	80.98	74.96	122.20	47.24
5720.00	37.40	PK	V	34.19	3.69	0.00	75.28	69.26	110.80	41.54
5700.00	26.88	PK	V	34.18	3.68	0.00	64.74	58.72	105.20	46.48
5650.00	27.63	PK	V	34.16	3.63	0.00	65.42	59.4	68.20	8.80
11490.00	53.03	PK	V	38.99	6.59	37.35	61.26	55.24	74.00	18.76
11490.00	39.65	AV	V	38.99	6.59	37.35	47.88	41.86	54.00	12.14
17235.00	50.70	PK	V	41.56	8.78	38.61	62.43	56.41	68.20	11.79
Middle Channel: 5785 MHz										
5785.00	65.71	PK	H	34.21	3.71	0.00	103.63	97.61	N/A	N/A
5785.00	56.85	AV	H	34.21	3.71	0.00	94.77	88.75	N/A	N/A
5785.00	69.64	PK	V	34.21	3.71	0.00	107.56	101.54	N/A	N/A
5785.00	60.88	AV	V	34.21	3.71	0.00	98.80	92.78	N/A	N/A
11570.00	52.96	PK	V	39.00	6.61	37.44	61.13	55.11	74.00	18.89
11570.00	38.20	AV	V	39.00	6.61	37.44	46.37	40.35	54.00	13.65
17355.00	48.32	PK	V	42.26	8.81	38.52	60.87	54.85	68.20	13.35
High Channel: 5825 MHz										
5825.00	65.52	PK	H	34.23	3.73	0.00	103.48	97.46	N/A	N/A
5825.00	56.14	AV	H	34.23	3.73	0.00	94.10	88.08	N/A	N/A
5825.00	69.07	PK	V	34.23	3.73	0.00	107.03	101.01	N/A	N/A
5825.00	60.24	AV	V	34.23	3.73	0.00	98.20	92.18	N/A	N/A
5850.00	34.44	PK	V	34.24	3.75	0.00	72.43	66.41	122.20	55.79
5855.00	27.98	PK	V	34.24	3.75	0.00	65.97	59.95	110.80	50.85
5875.00	28.80	PK	V	34.25	3.77	0.00	66.82	60.8	105.20	44.40
5925.00	27.88	PK	V	34.27	3.80	0.00	65.95	59.93	68.20	8.27
11650.00	54.03	PK	V	39.00	6.64	37.53	62.14	56.12	74.00	17.88
11650.00	39.68	AV	V	39.00	6.64	37.53	47.79	41.77	54.00	12.23
17475.00	50.74	PK	V	42.96	8.84	38.44	64.10	58.08	68.20	10.12

802.11n ht40




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Extrapolation result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark	Polar (H/V)	Factor (dB/m)						
Low Channel: 5755MHz										
5755.00	61.83	PK	H	34.20	3.70	0.00	99.73	93.71	N/A	N/A
5755.00	52.71	AV	H	34.20	3.70	0.00	90.61	84.59	N/A	N/A
5755.00	65.07	PK	V	34.20	3.70	0.00	102.97	96.95	N/A	N/A
5755.00	56.25	AV	V	34.20	3.70	0.00	94.15	88.13	N/A	N/A
5725.00	40.75	PK	V	34.19	3.69	0.00	78.63	72.61	122.20	49.59
5720.00	38.53	PK	V	34.19	3.69	0.00	76.41	70.39	110.80	40.41
5700.00	31.77	PK	V	34.18	3.68	0.00	69.63	63.61	105.20	41.59
5650.00	27.17	PK	V	34.16	3.63	0.00	64.96	58.94	68.20	9.26
11510.00	50.45	PK	V	39.00	6.59	37.37	58.67	52.65	74.00	21.35
11510.00	38.52	AV	V	39.00	6.59	37.37	46.74	40.72	54.00	13.28
17265.00	48.28	PK	V	41.74	8.79	38.58	60.23	54.21	68.20	13.99
High Channel: 5795 MHz										
5795.00	61.52	PK	H	34.22	3.71	0.00	99.45	93.43	N/A	N/A
5795.00	52.93	AV	H	34.22	3.71	0.00	90.86	84.84	N/A	N/A
5795.00	64.49	PK	V	34.22	3.71	0.00	102.42	96.4	N/A	N/A
5795.00	55.53	AV	V	34.22	3.71	0.00	93.46	87.44	N/A	N/A
5850.00	28.84	PK	V	34.24	3.75	0.00	66.83	60.81	122.20	61.39
5855.00	27.42	PK	V	34.24	3.75	0.00	65.41	59.39	110.80	51.41
5875.00	26.50	PK	V	34.25	3.77	0.00	64.52	58.5	105.20	46.70
5925.00	27.15	PK	V	34.27	3.80	0.00	65.22	59.2	68.20	9.00
11590.00	49.00	PK	V	39.00	6.62	37.46	57.16	51.14	74.00	22.86
11590.00	37.62	AV	V	39.00	6.62	37.46	45.78	39.76	54.00	14.24
17385.00	47.53	PK	V	42.43	8.82	38.50	60.28	54.26	68.20	13.94


802.11 ac80

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Extrapolation result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark	Polar (H/V)	Factor (dB/m)						
Middle Channel: 5775 MHz										
5775.00	60.15	PK	H	34.21	3.70	0.00	98.06	92.04	N/A	N/A
5775.00	49.83	AV	H	34.21	3.70	0.00	87.74	81.72	N/A	N/A
5775.00	62.34	PK	V	34.21	3.70	0.00	100.25	94.23	N/A	N/A
5775.00	51.64	AV	V	34.21	3.70	0.00	89.55	83.53	N/A	N/A
5725.00	36.73	PK	V	34.19	3.69	0.00	74.61	68.59	122.20	53.61
5720.00	35.86	PK	V	34.19	3.69	0.00	73.74	67.72	110.80	43.08
5700.00	31.68	PK	V	34.18	3.68	0.00	69.54	63.52	105.20	41.68
5650.00	27.10	PK	V	34.16	3.63	0.00	64.89	58.87	68.20	9.33
5850.00	32.90	PK	V	34.24	3.75	0.00	70.89	64.87	122.20	57.33
5855.00	31.91	PK	V	34.24	3.75	0.00	69.90	63.88	110.80	46.92
5875.00	27.83	PK	V	34.25	3.77	0.00	65.85	59.83	105.20	45.37
5925.00	27.68	PK	V	34.27	3.80	0.00	65.75	59.73	68.20	8.47
11550.00	46.57	PK	V	39.00	6.61	37.42	54.76	48.74	74.00	25.26
11550.00	33.92	AV	V	39.00	6.61	37.42	42.11	36.09	54.00	17.91
17325.00	48.06	PK	V	42.09	8.80	38.54	60.41	54.39	68.20	13.81

**Worst Test Plots (802.11n ht20 5200MHz)
Horizontal:**



Fundamental
Test with Band
Rejection Filter







Vertical:

Fundamental Test with Band Rejection Filter





FCC §15.407(a)(e) – EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH

Applicable Standard

15.407(a)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

Test Data

Environmental Conditions

Temperature:	27.8°C
Relative Humidity:	60 %
ATM Pressure:	100.6kPa

The testing was performed by Blake Yang on 2019-02-22.

Test Result: Compliance. Please refer to the following tables and plots.

Test mode: Transmitting

5150-5250MHz:

Mode	Frequency (MHz)	26 dB Emission Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11a	5180	26.080	17.166
	5200	25.520	17.006
	5240	26.560	17.086
802.11n ht20	5180	27.920	18.044
	5200	28.640	18.044
	5240	28.880	17.964
802.11n ht40	5190	45.440	37.046
	5230	60.318	37.685
802.11 ac80	5210	125.690	76.966


5725-5850MHz:

Mode	Frequency (MHz)	6 dB mission Bandwidth (MHz)	6dB Emission bandwidth Limits (MHz)	99% Occupied Bandwidth (MHz)
802.11 a	5745	15.280	≥ 0.5	16.926
	5785	15.200	≥ 0.5	16.926
	5825	15.200	≥ 0.5	16.926
802.11 n20	5745	15.200	≥ 0.5	17.884
	5785	15.200	≥ 0.5	17.804
	5825	15.200	≥ 0.5	17.725
802.11 n40	5755	35.200	≥ 0.5	36.886
	5795	35.200	≥ 0.5	36.886
802.11 ac80	5775	75.520	≥ 0.5	76.327


Note: the 99% Occupied Bandwidth have not fall into the band 5150-5250MHz or 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.

**26dB Emission Bandwidth:
5150-5250MHz:**


802.11a 5180MHz




802.11a 5200MHz




802.11a 5240MHz




802.11n ht20 5180MHz




802.11n ht20 5200MHz




802.11n ht20 5240MHz




802.11n ht40 5190MHz



802.11n ht40 5230MHz




802.11 ac80 5210MHz




Date: 15.MAR.2019 04:40:56

**99% Occupied Bandwidth:
5150-5250MHz:**

802.11a 5180MHz




802.11a 5200MHz




802.11a 5240MHz




802.11n ht20 5180MHz



802.11n ht20 5200MHz




802.11n ht20 5240MHz




802.11n ht40 5190MHz



802.11n ht40 5230MHz




802.11 ac80 5210MHz



Date: 15.MAR.2019 04:36:31


5725-5850MHz
6dB Minimum Emission Bandwidth:

802.11a 5745MHz




Date: 15. MAR. 2019 04:42:09

802.11a 5785MHz




Date: 15. MAR. 2019 04:43:34


802.11a 5825MHz



802.11n ht20 5745MHz




802.11n ht20 5785MHz




Date: 15.MAR.2019 04:47:24

802.11n ht20 5825MHz




Date: 15.MAR.2019 04:48:59

802.11n ht40 5755MHz




Date: 15.MAR.2019 04:50:14

802.11n ht40 5795MHz



Date: 15.MAR.2019 04:51:13

802.11 ac80 5775MHz



Date: 15.MAR.2019 04:52:23

5725-5850MHz
99% Occupied Bandwidth:

802.11a 5745MHz




Date: 15. MAR. 2019 04:42:36

802.11a 5785MHz



Date: 15. MAR. 2019 04:44:01

802.11a 5825MHz




Date: 15.MAR.2019 04:45:15

802.11n ht20 5745MHz



Date: 15.MAR.2019 04:46:34

802.11n ht20 5785MHz




Date: 15.MAR.2019 04:47:39

802.11n ht20 5825MHz




Date: 15.MAR.2019 04:49:19

802.11n ht40 5755MHz




Date: 15.MAR.2019 04:50:25

802.11n ht40 5795MHz



Date: 15.MAR.2019 04:51:25

802.11 ac80 5775MHz



Date: 15.MAR.2019 04:52:47

FCC §15.407(a) –MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.407(a)

(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2018-12-10	2019-12-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

Test Data

Environmental Conditions

Temperature:	27.8°C
Relative Humidity:	60 %
ATM Pressure:	100.6kPa

The testing was performed by Blake Yang on 2019-02-22.

Test Mode: Transmitting

Band	Mode	Frequency (MHz)	Conducted Average Output Power (dBm)	Limit (dBm)
5150-5250MHz	802.11a	5180	13.88	24
		5200	13.94	
		5240	13.92	
	802.11n ht20	5180	14.08	
		5200	14.09	
		5240	14.02	
	802.11n ht40	5190	12.24	
		5230	14.00	
802.11ac80	5210	13.39		
5725-5850MHz	802.11a	5745	13.39	30
		5785	13.13	
		5825	12.73	
	802.11n ht20	5745	13.07	
		5785	12.95	
		5825	11.55	
	802.11n ht40	5755	12.16	
		5795	12.02	
	802.11ac80	5775	10.10	

Note: the duty cycle was calculated to the result.

FCC §15.407(a) - POWER SPECTRAL DENSITY

Applicable Standard

According to FCC §15.407(a)

(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.3~27.8°C
Relative Humidity:	34 ~59 %
ATM Pressure:	100.4 ~ 100.8 kPa

The testing was performed by Blake Yang on 2019-02-22 & 2019-02-28

Test Result: Compliance

Test Mode: Transmitting

5150-5250MHz:

Mode	Frequency (MHz)	Maximum Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)
802.11a	5180	8.06	11
	5200	7.97	
	5240	8.58	
802.11n ht20	5180	7.89	
	5200	7.86	
	5240	8.32	
802.11n ht40	5190	3.02	
	5230	5.48	
802.11ac80	5210	0.61	

5725-5850 MHz:


Mode	Frequency (MHz)	Maximum Power Spectral Density (dBm/300kHz)	Maximum Power Spectral Density (dBm/500kHz)	Limit (dBm/500kHz)
802.11a	5745	5.16	7.38	30
	5785	4.68	6.9	
	5825	4.50	6.72	
802.11n ht20	5745	4.40	6.62	
	5785	4.04	6.26	
	5825	2.68	4.9	
802.11n ht40	5755	1.06	3.28	
	5795	0.25	2.47	
802.11ac80	5775	-4.75	-2.53	

Note:


For 5.8GHz band, If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.

5150-5250MHz:


Power Spectral Density, 802.11a 5180MHz




Power Spectral Density, 802.11a 5200MHz




Power Spectral Density, 802.11a 5240MHz




Power Spectral Density, 802.11n ht20 5180MHz




Power Spectral Density, 802.11n ht20 5200MHz




Power Spectral Density, 802.11n ht20 5240MHz




Power Spectral Density, 802.11n ht40 5190MHz



Power Spectral Density, 802.11n ht40 5230MHz




Power Spectral Density, 802.11 ac80 5210MHz




5725-5850MHz:

Power Spectral Density, 802.11a 5745MHz




Power Spectral Density, 802.11a 5785MHz




Date: 15.MAR.2019 04:44:18

Power Spectral Density, 802.11a 5825MHz




Date: 15.MAR.2019 04:45:35

Power Spectral Density, 802.11n ht20 5745MHz




Date: 15.MAR.2019 04:46:54

Power Spectral Density, 802.11n ht20 5785MHz




Date: 15.MAR.2019 04:47:59

Power Spectral Density, 802.11n ht20 5825MHz




Date: 15.MAR.2019 04:49:36

Power Spectral Density, 802.11n ht40 5755MHz




Date: 15.MAR.2019 04:50:39

Power Spectral Density, 802.11n ht40 5795MHz



Date: 15.MAR.2019 04:51:39

Power Spectral Density, 802.11 ac80 5775MHz



Date: 15.MAR.2019 04:53:07

**** END OF REPORT ****