

Passive Test For WiFi2.4												
Freq (MHz)	Eff1 (dBi)	Eff2 (dBi)	Gain (dBi)	Gain (dBi)	DHS (dBi)	DHS (dBi)	Max (dBi)	Min (dBi)	Directivity (dBi)	Beamwidth (3dB)	AttH (dBi)	AttV (dBi)
2400	28.24	-8.81	-1.73	-3.58	13.785	12.451	-1.73	-20.53	4.08	7.5	49.04	48.91
2410	27.11	-5.67	-1.44	-3.59	14.104	13.005	-1.44	-20.63	4.23	6.0	49.03	48.93
2420	28.97	-5.38	-1.01	-3.16	14.971	13.995	-1.01	-20.38	4.37	6.0	49.09	48.97
2430	30.02	-5.23	-0.72	-2.87	15.445	14.572	-0.72	-20.92	4.51	6.0	49.13	49.11
2440	31.63	-5	-0.43	-2.58	16.285	15.345	-0.43	-22.05	4.57	7.5	49.13	49.11
2450	32.72	-4.85	-0.37	-2.52	16.929	15.796	-0.37	-23.58	4.49	6.0	49.39	49.35
2460	33.51	-4.73	-0.36	-2.51	17.411	16.102	-0.36	-25.12	4.39	6.0	49.39	49.35
2470	33.59	-4.74	-0.48	-2.63	17.581	16.007	-0.48	-23.03	4.26	7.5	49.39	49.3
2480	33.35	-4.77	-0.61	-2.76	17.541	15.81	-0.61	-20.92	4.16	7.5	49.44	49.35
2490	30.17	-5.2	-1.16	-3.31	15.899	14.266	-1.16	-19.91	4.05	6.0	49.19	49.13
2500	28.91	-5.39	-1.39	-3.51	15.203	13.706	-1.39	-18.93	4.1	6.0	49.32	49.3

Application Information	
Diversion	4.95.303
TotalTime	13m 10s 583ms
AdditionalInfor	NULL

