







6. SITE MAINTENANCE OPERATIONS

Back side

[1] Request OTP to open the site and assets

After arriving to the location, Check-in to the site via the app to receive an OTP to open the site/assets or send an SMS O, <SITE ID>, <PIN CODE>

Receive an Opening OTP to activate the key. OTP Validity is 10 minutes



[2] Open the site

The Opening **OTP** is automatically synced to the key immediately after the request, or manually inserted on the key's keypad in case of a Bluetooth failure or cellular data unavailability. The key is now activated, if the OTP is not entered within its validity period, a **new request must be made**.

Put the key into the lock, After the key's LED flashes **green** twice, turn the key to open the lock, Go inside the site and begin the maintenance work.



[3] Request OTP to close the site and assets

After finishing work, check-out of the site via the app to receive an OTP to close the site/assets or send an SMS C, <SITE ID>, <PIN CODE>

Receive a Closing OTP to activate the key.

OTP Validity is 10 minutes



[4] Close the site

The Closing **OTP** is automatically synced to the key immediately after the request or manually inserted on the key's keypad in case of a Bluetooth failure or cellular data unavailability. The key is now activated, if the OTP is not entered within its validity period, a **new request must be made**.

Put the key into the lock. After the key's LED flashes ${\it green}$ twice turn the key to close the lock.

NOTE for Steps 2 & 4

- The user may request access to the same site if approved by NOC.
 Once the site is closed, the user may need to open again. He must then submit a new request. If the site is already open, an open and close request has to be requested anyway, and the key should be inserted in the lock to log the visit.

 Access logs are automatically uploaded to the server during the Bluetooth synchronization process, or manually uploaded through a programmer in case of a Bluetooth failure.

7. LOCKS OPEN / CLOSE PROCEDURE

- Call the NOC immediately if you find
 Site is open, nobody on site
 Padlock is damaged
 Protection cap has not been closed





8.LOCKS INSTALLATION BEST PRACTICES









Padlocks MUST be installed HANGING DOWN

Do not install on the floor ALWAYS close the protection cap



PART NUMBER	PART NAME	REV	SCALE:
421-015A	AKEY BLE CGS PLUS USER MANUAL – ENG	00	1:1

FCC STATEMENT:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

Warning: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.

Increase the separation between the equipment and receiver.

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

Consult the dealer or an experienced radio/TV technician for help.