



FCC 47 CFR MPE REPORT

Arovast corporation

Levoit VeSync Core 300S Plus True HEPA Smart Air Purifier

Model Number: LAP-C302S-WUSR

Additional Model: LAP-C302S-WUSB, LAP-C302S- Followed by up to 4 characters

FCC ID: 2ARBY-CORE-300S

Applicant :	Arovast Corporation
Address:	1202 N. Miller St., Suite A, Anaheim, CA 92806, USA
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2403260
Date of Test:	Mar. 04, 2024~ Mar. 06, 2024
Date of Report:	Mar. 13, 2024

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the used antenna, the RF power density can be obtained

2. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	6.386	6±1	7	1.44	1.39	0.00139	1	Complies
π /4-DQPSK	6.129	6±1	7	1.44	1.39	0.00139	1	Complies
8DPSK	6.389	6±1	7	1.44	1.39	0.00139	1	Complies
BLE_GFSK	3.132	3±1	4	1.44	1.39	0.00070	1	Complies
802.11b	17.48	17±1	18	1.44	1.39	0.01749	1	Complies
802.11g	16.95	16±1	17	1.44	1.39	0.01389	1	Complies
802.11n H20	16.56	16±1	17	1.44	1.39	0.01389	1	Complies
802.11n H40	17.02	17±1	18	1.44	1.39	0.01749	1	Complies

End of Test Report