



# FCC 47 CFR MPE REPORT

Arovast Corporation

Air Purifier

Model Number: LAP-C401S-WUSR

Addition Model Number: LAP-C401S-KUSR

FCC ID: 2ARBY-CORE400S

Applicant:	Arovast Corporation
Address:	1202 N Miller St., Suite A, Anaheim, CA 92806, USA
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2407144
Date of Test:	Jul. 10, 2024 ~ Jul. 15, 2024
Date of Report:	Jul. 18, 2024

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2\text{m}$ , as well as the gain of the used antenna, the RF power density can be obtained

## 2. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm <sup>2</sup> )	Limited of Power Density (S) (mW /cm <sup>2</sup> )	Test Result
				(dBi)	(Linear)			
<b>2.4G Band</b>								
GFSK	6.233	6±1	7	2.04	1.60	0.0016	1	Complies
π/4-DQPSK	8.694	8±1	9	2.04	1.60	0.0025	1	Complies
8-DPSK	9.014	9±1	10	2.04	1.60	0.0032	1	Complies
BLE	3.916	4±1	5	2.04	1.60	0.0010	1	Complies
IEEE 802.11b	15.67	15±1	16	2.04	1.60	0.01267	1	Complies
IEEE 802.11g	17.50	17±1	18	2.04	1.60	0.02008	1	Complies
IEEE 802.11n HT20	16.76	17±1	18	2.04	1.60	0.02008	1	Complies
IEEE 802.11n HT40	16.47	17±1	18	2.04	1.60	0.02008	1	Complies

**End of Test Report**