

# MPE REPORT

FCC ID: 2ARBY-CS158-137-AF

Date of issue: Apr. 20, 2019

Report Number:	MTi190411E071
Sample Description:	Smart Air Fryer
Model(s):	CS158-AF, CS137-AF
Applicant:	Arovast Corporation
Address:	1202 N Miller St. Suite A, Anaheim, CA 92806, USA
Date of Test:	Mar. 29, 2019 to Apr. 20, 2019

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

<b>TEST RESULT CERTIFICATION</b>	
Applicant's name:	Arovast Corporation
Address:	1202 N Miller St. Suite A, Anaheim, CA 92806, USA
Manufacture's Name:	Zhejiang Tianxi Kitchen Appliance Co.,Ltd
Address:	No.1 West 2nd Road, Huzhen Town, Jinyun, Lishui, Zhejiang, China
Product name:	Smart Air Fryer
Trademark:	COSORI
Model and/or type reference .:	CS158-AF
Serial Model:	CS137-AF
RF Exposure Procedures:	KDB 447498 D01 v06

*This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.*

Tested by:




---

Demi Mu

Apr. 20, 2019

Reviewed by:




---

Blue Zheng

Apr. 20, 2019

Approved by:




---

Smith Chen

Apr. 20, 2019

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### MPE Calculation Method

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

### WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: FPCB Mounted Embedded Antenna;

WIFI antenna gain: 2.05 dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(2.05/10)}=1.60$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
		Ant A	Ant A	(dBm)	(mW)	Numeric		
2412	802.11b	13.88	13±1	14	25.118864	1.60	0.00800	1
2437		12.28	13±1	14	25.118864	1.60	0.00800	1
2462		12.73	13±1	14	25.118864	1.60	0.00800	1
2412	802.11g	9.37	10±1	11	12.589254	1.60	0.00401	1
2437		10.31	10±1	11	12.589254	1.60	0.00401	1
2462		10.97	10±1	11	12.589254	1.60	0.00401	1
2412	802.11n H20	9.46	10±1	11	12.589254	1.60	0.00401	1
2437		10.11	10±1	11	12.589254	1.60	0.00401	1
2462		10.68	10±1	11	12.589254	1.60	0.00401	1

### Conclusion:

For the max result:  $0.00800 \leq 1.0$  for 1g SAR, No SAR is required.

----END OF REPORT----