



FCC 47 CFR MPE REPORT

Arovast Corporation

Tower Fan

Model Number: LTF-F422S-WUSR

Additional Model: LTF-F422S-XXXX (where "X" may be blank,

number from 0 to 9 or letter from A to Z)

FCC ID: 2ARBY-F422SRA

Applicant:	Arovast Corporation
Address:	1775 FLIGHT WAY, SUITE 150 TUSTIN, CA 92782, USA
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2501057
Date of Test:	Dec. 04, 2024~ Dec. 19, 2024
Date of Report:	Jan. 07, 2025

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
BLE 1M	2402	8.31	6.776
	2440	8.87	7.709
	2480	8.07	6.412
BLE 2M	2402	8.63	7.295
	2440	9.10	8.128
	2480	8.19	6.592
IEEE 802.11b	2412	18.55	71.614
	2437	17.75	59.566
	2462	18.53	71.285
IEEE 802.11g	2412	19.08	80.910
	2437	18.56	71.779
	2462	19.24	83.946
IEEE 802.11n HT20	2412	17.98	62.806
	2437	17.28	53.456
	2462	17.89	61.518
IEEE 802.11n HT40	2422	17.37	54.576
	2437	16.92	49.204
	2452	17.07	50.933

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
				(dBi)	(Linear)			
2.4G Band								
BLE 1M	8.87	8±1	9	0.20	1.047	0.00165	1	Complies
BLE 2M	9.10	9±1	10	0.20	1.047	0.00208	1	Complies
IEEE 802.11b	18.55	18±1	19	0.20	1.047	0.01655	1	Complies
IEEE 802.11g	19.24	19±1	20	0.20	1.047	0.02083	1	Complies
IEEE 802.11n HT20	17.98	17±1	18	0.20	1.047	0.01314	1	Complies
IEEE 802.11n HT40	17.37	17±1	18	0.20	1.047	0.01314	1	Complies

End of Test Report