

1 Safety Human Exposure

1.1 Radio Frequency Exposure Compliance

1.1.1 Electromagnetic Fields RESULT: Test Specification

Pass

Test standard : CFR47 FCC Part 2: Section 2.1091
CFR47 FCC Part 1: Section 1.1310
FCC KDB Publication 447498 v06, section 7
RSS-102 Issue 5 March 2015, section 2.5.2

FCC ID: 2ARDBC-8031U
IC: 25276-C8031U

➤ FCC requirements

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

MPE Calculation Method according to KDB 447498 v06

Power Density: $S_{(mW/cm^2)} = PG/4\pi R^2$ or $EIRP/4\pi R^2$

Where:

S = power density (mW/cm²)

P = power input to the antenna (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm)

From the maximum conducted output power, the minimum mobile separation distance, d=20 cm, as well as the antenna gain, the RF power density can be calculated as below:

$S_{(mW/cm^2)} = PG/4\pi R^2$

a) EUT RF Exposure Evaluation operations, Worst Case mode

| Test Mode | Measured Power (dBm) | Antenna Gain (dBi) | Measured e.i.r.p (dBm) | $S_{(mW/cm^2)} = PG/4\pi R^2$ | Limit (mW/cm ²) |
|-------------------|----------------------|--------------------|------------------------|-------------------------------|-----------------------------|
| BLE | 2.8 | 1 | 3.8 | 0.0005 | 1.0 |
| 2.4GHz band Wi-Fi | 12.5 | 1 | 13.5 | 0.0045 | 1.0 |

The EUT power density for transmit simultaneously is 0.005 mW/cm² it is less than the limit 1.0 mW/cm²

➤ **IC requirements:** The EUT shall comply with the requirement of RSS-102 section 4 Exposure Limits.

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

a) EUT RF Exposure Evaluation standalone operations, Worst Case mode

| Test Mode | Maximum e.i.r.p (dBm) | Maximum e.i.r.p (W) | Limit (W) |
|-------------------|-----------------------|---------------------|-----------|
| 2.4GHz band Wi-Fi | 13.5 | 0.02238 | 2.68 |

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”