



# **FCC TEST REPORT**

**FCC ID:2ARE7- P31**

On Behalf of

**ShenZhenShi NewStone Technology co., Ltd**

**2.4G Transmitter**

**Model No.: P31**

Prepared for : ShenZhenShi NewStone Technology co., Ltd  
Address : B2 blvd, YuHong Industrial Park, No.20, XingYe West Road, ShaJing  
Town, ShenZhen, China,

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.  
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,  
Shenzhen, Guangdong, China

Report Number : A2007350-C01-R01  
Date of Receipt : August 07, 2020  
Date of Test : August 07, 2020- August 15, 2020  
Date of Report : August 17, 2020  
Version Number : V0

## TABLE OF CONTENTS

Description	Page
<b>1. Summary of Standards And Results .....</b>	<b>6</b>
1.1. Description of Standards and Results .....	6
<b>2. General Information.....</b>	<b>7</b>
2.1. Description of Device (EUT).....	7
2.2. Accessories of Device (EUT) .....	8
2.3. Tested Supporting System Details .....	8
2.4. Block Diagram of connection between EUT and simulators .....	8
2.5. Test Mode Description.....	8
2.6. Test Conditions .....	9
2.7. Additional instructions.....	10
2.8. Test Facility .....	11
2.9. Measurement Uncertainty.....	11
2.10. Test Equipment List .....	12
<b>3. Maximum Peak Output power .....</b>	<b>13</b>
3.1. Limit .....	13
3.2. Test Procedure .....	13
3.3. Test Setup.....	13
3.4. Test Result .....	13
<b>4. Bandwidth.....</b>	<b>14</b>
4.1. Limit .....	14
4.2. Test Procedure .....	14
4.3. Test Result .....	14
<b>5. Carrier Frequency Separation.....</b>	<b>14</b>
5.1. Limit .....	18
5.2. Test Procedure .....	18
5.3. Test Result .....	18
<b>6. Number Of Hopping Channel.....</b>	<b>19</b>
6.1. Limit .....	19
6.2. Test Procedure .....	19
6.3. Test Result .....	19
<b>7. Dwell Time.....</b>	<b>20</b>
7.1. Test limit .....	20
7.2. Test Procedure .....	20
7.3. Test Result .....	20
<b>8. Radiated emissions.....</b>	<b>23</b>
8.1. Limit .....	23
8.2. Block Diagram of Test setup .....	24
8.3. Test Procedure .....	25
8.4. Test Result .....	25

---

<b>9. Band Edge Compliance .....</b>	<b>29</b>
9.1. Block Diagram of Test Setup .....	29
9.2. Limit .....	29
9.3. Test Procedure .....	29
9.4. Test Result .....	29
<b>10. Power Line Conducted Emissions .....</b>	<b>33</b>
10.1. Block Diagram of Test Setup .....	33
10.2. Limit .....	33
10.3. Test Procedure .....	33
10.4. Test Result .....	33
<b>11. Antenna Requirements .....</b>	<b>34</b>
11.1. Limit .....	34
11.2. Result .....	34
<b>12. Test setup photo .....</b>	<b>35</b>
12.1. Photos of Radiated emission.....	35
<b>13. Photos of EUT .....</b>	<b>36</b>

### TEST REPORT DECLARATION

Applicant : ShenZhenShi NewStone Technology co., Ltd  
 Address : B2 blvd, YuHong Industrial Park, No.20, XingYe West Road, ShaJing Town, ShenZhen, China,  
 Manufacturer : ShenZhenShi NewStone Technology co., Ltd  
 Address : B2 blvd, YuHong Industrial Park, No.20, XingYe West Road, ShaJing Town, ShenZhen, China,  
 EUT Description : 2.4G Transmitter  
 (A) Model No. : P31  
 (B) Trademark : N/A

Measurement Standard Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247  
ANSI C63.10:2013**

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Lucas Pang  
 Project Engineer



Approved by (name + signature).....: Simple Guan  
 Project Manager



Date of issue..... : August 17, 2020

**Revision History**

Revision	Issue Date	Revisions	Revised By
V0	August 17, 2020	Initial released Issue	Lucas Pang

## 1. Summary Of Standards And Results

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013	N/A
Antenna requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	

## 2. General Information

### 2.1. Description of Device (EUT)

Description : 2.4G Transmitter

Model Number : P31

Diff : N/A

Trademark : N/A

Test Voltage : DC 6V from battery

Operation frequency : 2405-2478MHz

Channel No. : 73 Channels(Channel Spacing 1MHz)

Modulation type : GFSK

Antenna Type : Internal Antenna, Maximum Gain is 2dBi

Software version : V1.0

Hardware version : V1.0

Channel list:

2405-2478MHz:

Channel	Freq (MHz)	Channel	Freq (MHz)	Channel	Freq (MHz)	Channel	Freq (MHz)
1CH	2405	21CH	2425	41CH	2445	61CH	2465
2CH	2406	22CH	2426	42CH	2446	62CH	2466
3CH	2407	23CH	2427	43CH	2447	63CH	2467
4CH	2408	24CH	2428	44CH	2448	64CH	2468
5CH	2409	25CH	2429	45CH	2449	65CH	2469
6CH	2410	26CH	2430	46CH	2450	66CH	2470
7CH	2411	27CH	2431	47CH	2451	67CH	2471
8CH	2412	28CH	2432	48CH	2452	68CH	2472
9CH	2413	29CH	2433	49CH	2453	69CH	2473
10CH	2414	30CH	2434	50CH	2454	70CH	2474
11CH	2415	31CH	2435	51CH	2455	71CH	2475
12CH	2416	32CH	2436	52CH	2456	72CH	2476
13CH	2417	33CH	2437	53CH	2457	73CH	2478
14CH	2418	34CH	2438	54CH	2458		
15CH	2419	34CH	2439	55CH	2459		
16CH	2420	36CH	2440	56CH	2460		
17CH	2421	37CH	2441	57CH	2461		
18CH	2422	38CH	2442	58CH	2462		
19CH	2423	39CH	2443	59CH	2463		
20CH	2424	40CH	2444	60CH	2464		


## 2.2. Accessories of Device (EUT)

Accessory 1 : N/A

## 2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification
1	N/A	N/A	N/A	N/A	N/A

## 2.4. Block Diagram of connection between EUT and simulators



## 2.5. Test Mode Description

Tested mode, channel, and data rate information
---



Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2405
	Middle: CH37	2441
	High: CH73	2478

## 2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-45°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

## 2.7. Additional instructions

The operation (Used for test) from client

Mode	Special operated method is used. The operation provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.		
Power level setup in software			
Mode	Channel	Frequency (MHz)	Soft Set
GFSK	CH1	2405	TX level is set as defaults value.
	CH37	2441	
	CH73	2478	

## 2.8. Test Facility

Shenzhen Alpha Product Testing Co., Ltd  
 Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,  
 Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission

Registration Number: 293961

Designation Number: CN1236

July 15, 2019 Certificated by IC

Registration Number: CN0085

## 2.9. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.77dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.16 dB(Polarize: V)
	2.62dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.76dB(Polarize: V)
	3.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.22dB(Polarize: H)
	4.18dB(Polarize: V)
Uncertainty for radio frequency	$5.6 \times 10^{-8}$
Uncertainty for conducted RF Power	0.39dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

## 2.10.Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	N/A	2019.09.06	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	102137	2019.09.05	1Year
Spectrum analyzer	Agilent	N9020A	MY499100060	2019.09.05	1Year
Receiver	ROHDE&SCHWARZ	ESR	1316.3003K03-10208 2-Wa	2019.09.06	1Year
Receiver	R&S	ESCI	101165	2019.09.05	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2018.04.13	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	2018.04.13	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00059	2019.09.07	2Year
Cable	Resenberger	N/A	No.1	2019.09.05	1Year
Cable	Resenberger	N/A	No.2	2019.09.05	1Year
Cable	Resenberger	N/A	No.3	2019.09.05	1Year
Pre-amplifier	HP	HP8347A	2834A00455	2019.09.05	1Year
Pre-amplifier	Agilent	8449B	3008A02664	2019.09.05	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	2019.09.05	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2019.09.05	1Year
20db Attenuator	ICPROBING	IATS1	82347	2019.08.26	1Year
Horn Antenna	SCHWARZBECK	BBHA9170	00946	2019.09.07	2Year
Preamplifier	SKET	LNPA_1840-50	SK2018101801	2019.09.06	1Year
Power Meter	Agilent	E9300A	MY41496625	2019.09.06	1Year
Temp. & Humid. Chamber	Weihuang	WHTH-1000-40-8 80	100631	2019.09.06	1Year
Switching Mode Power Supply	JUNKE	JK12010S	20140927-6	2019.09.05	1Year

### 3. Maximum Peak Output Power

#### 3.1.Limit


Please refer section 15.247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

#### 3.2.Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

#### 3.3.Test Setup



#### 3.4.Test Result

Mode	Freq (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)	Result
GFSK	2405	6.283	4.249	21.00	Pass
	2441	5.735	3.745	21.00	Pass
	2478	5.520	3.565	21.00	Pass
Conclusion: PASS					

## 4. Bandwidth

### 4.1.Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


### 4.2.Test Procedure

The transmitter output was directly connected to a spectrum analyzer with a 50Ω cable. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### 4.3.Test Result


Frequency (MHz)	Antenna	99% OBW (MHz)	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
2405	Ant 1	0.4042	0.3244	N/A	Pass
2441	Ant 1	0.7969	0.9618	N/A	Pass
2478	Ant 1	0.8645	0.9134	N/A	Pass

OBW NVNT user 2405MHz Ant1




Date: 11.AUG.2020 14:02:21

-20 dB BW NVNT user 2405MHz Ant1




Date: 11.AUG.2020 14:02:24

OBW NVNT user 2441MHz Ant1



Date: 11.AUG.2020 14:23:02


-20 dB BW NVNT user 2441MHz Ant1



Date: 11.AUG.2020 14:23:06




OBW NVNT user 2478MHz Ant1



Date: 11.AUG.2020 14:23:47

-20 dB BW NVNT user 2478MHz Ant1



Date: 11.AUG.2020 14:23:50

## 5. Carrier Frequency Separation

### 5.1.Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


### 5.2.Test Procedure

The transmitter output was directly connected to a spectrum analyzer with a 50Ω cable. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW.

### 5.3.Test Result

Condition	Mode	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	2440.972	2441.984	1.012	0.609	Pass

CFS NVNT user 2441MHz



Date: 11.AUG.2020 14:44:20

## 6. Number Of Hopping Channel

### 6.1.Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


### 6.2.Test Procedure

The transmitter output was directly connected to a spectrum analyzer with a 50Ω cable. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

### 6.3.Test Result

Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	73	15	Pass

Hopping No. NVNT user 2441MHz



Date: 11.AUG.2020 15:01:27

## 7. Dwell Time

### 7.1. Test limit

Please refer section 15.247

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channels employed.

### 7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measurements were complete.

### 7.3. Test Result


PASS.

Detailed information please see the following page.


Mode	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (ms)	Limit (ms)	Conclusion
GFSK	2441	0.371	24.5	<400	PASS

Note:  
 Dwell time=66\*0.371==24.5ms

Dwell NVNT user 2441MHz



Date: 19.AUG.2020 15:20:42



Date: 22.AUG.2020 10:15:54

## 8. Radiated Emissions

### 8.1.Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

#### 15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

#### 15.209 Limit


FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB( $\mu\text{V}$ )/m (Peak) 54.0 dB( $\mu\text{V}$ )/m (Average)	

## 8.2. Block Diagram of Test setup


### 8.2.1 In 3m Anechoic Chamber Test Setup Diagram for 9KHzHz to 30MHz



### 8.2.2 In 3m Anechoic Chamber Test Setup Diagram for 30MHz to 1GHz



### 8.2.3 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.



### 8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1GHz test, 150 cm above the ground plane inside a semi-anechoic chamber for above 1GHz test
- (2) Setup EUT and simulator as shown in section 1.4 and 6.1
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
  - (a) Change work frequency or channel of device if practicable.
  - (b) Change modulation type of device if practicable.
  - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

### 8.4. Test Result


We have scanned the 10th harmonic from 9KHz to the EUT's highest frequency..  
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS

Polarization: *Vertical*




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		49.6197	11.71	14.04	25.75	40.00	-14.25	peak		
2		71.3800	11.46	11.11	22.57	40.00	-17.43	peak		
3		150.9603	10.27	15.06	25.33	43.50	-18.17	peak		
4		314.9279	11.91	14.48	26.39	46.00	-19.61	peak		
5		500.1256	12.37	18.21	30.58	46.00	-15.42	peak		
6	*	717.6879	11.97	21.99	33.96	46.00	-12.04	peak		

Note:1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Polarization: *Horizontal*



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree	Comment
1		39.0929	10.91	14.46	25.37	40.00	-14.63	peak			
2		59.7120	10.26	13.25	23.51	40.00	-16.49	peak			
3		160.5141	10.89	14.99	25.88	43.50	-17.62	peak			
4		427.4193	12.25	16.99	29.24	46.00	-16.76	peak			
5		500.1256	15.50	18.21	33.71	46.00	-12.29	peak			
6	*	702.7459	12.02	21.78	33.80	46.00	-12.20	peak			

Note: 1. \*: Maximum data; x: Over limit; !: over margin.

2. Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


Remark: All modes have been tested, and only worst data of GFSK Channel High mode was listed in this report.

From 1G-25GHz

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4810	44.88	V	33.95	10.18	34.26	54.75	74	19.25	PK
4810	39.15	V	33.95	10.18	34.26	49.02	54	4.98	AV
7215	/	/	/	/	/	/	/	/	
9620	/	/	/	/	/	/	/	/	
4810	45.17	H	33.95	10.18	34.26	55.04	74	18.96	PK
4810	35.98	H	33.95	10.18	34.26	45.85	54	8.15	AV
7215									
9620									
Test Mode: GFSK TX Mid									
4882	41.62	V	33.93	10.2	34.29	51.46	74	22.54	PK
4882	36.64	V	33.93	10.2	34.29	46.48	54	7.52	AV
7323	/	/	/	/	/	/	/	/	
9764	/	/	/	/	/	/	/	/	
4882	43.59	H	33.93	10.2	34.29	53.43	74	20.57	PK
4882	33.42	H	33.93	10.2	34.29	43.26	54	10.74	AV
7323									
9764									
Test Mode: GFSK TX High									
4956	42.89	V	33.98	10.22	34.25	52.84	74	21.16	PK
4956	34.64	V	33.98	10.22	34.25	44.59	54	9.41	AV
7434	/	/	/	/	/	/	/	/	
9912	/	/	/	/	/	/	/	/	
4956	44.14	H	33.98	10.22	34.25	54.09	74	19.91	PK
4956	32.38	H	33.98	10.22	34.25	42.33	54	11.67	AV
7434	/								
9912	/								
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

## 9. Band Edge Compliance

### 9.1. Block Diagram of Test Setup



### 9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 9.3. Test Procedure


All restriction band and non- restriction band have been tested , only worse case is reported.

### 9.4. Test Result


PASS. (See below detailed test data)

No-hopping  
CH-L

Horizontally




Vertically




CH-H

Horizontally




Vertically




Hopping  
CH-L

Horizontally




Vertically




CH-H


Horizontally



Vertically




No-hopping  
CH-L




Date: 19\_AUG\_2020 15:15:20

CH-H




Date: 19\_AUG\_2020 15:13:20

Hopping  
CH-L



Date: 19\_AUG\_2020 15:18:09

CH-H




Date: 19\_AUG\_2020 15:12:44



## 10. Power Line Conducted Emissions

### 10.1. Block Diagram of Test Setup



### 10.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB( $\mu$ V)	Average Level dB( $\mu$ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

### 10.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.

### 10.4. Test Result

Not applicable.

The EUT is supplied by battery only, so this item does not applicable.

## **11. Antenna Requirements**

### **11.1. Limit**


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **11.2. Result**

The EUT antenna is integrated Antenna. It complies with the standard requirement.

## 12. Test Setup Photo

### 12.1. Photos of Radiated emission





### 13.Photos Of EUT
























-----THE END OF REPORT-----