

# FCC Test Report

**Applicant** : TWELVE SOUTH, LLC

---

**Address** : 1503 KING ST STE201 Charleston, SC29405,  
USA, Charleston, USA Minor Outlying Islands

---

**Product Name** : Butterfly Travel Charger

---

**Report Date** : Oct. 19, 2023

---

**Shenzhen Anbotek Compliance Laboratory Limited**



**Shenzhen Anbotek Compliance Laboratory Limited**

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.  
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com

Code: AB-RF-05-b



Hotline

400-003-0500

www.anbotek.com.cn




# Contents

1. General Information.....	5
1.1. Client Information.....	5
1.2. Description of Device (EUT).....	5
1.3. Auxiliary Equipment Used During Test.....	6
1.4. Description of Test Modes.....	6
1.5. Description Of Test Setup.....	7
1.6. Test Equipment List.....	8
1.7. Measurement Uncertainty.....	9
1.8. Description of Test Facility.....	9
1.9. Disclaimer.....	9
2. Summary of Test Results.....	10
3. Conducted Emission Test.....	11
3.1. Test Standard and Limit.....	11
3.2. Test Setup.....	11
3.3. Test Procedure.....	11
3.4. Test Data.....	11
4. Radiation Spurious Emission.....	14
4.1. Test Standard and Limit.....	14
4.2. Test Setup.....	14
4.3. Test Procedure.....	15
4.4. Test Data.....	15
5. Antenna Requirement.....	20
5.1. Test Standard and Requirement.....	20
5.2. Antenna Connected Construction.....	20
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	21
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	21
APPENDIX III -- INTERNAL PHOTOGRAPH.....	21



## TEST REPORT

Applicant : Twelve South, LLC  
Manufacturer : Twelve South, LLC  
Product Name : Butterfly Travel Charger  
Test Model No. : TS-2304  
Reference Model No. : N/A  
Trade Mark : 

Rating(s) : Input: USB-C PD in 5V/3A & 9V/3A  
Output:  
Output for MagSafe (C222x): 5W/7.5W/15W;  
Output for Apple Watch (C962): Max 5W (Fast charger);  
No-load Output Voltage: 5V/1A, 7.5V/1A, 12V/1.25A;  
Full-load Output Voltage: 4.5V, 7.2V, 11V

Test Standard(s) : FCC Part15 Subpart C, Paragraph 15.209

Test Method(s) : ANSI C63.10: 2020


The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt : Sept. 12, 2023

Date of Test : Sept. 12 ~Oct. 11, 2023

Prepared By



(TuTu Hong)

Approved & Authorized Signer



(Edward Pan)



**Revision History**

Report Version	Description	Issued Date
R00	Original Issue.	Oct. 19, 2023




## 1. General Information

### 1.1. Client Information

Applicant	:	TWELVE SOUTH, LLC
Address	:	1503 KING ST STE201 Charleston, SC29405, USA, Charleston, USA Minor Outlying Islands
Manufacturer	:	TWELVE SOUTH, LLC
Address	:	1503 KING ST STE201 Charleston, SC29405, USA, Charleston, USA Minor Outlying Islands
Factory	:	TWELVE SOUTH, LLC
Address	:	1503 KING ST STE201 Charleston, SC29405, USA, Charleston, USA Minor Outlying Islands

### 1.2. Description of Device (EUT)

Product Name	:	Butterfly Travel Charger
Model No.	:	TS-2304
Reference Model No.	:	N/A
Trade Mark	:	
Test Power Supply	:	AC 120V, 60Hz for adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	Model: S-TR-152D-1C30-CY Input: 100-240V~, 50/60Hz, 0.8A Max PD Output: (30W)5V= 3A, 9V= 3A, 12V= 2.5A, 15V= 2A, 20V= 1.5A

#### RF Specification

Operation Frequency	:	128~360kHz
Modulation Type	:	FSK
Antenna Type	:	Inductive loop coil Antenna
Antenna Gain(Peak)	:	0 dBi

**Remark:** 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.2)All of the RF specification are provided by customer.



### 1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
Apple Watch	M/N: WR-50M
Mobile Phone	iPhone 12

### 1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Adapter+WPT Mode(Mobile Phone+Watch)
Mode 2	Adapter+WPT Mode(Mobile Phone)
Mode 3	Adapter+WPT Mode(Watch)

For Conducted Emission	
Final Test Mode	Description
Mode 1	Adapter+WPT Mode(Mobile Phone+Watch)
Mode 2	Adapter+WPT Mode(Mobile Phone)
Mode 3	Adapter+WPT Mode(Watch)



For Radiated Emission	
Final Test Mode	Description
Mode 1	Adapter+WPT Mode(Mobile Phone+Watch)
Mode 2	Adapter+WPT Mode(Mobile Phone)
Mode 3	Adapter+WPT Mode(Watch)

Note:

- (1) Test channel is 0.0351MHz, 0.3251MHz.
- (2) All the situation(full load, half load and empty load) has been tested,only the worst situation (full load 20W) was recorded in the report.



## 1.5. Description Of Test Setup



## 1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2023	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Oct. 13, 2022	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Oct. 23, 2022	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
10.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Oct. 23, 2022	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 19, 2022	1 Year
18.	Power Meter	Agilent	N1914A	MY50001102	Oct.26, 2022	1 Year





### 1.7. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
	:	Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

### 1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

#### ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

#### Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

### 1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



## 2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission Test	PASS
15.205/15.209	Spurious Emission	PASS




## 3. Conducted Emission Test

### 3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
Test Limit	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

**Remark:** (1) \*Decreasing linearly with logarithm of the frequency.  
 (2) The lower limit shall apply at the transition frequency.

### 3.2. Test Setup



### 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.4. Test Data


AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



### Conducted Emission Test Data

Test Site: 1# Shielded Room  
 Operating Condition: Mode 1  
 Test Specification: AC 120V, 60Hz for adapter  
 Comment: Live Line  
 Temp.(°C)/Hum.(%RH): 24.6°C/68%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1740	31.97	19.83	51.80	64.76	-12.96	QP	
2	0.1819	19.18	19.82	39.00	54.39	-15.39	AVG	
3	0.4700	15.78	19.85	35.63	46.51	-10.88	AVG	
4	0.5020	23.96	19.86	43.82	56.00	-12.18	QP	
5	0.7780	13.08	19.87	32.95	46.00	-13.05	AVG	
6	1.1260	23.14	19.86	43.00	56.00	-13.00	QP	
7	1.3900	13.60	19.86	33.46	46.00	-12.54	AVG	
8	1.4420	21.11	19.86	40.97	56.00	-15.03	QP	
9	1.7060	9.31	19.85	29.16	46.00	-16.84	AVG	
10	12.0260	22.80	20.04	42.84	60.00	-17.16	QP	
11	24.1140	23.45	20.46	43.91	60.00	-16.09	QP	
12	24.1140	17.06	20.46	37.52	50.00	-12.48	AVG	



### Conducted Emission Test Data

Test Site: 1# Shielded Room  
 Operating Condition: Mode 1  
 Test Specification: AC 120V, 60Hz for adapter  
 Comment: Neutral Line  
 Temp.(°C)/Hum.(%RH): 24.6°C/68%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	32.30	19.82	52.12	65.99	-13.87	QP	
2	0.1740	33.09	19.83	52.92	64.76	-11.84	QP	
3	0.1740	19.75	19.83	39.58	54.76	-15.18	AVG	
4	0.4820	24.77	19.85	44.62	56.30	-11.68	QP	
5	0.5100	14.03	19.86	33.89	46.00	-12.11	AVG	
6	0.6020	22.34	19.87	42.21	56.00	-13.79	QP	
7	1.3619	23.83	19.86	43.69	56.00	-12.31	QP	
8	1.3740	13.61	19.86	33.47	46.00	-12.53	AVG	
9	1.6900	21.22	19.85	41.07	56.00	-14.93	QP	
10	1.6900	9.79	19.85	29.64	46.00	-16.36	AVG	
11	12.3859	13.05	20.05	33.10	50.00	-16.90	AVG	
12	24.1140	15.83	20.46	36.29	50.00	-13.71	AVG	



## 4. Radiation Spurious Emission

### 4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
-		-	74.0	Peak	3

**Remark:**

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

### 4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz

### 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

### 4.4. Test Data


#### PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.



**Test Results (Between 9KHz – 150KHz)**

Test Mode: Mode 1  
 Distance: 3m  
 Power Source: AC 120V, 60Hz for adapter  
 Temp.(°C)/Hum.(%RH): 25.1°C/47%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor ( )	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	0.0141	8.89	20.19	29.08	124.52	-95.44	QP			
2	0.0181	17.02	20.20	37.22	122.35	-85.13	QP			
3	0.0316	17.06	20.56	37.62	117.53	-79.91	QP			
4	0.0351	40.93	20.49	61.42	116.62	-55.20	QP			
5	0.0580	18.53	20.36	38.89	112.27	-73.38	QP			
6	0.0808	9.64	20.36	30.00	109.40	-79.40	QP			





**Test Results (Between 0.15MHz – 30MHz)**

Test Mode: Mode 1  
 Distance: 3m  
 Power Source: AC 120V, 60Hz for adapter  
 Temp.(°C)/Hum.(%RH): 25.1°C/47%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor ( )	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	0.1722	8.68	20.32	29.00	102.83	-73.83	QP			
2	0.3251	12.01	20.29	32.30	97.34	-65.04	QP			
3	0.9087	7.95	20.26	28.21	68.45	-40.24	QP			
4	2.3836	-7.91	20.29	12.38	69.50	-57.12	QP			
5	10.3972	-4.06	20.52	16.46	69.50	-53.04	QP			
6	18.0393	-14.11	20.57	6.46	69.50	-63.04	QP			

**Remark:** According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.



**Test Results (Between 30MHz –1000 MHz)**


Test Mode: Mode 1  
 Distance: 3m  
 Power Source: AC 120V, 60Hz for adapter  
 Polarization: Horizontal  
 Temp.(°C)/Hum.(%RH): 22.5°C/52%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor ( )	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	49.0145	37.18	-17.14	20.04	40.00	-19.96	QP			
2	61.3463	46.46	-18.23	28.23	40.00	-11.77	QP			
3	73.6170	48.03	-21.67	26.36	40.00	-13.64	QP			
4	147.4036	48.74	-21.18	27.56	43.50	-15.94	QP			
5	239.1473	54.90	-16.52	38.38	46.00	-7.62	QP			
6	798.9797	40.38	-5.91	34.47	46.00	-11.53	QP			



Test Mode: Mode 1  
 Distance: 3m  
 Power Source: AC 120V, 60Hz for adapter  
 Polarization: Vertical  
 Temp.(°C)/Hum.(%RH): 22.5°C/52%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor ( )	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	36.7662	52.76	-17.63	35.13	40.00	-4.87	QP			
2	49.0145	52.27	-17.14	35.13	40.00	-4.87	QP			
3	61.3063	47.45	-18.21	29.24	40.00	-10.76	QP			
4	73.6170	55.03	-21.67	33.36	40.00	-6.64	QP			
5	134.5592	57.34	-21.06	36.28	43.50	-7.22	QP			
6	303.5437	56.22	-14.76	41.46	46.00	-4.54	QP			



## 5. Antenna Requirement

### 5.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 5.2. Antenna Connected Construction

The antenna is a Inductive loop coil Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.



## APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph\_RF

## APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

## APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

