

Maximum Permissible Exposure Evaluation

FCC ID: 2ARER-IPC200

1. Client Information

Applicant	:	Shenzhen Apeman Innovations Technology Co.,Ltd
Address	:	Building P11, Huanancheng, Longgang District, Shenzhen, China
Manufacturer	:	Shenzhen Apeman Innovations Technology Co.,Ltd
Address	:	Building P11, Huanancheng, Longgang District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Nooie Cam Outdoor	
Models No.	:	IPC200	
Model Different	:	N/A	
Product Description	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
		RF Output Power:	802.11b: 17.62dBm 802.11g: 15.54dBm 802.11n (HT20): 14.70dBm 802.11n (HT40): 13.98dBm
		Antenna Gain:	1.6dBi FPC Antenna
		Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK,QPSK,16QAM, 64QAM)
Power Supply	:	Adapter(TPA-46B050100UU): Input: AC 100-240V, 50/60Hz, 0.2A Output: DC 5V, 1000mA	
Software Version	:	V2.1.40	
Hardware Version	:	V1.0.3	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

TB-RF-075-1.0

MPE Calculations for WIFI

1. Antenna Gain:

PCB Antenna: 1.6dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
802.11b	17.62	17±1	18	1.6	20	0.01814
802.11g	15.54	15±1	16	1.6	20	0.01145
802.11n (HT20)	14.70	14±1	15	1.6	20	0.00909
802.11n (HT40)	13.98	14±1	15	1.6	20	0.00909

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n(HT20):2412~2462 MHz

802.11n(HT40): 2422MHz~2452MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.01814mW / cm^2 < limit 1mW / cm^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----