

RF Exposure

FCC ID: 2ARF2JML-310

1.0 INTRODUCTION

These calculations are based on the highest EIRP possible from the EUT considering maximum power and antenna gain. The highest output power of the EUT is 134.9 mW and the gain of the antenna is -1 dBi

1.0 SAR EXCLUSION RESULT

In accordance with FCC KDB Publication 447498 D01 V05R06 Clause 4.3.1 a),
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power, mW})/(\text{min. separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds as shown below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 of KDB 447498 is applied to determine SAR test exclusion.

According to the radiated max measurement, max. power of channel, including tune-up tolerance = 1 mW rounded to the nearest mW. The min. test separation distance = 200mm

The result is $(1/5) * ((2.45)^{0.5}) = 0.31$ which is less than 3.0 for 1-g SAR limit and ≤ 7.5 for 10-g SAR, hence the EUT is excluded from SAR evaluation according to FCC KDB Publication 447498 D01: General RF Exposure Guidance V06.

For transmit from 100-1500 MHz:

$[(\text{max. power allowed at numeric threshold for 50mm in 4.3.1a, mW})] + [(\text{min. separation distance} - 50, \text{mm}) * (\sqrt{\text{Freq(MHz)}})]$

This table is for devices with a separation greater than 50 mm

MHz	Max Power dBm	Max Ant Gain dBi	Duty Cycle %	EIRP mW	Min Sep mm	SAR Exc Threshold at 50mm 4.3.1 a) in mW	SAR Exclusion threshold per 4.3.1 b)1) in mW	Result	Notes
902.4	21.3	-1	100.0	107.2	200	157.9	1060.3	Exempt	Peak
915.0	21.3	-1	100.0	107.2	200	156.8	1071.8	Exempt	Peak
926.8	21.3	-1	100.0	107.2	200	155.8	1082.6	Exempt	Peak

2.0 MPE CALCULATION FROM OET 65 & FCC 1.1310

MHz	Max Power dBm	Max Ant Gain dBi	Duty Cycle %	EIRP Watts	(S) GP Limit mW/cm ²	Declared Minimum separation Distance (cm)	EUT power Density mW/cm ²	Result
902.4	21.3	-1	100.0	0.1072	0.602	20.000	0.0213	Pass
915.0	21.3	-1	100.0	0.1072	0.610	20.000	0.0213	Pass
926.8	21.3	-1	100.0	0.1072	0.618	20.000	0.0213	Pass

Notes on the above table:

In accordance with OET 65, 97-01, Power Density is calculated by

$$S = P \cdot G / (4 \cdot \pi \cdot R^2)$$

Where

S = power density (mW/cm²)

P = power input to the antenna (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm)

S is the power density General Population Limit from FCC 1.1310 Table 1

EIRP Power is the Peak Effective Radiated Power.

EIRP = (Average Conducted Power + Antenna gain) * Duty Cycle.

Since the calculated power density is less than the limit, this product fully meets the OET 65 requirements for the general population.