

## RF EXPOSURE REPORT

<b>Equipment Under Test</b>	<b>Bluetooth Audio</b>
<b>Modle Name</b>	<b>ARA-5090WF-E</b>
<b>Variant Model Name</b>	<b>-</b>
<b>FCC ID</b>	<b>2ARFV-ARA5090WFE</b>
<b>IC Number</b>	<b>24404-ARA5090WFE</b>
<b>Applicant</b>	<b>WORLDPLUS ELECTRONICS CO.,LTD</b>
<b>Manufacturer</b>	<b>WORLDPLUS ELECTRONICS CO.,LTD</b>
<b>Date of Test(s)</b>	<b>2020. 06. 05 ~ 2020. 06. 26</b>
<b>Date of Issue</b>	<b>2020. 06. 26</b>

In the configuration tested, the EUT complied with the standards specified above.

Issue to	Issue by
<b>WORLDPLUS ELECTRONICS CO.,LTD</b> <b>29, Cheomdan venture-ro 40beon-gil,</b> <b>Buk-gu, Gwangju, Korea</b>  <b>Tel.: +82-2-576-8217</b> <b>Fax: +82-2-576-8218</b>	<b>MOVON CORPORATION</b> <b>7, Seolleung-ro 94-gil, Gangnam-gu,</b> <b>Seoul-si, Korea</b>  <b>Tel.: +82-31-338-8837</b> <b>Fax: +82-31-338-8847</b>

# RF EXPOSURE

## 1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissible Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm <sup>2</sup> ]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1	30

f=frequency in MHz, \*= plane-wave equivalent power density

## MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm<sup>2</sup>]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

## 2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

## MPE Calculations : Bluetooth BDR

- Frequency Range : 2 402 MHz ~ 2 480 MHz
- Measured RF Output Power (Peak) : 2.27 dBm
- Target Power & Tolerance 1.00 dBm & ± 1.50 dB  
( Maximum : 2.50 dBm & Minimum : -0.50 dBm )
- Maximum Peak Antenna Gain : 0.50 dBi
- **Maximum Output Power for the Calculation : 2.50 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the  
The MPE calculation for this exposure is shown below.

<p>- EIRP = P + G</p> <p>= <u>2.50</u> dBm + <u>0.50</u> dBi</p> <p>= <u>3.00</u> dBm</p> <p>= <u>2.00</u> mW</p>	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	--

### Power Density at the specific separation

<p>- S = EIRP / (4 X R<sup>2</sup>π)</p> <p>= 2.00 / (4 X 20<sup>2</sup> X π)</p> <p>= <u>0.000 397</u> mW/cm<sup>2</sup></p>	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm<sup>2</sup>)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna ( <u>20</u> cm )</p>
---	--

### RF Exposure Compliance Issue

Therefore, EUT is not required the SAR Evaluation.

## MPE Calculations : Bluetooth EDR

- Frequency Range : 2 402 MHz ~ 2 480 MHz
- Measured RF Output Power (Peak) : 4.83 dBm
- Target Power & Tolerance 3.50 dBm & ± 1.50 dB  
( Maximum : 5.00 dBm & Minimum : 2.00 dBm )
- Maximum Peak Antenna Gain : 0.50 dBi
- **Maximum Output Power for the Calculation : 5.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the  
The MPE calculation for this exposure is shown below.

<p>- EIRP = P + G</p> <p>= <u>5.00</u> dBm + <u>0.50</u> dBi</p> <p>= <u>5.50</u> dBm</p> <p>= <u>3.55</u> mW</p>	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
---	--

### Power Density at the specific separation

<p>- S = EIRP / (4 X R<sup>2</sup>π)</p> <p>= 3.55 / (4 X 20<sup>2</sup> X π)</p> <p>= <u>0.000 706</u> mW/cm<sup>2</sup></p>	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm<sup>2</sup>)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna ( <u>20</u> cm )</p>
---	--

### RF Exposure Compliance Issue

Therefore, EUT is not required the SAR Evaluation.