



# Approval Sheet

Product : 900MHz Stubby Antenna

|                        |   |            |   |
|------------------------|---|------------|---|
| Customer Applied Model | 900MHz Stubby Antenna   |            |   |
| Customer               |   |            |   |
| Customer Part No.      |   |            |   |
| Supplier               | SGT   |            |   |
| Supplier Part No.      | SG-PS921  |            |   |
| Customer               | By designed   | By checked | By approved   |
|                        |   |            |   |
|                        |   |            |   |
| Supplier               | By Designed   | By checked | By approved   |
|                        |  |            |  |
|                        | Lee M.S   |            | Hwang S.G   |

**SGT**

Address : 5, Daerim-ro 17-gil, Yeongdeungpo-gu, Seoul, Republic of Korea

■ Revision History

| Revision No | Originator | Description of changes | Date of changes |
|-------------|------------|------------------------|-----------------|
| 1           | Lee M.S    | Initial release        | 2022.4.11       |
| 2           |            |                        |                 |
| 3           |            |                        |                 |
| 4           |            |                        |                 |
| 5           |            |                        |                 |
| 6           |            |                        |                 |
| 7           |            |                        |                 |
| 8           |            |                        |                 |
| 9           |            |                        |                 |
| 10          |            |                        |                 |
| 11          |            |                        |                 |
| 12          |            |                        |                 |

## Table of Contents

|  |                         |               |
|--|-------------------------|---------------|
| 1. General                             |                         |               |
| 1.1                                    | The Product             | ----- Page 4  |
| 1.2                                    | Electrical Properties   | ----- Page 4  |
| 1.3                                    | Mechanical Properties   | ----- Page 4  |
| 1.4                                    | Matching Value          | ----- Page 4  |
| 2. Electrical Properties               |                         |               |
| 2.1                                    | Frequency Bands         | ----- Page 5  |
| 2.2                                    | Impedance               | ----- Page 5  |
| 2.3                                    | VSWR                    | ----- Page 5  |
| 3. Mechanical Properties               |                         |               |
| 3.1                                    | Appearance              | ----- Page 6  |
| 3.2                                    | Drop                    | ----- Page 6  |
| 4. Environmental Resistance Properties |                         |               |
| 4.1                                    | Operational Temperature | ----- Page 7  |
| 4.2                                    | Temperature Cycling     | ----- Page 7  |
| 4.3                                    | Humidity                | ----- Page 8  |
| 4.4                                    | Sinusoidal Vibration    | ----- Page 8  |
| 5. Test Data                           |                         |               |
| 5.1                                    | Network Data            | ----- Page 9  |
| 5.2                                    | Radiation pattern       | ----- Page 10 |
| 6. Mechanical Drawing                  |                         | ----- Page 14 |

## 1. General

### 1.1 The Product

|                |                       |
|----------------|-----------------------|
| Customer Model | 900MHz Stubby Antenna |
| Antenna Type   | Helical Antenna       |
| Applications   | LoRa                  |


### 1.2 Electrical Properties

|                   |                   |
|-------------------|-------------------|
| Frequency Range   | 900~945MHz        |
| VSWR              | Less than 2.5 : 1 |
| Peak Gain         | 0.91 dBi          |
| Radiation Pattern | Omni-directional  |
| Polarization      | Linear            |

### 1.3 Mechanical Properties

|                         |               |
|-------------------------|---------------|
| Dimension               | See page 14   |
| Operational Temperature | -30°C ~ +85°C |
| Connector Type          | SMA-R         |

### 1.4 Matching Value



## 2. Electrical Properties

### 2.1 Frequency Band

|               |              |
|---------------|--------------|
| Band<br>Freq' | LoRa         |
| TX/RX         | 900 ~945 MHz |

### 2.2 Impedance

#### 2.2.1 Normal Value

50Ω ± Normal

#### 2.2.1 Measuring Method

The impedance over the frequency bands shall be as close as possible to 50Ω after matching. Both free space and talk position are considered.

### 2.3 VSWR

The impedance matching should be optimized in the more critical talk position.

#### 2.3.1 Maximum values in free space

|         |                 |
|---------|-----------------|
| SERVICE | 900 ~ 945 MHz   |
| VSWR    | Less than 2.5:1 |

#### 2.3.2 Measuring Method

A 50Ω coaxial cable is connected(soldered) to the 50Ω point, at the duplex-filter on the main PCB. The connection of the coaxial cable shall be done to introduce a minimum of mismatch. As much as possible the coaxial cable arrangement shall prevent influences from induced currents on the cable. In the other end, the coaxial cable is connected to a network analyzer. The measurement is performed at room temperature. The handset, including the PCB, must not in any significant way differ from the mass production, i.e. the antenna feeding network has to be equivalent to the feeding network in mass production. The specification shall be met in the entire frequency band.

### 3. Mechanical Properties

#### 3.1 Appearance

The appearance shall be according to the specification drawing on page 15.  
The antenna shall have no cuts, abrasion or other mechanical damages.

#### 3.2 Drop

##### 3.2.1 Drops

1 drop in retracted mode (3cycles)

##### 3.2.2 Drop Height

1.5m

##### 3.2.3 Drop Angle

180°

##### 3.2.4 Actual handset applied


##### 3.2.5 Demands

The original shape shall be possible to restore. The antenna shall satisfy the electrical demands, according to 2.4.1, after the test.

##### 3.2.6 Measuring Method

The antenna is placed in the handset or an equivalent test fixture.

The handset is dropped with the antenna downwards onto a metal plate.



**Figure3. Drop Test**

## 4. Environment Resistance Properties

### 4.1 Operational Temperature

#### 4.1.1. Low Operational Temperature

TLO =  $-30^{\circ}\text{C}$

#### 4.1.2 High Operational Temperature

THO =  $+80^{\circ}\text{C}$

#### 4.1.3 Demands

No visual deterioration shall occur, and the antenna shall satisfy the electrical demands, according to 2.4.1, during the test.

#### 4.1.4 Measuring Method

The antenna is placed in a climatic chamber at temperature TLO.

The antenna is taken out after 1 hour, and VSWR is immediately measured.

The antenna is placed in a climatic chamber at temperature THO.

The antenna is taken out after 1 hour, and VSWR is immediately measured.

### 4.2 Temperature Cycling

#### 4.2.1 Low Cycling Temperature

TLC =  $-30^{\circ}\text{C}$

#### 4.2.2 High Cycling Temperature

THC =  $+80^{\circ}\text{C}$


#### 4.2.3 Demands

No visual deterioration shall occur during the test. The antenna shall satisfy the electrical demands, according to 2.4.1.

#### 4.2.4 Measuring Method

The antenna is placed in a climatic chamber. The temperature is cycled as follows: The temperature is kept constantly at TLC for 1 hour, increased to THC during 1 hour, kept constantly at THC for 1 hour, and then decreased to TLC during 1 hour.

This procedure is repeated 10 times, ending at room temperature according to Figure 4 below.



**Figure 4. Temperature Cycling**

### 4.3 humidity

#### 4.3.1 Relative Humidity

95%

#### 4.3.2 Temperature

+55°C

#### 4.3.3 Demands

No visual deterioration shall occur during the test. The antenna shall satisfy the electrical demands, according to 2.4.1, after the test.

#### 4.3.4 Measuring Method

The antenna is placed in a climatic chamber for 24 hours. The antenna is taken out from the chamber and measured after another 24 hours in room temperature.

### 4.4 Sinusoidal Vibration

#### 4.4.1 Vibration Frequencies

10-55-10Hz (1cycle)

#### 4.4.2 Sweep Rate

1 octave/min (logarithmic)

#### 4.4.3 Maximum Amplitude

$A = 1.52\text{mm}$

#### 4.4.4 Maxim Acceleration


2g

#### 4.4.5 Crossover Frequency

18.2Hz

#### 4.4.7 Measuring Method

The fixed antenna is assembled in the test equipment. The vibration is done both in x-and z-directions, according to Figure 5(a), with a duration of 1 hour in each direction.




**Figure 5. Sinusoidal Vibrator**




## 5. Test Data

### 5.1 Network Data

- VSWR




- Smith Chart




## 5.2 Radiation Pattern

### 5.2.1 H Plane




| No. | Freq.    | PwrSurr | Eff.[%] | Avg.[dBi] | Peak[dBi] | $\theta$ [deg] | $\phi$ [deg] | H( $\theta=90$ ) |           |              |         |
|-----|----------|---------|---------|-----------|-----------|----------------|--------------|------------------|-----------|--------------|---------|
|     |          |         |         |           |           |                |              | Avg.[dBi]        | Peak[dBi] | $\phi$ [deg] | BW[deg] |
| 1   | 900.0000 | 52.55   | 52.55   | -2.79     | -0.33     | 90.00          | 330.00       | -1.46            | -0.33     | 330.00       | 999.00  |
| 2   | 910.0000 | 58.45   | 58.45   | -2.33     | -0.01     | 90.00          | 345.00       | -1.03            | -0.01     | 345.00       | 999.00  |
| 3   | 920.0000 | 59.36   | 59.36   | -2.26     | 0.07      | 90.00          | 330.00       | -0.99            | 0.07      | 330.00       | 999.00  |
| 4   | 930.0000 | 61.48   | 61.48   | -2.11     | 0.24      | 90.00          | 345.00       | -0.85            | 0.24      | 345.00       | 999.00  |
| 5   | 940.0000 | 68.46   | 68.46   | -1.65     | 0.72      | 90.00          | 345.00       | -0.42            | 0.72      | 345.00       | 999.00  |
| 6   | 945.0000 | 71.97   | 71.97   | -1.43     | 0.91      | 90.00          | 345.00       | -0.23            | 0.91      | 345.00       | 999.00  |

## 5.2.2 E1 Plane




| Frequency ( MHz ) | Average (dBi ) | Peak ( dBi ) |
|-------------------|----------------|--------------|
| <b>900</b>        | -2.85          | -0.53        |
| <b>910</b>        | -2.37          | -0.18        |
| <b>920</b>        | -2.21          | -0.15        |
| <b>930</b>        | -1.97          | -0.01        |
| <b>940</b>        | -1.40          | 0.53         |
| <b>945</b>        | -1.15          | 0.74         |

### 5.2.3 E2 Plane




| Frequency ( MHz ) | Average (dBi ) | Peak ( dBi ) |
|-------------------|----------------|--------------|
| <b>900</b>        | -3.82          | -1.22        |
| <b>910</b>        | -3.38          | -0.90        |
| <b>920</b>        | -3.32          | -0.91        |
| <b>930</b>        | -3.19          | -0.80        |
| <b>940</b>        | -2.73          | -0.30        |
| <b>945</b>        | -2.53          | -1.12        |

### 5.2.4 3D Pattern



## 6. Mechanical Drawing



|            |                    |                 |               |             |
|------------|--------------------|-----------------|---------------|-------------|
| 2          | SMA Plug 90°       | Cu              |               | 1           |
| 1          | Body1              | TPE             | black         | 1           |
| <b>No.</b> | <b>Description</b> | <b>Material</b> | <b>Finish</b> | <b>Q'ty</b> |