



FCC RADIO TEST REPORT

FCC ID : 2ARGE-6383
Equipment : Digital Media Receiver
Model Name : O2T2V3
Applicant : Flake LLC
4321 W. College Avenue; Suite 200
Appleton, Wisconsin 54914
Standard : FCC Part 15 Subpart C §15.247

The product was received on Jan. 22, 2019 and testing was started from Apr. 27, 2019 and completed on Jul. 10, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT	5
1.4 Testing Location	6
1.5 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	18
3.3 Power Spectral Density Measurement	19
3.4 Conducted Band Edges and Spurious Emission Measurement	26
3.5 Radiated Band Edges and Spurious Emission Measurement	35
3.6 AC Conducted Emission Measurement.....	39
3.7 Antenna Requirements.....	41
4 List of Measuring Equipment	42
5 Uncertainty of Evaluation.....	44
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report

Report No.	Version	Description	Issued Date
FR8O0521-02B	01	Initial issue of report	Jul. 14, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)
3.1	15.247(a)(2)	6dB Bandwidth	Pass
3.1	2.1049	99% Occupied Bandwidth	Reporting only
0	15.247(b)(3)	Peak Output Power	Pass
3.3	15.247(e)	Power Spectral Density	Pass
0	15.247(d)	Conducted Band Edges and Spurious Emission	Pass
0	15.247(d)	Radiated Band Edges and Spurious Emission	Pass
3.6	15.207	AC Conducted Emission	Pass
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Ann Lee

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Digital Media Receiver
Model Name	O2T2V3
FCC ID	2ARGE-6383
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE Zigbee

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	8.00 dBm (0.0063 W) for 1Mbps 8.00 dBm (0.0063 W) for 2Mbps
99% Occupied Bandwidth	1.032 MHz for 1Mbps 2.072 MHz for 2Mbps
Antenna Type / Gain	Flex Antenna with gain 5.1 dBi
Type of Modulation	Bluetooth LE : GFSK

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH16-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in two setup, without accessories and with accessories. The worst cases (without accessories) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1 :WLAN (2.4GHz) Link with AP Router + WLAN (5GHz) Link with Notebook + Bluetooth Link + Zigbee Link + Play Audio from Bluetooth Phone

2.3 Connection Diagram of Test System

<Bluetooth - LE Tx Mode >



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	Net Gear	R7000	FCC DoC	N/A	Unshielded,1.8m
2.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Notebook	DELL	Latitude E5570	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Mobile Phone	Apple	A1524	FCC DoC	N/A	N/A
5.	LED light	OSRAM	73674	DZO-IQHOME	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility "Compliance.exe Version 1.0.0.50" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


<1Mbps>

6 dB Bandwidth Plot on Channel 00




Date: 17.MAY.2019 01:40:13


6 dB Bandwidth Plot on Channel 19




Date: 17.MAY.2019 01:23:24



6 dB Bandwidth Plot on Channel 00




6 dB Bandwidth Plot on Channel 19



Date: 17.MAY.2019 00:58:52

6 dB Bandwidth Plot on Channel 39



Date: 17.MAY.2019 01:06:32




3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<1Mbps>

99% Bandwidth Plot on Channel 00




Date: 17.MAY.2019 01:21:42


99% Occupied Bandwidth Plot on Channel 19




Date: 17.MAY.2019 01:25:58

**99% Occupied Bandwidth Plot on Channel 39**


Date: 17.MAY.2019 01:30:28

<2Mbps>**99% Bandwidth Plot on Channel 00**

Date: 17.MAY.2019 00:56:01

99% Occupied Bandwidth Plot on Channel 19


Date: 17.MAY.2019 01:03:34

99% Occupied Bandwidth Plot on Channel 39


Date: 17.MAY.2019 01:10:51

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.



3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<1Mbps>

PSD 100kHz Plot on Channel 00



Date: 17.MAY.2019 01:20:09


PSD 100kHz Plot on Channel 19



Date: 17.MAY.2019 01:24:38




PSD 100kHz Plot on Channel 39



Date: 17.MAY.2019 01:28:59

<2Mbps>


PSD 100kHz Plot on Channel 00



Date: 17.MAY.2019 00:54:28




PSD 100kHz Plot on Channel 19



Date: 17.MAY.2019 01:01:56

PSD 100kHz Plot on Channel 39




Date: 17.MAY.2019 01:08:19

3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<1Mbps>

PSD 3kHz Plot on Channel 00




Date: 17.MAY.2019 01:19:46


PSD 3kHz Plot on Channel 19



Date: 17.MAY.2019 01:23:49

PSD 3kHz Plot on Channel 39



Date: 17.MAY.2019 01:28:14

<2Mbps>
PSD 3kHz Plot on Channel 00


Date: 17.MAY.2019 00:53:30




PSD 3kHz Plot on Channel 19



Date: 17.MAY.2019 00:59:52

PSD 3kHz Plot on Channel 39



Date: 17.MAY.2019 01:07:30

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots


<1Mbps>

Low Band Edge Plot on Channel 00




Date: 17.MAY.2019 01:20:31


High Band Edge Plot on Channel 39



Date: 17.MAY.2019 01:29:29

<2Mbps>
Low Band Edge Plot on Channel 00


Date: 17.MAY.2019 00:54:52

High Band Edge Plot on Channel 39


Date: 17.MAY.2019 01:08:42




3.4.6 Test Result of Conducted Spurious Emission Plots

<1Mbps>

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00



Date: 17.MAY.2019 01:20:52


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00




Date: 17.MAY.2019 01:21:14

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 17.MAY.2019 01:25:03

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 17.MAY.2019 01:25:22

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 17.MAY.2019 01:29:56

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 17.MAY.2019 01:30:11

<2Mbps>

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps


GFSK Channel 00



Date: 17.MAY.2019 00:55:16

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps


GFSK Channel 00



Date: 17.MAY.2019 00:55:32




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19




Date: 17.MAY.2019 01:02:23

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19




Date: 17.MAY.2019 01:02:43

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 17.MAY.2019 01:09:01

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 17.MAY.2019 01:09:35



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


See list of measuring equipment of this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 11, 2019	May 01, 2019~ Jun. 27, 2019	Jan. 10, 2020	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL6111D&0 0802N1D01N- 06	47020&06	30MHz to 1GHz	Oct. 13, 2018	May 01, 2019~ Jun. 27, 2019	Oct. 12, 2019	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-152 2	1G~18GHz	Sep. 07, 2018	May 01, 2019~ Jun. 27, 2019	Sep. 06, 2019	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 251	18GHz ~ 40GHz	Nov. 20, 2018	May 01, 2019~ Jun. 27, 2019	Nov. 19, 2019	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1000MHz	Oct. 02, 2018	May 01, 2019~ Jun. 27, 2019	Oct. 01, 2019	Radiation (03CH16-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 0055007	1GHz~18GHz	Apr. 01, 2019	May 01, 2019~ Jun. 27, 2019	Mar. 31, 2020	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY532702 64	1GHz~26.5GHz	Dec. 12, 2018	May 01, 2019~ Jun. 27, 2019	Dec.11, 2019	Radiation (03CH16-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	May 01, 2019~ Jun. 27, 2019	Jul. 15, 2019	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY572901 11	3Hz~26.5GHz	Nov. 29, 2018	May 01, 2019~ Jun. 27, 2019	Nov. 28, 2019	Radiation (03CH16-HY)
Spectrum Analyzer	Agilent	N9010A	MY542004 86	10Hz~44GHz	Oct. 19, 2018	May 01, 2019~ Jun. 27, 2019	Oct. 18, 2019	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	MY1082/2 6EA	30M-18G	Oct. 15, 2018	May 01, 2019~ Jun. 27, 2019	Oct. 14, 2019	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY15539/ 4	30M-18G	Feb. 26, 2019	May 01, 2019~ Jun. 27, 2019	Feb. 25, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36980/ 4	30M~18GHz	Apr. 15, 2019	May 01, 2019~ Jun. 27, 2019	Apr. 14, 2020	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	May 01, 2019~ Jun. 27, 2019	N/A	Radiation (03CH16-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 10, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Jul. 10, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jul. 10, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Jul. 10, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 10, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Jul. 10, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Jul. 10, 2019	Dec. 30, 2019	Conduction (CO05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB412923 44	N/A	Dec. 27, 2018	Apr. 27, 2019~ May 17, 2019	Dec. 26, 2019	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US404415 48	50MHz~18GHz	Dec. 27, 2018	Apr. 27, 2019~ May 17, 2019	Dec. 26, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	Apr. 27, 2019~ May 17, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	EM	EMSW18	SW107090 3	N/A	Dec. 19, 2018	Apr. 27, 2019~ May 17, 2019	Dec. 18, 2019	Conducted (TH05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.20
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.90
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.80
--	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.90
--	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Luffy Lin	Temperature:	21~25	°C
Test Date:	2019/4/27~2019/5/17	Relative Humidity:	51~54	%

<1Mbps>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE5.0	1Mbps	1	0	2402	1.030	0.712	0.50	Pass
BLE5.0	1Mbps	1	19	2440	1.032	0.712	0.50	Pass
BLE5.0	1Mbps	1	39	2480	1.028	0.712	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	1Mbps	1	0	2402	8.00	30.00	5.10	13.10	36.00	Pass
BLE5.0	1Mbps	1	19	2440	7.00	30.00	5.10	12.10	36.00	Pass
BLE5.0	1Mbps	1	39	2480	7.10	30.00	5.10	12.20	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE5.0	1Mbps	1	0	2402	7.34	-7.22	5.10	8.00	Pass
BLE5.0	1Mbps	1	19	2440	6.45	-8.14	5.10	8.00	Pass
BLE5.0	1Mbps	1	39	2480	6.39	-8.16	5.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<2Mbps>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	2.068	1.224	0.50	Pass
BLE5.0	2Mbps	1	19	2440	2.072	1.232	0.50	Pass
BLE5.0	2Mbps	1	39	2480	2.072	1.224	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	2Mbps	1	0	2402	8.00	30.00	5.10	13.10	36.00	Pass
BLE5.0	2Mbps	1	19	2440	7.00	30.00	5.10	12.10	36.00	Pass
BLE5.0	2Mbps	1	39	2480	7.00	30.00	5.10	12.10	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	7.14	-11.51	5.10	8.00	Pass
BLE5.0	2Mbps	1	19	2440	6.21	-12.11	5.10	8.00	Pass
BLE5.0	2Mbps	1	39	2480	6.21	-12.11	5.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	Temperature :	23.9~26℃
		Relative Humidity :	63.3~70.3%

EUT Information

Report NO : 800521-02
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	24.70	55.88	31.18	L1	OFF	19.4
0.152250	44.32	---	65.88	21.56	L1	OFF	19.4
0.159000	---	25.35	55.52	30.17	L1	OFF	19.4
0.159000	43.10	---	65.52	22.42	L1	OFF	19.4
0.165750	---	27.91	55.17	27.26	L1	OFF	19.4
0.165750	43.18	---	65.17	21.99	L1	OFF	19.4
0.181500	---	24.24	54.42	30.18	L1	OFF	19.4
0.181500	40.88	---	64.42	23.54	L1	OFF	19.4
0.201750	---	27.29	53.54	26.25	L1	OFF	19.4
0.201750	43.05	---	63.54	20.49	L1	OFF	19.4
0.235500	---	29.05	52.25	23.20	L1	OFF	19.4
0.235500	39.91	---	62.25	22.34	L1	OFF	19.4
0.651750	---	29.98	46.00	16.02	L1	OFF	19.4
0.651750	38.39	---	56.00	17.61	L1	OFF	19.4
3.212250	---	21.46	46.00	24.54	L1	OFF	19.5
3.212250	28.17	---	56.00	27.83	L1	OFF	19.5
19.846500	---	14.33	50.00	35.67	L1	OFF	19.7
19.846500	15.76	---	60.00	44.24	L1	OFF	19.7

EUT Information

Report NO : 800521-02
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	33.88	55.88	22.00	N	OFF	19.4
0.152250	51.51	---	65.88	14.37	N	OFF	19.4
0.161250	---	32.84	55.40	22.56	N	OFF	19.4
0.161250	49.81	---	65.40	15.59	N	OFF	19.4
0.168000	---	31.83	55.06	23.23	N	OFF	19.4
0.168000	48.85	---	65.06	16.21	N	OFF	19.4
0.179250	---	30.23	54.52	24.29	N	OFF	19.4
0.179250	47.98	---	64.52	16.54	N	OFF	19.4
0.190500	---	28.21	54.02	25.81	N	OFF	19.4
0.190500	46.03	---	64.02	17.99	N	OFF	19.4
0.197250	---	26.08	53.73	27.65	N	OFF	19.4
0.197250	41.86	---	63.73	21.87	N	OFF	19.4
0.208500	---	27.36	53.27	25.91	N	OFF	19.4
0.208500	43.64	---	63.27	19.63	N	OFF	19.4
0.249000	---	27.02	51.79	24.77	N	OFF	19.4
0.249000	45.77	---	61.79	16.02	N	OFF	19.4
0.262500	---	27.59	51.35	23.76	N	OFF	19.4
0.262500	45.60	---	61.35	15.75	N	OFF	19.4
0.280500	---	16.31	50.80	34.49	N	OFF	19.4
0.280500	25.46	---	60.80	35.34	N	OFF	19.4
0.820500	---	16.72	46.00	29.28	N	OFF	19.5

0.820500	22.67	---	56.00	33.33	N	OFF	19.5
3.630750	---	16.63	46.00	29.37	N	OFF	19.5
3.630750	21.88	---	56.00	34.12	N	OFF	19.5
19.981500	---	13.81	50.00	36.19	N	OFF	19.8
19.981500	14.78	---	60.00	45.22	N	OFF	19.8



Appendix C. Radiated Spurious Emission

Test Engineer :	Jacky Hung, Austin Li, and CR Liao	Temperature :	20~25°C
		Relative Humidity :	50~60%

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2389.8	56.5	-17.5	74	41.05	27.41	18.32	30.28	251	314	P	H
		2378.985	46.43	-7.57	54	31.03	27.39	18.3	30.29	251	314	A	H
	*	2402	108.97	-	-	93.47	27.45	18.33	30.28	251	314	P	H
	*	2402	108.4	-	-	92.9	27.45	18.33	30.28	251	314	A	H
		2328.165	56.46	-17.54	74	41.28	27.25	18.23	30.3	260	266	P	V
		2387.805	46.53	-7.47	54	31.09	27.41	18.31	30.28	260	266	A	V
	*	2402	107.03	-	-	91.53	27.45	18.33	30.28	260	266	P	V
	*	2402	106.38	-	-	90.88	27.45	18.33	30.28	260	266	A	V
BLE CH 19 2440MHz		2363.2	56.18	-17.82	74	40.85	27.34	18.28	30.29	230	309	P	H
		2366.56	46.61	-7.39	54	31.27	27.35	18.28	30.29	230	309	A	H
	*	2440	107.17	-	-	91.55	27.54	18.35	30.27	230	309	P	H
	*	2440	106.48	-	-	90.86	27.54	18.35	30.27	230	309	A	H
		2495.1	57.32	-16.68	74	41.49	27.69	18.39	30.25	230	309	P	H
		2499.58	46.98	-7.02	54	31.14	27.7	18.39	30.25	230	309	A	H
		2386.02	56.06	-17.94	74	40.63	27.4	18.31	30.28	250	269	P	V
		2350.32	46.3	-7.7	54	31.02	27.31	18.26	30.29	250	269	A	V
	*	2440	105.61	-	-	89.99	27.54	18.35	30.27	250	269	P	V
	*	2440	104.78	-	-	89.16	27.54	18.35	30.27	250	269	A	V
		2486.28	56.94	-17.06	74	41.15	27.66	18.38	30.25	250	269	P	V
		2499.37	46.93	-7.07	54	31.09	27.7	18.39	30.25	250	269	A	V



BLE CH 39 2480MHz	*	2480	106.95	-	-	91.18	27.65	18.38	30.26	229	301	P	H
	*	2480	106.23	-	-	90.46	27.65	18.38	30.26	229	301	A	H
		2488.2	57.4	-16.6	74	41.6	27.67	18.38	30.25	229	301	P	H
		2483.52	47.88	-6.12	54	32.09	27.66	18.38	30.25	229	301	A	H
	*	2480	104.34	-	-	88.57	27.65	18.38	30.26	272	266	P	V
	*	2480	103.7	-	-	87.93	27.65	18.38	30.26	272	266	A	V
		2485.48	56.64	-17.36	74	40.85	27.66	18.38	30.25	272	266	P	V
		2487.28	47.08	-6.92	54	31.28	27.67	18.38	30.25	272	266	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		3600	52.94	-21.06	74	72.57	29.42	12.9	61.95	298	311	P	H
		3600	49.04	-4.96	54	68.67	29.42	12.9	61.95	298	311	A	H
		4804	42.95	-31.05	74	58.84	32.41	13.8	62.1	100	0	P	H
		3600	49.18	-24.82	74	68.81	29.42	12.9	61.95	100	0	P	V
		4804	43.83	-30.17	74	59.72	32.41	13.8	62.1	100	0	P	V
BLE CH 19 2440MHz		3660	53.09	-20.91	74	72.48	29.55	13.03	61.97	296	333	P	H
		3660	48.69	-5.31	54	68.08	29.55	13.03	61.97	296	333	A	H
		4880	44.78	-29.22	74	60.41	32.56	13.92	62.11	100	0	P	H
		7320	47.58	-26.42	74	58.12	37.25	15.25	63.04	100	0	P	H
		3660	50.47	-23.53	74	69.86	29.55	13.03	61.97	219	275	P	V
		3660	46.02	-7.98	54	65.41	29.55	13.03	61.97	219	275	A	V
		4880	44.01	-29.99	74	59.64	32.56	13.92	62.11	100	0	P	V
		7320	47.04	-26.96	74	57.58	37.25	15.25	63.04	100	0	P	V
BLE CH 39 2480MHz		3720	53.82	-20.18	74	72.96	29.68	13.16	61.98	337	333	P	H
		3720	50.01	-3.99	54	69.15	29.68	13.16	61.98	337	333	A	H
		4960	42.4	-31.6	74	57.74	32.72	14.06	62.12	100	0	P	H
		7440	45.85	-28.15	74	56.14	37.42	15.29	63	100	0	P	H
		3720	49.58	-24.42	74	68.72	29.68	13.16	61.98	100	0	P	V
		4960	43.15	-30.85	74	58.49	32.72	14.06	62.12	100	0	P	V
		7440	46.71	-27.29	74	57	37.42	15.29	63	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		196.84	29.17	-14.33	43.5	44.84	14.94	1.74	32.35	-	-	P	H
		257.95	30.38	-15.62	46	40.89	19.59	2.3	32.4	-	-	P	H
		343.31	36.18	-9.82	46	45.66	20.2	2.78	32.46	-	-	P	H
		368.53	34.72	-11.28	46	43.34	20.89	2.97	32.48	-	-	P	H
		846.74	32.05	-13.95	46	30.49	29.01	4.64	32.09	-	-	P	H
		893.3	36.2	-9.8	46	34.37	29.01	4.65	31.83	100	0	P	H
		76.56	29.76	-10.24	40	48.19	13.02	0.95	32.4	-	-	P	V
		254.07	31.41	-14.59	46	42.42	19.09	2.29	32.39	-	-	P	V
		343.31	33.34	-12.66	46	42.82	20.2	2.78	32.46	-	-	P	V
		428.67	30.24	-15.76	46	36.78	22.79	3.19	32.52	-	-	P	V
		509.18	29.55	-16.45	46	34.83	23.96	3.35	32.59	-	-	P	V
		886.51	38.82	-7.18	46	37.06	28.97	4.66	31.87	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2381.295	56.84	-17.16	74	41.44	27.39	18.3	30.29	206	314	P	H
		2388.33	45.78	-8.22	54	30.34	27.41	18.31	30.28	206	314	A	H
	*	2402	108.61	-	-	93.11	27.45	18.33	30.28	206	314	P	H
	*	2402	106.89	-	-	91.39	27.45	18.33	30.28	206	314	A	H
		2367.015	56.86	-17.14	74	41.52	27.35	18.28	30.29	254	268	P	V
		2388.33	45.55	-8.45	54	30.11	27.41	18.31	30.28	254	268	A	V
	*	2402	107.35	-	-	91.85	27.45	18.33	30.28	254	268	P	V
	*	2402	104	-	-	88.5	27.45	18.33	30.28	254	268	A	V
BLE CH 19 2440MHz		2332.96	57.03	-16.97	74	41.83	27.27	18.23	30.3	214	314	P	H
		2388.54	45.42	-8.58	54	29.98	27.41	18.31	30.28	214	314	A	H
	*	2440	107.65	-	-	92.03	27.54	18.35	30.27	214	314	P	H
	*	2440	105.57	-	-	89.95	27.54	18.35	30.27	214	314	A	H
		2495.03	57.27	-16.73	74	41.44	27.69	18.39	30.25	214	314	P	H
		2498.18	46.05	-7.95	54	30.21	27.7	18.39	30.25	214	314	A	H
		2318.26	56.83	-17.17	74	41.69	27.23	18.21	30.3	247	270	P	V
		2382.94	45.45	-8.55	54	30.03	27.4	18.31	30.29	247	270	A	V
	*	2440	105.74	-	-	90.12	27.54	18.35	30.27	247	270	P	V
	*	2440	104.1	-	-	88.48	27.54	18.35	30.27	247	270	A	V
		2495.87	56.97	-17.03	74	41.14	27.69	18.39	30.25	247	270	P	V
		2484.25	46.06	-7.94	54	30.27	27.66	18.38	30.25	247	270	A	V



BLE CH 39 2480MHz	*	2480	106.24	-	-	90.47	27.65	18.38	30.26	229	300	P	H
	*	2480	104.63	-	-	88.86	27.65	18.38	30.26	229	300	A	H
		2489.16	58.43	-15.57	74	42.63	27.67	18.38	30.25	229	300	P	H
		2483.52	49.93	-4.07	54	34.14	27.66	18.38	30.25	229	300	A	H
	*	2480	104.39	-	-	88.62	27.65	18.38	30.26	239	275	P	V
	*	2480	102.75	-	-	86.98	27.65	18.38	30.26	239	275	A	V
		2495.12	57.59	-16.41	74	41.76	27.69	18.39	30.25	239	275	P	V
		2483.52	48.4	-5.6	54	32.61	27.66	18.38	30.25	239	275	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		3600	52.11	-21.89	74	71.74	29.42	12.9	61.95	328	324	P	H
		3600	48.64	-5.36	54	68.27	29.42	12.9	61.95	328	324	A	H
		4804	43.37	-30.63	74	59.26	32.41	13.8	62.1	100	0	P	H
		3600	47.22	-26.78	74	66.85	29.42	12.9	61.95	100	0	P	V
		4804	45.69	-28.31	74	61.58	32.41	13.8	62.1	100	0	P	V
BLE CH 19 2440MHz		3660	51.41	-22.59	74	70.8	29.55	13.03	61.97	280	329	P	H
		3660	47.44	-6.56	54	66.83	29.55	13.03	61.97	280	329	A	H
		4880	43.61	-30.39	74	59.24	32.56	13.92	62.11	100	0	P	H
		7320	47.32	-26.68	74	57.86	37.25	15.25	63.04	100	0	P	H
		3660	48.62	-25.38	74	68.01	29.55	13.03	61.97	100	0	P	V
		4880	43.38	-30.62	74	59.01	32.56	13.92	62.11	100	0	P	V
		7320	47.33	-26.67	74	57.87	37.25	15.25	63.04	100	0	P	V
BLE CH 39 2480MHz		3720	52.19	-21.81	74	71.33	29.68	13.16	61.98	289	15	P	H
		3720	48.11	-5.89	54	67.25	29.68	13.16	61.98	289	15	A	H
		4960	42.36	-31.64	74	57.7	32.72	14.06	62.12	100	0	P	H
		7440	46.13	-27.87	74	56.42	37.42	15.29	63	100	0	P	H
		3720	48.42	-25.58	74	67.56	29.68	13.16	61.98	100	0	P	V
		4960	43.38	-30.62	74	58.72	32.72	14.06	62.12	100	0	P	V
		7440	46.55	-27.45	74	56.84	37.42	15.29	63	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Jacky Hung, Austin Li, and CR Liao	Temperature :	20~25°C
		Relative Humidity :	50~60%

Note symbol





-L	Low channel location
-R	High channel location







<1Mbps>





2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02
Avg	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 800521-02



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH16-HV Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HV Condition : PEAK_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02
Avg.	 Site : 03CH16-HV Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HV Condition : AVG_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 800521-02







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	Left blank
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 800521-02



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	Left blank
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O0521-02
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 8O0521-02





2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02	 Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 800521-02



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 8O0521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 8O0521-02





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	Level (dBuV/m) Date: 2019-05-14 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02	Level (dBuV/m) Date: 2019-05-14 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 800521-02



Emission below 1GHz

2.4GHz BLE (LF)





BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH16-HY Condition : QP 3m BTL06_47020406 HORIZONTAL Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : QP 3m BTL06_47020406 VERTICAL Detector : Peak Project : 800521-02







<2Mbps>





2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Project : 800521-02
Avg	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Project : 800521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Project : 800521-02

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH16-HV Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HV Condition : PEAK_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02
Avg.	 Site : 03CH16-HV Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HV Condition : AVG_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800521-02









BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	Left blank
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800521-02



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	Left blank
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 8O0521-02	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 800521-02

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800521-02
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 800521-02





2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02	 Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 800521-02



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02	 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 800521-02



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	Level (dBuV/m) Date: 2019-05-14 Frequency (MHz) Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 800521-02	Level (dBuV/m) Date: 2019-05-14 Frequency (MHz) Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 800521-02




Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth –LE for 1Mbps	60.22	380	2.63	3kHz	2.20
Bluetooth –LE for 2Mbps	56.79	1070	0.93	1kHz	2.46




1Mbps



Date: 27.APR.2019 02:52:27

2Mbps



Date: 27.APR.2019 02:56:41

————THE END————