



No perfect status, Always seek for better!

SPECIFICATION

APPLICATION FOR APPROVAL

客户名称 CUSTOMER: 横店集团得邦照明股份有限公司

客户案号 CS P/N: A19 全彩智能灯泡

零件名称 PART NAME: AUK01993RB-2.4G BT 天线

耀登案号 DEVE NO. : A92488-90

承认日期 DATE: Sep. 7, 2021

客户确认:				
射频工程师	 结构工程师	研发经理	产品经理	
耀登电通科技(昆山)有限公司				
电气工程师	结构工程师	研发经理	项目经理	
范伟凡	陈红雪	钱磊	王显文	

总部

耀登電通科技(昆山)有限公司 江苏省昆山市周市镇迎宾路 15 号

TEL: 0512-57646998 FAX: 0512-57646168

Head Quarter

Auden Techno(KUNSHAN)CO.LTD

NO.15 YING-BIN ROAD, LUYANGTOWN, KUNSHAN, JIANGSU
CHINA

分公司:

耀登電通科技(昆山)有限公司西安分公司 西安市 高新区 唐延南路 10 号 中兴产业园 E1-04

TEL: 13382157879

耀登電通科技(昆山)有限公司深圳分公司

地址:深圳市南山区桃源街道红花岭工业区第五区 A 栋二楼

201-202(南区) TEL: 185 8845 5257

Branch

Auden Techno(KUNSHAN)CO.LTD. Xi 'an branch E1-04, zhongxing industrial park, no.10 tangyan south road, high-tech zone, xi 'an

Auden Techno(KUNSHAN)CO.LTD. Shenzhen branch Address: 201-202, 2nd floor, building A, zone 5, honghualing industrial zone, taoyuan street, nanshan district, shenzhen (southern district)

CONFIDENTIAL



No perfect status, Always seek for better!

INDEX

- 一、规格书封面(Cover)
- 二、规格书目录(Index)
- 三、天线基本参数(The Basic Parameters)
- 四、电气测试报告(RF Performance Test Report)
- 五、工程图纸(Product Drawing)
- 六、尺寸报告 (Dimensional check reports)
- 七、可靠性测试报告(Reliability test report)

CONFIDENTIAL



Auden Techno(KUNSHAN)CO.LTD ANTENNA SPECIFICATION

No perfect status, Always seek for better!

天线基本参数(The Basic Parameters)

项目(Item)	特性(Specifications)	
天线结构组成	镀镍线	
频率(Frequency)	2.4g	
驻波比 (V.S.W.R)	≤3	
增益 (Gain)	€3	
极化方式 (Polarization)	线极化	
特性阻抗 (Impedance)	50Ω	
塑胶材质(Plastic material)	无	
接头形式 (joint type)	无	
工作温度(Operation temperature)	-40°C to 150°C	
储存温度(Storage temperature)	-40°C to 150°C	
湿度 (humidity)	Non-condensing 65°C 95% RH	
天线图片	31. 00±0. 5	

CONFIDENTIAL



Auden Techno(KUNSHAN)CO.LTD ANTENNA SPECIFICATION

No perfect status, Always seek for better!

电气测试报告(RF Performance Test Report)


组装位置图片






Vswr

Item	Frequency Range	
WIFI	2400MHz - 2500MHz	



CONFIDENTIAL

Return loss



Main-无源测试数据

Frequency	Efficiency (%)	Gain (dBi)
2.4G	41.02	-0.2
2.41G	40.23	-0.27
2.42G	41.59	-0.01
2.43G	43.85	0.05
2.44G	41.88	-0.29
2.45G	47.86	0.49
2.46G	48.08	0.69
2.47G	50.12	1.07
2.48G	52	1.33
2.49G	48.42	1.05
2.5G	47.53	0.98


CONFIDENTIAL



Auden Techno(KUNSHAN)CO.LTD ANTENNA SPECIFICATION

No perfect status, Always seek for better!

工程图纸(Product Drawing)



CONFIDENTIAL