

# FCC Radio Test Report

## FCC ID: 2ARGH-PV101A

### Original Grant

**Report No.** : TB-FCC162073  
**Applicant** : PICA VUE INC  
**Equipment Under Test (EUT)**  
**EUT Name** : 10.1 INCH ANDROID TABLET  
**Model No.** : PV101A  
**Series Model No.** : N/A  
**Brand Name** : PICA VUE  
**Receipt Date** : 2018-09-25  
**Test Date** : 2018-09-28 to 2018-10-16  
**Issue Date** : 2018-10-17  
**Standards** : FCC Part 15, Subpart C (15.247: 2018)  
**Test Method** : ANSI C63.10: 2013  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,  
The EUT technically complies with the FCC and IC requirements

**Test/Witness Engineer** : *Jason xu* Jason Xu  
**Test/Witness Engineer** : *IVAN SU* Ivan Su  
**Approved & Authorized** : *Ray Lai* Ray Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



## Contents

<b>CONTENTS</b> .....	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT</b> .....	<b>5</b>
1.1 Client Information.....	5
1.2 General Description of EUT (Equipment Under Test) .....	5
1.3 Block Diagram Showing the Configuration of System Tested.....	7
1.4 Description of Support Units .....	7
1.5 Description of Test Mode.....	7
1.6 Description of Test Software Setting .....	9
1.7 Measurement Uncertainty .....	9
1.8 Test Facility.....	10
<b>2. TEST SUMMARY</b> .....	<b>11</b>
<b>3. TEST EQUIPMENT</b> .....	<b>12</b>
<b>4. CONDUCTED EMISSION TEST</b> .....	<b>13</b>
4.1 Test Standard and Limit.....	13
4.2 Test Setup.....	13
4.3 Test Procedure.....	13
4.4 EUT Operating Mode .....	14
4.5 Test Data.....	14
<b>5. RADIATED EMISSION TEST</b> .....	<b>15</b>
5.1 Test Standard and Limit.....	15
5.2 Test Setup.....	16
5.3 Test Procedure.....	17
5.4 EUT Operating Condition .....	18
5.5 Test Data.....	18
<b>6. RESTRICTED BANDS REQUIREMENT</b> .....	<b>19</b>
6.1 Test Standard and Limit.....	19
6.2 Test Setup.....	19
6.3 Test Procedure.....	19
6.4 EUT Operating Condition .....	20
6.5 Test Data.....	20
<b>7. BANDWIDTH TEST</b> .....	<b>21</b>
7.1 Test Standard and Limit.....	21
7.2 Test Setup.....	21
7.3 Test Procedure.....	21
7.4 EUT Operating Condition .....	21
7.5 Test Data.....	21
<b>8. PEAK OUTPUT POWER TEST</b> .....	<b>22</b>
8.1 Test Standard and Limit.....	22



8.2 Test Setup.....	22
8.3 Test Procedure.....	22
8.4 EUT Operating Condition .....	22
8.5 Test Data.....	22
<b>9. POWER SPECTRAL DENSITY TEST .....</b>	<b>23</b>
9.1 Test Standard and Limit.....	23
9.2 Test Setup.....	23
9.3 Test Procedure.....	23
9.4 EUT Operating Condition .....	23
9.5 Test Data.....	23
<b>10. ANTENNA REQUIREMENT.....</b>	<b>24</b>
10.1 Standard Requirement.....	24
10.2 Antenna Connected Construction .....	24
<b>ATTACHMENT A-- CONDUCTED EMISSION TEST DATA .....</b>	<b>25</b>
<b>ATTACHMENT B-- RADIATED EMISSION TEST DATA .....</b>	<b>29</b>
<b>ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT TEST DATA.....</b>	<b>49</b>
<b>ATTACHMENT D-- BANDWIDTH TEST DATA.....</b>	<b>64</b>
<b>ATTACHMENT E-- PEAK OUTPUT POWER TEST DATA.....</b>	<b>70</b>
<b>ATTACHMENT F-- POWER SPECTRAL DENSITY TEST DATA.....</b>	<b>73</b>







# 1. General Information about EUT

## 1.1 Client Information

<b>Applicant</b>	:	PICAVUE INC
<b>Address</b>	:	507 DALTRY CT, CHALFONT, USA
<b>Manufacturer</b>	:	PICAVUE INC
<b>Address</b>	:	507 DALTRY CT, CHALFONT, USA

## 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	10.1 INCH ANDROID TABLET	
<b>Models No.</b>	:	PV101A	
<b>Model Different</b>	:	N/A	
<b>Product Description</b>	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
		Number of Channel:	802.11b/g/n(HT20):11 channels <b>see note(3)</b>
		RF Output Power:	802.11b: 8.67dBm 802.11g: 7.81dBm 802.11n (HT20): 7.76dBm
		Antenna Gain:	1.14dBi PCB Antenna
		Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK,QPSK,16QAM, 64QAM)
		Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
<b>Power Supply</b>	:	DC Voltage Supply from DC Adapter(FJ-SW1202000U). DC Voltage supplied by Li-ion battery.	
<b>Power Rating</b>	:	Input: DC 12V2A by DC Adapter. DC 3.7V by 5000mAh Li-ion battery.	
<b>Software Version</b>	:	N/A	
<b>Hardware Version</b>	:	N/A	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	



**Note:**

- (1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v05.
- (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



## (3) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		

Note: CH 01~CH 11 for 802.11b/g/n(HT20)

(4) The Antenna information about the equipment is provided by the applicant.

### 1.3 Block Diagram Showing the Configuration of System Tested



### 1.4 Description of Support Units

The EUT has been tested as an independent unit.

### 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follows was evaluated respectively.



For Conducted Test	
Final Test Mode	Description
Mode 1	Normal Working with TX B Mode

For Radiated Test	
Final Test Mode	Description
Mode 2	TX Mode B Mode Channel 01/06/11
Mode 3	TX Mode G Mode Channel 01/06/11
Mode 4	TX Mode N(HT20) Mode Channel 01/06/11

**Note:**

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.  
According to ANSI C63.10 standards, the measurements are performed at the highest, Middle, lowest available channels, and the worst case data rate as follows:  
802.11b Mode: CCK (1 Mbps)  
802.11g Mode: OFDM (6 Mbps)  
802.11n (HT20) Mode: MCS 0 (6.5 Mbps)
- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a portable unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.



## 1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software Version	RFTestTool.exe		
	Channel	CH 01	CH 06
IEEE 802.11b DSSS	39	39	40
IEEE 802.11g OFDM	30	30	30
IEEE 802.11n (HT20)	30	30	30

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz	$\pm 3.42$ dB
	150kHz to 30MHz	$\pm 3.42$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.40$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB



## 1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **A2LA Certificate No.: 4750.01**

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01. FCC Accredited Test Site Number: 854351.

### **IC Registration No.: (11950A-1)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.



## 2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 2				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS 247 5.4 (4)	Peak Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(d)& 15.209	RSS 247 5.5	Transmitter Radiated Spurious Emission	PASS	N/A
<p><b>Note:</b> "/" for no requirement for this test item. N/A is an abbreviation for Not Applicable.</p>				



### 3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 18, 2018	Jul. 17, 2019
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 18, 2018	Jul. 17, 2019
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 18, 2018	Jul. 17, 2019
LISN	Rohde & Schwarz	ENV216	101131	Jul. 18, 2018	Jul. 17, 2019
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 18, 2018	Jul. 17, 2019
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 18, 2018	Jul. 17, 2019
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.16, 2018	Mar. 15, 2019
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar.16, 2018	Mar. 15, 2019
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.16, 2018	Mar. 15, 2019
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.16, 2018	Mar. 15, 2019
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 14, 2018	Jul. 13, 2019
Pre-amplifier	Sonoma	310N	185903	Mar.17, 2018	Mar. 16, 2019
Pre-amplifier	HP	8449B	3008A00849	Mar.17, 2018	Mar. 16, 2019
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.17, 2018	Mar. 16, 2019
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 18, 2018	Jul. 17, 2019
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 18, 2018	Jul. 17, 2019
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Oct. 26, 2017	Oct. 25, 2018
Vector Signal Generator	Agilent	N5182A	MY50141294	Oct. 26, 2017	Oct. 25, 2018
Analog Signal Generator	Agilent	N5181A	MY50141953	Oct. 26, 2017	Oct. 25, 2018
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Oct. 26, 2017	Oct. 25, 2018



## 4. Conducted Emission Test

### 4.1 Test Standard and Limit

- 4.1.1 Test Standard  
 FCC Part 15.207
- 4.1.2 Test Limit


**Conducted Emission Test Limit**

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2 Test Setup



### 4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.



I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

#### 4.4 EUT Operating Mode

Please refer to the description of test mode.

#### 4.5 Test Data

Please refer to the Attachment A.



## 5. Radiated Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.209

#### 5.1.2 Test Limit

#### Radiated Emission Limits ( 9 kHz~1000 MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### Radiated Emission Limit (Above 1000MHz)


Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54

**Note:**


- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)



5.2 Test Setup




Below 30MHz Test Setup



Below 1000MHz Test Setup





Above 1GHz Test Setup

### 5.3 Test Procedure

- (1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency Below 1GHz. The EUT was placed on a rotating 0.8m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.



(8) For the actual test configuration, please see the test setup photo.

#### 5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

#### 5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.



## 6. Restricted Bands Requirement


### 6.1 Test Standard and Limit

- 6.1.1 Test Standard
  - FCC Part 15.247(d)
  - FCC Part 15.209
  - FCC Part 15.205

### 6.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

### 6.2 Test Setup



### 6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency Below 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.



- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

#### 6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

#### 6.5 Test Data

Please refer to the Attachment C.



## 7. Bandwidth Test

### 7.1 Test Standard and Limit


#### 7.1.1 Test Standard

FCC Part 15.247 (a)(2)

#### 7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	$\geq 500$ KHz (6dB bandwidth)	2400~2483.5

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (3) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

### 7.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

### 7.5 Test Data

Please refer to the Attachment D.



## 8. Peak Output Power Test

### 8.1 Test Standard and Limit


#### 8.1.1 Test Standard

FCC Part 15.247 (b)

#### 8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

### 8.2 Test Setup



### 8.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v05. The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

### 8.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

### 8.5 Test Data

Please refer to the Attachment E.



## 9. Power Spectral Density Test

### 9.1 Test Standard and Limit


#### 9.1.1 Test Standard

FCC Part 15.247 (e)

#### 9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser center frequency to DTS channel center frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

### 9.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

### 9.5 Test Data

Please refer to the Attachment F.



## 10. Antenna Requirement

### 10.1 Standard Requirement

#### 10.1.1 Standard

FCC Part 15.203

#### 10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 10.2 Antenna Connected Construction

The gains of the antenna used for transmitting is 1.14dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

#### Result


The EUT antenna is a PCB Antenna. It complies with the standard requirement.

Antenna Type
<input type="checkbox"/> Permanent attached antenna
<input checked="" type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna



## Attachment A-- Conducted Emission Test Data

Temperature:	24 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60Hz		
Terminal:	Line		
Test Mode:	Normal working with TX B Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1539	32.60	9.64	42.24	65.78	-23.54	QP
2		0.1539	9.94	9.64	19.58	55.78	-36.20	AVG
3		0.1819	30.19	9.65	39.84	64.39	-24.55	QP
4		0.1819	12.37	9.65	22.02	54.39	-32.37	AVG
5		0.2180	29.05	9.64	38.69	62.89	-24.20	QP
6		0.2180	13.64	9.64	23.28	52.89	-29.61	AVG
7		0.3500	27.53	9.58	37.11	58.96	-21.85	QP
8		0.3500	18.62	9.58	28.20	48.96	-20.76	AVG
9		0.4140	27.32	9.58	36.90	57.57	-20.67	QP
10	*	0.4140	19.14	9.58	28.72	47.57	-18.85	AVG
11		14.0820	24.29	10.54	34.83	60.00	-25.17	QP
12		14.0820	18.48	10.54	29.02	50.00	-20.98	AVG

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**



<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	Normal working with TX B Mode		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1620	31.79	9.64	41.43	65.36	-23.93	QP
2		0.1620	13.52	9.64	23.16	55.36	-32.20	AVG
3		0.2140	29.70	9.64	39.34	63.04	-23.70	QP
4		0.2140	18.20	9.64	27.84	53.04	-25.20	AVG
5		0.2420	24.55	9.62	34.17	62.02	-27.85	QP
6		0.2420	13.13	9.62	22.75	52.02	-29.27	AVG
7		0.2700	24.68	9.59	34.27	61.12	-26.85	QP
8		0.2700	14.86	9.59	24.45	51.12	-26.67	AVG
9		0.4220	27.04	9.58	36.62	57.41	-20.79	QP
10	*	0.4220	19.61	9.58	29.19	47.41	-18.22	AVG
11		13.9700	24.35	10.53	34.88	60.00	-25.12	QP
12		13.9700	18.29	10.53	28.82	50.00	-21.18	AVG

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**



<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 240V/60Hz		
<b>Terminal:</b>	Line		
<b>Test Mode:</b>	Normal working with TX B Mode		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1500	40.35	9.58	49.93	65.99	-16.06	QP
2		0.1500	18.26	9.58	27.84	55.99	-28.15	AVG
3	*	0.1819	39.03	9.58	48.61	64.39	-15.78	QP
4		0.1819	19.13	9.58	28.71	54.39	-25.68	AVG
5		0.2040	36.31	9.58	45.89	63.44	-17.55	QP
6		0.2040	16.90	9.58	26.48	53.44	-26.96	AVG
7		0.2260	34.94	9.58	44.52	62.59	-18.07	QP
8		0.2260	11.50	9.58	21.08	52.59	-31.51	AVG
9		0.2779	32.38	9.59	41.97	60.88	-18.91	QP
10		0.2779	13.62	9.59	23.21	50.88	-27.67	AVG
11		0.4180	29.28	9.60	38.88	57.49	-18.61	QP
12		0.4180	20.24	9.60	29.84	47.49	-17.65	AVG

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**



<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 240V/60Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	Normal working with TX B Mode		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1620	39.91	9.64	49.55	65.36	-15.81	QP
2		0.1620	19.90	9.64	29.54	55.36	-25.82	AVG
3		0.1900	38.75	9.65	48.40	64.03	-15.63	QP
4		0.1900	20.74	9.65	30.39	54.03	-23.64	AVG
5		0.2300	34.00	9.63	43.63	62.45	-18.82	QP
6		0.2300	13.20	9.63	22.83	52.45	-29.62	AVG
7		0.2779	32.27	9.59	41.86	60.88	-19.02	QP
8		0.2779	14.98	9.59	24.57	50.88	-26.31	AVG
9		0.3460	29.86	9.57	39.43	59.06	-19.63	QP
10		0.3460	20.32	9.57	29.89	49.06	-19.17	AVG
11		0.4180	31.48	9.58	41.06	57.49	-16.43	QP
12	*	0.4180	22.65	9.58	32.23	47.49	-15.26	AVG

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**



## Attachment B-- Radiated Emission Test Data


### 9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

### 30MHz~1GHz

Temperature:	24 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		47.6586	36.38	-22.46	13.92	40.00	-26.08	QP
2		55.6094	36.72	-23.87	12.85	40.00	-27.15	QP
3		122.8340	35.99	-22.34	13.65	43.50	-29.85	QP
4		216.7828	43.16	-19.03	24.13	46.00	-21.87	QP
5		321.0608	38.27	-15.52	22.75	46.00	-23.25	QP
6	*	396.2415	38.83	-12.45	26.38	46.00	-19.62	QP

\*:Maximum data    x:Over limit    !:over margin

Emission Level= Read Level+ Correct Factor



<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX B Mode 2412MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	46.6664	50.42	-22.13	28.29	40.00	-11.71	QP
2		103.8055	50.01	-22.23	27.78	43.50	-15.72	QP
3		197.8928	42.11	-19.93	22.18	43.50	-21.32	QP
4		318.8170	35.29	-15.59	19.70	46.00	-26.30	QP
5		502.9395	32.75	-10.52	22.23	46.00	-23.77	QP
6		661.1505	30.55	-7.83	22.72	46.00	-23.28	QP


\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**



**Above 1GHz**

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX B Mode 2412MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1		4824.060	50.03	14.55	64.58	74.00	-9.42	peak
2	*	4824.060	30.57	14.55	45.12	54.00	-8.88	AVG

Emission Level= Read Level+ Correct Factor



<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX B Mode 2412MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4823.930	29.43	14.55	43.98	54.00	-10.02	AVG
2		4826.080	42.81	14.57	57.38	74.00	-16.62	peak

Emission Level= Read Level+ Correct Factor



<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX B Mode 2437MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4873.810	43.82	14.86	58.68	74.00	-15.32	peak
2	*	4874.590	29.57	14.86	44.43	54.00	-9.57	AVG

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX B Mode 2437MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4874.670	41.83	14.86	56.69	74.00	-17.31	peak
2	*	4874.670	29.48	14.86	44.34	54.00	-9.66	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX B Mode 2462MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4922.660	31.17	15.17	46.34	54.00	-7.66	AVG
2		4924.030	43.82	15.17	58.99	74.00	-15.01	peak

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX B Mode 2462MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.710	29.78	15.17	44.95	54.00	-9.05	AVG
2		4924.870	43.47	15.18	58.65	74.00	-15.35	peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX G Mode 2412MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4822.820	43.42	14.55	57.97	74.00	-16.03	peak
2	*	4823.380	29.34	14.55	43.89	54.00	-10.11	AVG

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX G Mode 2412MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	*	4824.190	29.30	14.55	43.85	54.00	-10.15	AVG
2		4826.380	42.85	14.57	57.42	74.00	-16.58	peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX G Mode 2437MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4873.690	43.32	14.86	58.18	74.00	-15.82	peak
2	*	4873.690	30.70	14.86	45.56	54.00	-8.44	AVG

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX G Mode 2437MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4872.890	43.75	14.85	58.60	74.00	-15.40	peak
2	*	4874.430	29.47	14.86	44.33	54.00	-9.67	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX G Mode 2462MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4922.430	44.80	15.17	59.97	74.00	-14.03	peak
2	*	4924.710	29.82	15.18	45.00	54.00	-9.00	AVG

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX G Mode 2462MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4923.110	29.75	15.17	44.92	54.00	-9.08	AVG
2		4925.410	43.92	15.19	59.11	74.00	-14.89	peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX N(HT20) Mode 2412MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4823.670	29.34	14.55	43.89	54.00	-10.11	AVG
2		4824.500	43.57	14.55	58.12	74.00	-15.88	peak

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX N(HT20) Mode 2412MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	*	4823.830	29.21	14.55	43.76	54.00	-10.24	AVG
2		4825.040	43.31	14.56	57.87	74.00	-16.13	peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX N(HT20) Mode 2437MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4872.540	43.96	14.85	58.81	74.00	-15.19	peak
2	*	4874.970	29.54	14.86	44.40	54.00	-9.60	AVG

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX N(HT20) Mode 2437MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4874.530	29.48	14.86	44.34	54.00	-9.66	AVG
2		4876.000	43.72	14.87	58.59	74.00	-15.41	peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX N(HT20) Mode 2462MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4922.740	29.86	15.17	45.03	54.00	-8.97	AVG
2		4925.450	43.83	15.19	59.02	74.00	-14.98	peak

Emission Level= Read Level+ Correct Factor



<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX N(HT20) Mode 2462MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4923.160	43.40	15.17	58.57	74.00	-15.43	peak
2	*	4923.530	29.73	15.17	44.90	54.00	-9.10	AVG

Emission Level= Read Level+ Correct Factor


## Attachment C-- Restricted Bands Requirement Test Data

### (1) Radiation Test






<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX B Mode 2412MHZ		
<b>Remark:</b>	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	43.95	2.82	46.77	Fundamental Frequency		peak
2		2390.000	34.10	2.82	36.92	Fundamental Frequency		AVG
3	*	2412.800	84.07	2.94	87.01	54.00	33.01	AVG
4	X	2413.000	88.20	2.94	91.14	74.00	17.14	peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX B Mode 2462MHz		
<b>Remark:</b>	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2461.200	96.53	3.27	99.80	Fundamental Frequency		AVG
2	X	2463.000	101.18	3.27	104.45	Fundamental Frequency		peak
3		2483.500	48.19	3.41	51.60	74.00	-22.40	peak
4		2483.500	35.01	3.41	38.42	54.00	-15.58	AVG

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX B Mode 2462MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2461.200	82.40	3.27	85.67	Fundamental Frequency		AVG
2	X	2463.000	86.50	3.27	89.77	Fundamental Frequency		peak
3		2483.500	44.00	3.41	47.41	74.00	-26.59	peak
4		2483.500	32.95	3.41	36.36	54.00	-17.64	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX G Mode 2412MHz		
<b>Remark:</b>	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	51.55	2.82	54.37	74.00	-19.63	peak
2		2390.000	39.88	2.82	42.70	54.00	-11.30	AVG
3	X	2405.800	99.18	2.90	102.08	Fundamental Frequency		peak
4	*	2405.800	89.44	2.90	92.34	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX G Mode 2412MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	46.22	2.82	49.04	74.00	-24.96	peak
2		2390.000	33.52	2.82	36.34	54.00	-17.66	AVG
3	X	2410.800	85.54	2.93	88.47	Fundamental Frequency		peak
4	*	2418.400	75.43	2.98	78.41	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX G Mode 2462MHz		
<b>Remark:</b>	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2455.600	89.05	3.23	92.28	Fundamental Frequency		AVG
2	X	2468.400	98.88	3.31	102.19	Fundamental Frequency		peak
3		2483.500	55.56	3.41	58.97	74.00	-15.03	peak
4		2483.500	39.30	3.41	42.71	54.00	-11.29	AVG

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX G Mode 2462MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2467.800	84.41	3.31	87.72	Fundamental Frequency		peak
2	*	2468.200	74.66	3.31	77.97	Fundamental Frequency		AVG
3		2483.500	44.10	3.41	47.51	74.00	-26.49	peak
4		2483.500	33.14	3.41	36.55	54.00	-17.45	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX N(HT20) Mode 2412MHZ		
<b>Remark:</b>	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	51.46	2.82	54.28	74.00	-19.72	peak
2		2390.000	40.53	2.82	43.35	54.00	-10.65	AVG
3	X	2405.800	100.03	2.90	102.93	Fundamental Frequency		peak
4	*	2405.800	89.17	2.90	92.07	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor




<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX N(HT20) Mode 2412MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	44.55	2.82	47.37	74.00	-26.63	peak
2		2390.000	33.65	2.82	36.47	54.00	-17.53	AVG
3	X	2411.600	85.01	2.94	87.95	Fundamental Frequency		peak
4	*	2413.000	75.21	2.94	78.15	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX N(HT20) Mode 2462MHz		
<b>Remark:</b>	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2455.600	88.14	3.23	91.37	Fundamental Frequency		AVG
2	X	2456.000	97.76	3.23	100.99	Fundamental Frequency		peak
3		2483.500	54.76	3.41	58.17	74.00	-15.83	peak
4		2483.500	39.33	3.41	42.74	54.00	-11.26	AVG

Emission Level= Read Level+ Correct Factor



<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX N(HT20) Mode 2462MHz		
<b>Remark:</b>	N/A		





No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2455.800	84.47	3.23	87.70	Fundamental Frequency		peak
2	*	2468.200	75.09	3.31	78.40	Fundamental Frequency		AVG
3		2483.500	44.56	3.41	47.97	74.00	-26.03	peak
4		2483.500	33.52	3.41	36.93	54.00	-17.07	AVG

Emission Level= Read Level+ Correct Factor



(2) Conducted Test

Temperature:	24 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		







Temperature:	24 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX G Mode 2412MHz / TX G Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		



Temperature:	24 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT20) Mode 2412MHz / TX N(HT20) Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		






## Attachment D-- Bandwidth Test Data


Temperature:	24 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11B Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	7.595	13.990	>=0.5
2437	9.024	13.969	
2462	8.576	13.979	

### 802.11B Mode


#### 2412 MHz




**802.11B Mode**  
**2437 MHz**




**802.11B Mode**  
**2462 MHz**






<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Test Mode:</b>	TX 802.11G Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	16.28	16.446	>=0.5
2437	16.05	16.440	
2462	16.02	16.432	
<b>802.11G Mode</b>			
<b>2412 MHz</b>			
 <p>Keysight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.41200000 GHz</p> <p>Center Freq: 2.412000000 GHz</p> <p>Trig: Free Run</p> <p>#Gain: Low</p> <p>#Atten: 10 dB</p> <p>Avg/Hold: &gt;10/10</p> <p>Radio Std: None</p> <p>Radio Device: BTS</p> <p>10 dB/div</p> <p>Ref 20.00 dBm</p> <p>Center 2.412 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 4 ms</p> <p><b>Occupied Bandwidth 16.446 MHz</b></p> <p>Total Power 4.97 dBm</p> <p>Transmit Freq Error 1.933 kHz</p> <p>% of OBW Power 99.00 %</p> <p>x dB Bandwidth 16.28 MHz</p> <p>x dB -6.00 dB</p>			


**802.11G Mode**  
**2437 MHz**




**802.11G Mode**  
**2462 MHz**






<b>Temperature:</b>	24 °C	<b>Relative Humidity:</b>	56%
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Test Mode:</b>	TX 802.11N(HT20) Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	17.54	17.687	≥0.5
2437	17.58	17.678	
2462	17.58	17.686	
<b>802.11N(HT20) Mode</b>			
<b>2412 MHz</b>			
			

**802.11N(HT20) Mode  
2437 MHz**



**802.11N(HT20) Mode  
2462 MHz**





## Attachment E-- Peak Output Power Test Data


<b>Test Conditions:</b>		Continuous transmitting Mode	
<b>Temperature:</b>		24 °C	<b>Relative Humidity:</b> 56%
<b>Test Voltage:</b>		AC 120V/60HZ	
Mode	Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
802.11b	2412	8.66	30
	2437	8.13	
	2462	8.67	
802.11g	2412	7.75	
	2437	7.42	
	2462	7.81	
802.11n (HT20)	2412	7.71	
	2437	7.41	
	2462	7.76	
<b>Result: PASS</b>			

Duty Cycle		
Mode	Channel frequency (MHz)	Test Result
802.11b	2412	>98%
	2437	
	2462	
802.11g	2412	
	2437	
	2462	
802.11n (HT20)	2412	
	2437	
	2462	
Please see below plots		

**802.11 B Mode 2437 MHz**




**802.11 G Mode 2437 MHz**





802.11 N(HT20) Mode 2437 MHz




## Attachment F-- Power Spectral Density Test Data

Temperature:	24 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11B Mode		
Channel Frequency (MHz)	Power Density (dBm/3 kHz)	Limit (dBm/3kHz)	
2412	-15.084	8	
2437	-16.224		
2462	-14.582		


802.11B Mode

2412 MHz






**802.11B Mode**  
**2437 MHz**




**802.11B Mode**  
**2462 MHz**




Temperature:	24 °C	Temperature:	24 °C
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11G Mode		
Channel Frequency (MHz)	Power Density (dBm/3 kHz)	Limit (dBm/3kHz)	
2412	-22.634	8	
2437	-23.513		
2462	-22.130		
<b>802.11G Mode</b>			
<b>2412 MHz</b>			



**802.11G Mode**  
**2437 MHz**




**802.11G Mode**  
**2462 MHz**




<b>Temperature:</b>	24 °C	<b>Temperature:</b>	24 °C
<b>Test Voltage:</b>	AC 120V/60HZ		
<b>Test Mode:</b>	TX 802.11N(HT20) Mode		
Channel Frequency (MHz)	Power Density (dBm/3 kHz)	Limit (dBm/3kHz)	
2412	-23.123	8	
2437	-23.619		
2462	-22.538		
<b>802.11N(HT20) Mode</b>			
<b>2412 MHz</b>			
<p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.41200000 GHz Ref Offset 3.63 dB Ref 23.63 dBm Mkr1 2.418 903 GHz -23.123 dBm Center 2.41200 GHz #Res BW 3.0 kHz #VBW 10 kHz Span 35.08 MHz Sweep 3.699 s (10001 pts)</p>			



**802.11N(HT20) Mode  
2437 MHz**



**802.11N(HT20) Mode  
2462 MHz**



-----END OF REPORT-----