



FCC TEST REPORT

Test report

On Behalf of

Xiamen Caimore Communication Technology Co.,Ltd.

For

Wireless Router

**Model No.: CM520-8AF, CM520-87F, CM520-86F, CM520-89F,
CM520-91F, CM520-8VF, CM520-8BF, CM520-8CF, CM520-61F,
CM520**

FCC ID: 2ARILCM520-8AF

Prepared for : Xiamen Caimore Communication Technology Co.,Ltd.
#2 of 302 Unit, 23# Wanghai Road, Xiamen Software Park II, Xiamen,China

Prepared By : Shenzhen HUAKE Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an
District, Shenzhen City, China

Date of Test: Oct. 12, 2018~Nov. 13, 2018

Date of Report: Nov. 13, 2018

Report Number: HK1811011423E



TEST RESULT CERTIFICATION

Applicant's name Xiamen Caimore Communication Technology Co.,Ltd.
Address..... #2 of 302 Unit, 23# Wanghai Road, Xiamen Software Park II, Xiamen,China
Manufacture's Name..... Xiamen Caimore Communication Technology Co.,Ltd.
Address..... #2 of 302 Unit, 23# Wanghai Road, Xiamen Software Park II, Xiamen,China

Product description Wireless Router
Brand Name CAIMORE
Mode Name CM520-8AF
Serial Model CM520-87F,CM520-86F,CM520-89F,CM520-91F,CM520-8VF,CM520-8BF,CM520-8CF,CM520-61F, CM520
Difference Description The difference between the models is only to distinguish customer needs for customizing the product model, which has no effect on the judgment of product's safety and EMC.

Standards FCC Rules and Regulations Part 15 Subpart C Section 15.247
KDB 558074 D01 15.247 Meas Guidance v05

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test
Date (s) of performance of tests Oct. 12, 2018~Nov. 13, 2018
Date of Issue Nov. 13, 2018
Test Result Pass

Testing Engineer : [Signature]
(Gary Qian)

Technical Manager : [Signature]
(Eden Hu)

Authorized Signatory : [Signature]
(Jason Zhou)



Revision	Issue Date	Revisions	Revised By
V1.0	Nov. 13, 2018	Initial Issue	Jason Zhou



TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. PRODUCT DESCRIPTION	6
1.2. TABLE OF CARRIER FREQUENCYS	6
1.3. IEEE 802.11N MODULATION SCHEME	7
1.4. RELATED SUBMITTAL(S) / GRANT (S)	7
1.5. TEST METHODOLOGY	8
1.6. SPECIAL ACCESSORIES	8
1.7. EQUIPMENT MODIFICATIONS.....	8
2. MEASUREMENT UNCERTAINTY	9
3. DESCRIPTION OF TEST MODES	10
4 SYSTEM TEST CONFIGURATION	11
4.1. CONFIGURATION OF EUT SYSTEM.....	11
4.2. EQUIPMENT USED IN EUT SYSTEM.....	11
4.3. SUMMARY OF TEST RESULTS	11
5. TEST FACILITY	12
6. OUTPUT POWER	13
7.1. MEASUREMENT PROCEDURE	13
6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
6.3. LIMITS AND MEASUREMENT RESULT	14
7. 6DB BANDWIDTH	16
7.1. MEASUREMENT PROCEDURE	16
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	16
8.3. LIMITS AND MEASUREMENT RESULTS	17
9. CONDUCTED SPURIOUS EMISSION	20
9.1. MEASUREMENT PROCEDURE	20
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	20
9.3. MEASUREMENT EQUIPMENT USED	20
9.4. LIMITS AND MEASUREMENT RESULT	21
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	28
10.1 MEASUREMENT PROCEDURE	28
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	28
10.3 MEASUREMENT EQUIPMENT USED	28
10.4 LIMITS AND MEASUREMENT RESULT.....	29
11. RADIATED EMISSION	32
11.1. MEASUREMENT PROCEDURE.....	32



- 11.2. TEST SETUP 33
- 11.3. LIMITS AND MEASUREMENT RESULT 34
- 11.4. TEST RESULT 35
- 12. BAND EDGE EMISSION 38**
 - 12.1. MEASUREMENT PROCEDURE 38
 - 12.2. TEST SET-UP 38
 - 12.3. RADIATED TEST RESULT 39
 - 12.4. CONDUCTED TEST RESULT 40
- 13. FCC LINE CONDUCTED EMISSION TEST 42**
 - 13.1. LIMITS OF LINE CONDUCTED EMISSION TEST 42
 - 13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 42
 - 13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 43
 - 13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 44
 - 13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST 45
- APPENDIX A: PHOTOGRAPHS OF TEST SETUP 47**



1. GENERAL INFORMATION

1.1. PRODUCT DESCRIPTION

The EUT is designed as “Wireless Router”. It is designed by way of utilizing the DSSS and OFDM technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.412 GHz~2.462GHz
Output Power	IEEE 802.11b: 13.60 dBm, IEEE 802.11g: 11.70 dBm; IEEE 802.11n(20): 11.68 dBm,IEEE 802.11n(40): 11.00 dBm
Modulation	DSSS(DBPSK/DQPSK/CCK);OFDM(BPSK/QPSK/16-QAM/64-QAM)
Number of channels	11 Channels (IEEE802.11b/g/n20)& 7 Channels (IEEE802.11n40)
Hardware Version	V12
Software Version	V3.3.5
Antenna Designation	Monopole Antenna
Antenna Gain	2.0dBi
Power Supply	DC9V

1.2. TABLE OF CARRIER FREQUENCIES

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	1	2412 MHZ
	2	2417 MHZ
	3	2422 MHZ
	4	2427 MHZ
	5	2432 MHZ
	6	2437 MHZ
	7	2442 MHZ
	8	2447 MHZ
	9	2452 MHZ
	10	2457 MHZ
	11	2462 MHZ

Note: For 20MHZ bandwidth system use Channel 1 to Channel 11

For 802.11n 40MHZ bandwidth system use Channel 3 to Channel 9.

**1.3. IEEE 802.11N MODULATION SCHEME**

MCS Index	Nss	Modulation	R	NBPS	NCBPS		NDBPS		Data rate(Mbps)	
					800nsGI					
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPS	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval

1.4. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2ARILCM520-8AF** filing to comply with the FCC Part 15 requirements.



1.5. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013).

Radiated testing was performed at an antenna to EUT distance 3 meters.

Others testing (listed at item 5.3) was performed according to the procedures in FCC Part 15.247 rules KDB 558074 D01 DTS Meas Guidance v04.

1.6. SPECIAL ACCESSORIES

Refer to section 5.2.

1.7. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.



2. MEASUREMENT UNCERTAINTY

Test	Measurement Uncertainty	Notes
Transmitter power conducted	± 0.57 dB	(1)
Transmitter power Radiated	± 2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	± 2.20 dB	(1)
Occupied Bandwidth	± 0.01 ppm	(1)
Radiated Emission 30~1000MHz	± 4.10 dB	(1)
Radiated Emission Above 1GHz	± 4.32 dB	(1)
Conducted Disturbance 0.15~30MHz	± 3.20 dB	(1)

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



3. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal operating

Note:
Transmit by 802.11b with Data rate (1/2/5.5/11)
Transmit by 802.11g with Data rate (6/9/12/18/24/36/48/54)
Transmit by 802.11n (20MHz) with Data rate (6.5/13/19.5/26/39/52/58.5/65)
Transmit by 802.11n (40MHz) with Data rate (13.5/27/40.5/54/81/108/121.5/135)

Note:


1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency Individually, and the eut is operating at its maximum duty cycle>or equal 98%
2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.



4 SYSTEM TEST CONFIGURATION

4.1. CONFIGURATION OF EUT SYSTEM

Configure:



4.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Wireless Router	CM520-8AF	2ARILCM520-8AF	EUT
2	Adapter	CW0901500EU	DC 9.0V 1.5A	Accessory
3	Antenna	N/A	N/A	Accessory
4	Network Cable	N/A	N/A	Accessory
5	Network patch cable	N/A	N/A	Accessory

Note: All the accessories have been used during the test in conduction emission test.

4.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Output Power	Compliant
§15.247	6 dB Bandwidth	Compliant
§15.247	Conducted Spurious Emission	Compliant
§15.247	Maximum Conducted Output Power SPECTRAL Density	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Line Conduction Emission	Compliant



5. TEST FACILITY

Site	Shenzhen HUAKE Testing Technology Co., Ltd.
Location	1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China
Designation Number	CN1229
Test Firm Registration Number : 616276	

ALL TEST EQUIPMENT LIST

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power meter	Agilent	E4417B	HKE-107	Dec. 28, 2018
Power Sensor	Agilent	E9327A	HKE-113	Dec. 28, 2018
RF cable	Times	1-40G	HKE-034	Dec. 28, 2018
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 28, 2018
Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 28, 2018
RF Cable (9KHz-26.5GHz)	Tonscend	170660	N/A	Dec. 28, 2018
Signal generator	Agilent	N5183A	HKE-071	Dec. 28, 2018
Receiver	R&S	ESCI-7	HKE-010	Dec. 28, 2018
Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 28, 2018
Preamplifier	EMCI	EMC051845SE	HKE-015	Dec. 28, 2018
Preamplifier	Agilent	83051A	HKE-016	Dec. 28, 2018
Loop antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 28, 2018
Broadband antenna	Schwarzbeck	VULB 9163	HKE-012	Dec. 28, 2018
Horn antenna	Schwarzbeck	9120D	HKE-013	Dec. 28, 2018
Antenna Mast	Keleto	CC-A-4M	N/A	N/A
Position controller	Taiwan MF	MF7802	HKE-011	Dec. 28, 2018
Radiated test software	Tonscend	TS+ Rev 2.5.0.0	HKE-082	N/A
RF cable (9KHz-1GHz)	Times	381806-001	N/A	N/A
RF cable	Times	1-40G	HKE-034	Dec. 28, 2018



6. OUTPUT POWER

7.1. MEASUREMENT PROCEDURE


For max average conducted output power test:

1. Connect EUT RF output port to power probe through an RF attenuator.
2. Connect the power probe to the PC.
3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Record the maximum power from the software.

Note : The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

AVERAGE POWER SETUP





6.3. LIMITS AND MEASUREMENT RESULT

TEST ITEM	OUTPUT POWER
TEST MODE	802.11b with data rate 1

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	13.00	30	Pass
2.437	13.32	30	Pass
2.462	13.60	30	Pass

TEST ITEM	OUTPUT POWER
TEST MODE	802.11g with data rate 6

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	9.98	30	Pass
2.437	11.18	30	Pass
2.462	11.70	30	Pass

TEST ITEM	OUTPUT POWER
TEST MODE	802.11n 20 with data rate 6.5

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	9.90	30	Pass
2.437	11.09	30	Pass
2.462	11.68	30	Pass



TEST ITEM	OUTPUT POWER
TEST MODE	802.11n 40 with data rate 13.5

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.422	7.64	30	Pass
2.437	11.00	30	Pass
2.452	7.95	30	Pass




7. 6dB BANDWIDTH

7.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW \geq 3 \times RBW.
4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)









**8.3. LIMITS AND MEASUREMENT RESULTS**

Mode	Channel	6dB Bandwidth [MHz]	Verdict
11b	LCH	10.10	PASS
	MCH	10.09	PASS
	HCH	10.09	PASS
11g	LCH	15.16	PASS
	MCH	15.35	PASS
	HCH	15.35	PASS
11nHT20	LCH	15.16	PASS
	MCH	15.17	PASS
	HCH	15.33	PASS
11nHT40	LCH	35.24	PASS
	MCH	35.23	PASS
	HCH	35.24	PASS



Test Graph







9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW > RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW > RBW) are conform to the requirement.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2.

9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.



9.4. LIMITS AND MEASUREMENT RESULT



LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
<p>In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 30 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.</p> <p>In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a)</p>	<p>Refer Test Graph</p>	<p>PASS</p>



Test Graph



11B-LCH

11B-LCH




11B-LCH




11B-MCH



11B-MCH


11B-MCH









11G-MCH




11G-MCH




11G-MCH




11G-HCH



11G-HCH




11G-HCH







11nHT20-LCH




11nHT20-LCH




11nHT20-LCH




11nHT20-MCH



11nHT20-MCH





11nHT20-MCH







11nHT20-HCH

11nHT20-HCH





11nHT20-HCH

11nHT40-LCH



11nHT40-LCH



11nHT40-LCH







11nHT40-MCH

11nHT40-MCH





11nHT40-MCH

11nHT40-HCH



11nHT40-HCH

11nHT40-HCH





10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

10.1 MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of AVGPSD-1 in the ANSI C63.10 (2013) item 11.10 was used in this testing.

10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 8.2.

10.3 MEASUREMENT EQUIPMENT USED

Refer To Section 6.