# Prediction of MPE at a given distance

# 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
	(B) Limits for Gener	al Population/Uncontrolled	Exposure	
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

# 2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

#### 3. Result

### For Worst case Mode: 2.4G WIFI 2412-2462MHz

Maximum peak output power at antenna input terminal: 19.811 (dBm)

Maximum peak output power at antenna input terminal: 95.7

Antenna gain(typical): 2.5 (dBi)

Maximum antenna gain: 1.78 (numeric)

Prediction distance: 20 (cm)

Sourse Based Time Average Duty Cycle: 100 (%)

Prediction frequency: 2412 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm^2)

Power density at prediction frequency: <u>0.0338 (mW /cm^2)</u>

Power density at prediction frequency: <u>0.338 (W/m^2)</u>

Power density at a given distance is 0.0338<1 mW/cm<sup>2</sup>

## For Worst case Mode: 5G WIFI 5150-5252MHz and 5.745GHz-5.825GHz

Maximum peak output power at antenna input terminal: 12.05 (dBm)

Maximum peak output power at antenna input terminal: 16.03 (mW)

Antenna gain(typical): 2.5 (dBi)

Maximum antenna gain: 1.78 (numeric)

Prediction distance: 20 (cm)

Sourse Based Time Average Duty Cycle: 100 (%)

Prediction frequency: 5230 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm^2)

Power density at prediction frequency: 0.0057 (mW /cm^2)

Power density at prediction frequency: 0.057 (W/m^2)

Power density at a given distance is 0.0057<1 mW/cm^2

Some radios transmit simultaneously, and the max evaluated ratio value are as below:

For Worst case Mode

2.4G WiFi + 5G WiFi

Ratio: MPE<sub>2.4G WiFi</sub>/Limit<sub>above 1500 +</sub> MPE<sub>5G WiFi</sub> /Limit<sub>above 1500</sub> = **0.0395** 

 $(mW/cm^2) < 1 (mW/cm^2)$