


# VAP11G-300 Quick Setting Guide

## I. Connect Method:



## II. Set Network:

1. Power on VAP11G-300 (5V/1A) ;

2. Terminal device connect to VAP11G-300:

① Computer connect the network port of VAP11G-300 by wired;


② Or connect WiFi signal of VAP11G-300 by Smart phone and computer, its

parameters as below:


WiFi SSID: VONETS\_\*\*\*\*\*

WiFi password: 12345678


3. Open browser, input configured address: <http://vonets.cfg> ( or 192.168.251.254);




4. Input user name and password, both are admin, click "Login" to enter configured page:




5. “Scan Hotspots”, click the source WiFi hotspot, click “Next”;



6. Enter Source WiFi hotspot password, click “Apply”;



7. Click “Reboot”, VAP11G-300 will connect the configured WiFi hotspot automatically, if connected successfully, its blue light will quick flash.



### FCC warning:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance

could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

To maintain compliance with FCC's RF Exposure guidelines, This equipment should be installed and operated with minimum distance between 20cm the radiator your body: Use only the supplied antenna.

**FCC ID: 2ARNO-VAP11G-300**