

Report No.: BTL-FCCP-2-2005T134

0659

Maximum Permissible Exposure Report

FCC ID: 2ARP8-SG200

Report No. : BTL-FCCP-2-2005T134
Equipment : ZigBee Lighting Control Box

Model Name : SG200-C

Brand Name :

Lumani

Applicant : Lumani Pte Ltd

Address : 71 Ayer Rajah Crescent #02-10/11 Singapore 139951

Manufacturer : Billion Electric Co., Ltd.

Address : 8F., No.192, Sec. 2, Zhongxing Rd., Xindian Dist., New Taipei City 231,

Taiwan (R.O.C.)

According : FCC Guidelines for Human Exposure IEEE C95.1

Date of Receipt : 2020/5/28

Date of Test : 2020/5/28~ 2020/6/22

Issued Date : 2020/6/24

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by

Peter Chen, Engineer

Approved by : Scott Hsu , Manager

BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: www.newbtl.com



Report No.: BTL-FCCP-2-2005T134

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna

Table for Filed Antenna:

Ant.	Brand	Model	Туре	Connector	Gain (dBi)
1	M -gear	C942-510009-A	Dipole	SMA Plug Reverse	1.8

TEST RESULTS

Frequency (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	Maximum Conducted Output Power (dBm)	Maximum Conducted Output Power (mW)	Power Density	Limit of Power Density (S) (mW/cm²)
2405	1.8	1.5136	7.67	5.8479	0.0018	1.0000

NOTE: The calculated distance is 20 cm.

End of Test Report