



# TEST REPORT

**APPLICANT** : Shenzhen Jaguar Wave Technology LTD  
**PRODUCT NAME** : Wireless Gigabit Mobile Hotspot  
**MODEL NAME** : JW-MRD-6001  
**BRAND NAME** : JAGUAR WAVE/SUGAR lady  
**FCC ID** : 2ARPAJW-MRD-6001  
**STANDARD(S)** : 47 CFR Part 15 Subpart C  
**RECEIPT DATE** : 2019-08-02  
**TEST DATE** : 2019-08-09 to 2019-08-21  
**ISSUE DATE** : 2019-08-30

Edited by: Zeng Xiaoying  
Zeng Xiaoying (Rapporteur)  
Approved by: Peng Huarui  
Peng Huarui ( Supervisor )

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# DIRECTORY

- 1. Technical Information ..... 4
  - 1.1. Applicant and Manufacturer Information ..... 4
  - 1.2. Equipment Under Test (EUT) Description ..... 4
  - 1.3. Test Standards and Results ..... 7
  - 1.4. Environmental Conditions ..... 8
- 2. 47 CFR Part 15C Requirements ..... 9
  - 2.1. Antenna requirement ..... 9
  - 2.2. Duty Cycle Of Test Signal ..... 9
  - 2.3. Maximum Peak and Average Conducted Output Power ..... 13
  - 2.4. Bandwidth ..... 16
  - 2.5. Conducted Spurious Emissions and Band Edge ..... 25
  - 2.6. Power spectral density (PSD) ..... 38
  - 2.7. Conducted Emission ..... 47
  - 2.8. Restricted Frequency Bands ..... 51
  - 2.9. Radiated Emission ..... 63
- Annex A Test Uncertainty ..... 79
- Annex B Testing Laboratory Information ..... 80



<b>Change History</b>		
<b>Version</b>	<b>Date</b>	<b>Reason for change</b>
1.0	2019-08-30	First edition



# 1. Technical Information

Note: Provide by applicant.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	Shenzhen Jaguar Wave Technology LTD
<b>Applicant Address:</b>	Unit 1002/1003, Block 2A, Tongtai Times Center, No.6259 Baoan Road, Fuhai Street, Baoan District, Shenzhen City, P.R.China
<b>Manufacturer:</b>	Shenzhen Jaguar Wave Technology LTD
<b>Manufacturer Address:</b>	Unit 1002/1003, Block 2A, Tongtai Times Center, No.6259 Baoan Road, Fuhai Street, Baoan District, Shenzhen City, P.R.China

## 1.2. Equipment Under Test (EUT) Description

<b>Product Name:</b>	Wireless Gigabit Mobile Hotspot	
<b>Serial No:</b>	(N/A, marked #1 by test site)	
<b>Hardware Version:</b>	P1	
<b>Software Version:</b>	1.0.201810120116	
<b>Equipment type:</b>	WLAN2.4G	
<b>Modulation Type:</b>	DSSS, OFDM	
<b>Operating Frequency Range:</b>	802.11b/g/ n(HT20): 2.412GHz - 2.462GHz 802.11 n(HT40): 2.422GHz - 2.452GHz	
<b>Antenna Type:</b>	PIFA Antenna	
<b>Antenna Gain:</b>	Ant 0: -1.5 dBi; Ant 1: -1.5 dBi	
<b>Directional Gain:</b>	1.51 dBi <small>Note 3</small>	
<b>Accessory Information:</b>	Battery	
	<b>Brand Name:</b>	N/A
	<b>Model No.:</b>	JW-MRD-6001
	<b>Serial No.:</b>	(N/A, marked #1 by test site)
	<b>Capacity:</b>	4000mAh
	<b>Rated Voltage:</b>	3.85V
	<b>Charge Limit:</b>	4.40V



<b>Accessory Information:</b>	AC Adapter	
	Brand Name:	N/A
	Model No.:	TN-090200U1
	Serial No.:	(N/A, marked #1 by test site)
	Rated Output:	5V=3A or 9V=2A or 12V=1.5A
	Rated Input:	100-240V ~ 50/60Hz 0.5A

**Note 1:** We use the dedicated software to control the EUT continuous transmission.

**Note 2:** The EUT has two antennas, only 802.11n modulation mode supports a MIMO function.

<b>Modulation Mode:</b>	<b>TX Function</b>	<b>Relationship between the two output signals</b>
802.11b	1TX	Uncorrelated
802.11g	1TX	Uncorrelated
802.11n	2TX	Correlated

**Note 3:** According to KDB 662911 D01, the directional gain =  $G_{ANT} + 10\log(N_{ANT})$  dBi, where  $G_{ANT}$  is the maximum antenna gain in dBi,  $N_{ANT}$  is the number of outputs.

**Note 4:** For conducted test item Peak Power and Power spectral density of each modulation mode, we recorded the test result of two antennas separately, for other conducted test items both of the two antennas were tested separately, we only recorded the worst test result(Ant 0) in this report.

**Note 5:** All radiation test items for 802.11n modulation mode operate at MIMO mode during the test. Other modulation mode operate at SISO mode, both of the two antennas were tested separately, we only recorded the worst test result(Ant 0) in this report.

**Note 6:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

### 1.3. The channel number and frequency

Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
802.11b/g/ n(HT20)	<b>1</b>	<b>2412</b>	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	<b>11</b>	<b>2462</b>
	5	2432		
	<b>6</b>	<b>2437</b>		
	7	2442		
Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
n(HT40)	<b>3</b>	<b>2422</b>	8	2447
	4	2427	<b>9</b>	<b>2452</b>
	5	2432		
	<b>6</b>	<b>2437</b>		
	7	2442		

**Note1:** The Lowest Channel (1), Middle Channel (6) and Highest Channel (11) was selected test for 802.11b/g/n(HT20) mode;

**Note2:** The Lowest Channel (3), Middle Channel (6) and Highest Channel (9) was selected test for n(HT40) mode;



## 1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle Of Test Signal	Aug 09, 2019	Zhou Chuang	PASS	No deviation
3	15.247(b)	Maximum Peak and Average Conducted Output Power	Aug 21, 2019	Zhou Chuang	PASS	No deviation
4	15.247(a)	Bandwidth	Aug 09, 2019	Zhou Chuang	PASS	No deviation
5	15.247(d)	Conducted Spurious Emission and Band Edge	Aug 09, 2019	Zhou Chuang	PASS	No deviation
6	15.247(e)	Power spectral density (PSD)	Aug 14, 2019	Zhou Chuang	PASS	No deviation
7	15.207	Conducted Emission	Aug 18, 2019	Peng Xuewei	PASS	No deviation
8	15.247(d)	Restricted Frequency Bands	Aug 16, 2019	Peng Xuewei	PASS	No deviation
9	15.209, 15.247(d)	Radiated Emission	Aug 16, 2019	Peng Xuewei	PASS	No deviation

**Note1:** The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013, KDB558074 D01 v05r02 and KDB662911 D01 v02r01.

**Note2:** The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 12dB contains two parts that cable loss 2dB and Attenuator 10dB.

**Note 3:** Additions to, deviation, or exclusions from the method should be judged in the "method



determination" column of add, deviate or exclude from the specific method should be explained in the "Remark" of the above table.

## 1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106





## 2. 47 CFR Part 15C Requirements

### 2.1. Antenna requirement

#### 2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

### 2.2. Duty Cycle Of Test Signal


#### 2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than  $\pm 2\%$ ; otherwise, the duty cycle is considered to be nonconstant.

**2.2.2. Test Description**

**A. Test Set:**



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.


**2.2.3. Test Result**

**A. Test Verdict:**


Test Mode	Duty Cycle (%) (D)	Duty Factor ( $10 \cdot \lg[1/D]$ )
802.11b	99.04	0.04
802.11g	94.95	0.23
802.11n(HT20)	95.07	0.22
802.11n(HT40)	90.05	0.46




B. Test Plots




(Channel 1, 2412MHz, 802.11b)



(Channel 1, 2412MHz, 802.11g)



(Channel 1, 2412MHz, 802.11 n(HT20))



(Channel 3, 2422MHz, 802.11 n(HT40))

## 2.3. Maximum Peak and Average Conducted Output Power


### 2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

### 2.3.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

#### A. Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.





2.3.3. Test Result

Maximum Peak Conducted Output Power

802.11b Test Mode

Channel	Frequency (MHz)	Measured Peak Power				Limit (dBm)		Verdict
		ANT 0		ANT 1		dBm	W	
		dBm	W	dBm	W			
1	2412	<b>18.24</b>	<b>0.067</b>	17.78	0.060	30	1	PASS
6	2437	18.10	0.065	17.68	0.059			PASS
11	2462	18.21	0.066	<b>17.91</b>	<b>0.062</b>			PASS

802.11g Test mode

Channel	Frequency (MHz)	Measured Peak Power				Limit (dBm)		Verdict
		ANT 0		ANT 1		dBm	W	
		dBm	W	dBm	W			
1	2412	21.28	0.134	20.63	0.116	30	1	PASS
6	2437	<b>21.37</b>	<b>0.137</b>	20.58	0.114			PASS
11	2462	21.16	0.131	<b>20.76</b>	<b>0.119</b>			PASS

802.11n(HT20) Test mode

Channel	Frequency (MHz)	Measured Peak Power (dBm)		Total Power (W)	Total Power (dBm)	Limit		Verdict
		ANT 0	ANT 1			dBm	W	
1	2412	19.58	19.07	0.172	22.34	30	1	PASS
6	2437	19.51	18.98	0.168	22.26			PASS
11	2462	19.66	19.27	<b>0.177</b>	<b>22.48</b>			PASS

**Note:** Directional gain =  $-1.5\text{dBi} + 10\log(2) = 1.51\text{dBi} < 6\text{dBi}$ , so the power limit is 1W(30dBm).

802.11n(HT40) Test mode

Channel	Frequency (MHz)	Measured Peak Power (dBm)		Total Power (W)	Total Power (dBm)	Limit		Verdict
		ANT 0	ANT 1			dBm	W	
3	2422	20.14	19.74	<b>0.197</b>	<b>22.95</b>	30	1	PASS
6	2437	19.91	19.45	0.186	22.70			PASS
9	2452	19.90	19.41	0.185	22.67			PASS

**Note:** Directional gain =  $-1.5\text{dBi} + 10\log(2) = 1.51\text{dBi} < 6\text{dBi}$ , so the power limit is 1W(30dBm).



**Maximum Average Conducted Output Power**

**802.11b Test Mode**

Frequency (MHz)	Average Power							Limit		Verdict
	Measured		Duty Factor	Duty factor Calculated						
	ANT0	ANT1		ANT0		ANT1				
	dBm	dBm	dBm	W	dBm	W	dBm	W		
2412	15.58	15.18	0.04	15.62	0.036	15.22	0.033	30	1	PASS
2437	15.51	15.05		15.55	0.036	15.09	0.032			PASS
2462	15.59	15.28		<b>15.63</b>	<b>0.037</b>	<b>15.32</b>	<b>0.034</b>			PASS

**802.11g Test Mode**

Frequency (MHz)	Average Power							Limit		Verdict
	Measured		Duty Factor	Duty factor Calculated						
	ANT0	ANT1		ANT0		ANT1				
	dBm	dBm	dBm	W	dBm	W	dBm	W		
2412	15.07	14.58	0.23	<b>15.30</b>	<b>0.034</b>	14.81	0.030	30	1	PASS
2437	14.93	14.47		15.16	0.033	14.70	0.030			PASS
2462	15.04	14.73		15.27	0.034	<b>14.96</b>	<b>0.031</b>			PASS

**802.11 n(HT20) Test Mode**

Frequency (MHz)	Average Power						Limit		Verdict	
	Measured		Duty Factor	Total Power with Duty Factor						
	ANT0	ANT1		W		dBm				
	dBm	dBm	dBm	W	dBm	dBm	W			
2412	12.94	12.52	0.22	0.038		15.77		30	1	PASS
2437	12.90	12.38		0.037		15.68				PASS
2462	12.94	12.61		<b>0.038</b>		<b>15.81</b>				PASS

**Note:** Directional gain =  $-1.5\text{dBi} + 10\log(2) = 1.51\text{dBi} < 6\text{dBi}$ , so the power limit is 1W(30dBm).

**802.11 n(HT40) Test Mode**

Frequency (MHz)	Average Power						Limit		Verdict	
	Measured		Duty Factor	Total Power with Duty Factor						
	ANT0	ANT1		W		dBm				
	dBm	dBm	dBm	W	dBm	dBm	W			
2422	13.08	12.66	0.46	0.039		15.94		30	1	PASS
2437	13.07	12.55		0.039		15.88				PASS
2452	13.39	12.50		<b>0.040</b>		<b>16.03</b>				PASS

**Note:** Directional gain =  $-1.5\text{dBi} + 10\log(2) = 1.51\text{dBi} < 6\text{dBi}$ , so the power limit is 1W(30dBm).


## 2.4. Bandwidth

### 2.4.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 2.4.2. Test Description

#### A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

### 2.4.3. Test procedure

KDB 558074 Section 8.2 was used in order to prove compliance.





2.4.4. Test Result

802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	8.064	≥500	PASS
6	2437	8.063	≥500	PASS
11	2462	8.064	≥500	PASS

B. Test Plots



(Channel 1, 802.11b)



(Channel 6, 802.11b)



(Channel 11, 802.11b)



**802.11g Test mode**

**A. Test Verdict:**

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.29	≥500	PASS
6	2437	16.27	≥500	PASS
11	2462	16.08	≥500	PASS

**B. Test Plots:**



(Channel 1, 802.11g)





(Channel 6, 802.11g)



(Channel 11, 802.11g)




802.11n(HT20) Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.81	≥500	PASS
6	2437	17.16	≥500	PASS
11	2462	17.16	≥500	PASS


B. Test Plots:



(Channel 1, 802.11n(HT20))



(Channel 6, 802.11n(HT20))



(Channel 11, 802.11n(HT20))






802.11n(HT40) Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
3	2422	35.15	≥500	PASS
6	2437	35.74	≥500	PASS
9	2452	35.72	≥500	PASS


B. Test Plots:



(Channel 3, 802.11n(HT40))



(Channel 6, 802.11n(HT40))



(Channel 9, 802.11n(HT40))




## 2.5. Conducted Spurious Emissions and Band Edge

### 2.5.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 2.5.2. Test Description

#### A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

### 2.5.3. Test procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.




2.5.4. Test Result

802.11b Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-43.09	8.35	-11.65	PASS
6	2437	-44.04	8.34	-11.66	PASS
11	2462	-43.13	8.41	-11.59	PASS


B. Test Plots:



(Channel = 1, 30MHz to 25GHz)



(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)





(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-44.09	1.26	-18.74	PASS
6	2437	-44.63	2.57	-17.43	PASS
11	2462	-43.51	4.82	-15.18	PASS


B. Test Plots:



(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)





(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




802.11n(HT20) Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-44.10	2.62	-17.38	PASS
6	2437	-44.19	0.90	-19.10	PASS
11	2462	-49.19	-2.35	-22.35	PASS

B. Test Plots:




(Channel = 1, 30MHz to 25GHz)






(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




802.11n(HT40) Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
3	2422	-42.19	0.74	-19.26	PASS
6	2437	-43.90	-2.18	-22.18	PASS
9	2452	-49.17	-4.10	-24.10	PASS

B. Test Plots:




(Channel = 3, 30MHz to 25GHz)






(Band Edge, Channel = 3)



(Channel = 6, 30MHz to 25GHz)



(Channel = 9, 30MHz to 25GHz)



(Band Edge, Channel = 9)


## 2.6. Power spectral density (PSD)

### 2.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### 2.6.2. Test Description

#### A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

### 2.6.3. Test procedure

KDB 558074 Section 8.4 was used in order to prove compliance.





2.6.4. Test Result

802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)		Limit (dBm/3kHz)	Verdict
		ANT 0	ANT 1		
1	2412	6.03	5.40	8	PASS
6	2437	3.36	6.81	8	PASS
11	2462	5.92	2.97	8	PASS

B. Test Plots:



(Channel = 1, 802.11b, ANT 0)



(Channel = 6, 802.11b, ANT 0)



(Channel = 11, 802.11b, ANT 0)






802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)		Limit (dBm/3kHz)	Verdict
		ANT 0	ANT 1		
1	2412	-10.67	-10.41	8	PASS
6	2437	-11.13	-10.10	8	PASS
11	2462	-10.13	-11.30	8	PASS


B. Test Plots:



(Channel = 1, 802.11g, ANT 0)



(Channel = 6, 802.11g, ANT 0)



(Channel = 11, 802.11g, ANT 0)




**802.11n(HT20) Test mode**

**A. Test Verdict:**

Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
		ANT 0	ANT 1			
1	2412	-12.24	-12.11	-9.16	8	PASS
6	2437	-11.35	-12.78	-9.00	8	PASS
11	2462	-11.46	-13.11	-9.20	8	PASS


**Note:** Directional gain =  $-1.5\text{dBi} + 10\log(2) = 1.51\text{dBi} < 6\text{dBi}$ , so the power limit is 8 dBm/3kHz.

**B. Test Plots:**




(Channel = 1, 802.11n(HT20), ANT0)





(Channel = 6, 802.11n(HT20), ANT0)



(Channel = 11, 802.11n(HT20), ANT0)


**802.11n(HT40) Test mode**

**A. Test Verdict:**


Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
		ANT 0	ANT 1			
3	2422	-13.95	-15.20	-11.52	8	PASS
6	2437	-13.48	-14.89	-11.12	8	PASS
9	2452	-14.16	-14.70	-11.41	8	PASS

**Note:** Directional gain =  $-1.5\text{dBi} + 10\log(2) = 1.51\text{dBi} < 6\text{dBi}$ , so the power limit is 8 dBm/3kHz.


**B. Test Plots:**



(Channel = 3, 802.11n(HT40))



(Channel = 6, 802.11n(HT40))



(Channel = 9, 802.11n(HT40))

## 2.7. Conducted Emission

### 2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

**NOTE:**

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 2.7.2. Test Description

#### A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.



### 2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

**Note:** Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

#### A. Test setup:

Test Mode: EUT+ADAPTOR + WIFI TX

Test Voltage: AC 120V/60Hz

The measurement results are obtained as below:


$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

$U_R$ : Receiver Reading

$A_{\text{Factor}}$ : Voltage division factor of LISN




**B. Test Plots:**



(L Phase)

NO.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1815	44.71	33.14	64.42	54.42	Line	PASS
2	0.4242	41.67	32.10	57.37	47.37		PASS
3	0.5236	45.32	36.45	56.00	46.00		PASS
4	0.6270	44.68	35.50	56.00	46.00		PASS
5	0.9008	40.52	30.54	56.00	46.00		PASS
6	2.1293	41.91	31.50	56.00	46.00		PASS



(N Phase)

NO.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1502	49.03	35.66	65.99	55.99	Neutral	PASS
2	0.4157	43.52	35.57	57.53	47.53		PASS
3	0.5774	47.35	37.99	56.00	46.00		PASS
4	0.6175	47.55	38.85	56.00	46.00		PASS
5	2.1043	45.80	37.11	56.00	46.00		PASS
6	8.8128	43.58	34.96	60.00	50.00		PASS


## 2.8. Restricted Frequency Bands

### 2.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 2.8.2. Test Description

#### A. Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

**2.8.3. Test procedure**

KDB 558074 Section 8.6 and 8.7 was used in order to prove compliance.

**2.8.4. Test Result**

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m


**Note:** Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

**802.11b Test mode****A. Test Verdict:**


Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dBuV)	$A_T$ (dB)	$A_{\text{Factor}}$ (dB@3m)	Max. Emission E (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Verdict
		PK/ AV						
1	2385.21	PK	48.27	-29.67	32.56	51.16	74	PASS
1	2388.73	AV	47.79	-29.67	32.56	50.68	54	PASS
11	2485.45	PK	47.67	-29.67	32.56	50.56	74	PASS
11	2485.07	AV	47.29	-29.67	32.56	50.18	54	PASS



B. Test Plots:




(Channel = 1 PEAK, 802.11b)



(Channel = 1 AVG, 802.11b)





(Channel = 11 PEAK, 802.11b)



(Channel = 11 AVG, 802.11b)




802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading	A <sub>T</sub> (dB)	A <sub>Factor</sub> (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV	U <sub>R</sub> (dBuV)					
1	2383.02	PK	47.90	-29.67	32.56	50.79	74	PASS
1	2380.56	AV	46.39	-29.67	32.56	49.28	54	PASS
11	2484.33	PK	46.98	-29.67	32.56	49.87	74	PASS
11	2484.17	AV	46.16	-29.67	32.56	49.05	54	PASS


B. Test Plots:




(Channel = 1 PEAK, 802.11g)



(Channel = 1 AVG, 802.11g)



(Channel = 11 PEAK, 802.11g)



(Channel = 11 AVG, 802.11g)


**802.11 n(HT20) Test mode**

**A. Test Verdict:**


Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dBμV)	$A_T$ (dB)	$A_{Factor}$ (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2387.62	PK	47.80	-29.67	32.56	50.69	74	PASS
1	2387.06	AV	46.54	-29.67	32.56	49.43	54	PASS
11	2484.83	PK	47.29	-29.67	32.56	50.18	74	PASS
11	2484.27	AV	47.31	-29.67	32.56	50.20	54	PASS



B. Test Plots:




(Channel = 1 PEAK, 802.11n(HT20))




(Channel = 1 AVG, 802.11n(HT20))





(Channel = 11 PEAK, 802.11n(HT20))



(Channel = 11 AVG, 802.11n(HT20))




802.11n(HT40) Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading	$A_T$	$A_{Factor}$	Max. Emission	Limit	Verdict
		PK/ AV	$U_R$ (dBuV)	(dB)	(dB@3m)	E (dBμV/m)	(dBμV/m)	
3	2377.04	PK	47.67	-29.67	32.56	50.56	74	PASS
3	2387.39	AV	48.12	-29.67	32.56	51.01	54	PASS
9	2484.73	PK	47.38	-29.67	32.56	50.27	74	PASS
9	2483.99	AV	47.09	-29.67	32.56	49.98	54	PASS


B. Test Plots:




(Channel = 3 PEAK, 802.11n(HT40))



(Channel = 3 AVG, 802.11n(HT40))



(Channel = 9 PEAK, 802.11n(HT40))



(Channel = 9 AVG, 802.11n(HT40))





## 2.9. Radiated Emission

### 2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.


For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.9.2. Test Description

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



## 3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading



For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

### 2.9.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m

During the test, the total correction Factor  $A_T$  and  $A_{\text{Factor}}$  were built in test software.


**Note1:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

**Note2:** For the frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Note3:** For the frequency, which started from 25GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


**802.11b Test mode**

**Plots for Channel = 1**



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	27.96	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
158.686	30.81	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2450.180	46.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4823.604	49.17	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8405.456	46.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12684.634	47.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
42.140	28.15	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
271.589	25.79	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2449.540	46.86	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4823.900	51.71	N/A	47.50	74.00	N/A	54.00	Vertical	PASS
7999.382	47.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10419.022	47.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




Plot for Channel = 6



Fre. (MHz)	Pk (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
34.856	29.99	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
156.258	31.24	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2105.082	45.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4874.013	47.30	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5644.153	47.21	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9133.588	46.71	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
43.354	29.12	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
2097.399	46.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4874.100	53.94	N/A	51.16	74.00	N/A	54.00	Vertical	PASS
5700.164	47.38	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8385.852	47.30	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13608.802	47.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.070	30.15	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
158.686	30.50	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2452.741	46.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4924.423	48.21	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8467.067	46.88	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12323.368	47.15	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	29.50	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
299.512	25.50	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2390.576	47.99	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4923.900	53.30	N/A	50.23	74.00	N/A	54.00	Vertical	PASS
8951.555	47.88	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12541.808	47.75	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




**802.11g Test mode**

Plots for Channel = 1




(Antenna Horizontal, 30MHz to 25GHz)




(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
42.140	27.92	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
152.616	29.96	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2495.638	46.20	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4526.750	45.98	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5669.358	47.25	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11735.261	47.14	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	29.14	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
310.438	27.25	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2489.876	45.93	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5730.969	46.80	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8539.880	46.80	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13059.902	47.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
38.498	29.64	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
104.055	26.26	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2041.697	46.14	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4733.988	46.27	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5602.146	46.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12144.135	47.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
37.284	28.57	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
99.199	25.40	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2411.124	46.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3202.109	46.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4921.622	47.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8951.555	47.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




**802.11n(HT20) Test mode**

Plots for Channel = 1




(Antenna Horizontal, 30MHz to 25GHz)




(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Antenna Horizontal, 30MHz to 25GHz)




(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	29.24	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
156.258	30.70	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2073.709	45.20	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4535.152	46.36	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5781.378	46.83	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12194.544	47.17	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	30.09	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
287.372	25.95	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2487.955	46.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4507.147	46.16	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5716.967	47.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9074.777	47.54	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

**802.11n(HT40) Test mode**

Plots for Channel = 3




(Antenna Horizontal, 30MHz to 25GHz)




(Antenna Vertical, 30MHz to 25GHz)

Plots for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
44.568	28.62	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
162.328	27.40	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2411.765	46.95	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5686.161	47.08	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8845.135	46.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12116.130	47.47	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	28.99	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
306.796	27.10	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2451.461	46.83	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5221.277	45.18	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7920.967	46.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13972.868	47.53	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




Plots for Channel = 9



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	29.29	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
198.748	27.33	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2197.279	45.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4451.137	45.86	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8934.752	46.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13107.510	46.93	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	29.59	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
95.557	26.01	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2406.002	46.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4507.147	46.43	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7876.159	46.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12914.275	47.76	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)



## Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power spectral density (PSD)	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{ dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$



## Annex B Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

<b>Laboratory Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
<b>Laboratory Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
<b>Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



#### 4. Test Equipments Utilized

##### 4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Attenuator 1	(N/A.)	10dB	Resnet	N/A	N/A
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2019.04.09	2020.04.08
USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2019.04.16	2020.04.15
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

##### 4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY56400093	N9038A	KEYSIGHT	2019.05.08	2020.05.09
LISN	812744	NSLK 8127	Schwarzbeck	2019.05.08	2020.05.09
Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2019.05.08	2020.05.09
Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A

##### 4.3 List of Software Used

Description	Manufacturer	Software Version
Test system	Tonscend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V 1.0

**4.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY54130016	N9038A	Agilent	2018.08.04	2019.08.03
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2019.05.08	2020.05.09
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2019.02.15	2020.02.14
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2018.08.06	2019.08.05
Test Antenna – Horn	BBHA9170 #774	BBHA9170	Schwarzbeck	2018.08.02	2019.08.01
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2018.12.01	2019.11.30
Anechoic Chamber	N/A	9m*6m*6m	CRT	2017.11.19	2020.11.18

————— END OF REPORT —————