



# RF EXPOSURE EVALUATION REPORT

**APPLICANT** : Shenzhen Jaguar Wave Technology LTD  
**PRODUCT NAME** : Outdoor 60GHz PTP  
**MODEL NAME** : JW-PTP6030  
**BRAND NAME** : JAGUAR WAVE  
**FCC ID** : 2ARPAJW-PTP6030  
**STANDARD(S)** : 47CFR 2.1091  
KDB 447498  
**RECEIPT DATE** : 2020-09-15  
**TEST DATE** : 2020-10-19 to 2020-10-26  
**ISSUE DATE** : 2021-02-02

Edited by: *Gan Yueming*  
Gan Yueming (Rapporteur)

Approved by: *Peng Huarui*  
Peng Huarui (Supervisor)

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# DIRECTORY

- 1. Technical Information..... 3
  - 1.1 Applicant and Manufacturer Information..... 3
  - 1.2 Equipment under Test (EUT) Description..... 3
  - 1.3 Applied Reference Documents ..... 4
- 2. Device Category and RF Exposure Limit ..... 5
- 3. RF Output Power ..... 6
- 4. RF Exposure Assessment..... 7
- Annex A General Information..... 8

Change History		
Version	Date	Reason for Change
1.0	2021-02-02	First edition



# 1. Technical Information

**Note:** Provide by applicant.

## 1.1 Applicant and Manufacturer Information

<b>Applicant:</b>	Shenzhen Jaguar Wave Technology LTD
<b>Applicant Address:</b>	Unit 1002/1003, Block 2A, Tongtai Times Center, No.6259 Baoan Road, Fuhai Street, Baoan District, Shenzhen City, P.R.China
<b>Manufacturer:</b>	Shenzhen Jaguar Wave Technology LTD
<b>Manufacturer Address:</b>	Unit 1002/1003, Block 2A, Tongtai Times Center, No.6259 Baoan Road, Fuhai Street, Baoan District, Shenzhen City, P.R.China

## 1.2 Equipment under Test (EUT) Description

<b>Product Name:</b>	Outdoor 60GHz PTP
<b>Hardware Version:</b>	V2.1
<b>Software Version:</b>	1.0.20200903175528
<b>Transmitting Frequency:</b>	WLAN 60GHz: 58.32 GHz ~ 64.80 GHz
<b>Modulation Type:</b>	802.11ad: PHY
<b>Data Rate:</b>	MCS1 ~ MCS9
<b>Antenna Gain:</b>	25dBi

**Note:**

When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% risk level.



### 1.3 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title	Method determination /Remark
1	47 CFR§2.1091	Radio Frequency Radiation Exposure Assessment: mobile devices	No deviation
2	KDB 447498 D01v06	General RF Exposure Guidance	No deviation

**Note 1:** The test item is not applicable.

**Note 2:** Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.



## 2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

### Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

### General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

**Table 1—Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz\* = Plane-wave equivalent power density



### 3. RF Output Power

#### <WLAN 60GHz>

	Mode	Data Rate	Channel	Frequency (MHz)	Average power(dBm)	Tune-up Power
WLAN 60GHz	802.11ad	MCS1	CH 1	58.32	<b>7.99</b>	<b>8.5</b>
			CH 2	60.48	5.77	6.0
			CH 4	64.80	3.16	4.0

**Note:**

1. According to KDB 447498 Section 4.3, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. The output power of 60GHz WLAN is derived from the report 2009RSU045-U1.

## 4. RF Exposure Assessment

### ➤ Standalone Transmission Assessment:

Bands	Frequency (MHz)	Tune-up Power(dBm)	Antenna Gain(dBi)	EIRP (mW)	Power Density (mW/cm <sup>2</sup> )	Limit for MPE (mW/cm <sup>2</sup> )
WLAN 60GHz	58.32	8.5	25.0	2238.72	0.446	1.0

### Note:

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

2. MPE calculate method

$$\text{Power Density} = \text{EIRP}/4\pi R^2$$

Where: EIRP = P+G

P = Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)

### ➤ Simultaneous Transmission Assessment:

This device only incorporates a WLAN 60GHz transmitter, Therefore simultaneous SAR assessment is not required.

### ➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



## Annex A General Information

### 1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

### 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

The FCC designation number is CN1192, the test firm registration number is 226174.

————— END OF REPORT —————