


EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	21.8°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Vertical




No.	Mk	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	31.3992	29.33	7.21	36.54	40.00	-3.46	peak
2	!	43.3534	25.85	9.51	35.36	40.00	-4.64	peak
3		72.0841	21.77	11.66	33.43	40.00	-6.57	peak
4	!	81.2116	25.25	9.94	35.19	40.00	-4.81	peak
5		120.2766	24.18	12.97	37.15	43.50	-6.35	peak
6		146.3735	24.85	12.58	37.43	43.50	-6.07	peak

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

- 2. The "Factor" value can be calculated automatically by software of measurement system.
- 3. All test modes had been pre-tested. The 802.11b at low channel is the worst case and recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Dedicated Psychological Psycholo






Radiated emission above 1GHz

EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Tree
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4824.000	51.46	0.08	51.54	74	-22.46	peak
4824.000	45.21	0.08	45.29	54	-8.71	AVG
7236.000	48.76	2.21	50.97	74	-23.03	peak
7236.000	41.67	2.21	43.88	54	-10.12	AVG
			@			69
emark:			20	8		
actor = Anter	nna Factor + Cab	le Loss – Pre-a	amplifier.			®

EUT	UT Smart Ambient Light Bar Model		SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Vertical

(dBµV)	(4D)				I Valua Tima
	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
50.81	0.08	50.89	74	-23.11	peak
44.55	0.08	44.63	54	-9.37	AVG
47.62	2.21	49.83	74	-24.17	peak
40.54	2.21	42.75	54	-11.25	AVG
60	· · · · · · · · · · · · · · · · · · ·				8
	G ^C				100
	44.55 47.62 40.54	44.55 0.08 47.62 2.21 40.54 2.21	44.55 0.08 44.63 47.62 2.21 49.83 40.54 2.21 42.75	44.55 0.08 44.63 54 47.62 2.21 49.83 74	44.55 0.08 44.63 54 -9.37 47.62 2.21 49.83 74 -24.17 40.54 2.21 42.75 54 -11.25



g/Inspection The test results




EUT	Smart Ambient Light Bar	Model Name	SCAL001	
Temperature	25°C	Relative Humidity	60%	
Pressure	960hPa	Test Voltage	Normal Voltage	
Test Mode	802.11b with date rate 1 2437MHz	Antenna	Horizontal	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4874.000	52.34	0.14	52.48	74	-21.52	peak
4874.000	45.28	0.14	45.42	54	-8.58	AVG
7311.000	49.55	2.36	51.91	74	-22.09	peak
7311.000	42.77	2.36	45.13	54	-8.87	AVG
-66		8				8
temark:						20
actor = Anter	na Factor + Cable	Loss – Pre	amplifier.	@		

Fastan Automos I	Fastan (Oslala	Lana Dan amariffan
Factor = Antenna I	Factor + Cable	Loss – Pre-amplifier.

EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHz	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Time
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4874.000	51.36	0.14	51.5	74	-22.5	peak
4874.000	46.07	0.14	46.21	54	-7.79	AVG
7311.000	48.76	2.36	51.12	74	-22.88	peak
7311.000	42.16	2.36	44.52	54	-9.48	AVG
	@				©	
	L - C -	•			U ,	
mark:						





EUT	Smart Ambient Light Bar	Model Name	SCAL001	
Temperature	25°C	Relative Humidity	60%	
Pressure	960hPa	Test Voltage	Normal Voltage	
Test Mode	802.11b with date rate 1 2462MHz	Antenna	Horizontal	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Time
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4924.000	52.64	0.22	52.86	74	-21.14	peak
4924.000	44.67	0.22	44.89	54	-9.11	AVG
7386.000	49.27	2.64	51.91	74	-22.09	peak
7386.000	40.65	2.64	43.29	54	-10.71	AVG
<u>,C</u>			1,04		8	
emark:						

EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHz	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4924.000	52.72	0.22	52.94	74	-21.06	peak
4924.000	46.03	0.22	46.25	54	-7.75	AVG
7386.000	48.61	2.64	51.25	74	-22.75	peak
7386.000	43.48	2.64	46.12	54	-7.88	AVG
@						

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Emission Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been pre-tested. The 802.11b mode is the worst case and recorded in the report.



Test result for band edge emission at restricted bands

EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHz	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated restriction Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement





EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHz	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement






EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement






EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHz	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement






EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHz	Antenna	Vertical

Test Graph for Peak Measurement




Test Graph for Average Measurement






EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHz	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated restriction Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement






EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n20 with data rate 6.5 2412MHz	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement






EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n20 with data rate 6.5 2412MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement





EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n20 with data rate 6.5 2462MHz	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement






EUT	Smart Ambient Light Bar	Model Name	SCAL001
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n20 with data rate 6.5 2462MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement





12. LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST


F	Maximum RF Line Voltage			
Frequency	Q.P (dBμV)	Average (dBμV)		
150kHz~500kHz	66-56	56-46		
500kHz~5MHz	56	46		
5MHz~30MHz	60	50		

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST







12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 Ohm load; the second scan had Line 1 connected to a 50 Ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case was reported on the Summary Data page.



12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



MEASUREMENT RESULT: "agc fin"

2022/1/14 1:0 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.666000	44.80	5.4	56	11.2	QP	L1	GND
2.006000	47.80	6.5	56	8.2	QP	L1	GND
21.398000	47.30	8.9	60	12.7	QP	L1	GND
22.090000	45.40	9.0	60	14.6	QP	L1	GND
22.754000	47.30	9.0	60	12.7	QP	L1	GND
24.090000	48.50	9.1	60	11.5	QP	L1	GND

MEASUREMENT RESULT: "agc fin2"


2022/1/14 Frequency MH:		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.63400 0.66600 2.00600 3.34600 4.01400	0 35.40 0 37.40 0 35.20	5.4 5.4 6.5 6.5	46 46 46 46	12.7 10.6 8.6 10.8 8.9	AV AV AV AV	L1 L1 L1 L1	GND GND GND GND GND
4.68600	34.80	6.6	46	11.2	AV	L1	GND

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



Line Conducted Emission Test Line 2-N



MEASUREMENT RESULT: "agc fin"


2022/1/14 1:04 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
21.418000	55.90	8.9	60	4.1	QP	N	GND
22.082000	54.60	9.0	60	5.4	QP	N	GND
22.754000	55.70	9.0	60	4.3	QP	N	GND
23.422000	51.20	9.1	60	8.8	QP	N	GND
24.090000	55.30	9.1	60	4.7	QP	N	GND
24.766000	54.60	9.1	60	5.4	QP	N	GND

MEASUREMENT RESULT: "agc fin2"

2022/1/14 1:04 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
1.338000 2.010000 2.678000 4.018000	34.80 37.40 32.20 36.60	5.9 6.5 6.5 6.5	46 46 46 46	11.2 8.6 13.8 9.4	AV AV AV	N N N	GND GND GND GND
4.682000 6.694000	34.40 37.70	6.6 6.7	46 50	11.6 12.3	AV AV	N N	GND GND

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated restriction. Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC09264220101AP02

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC09264220101AP03

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.