

# TEST REPORT

Reference No..... : WTX22X11236923W001  
FCC ID ..... : 2ARPVRB-SGA-054  
Applicant ..... : Kool Brands, LLC.  
Address..... : P.O. Box 41270, Reno, NV 89504  
Manufacturer ..... : Innex, Inc  
Address..... : 2/F, Bld#10, TongFuYu Industrial park, Lezhujiao, Xixiang, Ban'an,  
Shenzhen, China  
Product Name ..... : SEGA Genesis BIG6 Wireless Arcade Pad 8 Button - 2.4GHz  
Model No..... : RB-SGA-054  
Standards ..... : FCC Part 15.249  
Date of Receipt sample .... : 2022-11-24  
Date of Test..... : 2022-11-24 to 2022-12-07  
Date of Issue ..... : 2022-12-07  
Test Report Form No. .... : WTX\_Part 15\_249W  
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

**Prepared By:**


**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Approved by:



Mike Shi

Silin Chen

## **TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY .....	5
1.4 TEST FACILITY .....	5
1.5 EUT SETUP AND TEST MODE .....	6
1.6 MEASUREMENT UNCERTAINTY.....	7
1.7 TEST EQUIPMENT LIST AND DETAILS .....	8
<b>2. SUMMARY OF TEST RESULTS.....</b>	<b>11</b>
<b>3. ANTENNA REQUIREMENTS .....</b>	<b>12</b>
3.1 STANDARD APPLICABLE .....	12
3.2 TEST RESULT.....	12
<b>4. RADIATED EMISSIONS .....</b>	<b>13</b>
4.1 STANDARD APPLICABLE .....	13
4.2 TEST PROCEDURE .....	13
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	16
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	16
<b>5. OUT OF BAND EMISSIONS .....</b>	<b>21</b>
5.1 STANDARD APPLICABLE .....	21
5.2 TEST PROCEDURE .....	21
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	21
<b>6. EMISSION BANDWIDTH.....</b>	<b>26</b>
6.1 STANDARD APPLICABLE .....	26
6.2 TEST PROCEDURE .....	26
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	26
<b>7. DUTY CYCLE .....</b>	<b>28</b>
7.1 STANDARD APPLICABLE .....	28
7.2 TEST PROCEDURE .....	28
7.3 SUMMARY OF TEST RESULTS/PLOTS.....	28
<b>8. CONDUCTED EMISSIONS .....</b>	<b>32</b>
8.1 TEST PROCEDURE .....	32
8.2 BASIC TEST SETUP BLOCK DIAGRAM .....	32
8.3 TEST RECEIVER SETUP .....	32
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	32
<b>APPENDIX PHOTOGRAPHS.....</b>	<b>35</b>

**Report version**

Version No.	Date of issue	Description
Rev.00	2022-12-07	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	SEGA Genesis BIG6 Wireless Arcade Pad 8 Button - 2.4GHz
Trade Name:	Retro-Bit
Model No.:	RB-SGA-054
Adding Model(s):	RB-SGA-091, RB-SGA-092, RB-SGA-093, RB-SGA-094, RB-SGA-095, RB-SGA-096, RB-SGA-097, RB-SGA-098, RB-SGA-099
Rated Voltage:	Charging Port: DC 5V Battery:DC3.7V
Battery Capacity	500mAh
Power Adapter Model:	/
<p><i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model RB-SGA-054, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Frequency Range:	2410MHz-2470MHz
Max. Field Strength:	101.65dBuV/m
Modulation:	GFSK
Quantity of Channels:	31
Channel Separation:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	1.5dBi
<p><i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i></p>	

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.249:** Operation within the bands 902-928MHz, 2400-2483.5MHz, 5725-5875MHz, and 24.0-24.25GHz.

**ANSI C63.10-2013:** American National Standard for Testing Unlicensed Wireless Devices.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

### 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest

possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2410MHz
TM2	Middle Channel	2440MHz
TM3	High Channel	2470MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Type-C CABLE	1.20	Shielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Computer	Lenovo	L13 Yoga	/

### 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-26GHz ±3.92dB

**1.7 Test Equipment List and Details**

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
SEMT-1075	Communication Tester	Rohde & Schwarz	CMW500	148650	2022-03-22	2023-03-21
SEMT-1063	GSM Tester	Rohde & Schwarz	CMU200	114403	2022-03-22	2023-03-21
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2022-03-25	2023-03-24
SEMT-1079	Spectrum Analyzer	Agilent	N9020A	US47140102	2022-03-22	2023-03-21
SMET-1313	Spectrum Analyzer	Agilent	N9020A	MY54320548	2022-03-22	2023-03-21
SEMT-1080	Signal Generator	Agilent	83752A	3610A01453	2022-03-22	2023-03-21
SEMT-1081	Vector Signal Generator	Agilent	N5182A	MY47070202	2022-03-22	2023-03-21
SEMT-1028	Power Divider	Weinschel	1506A	PM204	2022-03-22	2023-03-21
SEMT-1082	Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2022-03-22	2023-03-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	/	/
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	/	/
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	/	/
SEMT-C004	Cable	Zheng DI	2M0RFC	/	/	/
SEMT-C005	Cable	Zheng DI	1M0RFC	/	/	/
SEMT-C006	Cable	Zheng DI	1M0RFC	/	/	/
<input checked="" type="checkbox"/> Chamber A: Below 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2022-01-07	2023-01-06
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2023-03-19
SEMT-1068	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2021-03-20	2023-03-19
<input checked="" type="checkbox"/> Chamber A: Above 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21



SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2022-03-22	2023-03-21
SEMT-1042	Horn Antenna	ETS	3117	00086197	2021-03-19	2023-03-18
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2021-04-27	2023-04-26
SEMT-1216	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2022-03-25	2023-03-24
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2022-03-22	2023-03-21
<input type="checkbox"/> Chamber B:Below 1GHz						
SEMT-1068	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2023-04-08
SEMT-1067	Amplifier	Agilent	8447D	2944A10179	2022-03-22	2023-03-21
SEMT-1066	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2022-03-22	2023-03-21
<input type="checkbox"/> Chamber C:Below 1GHz						
SEMT-1319	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2022-01-07	2023-01-06
SEMT-1343	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2023-05-27
SEMT-1333	Amplifier	HP	8447F	2944A03869	2022-03-22	2023-03-21
<input checked="" type="checkbox"/> Conducted Room 1#						
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2022-03-21	2023-03-20
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2022-03-25	2023-03-24
SEMT-1003	AC LISN	Schwarz beck	NSLK8126	8126-224	2022-03-22	2023-03-21
<input type="checkbox"/> Conducted Room 2#						
SEMT-1334	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2022-03-22	2023-03-21
SEMT-1336	LISN	Rohde & Schwarz	ENV 216	100097	2022-03-22	2023-03-21

<b>Software List</b>			
<b>Description</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Version</b>
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing.

## 2. SUMMARY OF TEST RESULTS

---

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.209(a)(f)	Radiated Spurious Emissions	Compliant
§15.249(a)	Field Strength of Emissions	Compliant
§15.249(d)	Out of Band Emission	Compliant
§15.215(c)	Emission Bandwidth	Compliant

N/A: Not applicable.

### **3. Antenna Requirements**

---

#### **3.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **3.2 Test Result**

This product has a PCB antenna, fulfill the requirement of this section.

## 4. Radiated Emissions

---

### 4.1 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 4.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz  
 RBW=10KHz,  
 VBW =30KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak

Frequency :30MHz-1GHz  
 RBW=120KHz,  
 VBW=300KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, QP

Frequency :Above 1GHz  
 RBW=1MHz,  
 VBW=3MHz(Peak), 10Hz(AV)  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, AV

### 4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$


### 4.4 Summary of Test Results/Plots

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*




➤ Spurious Emissions Below 1GHz

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	46.3402	26.56	-7.24	19.32	40.00	-20.68	-	-	peak
2	69.8450	29.67	-11.05	18.62	40.00	-21.38	-	-	peak
3	108.2667	27.03	-8.13	18.90	43.50	-24.60	-	-	peak
4	312.1794	35.05	-4.81	30.24	46.00	-15.76	-	-	peak
5	420.5803	27.49	-3.08	24.41	46.00	-21.59	-	-	peak
6	724.2611	29.73	1.58	31.31	46.00	-14.69	-	-	peak

Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	49.3594	27.20	-7.31	19.89	40.00	-20.11	-	-	peak
2	69.8450	30.50	-11.05	19.45	40.00	-20.55	-	-	peak
3	99.1797	26.79	-8.29	18.50	43.50	-25.00	-	-	peak
4	167.2368	31.98	-10.79	21.19	43.50	-22.31	-	-	peak
5	294.1137	25.49	-5.21	20.28	46.00	-25.72	-	-	peak
6	508.2582	30.14	-2.01	28.13	46.00	-17.87	-	-	peak

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

## Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Duty Cycle Factor	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2410MHz								
2410	110.06	-8.41	N/A	101.65	114.00	-12.35	H	PK
2410	/	/	-21.69	79.96	94.00	-14.04	H	AV
4820	65.51	-2.83	N/A	62.68	74.00	-11.32	H	PK
4820	/	/	-21.69	40.99	54.00	-13.01	H	AV
7230	50.19	2.81	N/A	53.00	74.00	-21.00	H	PK
7230	/	/	-21.69	31.31	54.00	-22.69	H	AV
2410	108.59	-8.41	N/A	100.18	114.00	-13.82	V	PK
2410	/	/	-21.69	78.49	94.00	-15.51	V	AV
4820	61.05	-2.83	N/A	58.22	74.00	-15.78	V	PK
4820	/	/	-21.69	36.53	54.00	-17.47	V	AV
7230	51.39	2.81	N/A	54.20	74.00	-19.80	V	PK
7230	/	/	-21.69	32.51	54.00	-21.49	V	AV
Middle Channel-2440MHz								
2440	106.81	-8.30	N/A	98.51	114.00	-15.49	H	PK
2440	/	/	-22.28	76.23	94.00	-17.77	H	AV
4880	58.57	-2.71	N/A	55.86	74.00	-18.14	H	PK
4880	/	/	-22.28	33.58	54.00	-20.42	H	AV
7320	47.50	3.12	N/A	50.62	74.00	-23.38	H	PK
7320	/	/	-22.28	28.34	54.00	-25.66	H	AV
2440	103.24	-10.78	N/A	92.46	114.00	-21.54	V	PK
2440	/	/	-22.28	70.18	94.00	-23.82	V	AV
4880	55.28	-5.90	N/A	49.38	74.00	-24.62	V	PK
4880	/	/	-22.28	27.1	54.00	-26.9	V	AV
7320	47.36	-1.58	N/A	45.78	74.00	-28.22	V	PK
7320	/	/	-22.28	23.5	54.00	-30.5	V	AV
High Channel-2470MHz								
2470	103.53	-8.19	N/A	95.34	114.00	-18.66	H	PK
2470	/	/	-21.69	73.65	94.00	-20.35	H	AV
4940	56.94	-2.60	N/A	54.34	74.00	-19.66	H	PK
4940	/	/	-21.69	32.65	54.00	-21.35	H	AV
7410	50.28	3.44	N/A	53.72	74.00	-20.28	H	PK
7410	/	/	-21.69	32.03	54.00	-21.97	H	AV
2470	99.62	-8.19	N/A	91.43	114.00	-22.57	V	PK
2470	/	/	-21.69	69.74	94.00	-24.26	V	AV

Reference No.: WTX22X11236923W001

4940	54.72	-2.60	N/A	52.12	74.00	-21.88	V	PK
4940	/	/	-21.69	30.43	54.00	-23.57	V	AV
7410	47.36	3.44	N/A	50.80	74.00	-23.20	V	PK
7410	/	/	-21.69	29.11	54.00	-24.89	V	AV

*Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. The measurements greater than 20dB below the limit from 9kHz to 30MHz..*

## 5. Out of Band Emissions

---

### 5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### 5.2 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.

### 5.3 Summary of Test Results/Plots

Test mode	Frequency	Limit	Result
	MHz	dBuV / dBc	
Lowest	2310.00	<54dBuV	Pass
	2390.00	<54dBuV	Pass
	2400.00	<54dBuV	Pass
Highest	2483.50	<54dBuV	Pass
	2500.00	<54dBuV	Pass


The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.

Please refer to the test plots as below.

Reference No.: WTX22X11236923W001


RBW: 1MHz; VBW: 3MHz

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency	Reading	Correct	Duty Cycle Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	dB	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	54.52	-8.78	N/A	45.74	74.00	-28.26	peak
	/	/	/	-21.69	24.05	54.00	-29.95	ave
2	2390.000	72.04	-8.48	N/A	63.56	74.00	-10.44	peak
	/	/	/	-21.69	41.87	54.00	-12.13	ave
3	2409.990	110.06	-8.41	N/A	101.65	114.00	-12.35	peak
	/	/	/	-21.69	79.96	94.00	-14.04	ave

Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------




No.	Frequency	Reading	Correct	Duty Cycle Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	dB	(dBuV/m)	(dBuV/m)	(dB)	
1	2469.480	103.53	-8.20	N/A	95.33	114.00	-18.67	peak
	/	/	/	-21.69	73.64	94.00	-20.36	ave
2	2483.500	63.99	-8.14	N/A	55.85	74.00	-18.15	peak
	/	/	/	-21.69	34.16	54.00	-19.84	ave
3	2500.000	57.96	-8.08	N/A	49.88	74.00	-24.12	peak
	/	/	/	-21.69	28.19	54.00	-25.81	ave

Band edge

RBW: 100kHz; VBW: 300kHz


Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2400.000	53.51	-8.45	45.06	54.00	-8.94	peak



Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	47.37	-8.14	39.23	54.00	-14.77	peak
2	2485.020	58.48	-8.14	50.34	54.00	-3.66	peak

## 6. Emission Bandwidth

---

### 6.1 Standard Applicable

According to 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 6.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW  $\geq$ 1% 20dB Bandwidth, VBW  $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

### 6.3 Summary of Test Results/Plots

Test Channel	20dB Bandwidth(kHz)
Low Channel	2.26
Middle Channel	1.97
High Channel	2.00


*Please refer to the following test plots:*

Low Channel




Date: 3.DEC.2022 14:40:54

Middle Channel



Date: 3.DEC.2022 14:37:42

High Channel



Date: 3.DEC.2022 14:39:29

## 7. Duty Cycle

---

### 7.1 Standard Applicable

According to FCC Part 15.35 (c), for pulse operation transmitter, the averaging pulsed emissions are calculated by peak value of measured emission plus duty cycle factor.


### 7.2 Test Procedure

With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency we need test, than set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.

### 7.3 Summary of Test Results/Plots


Channel	Width of Pulse (ms)	Quantity of Pulse	Total Time ( $T_{on}$ )	Test Period (Periodic Time) (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)
Low	0.84	1	0.84	10.20	8.24	-21.69
Middle	0.78	1	0.78	10.14	7.69	-22.28
High	0.84	1	0.84	10.20	8.24	-21.69

Please refer to the attached test plots:




Middle Channel

Test Pattern 1




Date: 3.DEC.2022 15:00:42

Test Pattern 2



Date: 3.DEC.2022 14:59:43



## 8. Conducted Emissions


---

### 8.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

### 8.2 Basic Test Setup Block Diagram



### 8.3 Test Receiver Setup


During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency .....	150kHz
Stop Frequency .....	30MHz
Sweep Speed .....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth .....	9kHz
Quasi-Peak Adapter Mode .....	Normal

### 8.4 Summary of Test Results/Plots




Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1500	46.65	10.32	56.97	66.00	-9.03	QP
2	0.1620	30.35	10.31	40.66	55.36	-14.70	AVG
3	4.0500	27.40	10.30	37.70	56.00	-18.30	QP
4	4.1180	14.30	10.31	24.61	46.00	-21.39	AVG
5	13.2940	33.98	10.27	44.25	60.00	-15.75	QP
6	20.4340	24.19	10.37	34.56	50.00	-15.44	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1540	46.16	10.32	56.48	65.78	-9.30	QP
2	0.1900	26.57	10.30	36.87	54.04	-17.17	AVG
3	6.6980	20.30	10.34	30.64	50.00	-19.36	AVG
4	6.8380	31.86	10.34	42.20	60.00	-17.80	QP
5	13.1380	33.55	10.28	43.83	60.00	-16.17	QP
6	21.9900	24.19	10.37	34.56	50.00	-15.44	AVG

## APPENDIX PHOTOGRAPHS

---

Please refer to “ANNEX”

\*\*\*\* END OF REPORT \*\*\*\*