

# FCC Radio Test Report

## FCC ID: 2ARQU-WXC001

### Original Grant

**Report No.** : TB-FCC163358  
**Applicant** : Mianyang Highly-Tech Jingweida Scientific Co., Ltd  
**Equipment Under Test (EUT)**  
**EUT Name** : Wireless Charger  
**Model No.** : WXC001-XX  
**Serial Model No.** : N/A  
**Brand Name** : JWD  
**Receipt Date** : 2018-12-12  
**Test Date** : 2018-12-13 to 2018-12-24  
**Issue Date** : 2018-12-25  
**Standards** : FCC Part 15: 2018, Subpart C(15.209)  
**Test Method** : ANSI C63.10: 2013  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,

**Test/Witness Engineer** : *Jason Xu*  
**Engineer Supervisor** : *Ivan Su*  
**Engineer Manager** : *Ray Lai*



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

---

---

# Contents

- CONTENTS.....2**
- 1. GENERAL INFORMATION ABOUT EUT .....4**
  - 1.1 Client Information.....4
  - 1.2 General Description of EUT (Equipment Under Test) .....4
  - 1.3 Block Diagram Showing the Configuration of System Tested.....5
  - 1.4 Description of Support Units .....5
  - 1.5 Description of Test Mode.....5
  - 1.6 Description of Test Software Setting .....6
  - 1.7 Measurement Uncertainty .....7
  - 1.8 Test Facility.....7
- 2. TEST SUMMARY .....8**
- 3. TEST EQUIPMENT .....9**
- 4. CONDUCTED EMISSION TEST .....10**
  - 4.1 Test Standard and Limit.....10
  - 4.2 Test Setup.....10
  - 4.3 Test Procedure.....10
  - 4.4 EUT Operating Mode .....11
  - 4.5 Test Data.....11
- 5. RADIATED EMISSION TEST .....12**
  - 5.1 Test Standard and Limit.....12
  - 5.2 Test Setup.....13
  - 5.3 Test Procedure.....14
  - 5.4 EUT Operating Condition .....14
  - 5.5 Test Data.....14
- 6. BANDWIDTH MEASUREMENT .....15**
  - 6.1 Test Standard and Limit.....15
  - 6.2 Test Setup.....15
  - 6.3 Test Procedure.....15
  - 6.4 EUT Operating Condition .....15
  - 6.5 Test Data.....15
- 7. ANTENNA REQUIREMENT .....16**
  - 7.1 Standard Requirement.....16
  - 7.2 Antenna Connected Construction .....16
  - 7.3 Result.....16
- ATTACHMENT A-- CONDUCTED EMISSION TEST DATA .....17**
- ATTACHMENT B-- RADIATED EMISSION TEST DATA .....21**



# 1. General Information about EUT

## 1.1 Client Information

<b>Applicant</b>	:	Mianyang Highly-Tech Jingweida Scientific Co., Ltd
<b>Address</b>	:	Yongxing Industry Park, Hi-tech Zone Mianyang, Sichuan Province, China
<b>Manufacturer</b>	:	Mianyang Highly-Tech Jingweida Scientific Co., Ltd
<b>Address</b>	:	Yongxing Industry Park, Hi-tech Zone Mianyang, Sichuan Province, China

## 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	Wireless Charger	
<b>Models No.</b>	:	WXC001-XX	
<b>Model Difference</b>	:	N/A	
<b>Product Description</b>	:	Operation Frequency:	110KHz-205KHz
	:	Modulation Type:	MSK
	:	Antenna:	Coil Antenna
<b>Power Supply</b>	:	Input: 5V/2A Output: 5V/1A	
<b>Charging Distance</b>	:	≤8mm	
<b>Software Version</b>	:	N/A	
<b>Hardware Version</b>	:	N/A	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	


**Note:**

(1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(2) Channel List:

Low Frequency(KHz)	Middle Frequency(KHz)	High Frequency(KHz)
110	158	205
Note: Operation Frequency=110+1*k, k ∈ (0,1,2,3.....,93)		

### 1.3 Block Diagram Showing the Configuration of System Tested Charging + TX Mode



### 1.4 Description of Support Units

Name	Model	S/N	Manufacturer	Used “√”
Load	5W	----	----	√
Adapter	EP-TA200	----	SAMSUNG	√

Input: AC100-240V,50/60Hz, 0.5A Output: DC 5V, 1A.

### 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

Pretest Mode	
Final Test Mode	Description
Mode 1	TX Mode(Low CH)
Mode 2	TX Mode(Middle CH)
Mode 3	TX Mode(High CH)
Mode 4	Keeping TX Mode(5V/1A)
For Conducted Test	
Final Test Mode	Description
Mode 4	Keeping TX Mode(5V/1A)

For Radiated Test	
Final Test Mode	Description
Mode 4	Keeping TX Mode(5V/1A)
For Bandwidth Test	
Final Test Mode	Description
Mode 1	TX Mode(Low CH)

**Note:**

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.  
According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:  
TX Mode: Transmitting mode.
- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a portable unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

<b>Test Software Version</b>	<b>N/A</b>
Frequency	110-205KHz

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz	$\pm 3.42$ dB
	150kHz to 30MHz	$\pm 3.42$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.40$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB

## 1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **A2LA Certificate No.: 4750.01**

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.

### **IC Registration No.: (11950A-1)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

## 2. Test Summary

FCC Part 15 Subpart C(15.209)			
Standard Section	Test Item	Judgment	Remark
15.203	Antenna Requirement	PASS	N/A
15.207(a)	Conducted Emission	PASS	N/A
15.209(a)(f)	Radiated emissions	PASS	N/A
15.215	Bandwidth	PASS	N/A

**Note:** N/A is an abbreviation for Not Applicable.



### 3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 18, 2018	Jul. 17, 2019
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 18, 2018	Jul. 17, 2019
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 18, 2018	Jul. 17, 2019
LISN	Rohde & Schwarz	ENV216	101131	Jul. 18, 2018	Jul. 17, 2019
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 18, 2018	Jul. 17, 2019
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 18, 2018	Jul. 17, 2019
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.16, 2018	Mar. 15, 2019
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar.16, 2018	Mar. 15, 2019
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.16, 2018	Mar. 15, 2019
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.16, 2018	Mar. 15, 2019
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 03, 2018	Jul. 02, 2019
Pre-amplifier	Sonoma	310N	185903	Mar.17, 2018	Mar. 16, 2019
Pre-amplifier	HP	8449B	3008A00849	Mar.17, 2018	Mar. 16, 2019
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.17, 2018	Mar. 16, 2019
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 18, 2018	Jul. 17, 2019
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 18, 2018	Jul. 17, 2019
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Oct. 26, 2017	Oct. 25, 2018
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 15, 2018	Sep. 14, 2019
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 15, 2018	Sep. 14, 2019
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 15, 2018	Sep. 14, 2019
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 15, 2018	Sep. 14, 2019
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 15, 2018	Sep. 14, 2019
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 15, 2018	Sep. 14, 2019

## 4. Conducted Emission Test

### 4.1 Test Standard and Limit

#### 4.1.1 Test Standard

FCC Part 15.207

#### 4.1.2 Test Limit

#### Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) \*Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2 Test Setup



### 4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9 kHz, and the test frequency band is from 0.15MHz to 30MHz.

#### 4.4 EUT Operating Mode

Please refer to the description of test mode.

#### 4.5 Test Data

Please refer to the Attachment A.

## 5. Radiated Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.209(a)(f)

#### 5.1.2 Test Limit

#### Radiated Emission Limits ( 9 kHz~1000 MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


#### Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54


**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup

### 5.3 Test Procedure

- (1) Measurements at frequency 9KHz~30MHz and Below 1GHz. The EUT was placed on a rotating 0.8m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) 9KHz~30MHz the test antenna 1m away from the ground, Both 0° and 90° antenna are set to make measurement.  
Below 1GHz the test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For 9kHz to 150kHz, Set the spectrum analyzer as:  
RBW= 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.  
For 150kHz to 30MHz, Set the spectrum analyzer as:  
RBW= 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple
- (8) For the actual test configuration, please see the test setup photo.

### 5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

### 5.5 Test Data

Please refer to the Attachment B.


## 6. Bandwidth Measurement

### 6.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.215

### 6.2 Test Setup



### 6.3 Test Procedure

1. The transmitter shall be operated at its maximum carrier power measured under normal test conditions;
2. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
3. The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

### 6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

### 6.5 Test Data

Please refer to the Attachment C.

## 7. Antenna Requirement

### 7.1 Standard Requirement

#### 7.1.1 Standard

FCC Part 15.203

#### 7.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 7.2 Antenna Connected Construction

The antenna is Coil Antenna, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### 7.3 Result


The EUT antenna is a Coil Antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna



## Attachment A-- Conducted Emission Test Data


Temperature:	24°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Line		
Test Mode:	TX Mode(5V/1A)		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1700	43.24	9.58	52.82	64.96	-12.14	QP
2		0.1700	27.79	9.58	37.37	54.96	-17.59	AVG
3		0.2060	40.84	9.58	50.42	63.36	-12.94	QP
4		0.2060	25.20	9.58	34.78	53.36	-18.58	AVG
5		0.2380	36.19	9.58	45.77	62.16	-16.39	QP
6		0.2380	20.42	9.58	30.00	52.16	-22.16	AVG
7		0.2740	33.21	9.59	42.80	60.99	-18.19	QP
8		0.2740	17.64	9.59	27.23	50.99	-23.76	AVG
9		0.3020	28.73	9.59	38.32	60.19	-21.87	QP
10		0.3020	13.09	9.59	22.68	50.19	-27.51	AVG
11		0.3540	26.09	9.60	35.69	58.87	-23.18	QP
12		0.3540	11.26	9.60	20.86	48.87	-28.01	AVG

Emission Level= Read Level+ Correct Factor


<b>Temperature:</b>	24°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	TX Mode(5V/1A)		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1740	40.86	9.64	50.50	64.76	-14.26	QP
2		0.1740	25.87	9.64	35.51	54.76	-19.25	AVG
3		0.2060	37.27	9.65	46.92	63.36	-16.44	QP
4		0.2060	22.27	9.65	31.92	53.36	-21.44	AVG
5		0.2420	34.21	9.62	43.83	62.02	-18.19	QP
6		0.2420	19.06	9.62	28.68	52.02	-23.34	AVG
7		0.2644	29.46	9.60	39.06	61.29	-22.23	QP
8		0.2644	14.66	9.60	24.26	51.29	-27.03	AVG
9		0.3740	23.13	9.58	32.71	58.41	-25.70	QP
10		0.3740	9.93	9.58	19.51	48.41	-28.90	AVG
11		0.7740	27.91	9.59	37.50	56.00	-18.50	QP
12	*	0.7740	22.44	9.59	32.03	46.00	-13.97	AVG

Emission Level= Read Level+ Correct Factor


<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 240V/60 Hz		
<b>Terminal:</b>	Line		
<b>Test Mode:</b>	TX Mode(5V/1A)		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1780	35.27	9.58	44.85	64.57	-19.72	QP
2		0.1780	18.40	9.58	27.98	54.57	-26.59	AVG
3		0.2100	33.66	9.58	43.24	63.20	-19.96	QP
4		0.2100	17.73	9.58	27.31	53.20	-25.89	AVG
5		0.2500	31.27	9.58	40.85	61.75	-20.90	QP
6		0.2500	15.31	9.58	24.89	51.75	-26.86	AVG
7		0.2860	29.27	9.59	38.86	60.64	-21.78	QP
8		0.2860	13.60	9.59	23.19	50.64	-27.45	AVG
9		0.3220	27.65	9.59	37.24	59.65	-22.41	QP
10		0.3220	12.17	9.59	21.76	49.65	-27.89	AVG
11	*	0.7860	29.70	9.61	39.31	56.00	-16.69	QP
12		0.7860	19.21	9.61	28.82	46.00	-17.18	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 240V/60 Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	TX Mode(5V/1A)		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1768	36.69	9.65	46.34	64.63	-18.29	QP
2		0.1768	20.84	9.65	30.49	54.63	-24.14	AVG
3		0.2140	33.76	9.64	43.40	63.04	-19.64	QP
4		0.2140	18.67	9.64	28.31	53.04	-24.73	AVG
5		0.2420	30.54	9.62	40.16	62.02	-21.86	QP
6		0.2420	15.51	9.62	25.13	52.02	-26.89	AVG
7		0.2740	25.70	9.59	35.29	60.99	-25.70	QP
8		0.2740	10.77	9.59	20.36	50.99	-30.63	AVG
9		0.3100	24.86	9.57	34.43	59.97	-25.54	QP
10		0.3100	10.98	9.57	20.55	49.97	-29.42	AVG
11		0.7860	27.86	9.59	37.45	56.00	-18.55	QP
12	*	0.7860	22.30	9.59	31.89	46.00	-14.11	AVG

Emission Level= Read Level+ Correct Factor

## Attachment B-- Radiated Emission Test Data

30MHz~1GHz

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX Mode(5V/1A)		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	33.3279	39.43	-15.50	23.93	40.00	-16.07	QP
2		56.3948	39.16	-23.97	15.19	40.00	-24.81	QP
3		85.2980	41.44	-22.24	19.20	40.00	-20.80	QP
4		191.0738	45.77	-19.82	25.95	43.50	-17.55	QP
5		210.7860	43.66	-19.36	24.30	43.50	-19.20	QP
6		286.9823	45.67	-16.46	29.21	46.00	-16.79	QP

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX Mode(5V/1A)		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	33.7986	50.98	-15.86	35.12	40.00	-4.88	QP
2		48.3318	51.60	-22.68	28.92	40.00	-11.08	QP
3		53.6932	50.34	-23.65	26.69	40.00	-13.31	QP
4		103.0800	44.86	-22.20	22.66	43.50	-20.84	QP
5		168.4138	50.15	-20.58	29.57	43.50	-13.93	QP
6		191.0738	51.12	-19.82	31.30	43.50	-12.20	QP

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**

**9KMz-30MHz**


<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120/60Hz		
<b>Ant. Pol.</b>	Ant. 0°		
<b>Test Mode:</b>	TX Mode(5V/1A)		
<b>Remark:</b>	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		0.0123	66.26	-10.33	55.93	126.08	-70.15	peak
2		0.0123	55.89	-10.33	45.56	106.08	-60.52	AVG
3		0.0151	64.33	-10.36	53.97	124.30	-70.33	peak
4		0.0151	53.61	-10.36	43.25	104.30	-61.05	AVG
5		0.0241	62.24	-10.09	52.15	120.23	-68.08	peak
6		0.0241	52.12	-10.09	42.03	100.23	-58.20	AVG
7		0.0331	72.53	-9.90	62.63	117.46	-54.83	peak
8		0.0331	61.68	-9.90	51.78	97.46	-45.68	AVG
9		0.0660	70.81	-10.06	60.75	111.46	-50.71	peak
10		0.0660	60.09	-10.06	50.03	91.46	-41.43	AVG
11	*	0.1491	80.30	-5.77	74.53	104.36	-29.83	peak
12		0.1491	69.40	-5.77	63.63	84.36	-20.73	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120/60Hz		
Ant. Pol.	Ant. 0°		
Test Mode:	TX Mode(5V/1A)		
Remark:	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		0.1500	90.89	-5.81	85.08	104.31	-19.23	peak
2		0.2955	76.58	-8.32	68.26	98.40	-30.14	peak
3		0.4421	83.72	-9.31	74.41	94.90	-20.49	peak
4		0.4421	73.08	-9.31	63.77	74.90	-11.13	AVG
5		0.5885	65.70	-9.83	55.87	72.38	-16.51	peak
6		0.7352	66.39	-10.04	56.35	70.42	-14.07	peak
7	*	1.4796	62.18	-10.33	51.85	64.25	-12.40	peak

Emission Level= Read Level+ Correct Factor




Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120/60Hz		
Ant. Pol.	Ant. 90°		
Test Mode:	TX Mode(5V/1A)		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		0.0151	68.78	-10.36	58.42	124.30	-65.88	peak
2		0.0151	58.69	-10.36	48.33	104.30	-55.97	AVG
3		0.0240	60.29	-10.09	50.20	120.26	-70.06	peak
4		0.0240	50.10	-10.09	40.01	100.26	-60.25	AVG
5		0.0331	70.31	-9.90	60.41	117.46	-57.05	peak
6		0.0331	60.23	-9.90	50.33	97.46	-47.13	AVG
7		0.0351	64.28	-9.98	54.30	116.95	-62.65	peak
8		0.0351	54.09	-9.98	44.11	96.95	-52.84	AVG
9		0.0660	65.16	-10.06	55.10	111.46	-56.36	peak
10		0.0660	55.08	-10.06	45.02	91.46	-46.44	AVG
11	*	0.1483	81.22	-5.74	75.48	104.41	-28.93	peak
12		0.1483	70.42	-5.74	64.68	84.41	-19.73	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120/60Hz		
Ant. Pol.	Ant. 90°		
Test Mode:	TX Mode(5V/1A)		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	0.1500	91.01	-5.81	85.20	104.31	-19.11	peak
2		0.2955	72.98	-8.32	64.66	98.40	-33.74	peak
3		0.4421	73.95	-9.31	64.64	94.90	-30.26	peak
4		0.4421	63.18	-9.31	53.87	74.90	-21.03	AVG
5		0.5885	60.49	-9.83	50.66	72.38	-21.72	peak
6		0.6899	60.28	-9.98	50.30	70.98	-20.68	peak
7		1.0320	55.36	-10.26	45.10	67.43	-22.33	peak

Emission Level= Read Level+ Correct Factor

-----END OF REPORT-----