

## RF Exposure Evaluation

**Limit**

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1-Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

**Evaluation Method**

Transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>,  $P_{out}$  = output power to antenna in mW,  $G$  = gain of antenna in linear scale;

$P_i$  = 3.1416,  $R$  = distance between observation point and center of the radiator in cm

**Conducted Power Results**

**WIFI**

Mode	Channel	Frequency (MHz)	Conducted Output Power (dBm)
802.11b	1	2412	11.17
	6	2437	11.78
	11	2462	11.84
802.11b	1	2412	11.89
	6	2437	11.65
	11	2462	11.85
802.11n(HT20)	1	2412	11.90
	6	2437	11.70
	11	2462	11.78

**Manufacturing tolerance**

**WIFI**

802.11b (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11	11	11

Tolerance $\pm$ (dB)	1	1	1
<b>802.11g (Peak)</b>			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11	11	11
Tolerance $\pm$ (dB)	1	1	1
<b>802.11n20 (Peak)</b>			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11	11	11
Tolerance $\pm$ (dB)	1	1	1

**Evaluation Results****WIFI**

Band/Mode	Antenna Distance (cm)	RF output power		Gain of antenna in linear scale	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
		dBm	mW				
802.11b	20	12	15.85	1.26	0.004	1.0	Pass
802.11g	20	12	15.85	1.26	0.004	1.0	Pass
802.11n20	20	12	15.85	1.26	0.004	1.0	Pass

*Remark:*

1. Output power including tune up tolerance;
2. The maximum antenna gain is 1dBi
3. The exposure safety distance is 20cm.

**Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE compliance per KDB 447498 v06.