



MPE ESTIMATION

FCC ID: 2ARRS-JAHD440BT

1, Limit for General Population/ Uncontrolled Exposures

| Frequency | Power density (mW/ cm ²) | Averaging time(minutes) |
|------------------|--------------------------------------|-------------------------|
| 300MHz----1.5GHz | F/1500 | 30 |
| 1.5GHz---100GHz | 1.0 | 30 |

Note: F= Frequency in MHz

2, Estimation Result

| Mode | Max PK Output power(dBm) | Tune Up Power(dBm) | Max Tune Up power(mW) | Antenna Gain(dBi) | Antenna Gain (numerical) | MPE (mW/cm ²) |
|------|--------------------------|--------------------|-----------------------|-------------------|--------------------------|---------------------------|
| EDR | 4.59 | 3.7±1(4.7) | 2.95 | 0 | 1 | 0.00059 |

$$Pd = \frac{Pout * G}{4\pi r^2};$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2112224936-E**, antenna gain=0dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.00059 mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

-----The End-----