

RF Exposure Evaluation Report

Product : SPORT SMART WATCH
Trade mark : MINISO
Model/Type reference : LT716
Serial Number : N/A
Report Number : EED32O80373002
FCC ID : 2ART4-LT716
Date of Issue : May 09, 2022
Test Standards : 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF
Exposure Guidance v06
Test result : PASS

Prepared for:

MINISO Corporation

**Room 2501, No. 486 Heye Square Kangwang Middle Road,
Liwan District, Guangzhou, Guangdong, China**

Prepared by:

**Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China**

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

mark.chen.

Mark Chen

Approved by:

Aaron Ma

Aaron Ma

Reviewed by:

Tom Chen

Tom Chen

Date of issue:

May 09, 2022

Check No.:1959180322



2 Version

Version No.	Date	Description
00	May 09, 2022	Original

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 SAR EVALUATION	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 <i>Standard Requirement</i>	6
5.1.2 <i>Limits</i>	6
5.1.3 <i>EUT RF Exposure</i>	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	8

4 General Information

4.1 Client Information

Applicant:	MINISO Corporation
Address of Applicant:	Room 2501, No. 486 Heye Square Kangwang Middle Road, Liwan District, Guangzhou, Guangdong, China
Manufacturer:	Shenzhen Kingstar Industrial Co.,Ltd
Address of Manufacturer:	Room 210, Minle Technology Building, Minle Industrial Park, Longhua Shenzhen China
Factory:	Shenzhen Kingstar Industrial Co.,Ltd
Address of Factory:	Room 210, Minle Technology Building, Minle Industrial Park, Longhua Shenzhen China

4.2 General Description of EUT

Product Name:	SPORT SMART WATCH
Model No.(EUT):	LT716
Trade Mark:	MINISO

4.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz
Modulation Type:	GFSK
Test Power Grade:	Default
Test Software of EUT:	EMI Test Tool
Antenna Type:	PCB Antenna
Antenna Gain:	0 dBi
Power Supply:	DC 3.7V
Max Conducted Peak Output Power:	-14.14dBm The Max Conducted Peak Output Power data refer to the report EED32O80373001
Sample Received Date:	Mar. 21, 2022
Sample tested Date:	Mar. 21, 2022 to Apr. 13, 2022
Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.	

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

1) For Bluetooth LE

Measurement Data:

BLE 1M:

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-14.45	-14±1	-15	0.032
Middle(2440MHz)	-14.14	-14±1	-15	0.032
Highest(2480MHz)	-14.5	-14±1	-15	0.032

BLE 2M:

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-14.48	-14±1	-15	0.032
Middle(2440MHz)	-14.26	-14±1	-15	0.032
Highest(2480MHz)	-14.47	-14±1	-15	0.032

Worst case is BLE 1M: GFSK

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-14.48	-14±1	-15	0.032	0.010	3.0
Middle (2441MHz)	-14.26	-14±1	-15	0.032	0.010	
Highest (2480MHz)	-14.47	-14±1	-15	0.032	0.010	

Conclusion: the calculated value ≤3.0, SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: EED32O80373001.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32O80373001 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***